AUTOMATIONtec LLC AT200 Installation Instructions

Thank you for purchasing an AUTOMATIONtec AT200 remote wireless transmitter. This transmitter operates in the 433MHz Industrial, Scientific, and Medical (ISM) band as regulated by the Federal Communication Commission (FCC) under the guidelines of Part 15.

The following is included in the AT200 installation kit:

- 1 AT200 Transmitter.
- 1 Installation Instructions

You will also need the following to complete this installation:

- 1 AT100 Receiver Gateway
- 1 One (1) small Philips type screwdriver
- 2 AA Batteries

Mounting hardware as needed.

To install:

- 1. Open the AT200 enclosure by removing the four (4) screws in each corner of the enclosure.
- 2. Insert 2 AA size batteries in the battery holders. Note the orientation of the batteries as specified on the circuit board.
- 3. Press the manual transmit button and verify the LED blinks.
- 4. Close the AT200 enclosure by installing the four (4) screws in each corner of the enclosure.

All other installation will involve the AT100 and its installation instructions.

Rev 02/09 001-1000-0181

AUTOMATIONtec LLC AT200 Installation Instructions

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance will void the user's authority to operate the equipment and void all warranties.

Rev 02/09 001-1000-0181