

# Test Report

## T-0329-4305-00 JP

Type / Model Name: PLB000998

FCC ID W5IPLB000998

Product Description: LPR-1D, LPR-2D

Applicant: Symeo GmbH

## EMC -- TEST REPORT

<b>Test Report No. :</b>	<b>T-0329-4305-00 JP</b>	2012-04-12
		Date of issue

Type / Model Name : PLB000998

FCC ID : W5IPLB000998

Product Description : LPR-1D, LPR-2D

**Applicant** : Symeo GmbH

Address : Professor-Messerschmitt-Str. 3

85579 Neubiberg / München

Germany

**Manufacturer** : Symeo GmbH

Address : Professor-Messerschmitt-Str. 3

85579 Neubiberg / München

Germany

<b>Test Result</b> according to the standards listed in clause 1 test standards:	<b>POSITIVE</b>
--	-----------------



Deutsche  
Akkreditierungsstelle  
D-PL-12141-01-01

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

File No. **T-0329-4305-00 JP**

## Contents

<b>1</b>	<b><u>TEST STANDARDS</u></b>	<b>4</b>
<b>2</b>	<b><u>OVERVIEW TEST RESULT</u></b>	<b>5</b>
<b>3</b>	<b><u>SUMMARY</u></b>	<b>6</b>
<b>4</b>	<b><u>EQUIPMENT UNDER TEST</u></b>	<b>7</b>
4.1	PHOTO DOCUMENTATION OF THE EUT	7
4.2	POWER SUPPLY SYSTEM	14
4.3	SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)	14
<b>5</b>	<b><u>TEST ENVIRONMENT</u></b>	<b>16</b>
5.1	ADDRESS OF THE TEST LABORATORY	16
5.2	STATEMENT REGARDING THE USAGE OF LOGOS AT TEST REPORTS	16
5.3	ENVIRONMENTAL CONDITIONS	16
5.4	STATEMENT OF THE MEASUREMENT UNCERTAINTY	16
5.5	MEASUREMENT PROTOCOL FOR FCC, VCCI AND AUSTEL	17
<b>6</b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b>19</b>
6.1	CONDUCTED DISTURBANCE	19
6.2	RADIATED DISTURBANCE (9kHz – 30MHz)	24
6.3	RADIATED DISTURBANCE (30MHz – 1000MHz)	33
6.4	RADIATED DISTURBANCE (1GHz – 40GHz)	82
6.5	BANDEDGES	131
6.6	FIELD STRENGTH OF EMISSION WITHIN BAND	180
<b>7</b>	<b><u>USED TEST EQUIPMENT AND ACCESSORIES</u></b>	<b>205</b>

File No. **T-0329-4305-00 JP**

## **1 TEST STANDARDS**

The tests were performed according to following standards:

FCC Part 15 Subpart A  
October 2010

Code of Regulations Part 15 (Radio Frequency Devices), Subpart A  
(General) of the Federal Communications Commission (FCC)

FCC Part 15 Subpart C  
October 2010

Code of Regulations Part 15 (Radio Frequency Devices), Subpart B  
(Unintentional Radiators) of the Federal Communications Commission  
(FCC)

Applied Paragraphs: §15.207, §15.209, §15.249

ANSI C63.4-2003

American National Standard for Methods of Measurement of Radio-  
Noise Emissions from Low-Voltage Electrical and Electronic  
Equipment in the Range of 9kHz – 40 GHz

File No. **T-0329-4305-00 JP**

## **2 OVERVIEW TEST RESULT**

Performed test(s)	Result		
	Passed	Failed	Not performed
Conducted disturbance	X		
Radiated disturbance (9kHz – 30MHz)	X		
Radiated disturbance (30MHz – 1000MHz)	X		
Radiated disturbance (1GHz – 40GHz)	X		
Bandedges	X		
Field strength of emission within band	X		

File No. **T-0329-4305-00 JP**

### 3 SUMMARY

#### GENERAL REMARKS:

The EUT has a TX mode and a RX mode but RX is without TX beacons not possible therefore the measurements were performed in TX mode only.

The EuT was tested with a host housing and motherboard supplied by manufacturer.

#### FINAL ASSESSMENT:

The equipment under test **fulfills** the EMC requirements cited in clause 1 test standards.

Date of receipt of test sample : acc. to storage records

Testing commenced on : 2012-02-07

Testing concluded on : 2012-03-23

Checked by:

Tested by:

---

Frank Scharnowski


---

Jürgen Pessinger

File No. **T-0329-4305-00 JP**


## 4 EQUIPMENT UNDER TEST

### 4.1 Photo documentation of the EuT



File No. **T-0329-4305-00 JP**





File No. **T-0329-4305-00 JP**




Periphery:



File No. **T-0329-4305-00 JP**

emitel AG, Ohmstrasse 1, 94342 STRASSKIRCHEN, DEUTSCHLAND Tel. / Phone: +49 (0) 94 24 94 82-0 Fax: +49 (0) 94 24 94 82-640  
emG\_F510\_02\_Rev9\_0 Freigabedatum / Date of release: 2012-02-07; Autor / Author: Martin Stern  
Seite / Page 9 von / of 205

**TESTREPORT**



File No. **T-0329-4305-00 JP**

emitel AG, Ohmstrasse 1, 94342 STRASSKIRCHEN, DEUTSCHLAND Tel. / Phone: +49 (0) 94 24 94 82-0 Fax: +49 (0) 94 24 94 82-640  
emG\_F510\_02\_Rev9\_0 Freigabedatum / Date of release: 2012-02-07; Autor / Author: Martin Stern  
Seite / Page 10 von / of 205

Antenna ANC000947, gain 6dBi



Antenna ANC000421, gain 10dBi



File No. **T-0329-4305-00 JP**

Antenna ANC000468, gain 13dBi



Antenna ANC000168, gain 23dBi



File No. **T-0329-4305-00 JP**



File No. **T-0329-4305-00 JP**

emitel AG, Ohmstrasse 1, 94342 STRASSKIRCHEN, DEUTSCHLAND Tel. / Phone: +49 (0) 94 24 94 82-0 Fax: +49 (0) 94 24 94 82-640  
emG\_F510\_02\_Rev9\_0 Freigabedatum / Date of release: 2012-02-07; Autor / Author: Martin Stern  
Seite / Page 13 von / of 205



## 4.2 Power supply system

Power supply voltage: 10-36V DC

## 4.3 Short description of the Equipment under Test (EuT)

The EuT is a wireless module used in systems for contactless, real time determination of distances and positions. The EuT can be used with different antennas. An adjustable attenuator is used to set the transmit power to keep the legal limit.

Number of tested samples: 1  
 Serial number: none

Dimensions: L: 11cm W: 5,5cm H: 1cm

### Radio equipment characteristics

#### FSK Channel

Frequency band(s): 5725MHz – 5875MHz  
 Operating frequency: 5729MHz – 5871MHz  
 Channel spacing: 1MHz  
 Number of RF-channels: 54 channels (CH00 – CH53)  
 Comments: None

#### Measurement band

Frequency band(s): 5725MHz – 5875MHz  
 Operating frequency: Depends on FSK channel usage\*  
 Channel spacing: variable  
 Number of RF-channels: 1 distance measurement band  
 Comments: None

\*measurement band is located between last available FSK channel in upper FSK frequency range and the first available FSK channel in the lower FSK frequency range, with a clearance of 3MHz.

### EuT operation mode:

The equipment under test was operated during the measurement under the following conditions:

- test software active, CH00 (5871MHz) adjusted

- test software active, CH27 (5755MHz) adjusted

- test software active, CH53 (5729MHz) adjusted

File No. **T-0329-4305-00 JP**



## EuT configuration:

The following interface cables and peripheral devices were connected during the measurements:

### Interface cables:

Interface cable	Length [m]	Type	Line		Line termination
			shielded	unshielded	
DC power line*	2,3	2-wires	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Power supply or 12V battery
RS232	2,1	3-wires	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Laptop
Antenna Cable 1	4,0	1-wire	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Antenna (Type 1, 2, 3 or 4)**
Antenna cable 2	4,0	1-wire	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Antenna (Type 1, 2, 3 or 4)**

\*connected to motherboard not directly to PLB000998

\*\*radiated tests were performed with each type of antenna

### Peripheral devices:

Kind of equipment		Model and/or Manufacturer
Power supply		EA-PS 3032-10B, emitel ID: 01-05/50-11-014
Laptop		Tecra A2, Toshiba, emitel ID: 01-01/01-05-005
Antenna Type 1		ANC000947, Symeo, 6dBi
Antenna Type 2		ANC000421, Symeo, 10dBi
Antenna Type 3		ANC000468, Symeo, 13dBi
Antenna Type 4		ANC000168, Symeo, 23dBi

File No. **T-0329-4305-00 JP**

## **5 TEST ENVIRONMENT**

### **5.1 Address of the test laboratory**

**emitel AG  
Ohmstrasse 1  
94342 STRASSKIRCHEN  
DEUTSCHLAND**

#### **Laboratory registration numbers:**

DAkkS Registration number:	D-PL-12141-01-01
KBA Registration number:	KBA-P 00057-01
SNCH Registration number:	SNCH 001/2005
FCC Registration number:	765810
IC Registration number:	IC 5066A-1

### **5.2 Statement regarding the usage of logos at test reports**

The logos of accreditation- and notification bodies displayed at this test reports are only valid for standards listed at the accreditation- or notification scope of emitel AG.

### **5.3 Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 86-106 kPa

All atmospheric pressure values refer to our Laboratory altitude of 324m.

### **5.4 Statement of the measurement uncertainty**

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16-4-2 /11.2003 „Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements“ and is documented in the quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer does have the sole responsibility for the continued compliance of the device.

File No. **T-0329-4305-00 JP**

## 5.5 Measurement Protocol for FCC, VCCI and AUSTEL

### 5.5.1 GENERAL INFORMATION

#### 5.5.1.1 Test Methodology

Conducted and radiated disturbance testing is performed according to the procedures in International Special Committee on Radio Interference (CISPR) Publication 22 (1997+A1:2000+A2:2002), European Standard EN 55022 (1998+A1:2000+A2:2003) and Australian Standard AS 3548 (which are based on CISPR 22).

The Japanese standard, "Voluntary Control Council for Interference (VCCI) by Data Processing Equipment and Electronic Office Machines, Technical Requirements" is technically equivalent to CISPR 22 (1997+A1:2000+A2:2002). For official compliance, a conformance report must be sent to and accepted by the VCCI.

In compliance with FCC Docket 92-152, "Harmonization of Rules for Digital Devices Incorporate International Standards", testing for FCC compliance may be done following the ANSI C63.4-2003 procedures and using the CISPR 22 Limits.

#### 5.5.1.2 Measurement Error

The data and results referenced in this document are true and accurate. The reader is cautioned that there is some measurement variability due to the tolerances of the test equipment that can contribute to a nominal product measurement uncertainty. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16-4-2 and is documented in the emitel AG quality system according to DIN EN ISO/IEC 17025. Furthermore, component differences and manufacturing process variability of production units similar to that tested may result in additional product uncertainty. If necessary, refer to the test lab for the actual measurement uncertainty for specific tests. The manufacturer has the sole responsibility of continued compliance of the device.

#### 5.5.1.3 Justification

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left unterminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum disturbances from the unit.

### 5.5.2 CONDUCTED DISTURBANCE

The final level, expressed in dB $\mu$ V, is arrived at by taking the reading directly from the EMI receiver. This level is compared directly to the CISPR limit, which is equivalent to the Australian AS 3548 limit.

To convert between dB $\mu$ V and  $\mu$ V, the following conversions apply:

$$\text{dB}\mu\text{V} = 20(\log \mu\text{V})$$

$$\mu\text{V} = \text{Inverse log}(\text{dB}\mu\text{V}/20)$$

File No. **T-0329-4305-00 JP**

### 5.5.3 RADIATED DISTURBANCE

The final level, expressed in dB $\mu$ V/m, is arrived at by taking the reading from the EMI receiver (Level dB $\mu$ V) and adding the antenna correction factor and cable loss factor (Factor dB) to it. This is done automatically in the EMI receiver, where the correction factor are stored. This result then has the CISPR limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets in section 5.2. The CISPR 22 limit is equivalent to the Australian AS 3548 limit.

Example:	CISPR B	Delta							
Frequency	Level	+	Factor	=	Final	-	Limit	=	CISPR B
(MHz)	(dB $\mu$ V)		(dB)		(dB $\mu$ V/m)		(dB $\mu$ V/m)		(dB)
37.19	10.2	+	12.0	=	22.2	-	40.0	=	-17.8

### 5.5.4 DETAILS OF TEST PROCEDURES

#### 5.5.4.1 General Standard Information

The test methods used comply with CISPR Publication 22 (1997+A1:2000+A2:2002), EN 55022 (1998+A1:2000+A2:2003) and AS 3548 (1992) - "Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment" and with ANSI C63.4-2003 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

#### 5.5.4.2 Conducted disturbance

Conducted disturbance on the 50 Hz and/or 60 Hz power interface of the EUT are measured in the frequency range of 150 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi peak detection, and a Line Impedance Stabilization Network (LISN), with 50 $\Omega$ /50  $\mu$ H (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 centimetres above the floor and is positioned 40 centimetres from the vertical ground plane (wall) of the screen room. If the minimum passing margin appears to be less than 20 dB with a peak mode measurement, the emissions are remeasured using a tuned receiver with quasi peak and average detection and recorded on the data sheets.

#### 5.5.4.3 Radiated disturbance

Radiated disturbance from the EUT are measured in the frequency range of 30 to 1000 MHz using a tuned receiver and appropriate broadband linearly polarized antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi peak detection and measurements above 1000 MHz are made with a 1 MHz/6 dB bandwidth and average/peak detection. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80 centimetres above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Interface cables that are closer than 40 centimetres to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimetres from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna was positioned 3, 10 or 30 meters horizontally from the EUT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarizations and the EUT are rotated 360 degrees.

File No. **T-0329-4305-00 JP**

## 6 TEST CONDITIONS AND RESULTS


### 6.1 Conducted disturbance

For test instruments and accessories used see section 7 Part A 4.

#### 6.1.1 Description of the test location

Test location:                      Shielded Room SK4

#### 6.1.2 Photo documentation of the test set-up



#### 6.1.3 Test specification

Environmental conditions:    Temperature: 23 ° C                      Humidity: 41 %                      Atmospheric pressure: 98 kPa

Frequency range:                      0.15 MHz - 30 MHz

The test was carried out in the following operation mode(s):

- test software active, CH27 (5755MHz) adjusted

#### 6.1.4 Test result

Minimal margin to limit    3,7 dB at 12,6 MHz

The requirements are **FULFILLED**.

Remarks:                      The test with one set of antenna ANC000421 10dBi.


File No. **T-0329-4305-00 JP**

### 6.1.5 Test protocol

Test point: L1  
 Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: The measurement was made at AC input port of the DC Power supply, Antenna ANC000421 10dBi connected, adjustable attenuator set to 14dB  
 Date: 2012-02-28  
 Tested by: Pessinger Jürgen

Result: SCAN

Start frequency [MHZ]	Stop frequency [MHZ]	Resolution bandwidth	step size	Measurement time	Detector
0.15	30	10 kHz	5 kHz	10 ms	Peak




File No. **T-0329-4305-00 JP**



Test point: L1  
 Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: The measurement was made at AC input port of the DC Power supply, Antenna ANC000421 10dBi connected, adjustable attenuator set to 14dB  
 Date: 2012-02-28  
 Tested by: Pessinger Jürgen

Result: PASS



Minimum margin to limit: 8,0 dB


Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV]		Limit [dBμV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
14,239	34,3	33,0	0,4	34,7	33,4	60,0	50,0	25,3	16,6
24,409	31,5	29,1	0,5	32,0	29,6	60,0	50,0	28,0	20,4
28,478	39,6	38,0	0,6	40,2	38,6	60,0	50,0	19,8	11,4
29,291	43,3	41,4	0,6	43,9	42,0	60,0	50,0	16,1	8,0

File No. **T-0329-4305-00 JP**

Test point: N  
 Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: The measurement was made at AC input port of the DC  
 Power supply, Antenna ANC000421 10dBi connected,  
 adjustable attenuator set to 14dB  
 Date: 2012-02-28  
 Tested by: Pessinger Jürgen

Result: SCAN


Start frequency [MHz]	Stop frequency [MHz]	Resolution bandwidth	step size	Measurement time	Detector
0.15	30	10 kHz	5 kHz	10 ms	Peak



File No. **T-0329-4305-00 JP**

Test point: N  
 Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: The measurement was made at AC input port of the DC Power supply, Antenna ANC000421 10dBi connected, adjustable attenuator set to 14dB  
 Date: 2012-02-28  
 Tested by: Pessinger Jürgen

Result: PASS



Minimum margin to limit: 3,7 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV]		Limit [dBμV]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
8,137	46,0	45,3	0,3	46,3	45,6	60,0	50,0	13,7	4,4
12,612	46,7	45,9	0,4	47,1	46,3	60,0	50,0	12,9	3,7
29,291	46,1	44,0	0,6	46,7	44,6	60,0	50,0	13,3	5,4

File No. T-0329-4305-00 JP

## 6.2 Radiated disturbance (9kHz – 30MHz)

For test instruments and accessories used see section 7 Part **SER 1**.

### 6.2.1 Description of the test location

Test location: OATS 3

Test distance: 3 metres

### 6.2.2 Photo documentation of the test set-up



### 6.2.3 Test specification

Environmental conditions: Temperature: 19 ° C Humidity: 42 % Atmospheric pressure: 99 kPa

Frequency range: 0,009 MHz - 30 MHz

The test was carried out in the following operation mode(s):

- test software active, CH00 (5871MHz) adjusted
- test software active, CH27 (5755MHz) adjusted
- test software active, CH53 (5729MHz) adjusted

### 6.2.4 Test result

The requirements are **FULFILLED**.

**Remarks:** The prescan shows that the Peak value is below the Average / QuasiPeak limit, therefore  
no final measurement was made.  
The test was performed with 4 sets of antenna types, refer to 4.3 EuT configuration.

File No. **T-0329-4305-00 JP**

### 6.2.5 Test protocol

Operation mode: test software active, CH00 (5871MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

				Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]	QP	AV
	QP	AV	QP	AV	QP	AV	AV
--	--						

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

				Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]	QP	AV
	QP	AV	QP	AV	QP	AV	AV
--	--						

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

				Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]	QP	AV
	QP	AV	QP	AV	QP	AV	AV
--	--						

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH00 (5871MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

						Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]	QP	AV	QP	AV
	QP	AV	QP	AV	QP	AV	QP	AV	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

						Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]	QP	AV	QP	AV
	QP	AV	QP	AV	QP	AV	QP	AV	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

						Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]	QP	AV	QP	AV
	QP	AV	QP	AV	QP	AV	QP	AV	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

Result: PASS

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	QP	AV		QP	AV	QP	AV	QP	AV
--	--								

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH27 (5755MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

Operation mode: test software active, CH53 (5729MHz) adjusted Result: PASS  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-22  
 Tested by: Pessinger Jürgen

		Minimum margin to limit:		-- dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]
	QP	AV	QP	AV	QP
--	--				

No emission (peak detector) exceeds the AV/QP limit of section 15.209 in the frequency range 0,009MHz to 30MHz.

File No. **T-0329-4305-00 JP**



### 6.3 Radiated disturbance (30MHz – 1000MHz)

For test instruments and accessories used see section 7 Part SER 2.

#### 6.3.1 Description of the test location

Test location: OATS 3

Test distance: 3 metres

#### 6.3.2 Photo documentation of the test set-up



#### 6.3.3 Test specification

Environmental conditions: Temperature: 18 ° C Humidity: 41 % Atmospheric pressure: 98 kPa

Frequency range: 30 MHz - 1000 MHz

The test was carried out in the following operation mode(s):

- test software active, CH00 (5871MHz) adjusted
- test software active, CH27 (5755MHz) adjusted
- test software active, CH53 (5729MHz) adjusted

#### 6.3.4 Test result

Minimal margin to limit 0,2 dB at 72,4 MHz

The requirements are **FULFILLED**.

**Remarks:** The test was performed with 4 sets of antenna types, refer to 4.3 EuT configuration.


File No. **T-0329-4305-00 JP**

### 6.3.5 Test protocol

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: **0,7 dB**


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,5	10,6	25,1	43,5	18,5
183,019	25,6	12,4	38,0	43,5	5,5
186,274	28,2	12,7	40,9	43,5	2,6
189,526	29,0	13,0	41,9	43,5	1,6
192,390	29,6	13,1	43,3	43,5	0,7
194,818	29,5	13,3	42,8	43,5	0,7
196,446	28,3	13,3	41,7	43,5	1,9
198,926	29,0	13,4	42,4	43,5	1,1
201,331	26,4	13,5	39,9	43,5	3,7
205,816	21,0	13,5	34,5	43,5	9,1
231,028	9,5	14,5	24,0	46,0	22,0
235,922	7,3	14,8	22,0	46,0	24,0
242,418	10,7	14,9	25,6	46,0	20,4

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,7 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,0	13,6	33,6	40,0	6,4
32,944	18,3	13,8	32,1	40,0	7,9
67,935	25,6	11,6	37,2	40,0	2,8
70,378	26,6	11,2	37,7	40,0	2,3
72,406	28,3	11,1	39,3	40,0	0,7
74,850	26,9	10,9	37,9	40,0	2,1
76,067	27,7	10,9	38,6	40,0	1,4
78,506	25,0	10,9	36,0	40,0	4,0
127,733	23,1	11,3	34,3	43,5	9,2
186,300	27,2	12,7	39,9	43,5	3,6
189,969	27,6	13,0	40,6	43,5	2,9
191,194	25,7	13,1	38,8	43,5	4,8
231,040	16,3	14,5	30,8	46,0	15,2

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,8 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,8	10,6	24,4	43,5	19,1
183,019	24,9	12,4	37,3	43,5	6,2
186,274	27,9	12,7	40,6	43,5	2,9
189,526	28,6	13,0	41,5	43,5	2,0
192,390	29,6	13,1	42,8	43,5	0,8
194,818	29,4	13,3	42,7	43,5	0,8
196,446	28,3	13,3	41,7	43,5	1,8
198,926	28,4	13,4	41,8	43,5	1,7
201,331	26,6	13,5	40,1	43,5	3,4
205,816	21,0	13,5	34,5	43,5	9,0
231,028	10,0	14,5	24,5	46,0	21,5
235,922	7,8	14,8	22,5	46,0	23,5
242,418	10,3	14,9	25,2	46,0	20,8

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 1 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,2	13,6	33,8	40,0	6,2
32,944	18,7	13,8	32,5	40,0	7,5
67,935	26,5	11,6	38,1	40,0	1,9
70,378	27,2	11,2	38,3	40,0	1,7
72,406	28,4	11,1	39,5	40,0	0,5
74,850	27,6	10,9	38,5	40,0	1,5
76,067	28,2	10,9	39,1	40,0	0,9
78,506	25,5	10,9	36,5	40,0	3,5
127,733	22,8	11,3	34,1	43,5	9,4
186,300	27,2	12,7	39,9	43,5	3,6
189,969	27,7	13,0	40,7	43,5	2,8
191,194	26,3	13,1	39,4	43,5	4,1
231,040	17,4	14,5	31,9	46,0	14,1

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 1 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,6 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,8	10,6	24,4	43,5	19,1
183,019	25,1	12,4	37,5	43,5	6,0
186,274	27,9	12,7	40,6	43,5	2,9
189,526	29,1	13,0	42,0	43,5	1,5
192,390	29,8	13,1	42,9	43,5	0,6
194,818	29,1	13,3	42,4	43,5	1,1
196,446	29,0	13,3	42,4	43,5	1,2
198,926	28,6	13,4	42,0	43,5	1,5
201,331	26,3	13,5	39,7	43,5	3,8
205,816	21,0	13,5	34,5	43,5	9,0
231,028	9,8	14,5	24,3	46,0	21,7
235,922	7,1	14,8	21,8	46,0	24,2
242,418	10,2	14,9	25,1	46,0	20,9


File No. T-0329-4305-00 JP



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,3	13,6	33,9	40,0	6,1
32,944	19,2	13,8	33,0	40,0	7,0
67,935	26,3	11,6	37,9	40,0	2,1
70,378	27,0	11,2	38,2	40,0	1,8
72,406	28,4	11,1	39,5	40,0	0,5
74,850	27,9	10,9	38,8	40,0	1,2
76,067	28,6	10,9	39,5	40,0	0,5
78,506	26,2	10,9	37,1	40,0	2,9
127,733	23,6	11,3	34,9	43,5	8,7
186,300	27,8	12,7	40,5	43,5	3,1
189,969	27,9	13,0	40,9	43,5	2,7
191,194	25,9	13,1	39,0	43,5	4,5
231,040	17,2	14,5	31,7	46,0	14,3

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 2 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,7	10,6	24,3	43,5	19,2
183,019	24,8	12,4	37,2	43,5	6,3
186,274	28,2	12,7	40,9	43,5	2,6
189,526	28,4	13,0	41,4	43,5	2,1
192,390	29,9	13,1	43,1	43,5	0,5
194,818	29,5	13,3	42,8	43,5	0,7
196,446	28,2	13,3	41,5	43,5	2,0
198,926	28,9	13,4	42,4	43,5	1,2
201,331	26,2	13,5	39,7	43,5	3,9
205,816	21,3	13,5	34,8	43,5	8,8
231,028	9,6	14,5	24,1	46,0	21,9
235,922	7,8	14,8	22,6	46,0	23,4
242,418	10,3	14,9	25,3	46,0	20,8

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,3 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,5	13,6	33,1	40,0	6,9
32,944	18,7	13,8	32,5	40,0	7,5
67,935	26,1	11,6	37,7	40,0	2,3
70,378	27,0	11,2	38,2	40,0	1,8
72,406	28,6	11,1	39,7	40,0	0,3
74,850	27,6	10,9	38,5	40,0	1,5
76,067	27,8	10,9	38,7	40,0	1,3
78,506	25,5	10,9	36,4	40,0	3,6
127,733	22,6	11,3	33,8	43,5	9,7
186,300	27,8	12,7	40,5	43,5	3,0
189,969	27,2	13,0	40,2	43,5	3,3
191,194	25,8	13,1	38,9	43,5	4,7
231,040	16,9	14,5	31,4	46,0	14,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,6 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,1	10,6	24,7	43,5	18,8
183,019	24,8	12,4	37,2	43,5	6,3
186,274	28,6	12,7	41,3	43,5	2,2
189,526	29,3	13,0	42,2	43,5	1,3
192,390	29,8	13,1	42,9	43,5	0,6
194,818	28,6	13,3	41,9	43,5	1,6
196,446	28,2	13,3	41,5	43,5	2,0
198,926	29,1	13,4	42,5	43,5	1,0
201,331	26,4	13,5	39,8	43,5	3,7
205,816	21,0	13,5	34,5	43,5	9,1
231,028	9,8	14,5	24,3	46,0	21,7
235,922	7,9	14,8	22,7	46,0	23,4
242,418	10,7	14,9	25,6	46,0	20,4

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 2 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,9 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,2	13,6	33,8	40,0	6,2
32,944	18,7	13,8	32,5	40,0	7,5
67,935	26,7	11,6	38,4	40,0	1,6
70,378	27,6	11,2	38,7	40,0	1,3
72,406	28,0	11,1	39,1	40,0	0,9
74,850	27,7	10,9	38,6	40,0	1,4
76,067	28,0	10,9	39,0	40,0	1,0
78,506	26,1	10,9	37,1	40,0	2,9
127,733	23,0	11,3	34,3	43,5	9,3
186,300	28,0	12,7	40,7	43,5	2,8
189,969	27,4	13,0	40,4	43,5	3,1
191,194	26,4	13,1	39,5	43,5	4,0
231,040	16,7	14,5	31,2	46,0	14,8

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,8 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,1	10,6	24,7	43,5	18,8
183,019	24,7	12,4	37,1	43,5	6,4
186,274	27,9	12,7	40,5	43,5	3,0
189,526	29,2	13,0	42,2	43,5	1,3
192,390	29,5	13,1	42,7	43,5	0,8
194,818	29,3	13,3	42,6	43,5	1,0
196,446	28,8	13,3	42,1	43,5	1,4
198,926	28,3	13,4	41,7	43,5	1,8
201,331	25,7	13,5	39,2	43,5	4,3
205,816	21,2	13,5	34,7	43,5	8,8
231,028	9,1	14,5	23,7	46,0	22,4
235,922	7,6	14,8	22,3	46,0	23,7
242,418	10,0	14,9	25,0	46,0	21,1


File No. T-0329-4305-00 JP



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,6	13,6	33,2	40,0	6,8
32,944	18,2	13,8	32,0	40,0	8,0
67,935	26,3	11,6	37,9	40,0	2,1
70,378	27,1	11,2	38,3	40,0	1,7
72,406	28,5	11,1	39,5	40,0	0,5
74,850	27,6	10,9	38,6	40,0	1,4
76,067	27,9	10,9	38,9	40,0	1,1
78,506	25,5	10,9	36,4	40,0	3,6
127,733	22,5	11,3	33,8	43,5	9,7
186,300	27,0	12,7	39,7	43,5	3,8
189,969	27,6	13,0	40,6	43,5	2,9
191,194	25,6	13,1	38,6	43,5	4,9
231,040	17,0	14,5	31,5	46,0	14,5

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,6 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,5	10,6	25,1	43,5	18,4
183,019	25,3	12,4	37,7	43,5	5,8
186,274	28,4	12,7	41,1	43,5	2,5
189,526	28,6	13,0	41,6	43,5	1,9
192,390	29,4	13,1	42,5	43,5	1,0
194,818	29,7	13,3	42,9	43,5	0,6
196,446	28,7	13,3	42,1	43,5	1,5
198,926	29,0	13,4	42,4	43,5	1,1
201,331	26,0	13,5	39,4	43,5	4,1
205,816	21,1	13,5	34,6	43,5	9,0
231,028	9,6	14,5	24,1	46,0	21,9
235,922	8,0	14,8	22,8	46,0	23,2
242,418	10,0	14,9	24,9	46,0	21,1

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,9	13,6	33,5	40,0	6,5
32,944	19,1	13,8	32,9	40,0	7,1
67,935	25,7	11,6	37,3	40,0	2,7
70,378	27,4	11,2	38,6	40,0	1,4
72,406	28,0	11,1	39,0	40,0	1,0
74,850	27,7	10,9	38,7	40,0	1,3
76,067	28,5	10,9	39,5	40,0	0,5
78,506	25,2	10,9	36,1	40,0	3,9
127,733	22,9	11,3	34,1	43,5	9,4
186,300	27,1	12,7	39,8	43,5	3,7
189,969	27,4	13,0	40,4	43,5	3,1
191,194	25,7	13,1	38,7	43,5	4,8
231,040	16,4	14,5	31,0	46,0	15,1

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,8 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,9	10,6	24,5	43,5	19,0
183,019	24,6	12,4	37,1	43,5	6,5
186,274	28,6	12,7	41,3	43,5	2,2
189,526	29,2	13,0	42,2	43,5	1,3
192,390	29,6	13,1	42,7	43,5	0,8
194,818	29,2	13,3	42,5	43,5	1,0
196,446	28,6	13,3	42,0	43,5	1,5
198,926	28,4	13,4	41,8	43,5	1,7
201,331	26,5	13,5	39,9	43,5	3,6
205,816	21,3	13,5	34,8	43,5	8,7
231,028	10,0	14,5	24,5	46,0	21,5
235,922	7,1	14,8	21,9	46,0	24,2
242,418	10,5	14,9	25,4	46,0	20,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000421 10dBi connected, adjustable  
attenuator set to 14dB, Antenna Port 1 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 1,0 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,4	13,6	34,0	40,0	6,0
32,944	18,7	13,8	32,5	40,0	7,5
67,935	25,8	11,6	37,4	40,0	2,6
70,378	26,9	11,2	38,1	40,0	1,9
72,406	28,0	11,1	39,0	40,0	1,0
74,850	27,8	10,9	38,7	40,0	1,3
76,067	27,8	10,9	38,8	40,0	1,2
78,506	25,7	10,9	36,6	40,0	3,4
127,733	23,4	11,3	34,7	43,5	8,8
186,300	27,4	12,7	40,1	43,5	3,4
189,969	27,8	13,0	40,8	43,5	2,7
191,194	25,5	13,1	38,6	43,5	4,9
231,040	16,4	14,5	30,9	46,0	15,1

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,5 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,8	10,6	24,4	43,5	19,2
183,019	24,9	12,4	37,3	43,5	6,2
186,274	28,7	12,7	41,4	43,5	2,1
189,526	28,6	13,0	41,5	43,5	2,0
192,390	29,9	13,1	43,0	43,5	0,5
194,818	28,9	13,3	42,2	43,5	1,3
196,446	29,2	13,3	42,5	43,5	1,0
198,926	28,5	13,4	42,0	43,5	1,6
201,331	26,2	13,5	39,7	43,5	3,8
205,816	21,6	13,5	35,1	43,5	8,4
231,028	9,4	14,5	23,9	46,0	22,1
235,922	7,5	14,8	22,3	46,0	23,7
242,418	9,9	14,9	24,8	46,0	21,2


File No. T-0329-4305-00 JP



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,7 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,8	13,6	33,4	40,0	6,6
32,944	18,4	13,8	32,2	40,0	7,8
67,935	25,8	11,6	37,4	40,0	2,6
70,378	27,4	11,2	38,6	40,0	1,4
72,406	28,2	11,1	39,3	40,0	0,7
74,850	26,8	10,9	37,7	40,0	2,3
76,067	27,8	10,9	38,7	40,0	1,3
78,506	25,2	10,9	36,1	40,0	3,9
127,733	22,6	11,3	33,9	43,5	9,6
186,300	27,5	12,7	40,2	43,5	3,3
189,969	27,5	13,0	40,5	43,5	3,0
191,194	25,6	13,1	38,6	43,5	4,9
231,040	16,9	14,5	31,5	46,0	14,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,4 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,6	10,6	24,2	43,5	19,3
183,019	25,1	12,4	37,5	43,5	6,0
186,274	27,9	12,7	40,6	43,5	2,9
189,526	29,0	13,0	41,9	43,5	1,6
192,390	30,0	13,1	43,1	43,5	0,4
194,818	29,1	13,3	42,4	43,5	1,1
196,446	29,0	13,3	42,4	43,5	1,1
198,926	28,7	13,4	42,1	43,5	1,4
201,331	25,7	13,5	39,2	43,5	4,3
205,816	20,8	13,5	34,3	43,5	9,2
231,028	9,9	14,5	24,4	46,0	21,6
235,922	7,7	14,8	22,4	46,0	23,6
242,418	10,6	14,9	25,5	46,0	20,5

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,9 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,7	13,6	33,3	40,0	6,7
32,944	18,6	13,8	32,4	40,0	7,6
67,935	25,7	11,6	37,3	40,0	2,7
70,378	26,4	11,2	37,6	40,0	2,4
72,406	28,0	11,1	39,1	40,0	0,9
74,850	27,2	10,9	38,2	40,0	1,8
76,067	27,6	10,9	38,5	40,0	1,5
78,506	25,3	10,9	36,2	40,0	3,8
127,733	23,4	11,3	34,7	43,5	8,8
186,300	27,3	12,7	39,9	43,5	3,6
189,969	27,0	13,0	40,0	43,5	3,5
191,194	26,1	13,1	39,2	43,5	4,3
231,040	16,5	14,5	31,1	46,0	14,9

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,7 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,9	10,6	25,5	43,5	18,0
183,019	25,7	12,4	38,1	43,5	5,4
186,274	28,9	12,7	41,6	43,5	1,9
189,526	29,3	13,0	42,2	43,5	1,3
192,390	29,7	13,1	42,8	43,5	0,7
194,818	29,4	13,3	42,7	43,5	0,8
196,446	28,8	13,3	42,1	43,5	1,4
198,926	28,8	13,4	42,2	43,5	1,3
201,331	26,2	13,5	39,7	43,5	3,8
205,816	21,7	13,5	35,2	43,5	8,3
231,028	10,5	14,5	25,0	46,0	21,0
235,922	8,2	14,8	22,9	46,0	23,1
242,418	11,0	14,9	26,0	46,0	20,0

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,3 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,8	13,6	33,4	40,0	6,6
32,944	18,9	13,8	32,7	40,0	7,3
67,935	26,6	11,6	38,2	40,0	1,8
70,378	27,0	11,2	38,1	40,0	1,9
72,406	28,6	11,1	39,8	40,0	0,3
74,850	27,8	10,9	38,7	40,0	1,3
76,067	28,3	10,9	39,2	40,0	0,8
78,506	25,6	10,9	36,5	40,0	3,5
127,733	23,1	11,3	34,3	43,5	9,2
186,300	28,0	12,7	40,7	43,5	2,8
189,969	27,5	13,0	40,5	43,5	3,0
191,194	26,3	13,1	39,3	43,5	4,2
231,040	16,6	14,5	31,1	46,0	14,9

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,8 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,1	10,6	24,7	43,5	18,8
183,019	24,5	12,4	36,9	43,5	6,6
186,274	28,7	12,7	41,4	43,5	2,1
189,526	29,2	13,0	42,1	43,5	1,4
192,390	29,6	13,1	42,7	43,5	0,8
194,818	29,3	13,3	42,6	43,5	0,9
196,446	28,5	13,3	41,8	43,5	1,7
198,926	28,6	13,4	42,0	43,5	1,5
201,331	26,3	13,5	39,8	43,5	3,8
205,816	21,2	13,5	34,7	43,5	8,9
231,028	10,0	14,5	24,5	46,0	21,5
235,922	7,2	14,8	21,9	46,0	24,1
242,418	9,9	14,9	24,9	46,0	21,1


File No. T-0329-4305-00 JP



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,8 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,3	13,6	33,9	40,0	6,1
32,944	18,8	13,8	32,6	40,0	7,4
67,935	26,0	11,6	37,6	40,0	2,4
70,378	26,9	11,2	38,1	40,0	1,9
72,406	28,1	11,1	39,2	40,0	0,8
74,850	27,8	10,9	38,7	40,0	1,3
76,067	27,8	10,9	38,7	40,0	1,3
78,506	25,5	10,9	36,4	40,0	3,6
127,733	23,3	11,3	34,6	43,5	8,9
186,300	27,4	12,7	40,1	43,5	3,5
189,969	27,3	13,0	40,3	43,5	3,2
191,194	25,8	13,1	38,9	43,5	4,7
231,040	16,9	14,5	31,4	46,0	14,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,8 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,4	10,6	25,0	43,5	18,5
183,019	25,2	12,4	37,6	43,5	5,9
186,274	28,4	12,7	41,1	43,5	2,4
189,526	28,5	13,0	41,5	43,5	2,0
192,390	29,6	13,1	42,8	43,5	0,8
194,818	28,8	13,3	42,1	43,5	1,4
196,446	28,2	13,3	41,5	43,5	2,0
198,926	29,2	13,4	42,6	43,5	0,9
201,331	25,7	13,5	39,2	43,5	4,3
205,816	21,4	13,5	34,9	43,5	8,6
231,028	9,7	14,5	24,2	46,0	21,8
235,922	7,9	14,8	22,7	46,0	23,4
242,418	10,3	14,9	25,2	46,0	20,8

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,8 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,9	13,6	33,5	40,0	6,5
32,944	18,8	13,8	32,6	40,0	7,4
67,935	26,1	11,6	37,8	40,0	2,2
70,378	27,1	11,2	38,3	40,0	1,7
72,406	28,1	11,1	39,2	40,0	0,8
74,850	27,6	10,9	38,5	40,0	1,5
76,067	27,9	10,9	38,8	40,0	1,2
78,506	25,8	10,9	36,8	40,0	3,2
127,733	22,8	11,3	34,0	43,5	9,5
186,300	27,8	12,7	40,5	43,5	3,0
189,969	27,1	13,0	40,1	43,5	3,4
191,194	25,6	13,1	38,7	43,5	4,8
231,040	16,7	14,5	31,3	46,0	14,7

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,7 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,9	10,6	24,5	43,5	19,1
183,019	25,5	12,4	37,9	43,5	5,6
186,274	28,0	12,7	40,6	43,5	2,9
189,526	28,6	13,0	41,6	43,5	2,0
192,390	29,6	13,1	42,8	43,5	0,8
194,818	29,5	13,3	42,8	43,5	0,7
196,446	28,9	13,3	42,2	43,5	1,3
198,926	28,5	13,4	41,9	43,5	1,6
201,331	26,1	13,5	39,5	43,5	4,0
205,816	21,6	13,5	35,1	43,5	8,4
231,028	10,0	14,5	24,6	46,0	21,5
235,922	7,5	14,8	22,3	46,0	23,7
242,418	10,0	14,9	25,0	46,0	21,0

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,6 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,7	13,6	33,3	40,0	6,7
32,944	18,5	13,8	32,3	40,0	7,7
67,935	26,1	11,6	37,8	40,0	2,2
70,378	26,7	11,2	37,9	40,0	2,1
72,406	28,4	11,1	39,4	40,0	0,6
74,850	27,7	10,9	38,7	40,0	1,3
76,067	27,9	10,9	38,8	40,0	1,2
78,506	25,7	10,9	36,6	40,0	3,4
127,733	22,9	11,3	34,1	43,5	9,4
186,300	27,5	12,7	40,2	43,5	3,4
189,969	27,3	13,0	40,3	43,5	3,2
191,194	25,6	13,1	38,7	43,5	4,8
231,040	16,9	14,5	31,4	46,0	14,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,4 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,6	10,6	25,2	43,5	18,3
183,019	25,3	12,4	37,7	43,5	5,8
186,274	28,5	12,7	41,2	43,5	2,3
189,526	28,9	13,0	41,9	43,5	1,6
192,390	30,0	13,1	43,1	43,5	0,4
194,818	29,6	13,3	42,9	43,5	0,7
196,446	29,3	13,3	42,7	43,5	0,8
198,926	29,1	13,4	42,5	43,5	1,0
201,331	27,0	13,5	40,5	43,5	3,1
205,816	21,4	13,5	34,9	43,5	8,6
231,028	10,1	14,5	24,7	46,0	21,3
235,922	7,7	14,8	22,4	46,0	23,6
242,418	10,5	14,9	25,4	46,0	20,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,6 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,6	13,6	33,2	40,0	6,8
32,944	18,9	13,8	32,7	40,0	7,3
67,935	25,9	11,6	37,5	40,0	2,5
70,378	27,5	11,2	38,6	40,0	1,4
72,406	27,9	11,1	38,9	40,0	1,1
74,850	27,0	10,9	37,9	40,0	2,1
76,067	28,5	10,9	39,4	40,0	0,6
78,506	25,7	10,9	36,7	40,0	3,3
127,733	22,6	11,3	33,9	43,5	9,6
186,300	27,8	12,7	40,5	43,5	3,0
189,969	27,9	13,0	40,9	43,5	2,7
191,194	25,8	13,1	38,8	43,5	4,7
231,040	16,3	14,5	30,9	46,0	15,1


File No. T-0329-4305-00 JP



Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,7 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,6	10,6	24,2	43,5	19,3
183,019	24,5	12,4	36,9	43,5	6,6
186,274	28,0	12,7	40,7	43,5	2,8
189,526	28,4	13,0	41,4	43,5	2,1
192,390	29,7	13,1	42,8	43,5	0,7
194,818	29,2	13,3	42,5	43,5	1,0
196,446	28,3	13,3	41,7	43,5	1,9
198,926	28,6	13,4	42,0	43,5	1,5
201,331	25,9	13,5	39,3	43,5	4,2
205,816	21,1	13,5	34,6	43,5	9,0
231,028	9,4	14,5	24,0	46,0	22,0
235,922	8,0	14,8	22,7	46,0	23,3
242,418	10,5	14,9	25,5	46,0	20,5

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,2 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,3	13,6	33,9	40,0	6,1
32,944	18,3	13,8	32,1	40,0	7,9
67,935	26,0	11,6	37,6	40,0	2,4
70,378	27,4	11,2	38,6	40,0	1,4
72,406	28,7	11,1	39,8	40,0	0,2
74,850	26,8	10,9	37,8	40,0	2,2
76,067	28,0	10,9	38,9	40,0	1,1
78,506	25,8	10,9	36,8	40,0	3,2
127,733	22,6	11,3	33,9	43,5	9,6
186,300	27,2	12,7	39,9	43,5	3,6
189,969	27,5	13,0	40,4	43,5	3,1
191,194	25,8	13,1	38,8	43,5	4,7
231,040	16,7	14,5	31,3	46,0	14,7

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,0	10,6	24,6	43,5	18,9
183,019	24,9	12,4	37,3	43,5	6,2
186,274	27,9	12,7	40,6	43,5	2,9
189,526	29,4	13,0	42,3	43,5	1,2
192,390	29,8	13,1	43,0	43,5	0,5
194,818	29,2	13,3	42,5	43,5	1,0
196,446	28,7	13,3	42,1	43,5	1,4
198,926	28,7	13,4	42,1	43,5	1,4
201,331	26,0	13,5	39,5	43,5	4,0
205,816	20,8	13,5	34,3	43,5	9,2
231,028	10,0	14,5	24,6	46,0	21,4
235,922	7,7	14,8	22,5	46,0	23,5
242,418	10,3	14,9	25,2	46,0	20,8

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,6 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,0	13,6	33,6	40,0	6,4
32,944	18,4	13,8	32,2	40,0	7,8
67,935	26,2	11,6	37,8	40,0	2,2
70,378	27,0	11,2	38,2	40,0	1,8
72,406	28,3	11,1	39,4	40,0	0,6
74,850	27,0	10,9	37,9	40,0	2,1
76,067	27,9	10,9	38,8	40,0	1,2
78,506	25,6	10,9	36,5	40,0	3,5
127,733	23,1	11,3	34,4	43,5	9,1
186,300	27,3	12,7	40,0	43,5	3,5
189,969	27,2	13,0	40,2	43,5	3,3
191,194	25,6	13,1	38,6	43,5	4,9
231,040	17,0	14,5	31,5	46,0	14,5

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,8 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,8	10,6	24,4	43,5	19,1
183,019	25,0	12,4	37,4	43,5	6,1
186,274	27,8	12,7	40,5	43,5	3,0
189,526	28,6	13,0	41,5	43,5	2,0
192,390	29,4	13,1	42,5	43,5	1,0
194,818	29,4	13,3	42,7	43,5	0,8
196,446	28,7	13,3	42,0	43,5	1,5
198,926	28,8	13,4	42,3	43,5	1,3
201,331	26,4	13,5	39,9	43,5	3,6
205,816	20,8	13,5	34,3	43,5	9,3
231,028	9,1	14,5	23,7	46,0	22,3
235,922	7,3	14,8	22,1	46,0	23,9
242,418	9,6	14,9	24,6	46,0	21,5

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000468 13dBi connected, adjustable  
attenuator set to 6dB, Antenna Port 2 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,9 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,0	13,6	33,6	40,0	6,4
32,944	18,3	13,8	32,1	40,0	7,9
67,935	26,1	11,6	37,7	40,0	2,3
70,378	27,2	11,2	38,4	40,0	1,6
72,406	28,0	11,1	39,1	40,0	0,9
74,850	27,6	10,9	38,5	40,0	1,5
76,067	27,9	10,9	38,9	40,0	1,1
78,506	25,6	10,9	36,5	40,0	3,5
127,733	23,3	11,3	34,6	43,5	9,0
186,300	27,2	12,7	39,9	43,5	3,6
189,969	27,2	13,0	40,2	43,5	3,3
191,194	25,8	13,1	38,9	43,5	4,6
231,040	16,5	14,5	31,0	46,0	15,0

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,6 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,1	10,6	24,7	43,5	18,8
183,019	25,1	12,4	37,5	43,5	6,0
186,274	28,3	12,7	41,0	43,5	2,5
189,526	29,0	13,0	42,0	43,5	1,6
192,390	29,8	13,1	42,9	43,5	0,6
194,818	29,2	13,3	42,5	43,5	1,0
196,446	28,7	13,3	42,0	43,5	1,5
198,926	28,8	13,4	42,2	43,5	1,3
201,331	26,3	13,5	39,8	43,5	3,8
205,816	21,3	13,5	34,8	43,5	8,7
231,028	9,7	14,5	24,2	46,0	21,8
235,922	7,6	14,8	22,4	46,0	23,7
242,418	10,3	14,9	25,2	46,0	20,8


File No. T-0329-4305-00 JP



Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,6 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,0	13,6	33,6	40,0	6,4
32,944	18,7	13,8	32,5	40,0	7,5
67,935	26,1	11,6	37,7	40,0	2,3
70,378	27,0	11,2	38,2	40,0	1,8
72,406	28,3	11,1	39,4	40,0	0,6
74,850	27,4	10,9	38,3	40,0	1,7
76,067	28,2	10,9	39,1	40,0	0,9
78,506	25,6	10,9	36,5	40,0	3,5
127,733	23,1	11,3	34,4	43,5	9,2
186,300	27,5	12,7	40,2	43,5	3,3
189,969	27,4	13,0	40,4	43,5	3,1
191,194	25,9	13,1	39,0	43,5	4,6
231,040	16,8	14,5	31,3	46,0	14,7

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,4 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,0	10,6	24,6	43,5	19,0
183,019	24,9	12,4	37,3	43,5	6,2
186,274	27,9	12,7	40,6	43,5	2,9
189,526	29,0	13,0	41,9	43,5	1,6
192,390	30,0	13,1	43,1	43,5	0,4
194,818	29,7	13,3	43,0	43,5	0,6
196,446	28,4	13,3	41,8	43,5	1,7
198,926	28,7	13,4	42,2	43,5	1,4
201,331	26,1	13,5	39,6	43,5	4,0
205,816	21,1	13,5	34,5	43,5	9,0
231,028	10,0	14,5	24,6	46,0	21,5
235,922	7,5	14,8	22,3	46,0	23,8
242,418	10,6	14,9	25,5	46,0	20,5

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,7 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,9	13,6	33,5	40,0	6,5
32,944	18,2	13,8	32,0	40,0	8,0
67,935	25,9	11,6	37,5	40,0	2,5
70,378	26,9	11,2	38,1	40,0	1,9
72,406	28,2	11,1	39,3	40,0	0,7
74,850	27,5	10,9	38,4	40,0	1,6
76,067	27,8	10,9	38,7	40,0	1,3
78,506	25,6	10,9	36,6	40,0	3,4
127,733	22,8	11,3	34,1	43,5	9,4
186,300	27,0	12,7	39,7	43,5	3,8
189,969	27,1	13,0	40,1	43,5	3,4
191,194	26,1	13,1	39,1	43,5	4,4
231,040	17,2	14,5	31,8	46,0	14,3

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,4 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,0	10,6	24,6	43,5	18,9
183,019	25,4	12,4	37,8	43,5	5,8
186,274	28,1	12,7	40,8	43,5	2,7
189,526	29,2	13,0	42,1	43,5	1,4
192,390	30,0	13,1	43,2	43,5	0,4
194,818	29,2	13,3	42,5	43,5	1,1
196,446	28,7	13,3	42,0	43,5	1,5
198,926	29,1	13,4	42,5	43,5	1,0
201,331	26,2	13,5	39,6	43,5	3,9
205,816	21,6	13,5	35,1	43,5	8,4
231,028	9,7	14,5	24,3	46,0	21,8
235,922	7,2	14,8	21,9	46,0	24,1
242,418	10,2	14,9	25,2	46,0	20,8

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,7	13,6	33,3	40,0	6,7
32,944	18,8	13,8	32,6	40,0	7,4
67,935	26,1	11,6	37,7	40,0	2,3
70,378	26,6	11,2	37,8	40,0	2,2
72,406	28,4	11,1	39,5	40,0	0,5
74,850	27,2	10,9	38,1	40,0	1,9
76,067	27,8	10,9	38,7	40,0	1,3
78,506	25,4	10,9	36,4	40,0	3,6
127,733	23,2	11,3	34,5	43,5	9,1
186,300	27,2	12,7	39,9	43,5	3,6
189,969	27,6	13,0	40,6	43,5	2,9
191,194	26,4	13,1	39,4	43,5	4,1
231,040	16,6	14,5	31,2	46,0	14,9

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,4 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	13,9	10,6	24,5	43,5	19,0
183,019	25,0	12,4	37,4	43,5	6,1
186,274	28,0	12,7	40,7	43,5	2,8
189,526	29,4	13,0	42,4	43,5	1,1
192,390	29,9	13,1	43,1	43,5	0,4
194,818	29,6	13,3	42,9	43,5	0,6
196,446	29,1	13,3	42,5	43,5	1,1
198,926	28,5	13,4	41,9	43,5	1,6
201,331	26,4	13,5	39,9	43,5	3,7
205,816	21,6	13,5	35,1	43,5	8,5
231,028	10,0	14,5	24,5	46,0	21,5
235,922	7,9	14,8	22,7	46,0	23,4
242,418	10,8	14,9	25,7	46,0	20,3

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 2 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	20,4	13,6	34,0	40,0	6,0
32,944	18,6	13,8	32,3	40,0	7,7
67,935	26,0	11,6	37,6	40,0	2,4
70,378	26,5	11,2	37,7	40,0	2,3
72,406	28,3	11,1	39,4	40,0	0,6
74,850	27,3	10,9	38,2	40,0	1,8
76,067	28,6	10,9	39,5	40,0	0,5
78,506	26,1	10,9	37,0	40,0	3,0
127,733	23,2	11,3	34,4	43,5	9,1
186,300	27,1	12,7	39,7	43,5	3,8
189,969	27,2	13,0	40,2	43,5	3,3
191,194	25,6	13,1	38,7	43,5	4,8
231,040	16,5	14,5	31,0	46,0	15,0


File No. T-0329-4305-00 JP



Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 2 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,4 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,2	10,6	24,8	43,5	18,7
183,019	25,1	12,4	37,5	43,5	6,0
186,274	27,8	12,7	40,5	43,5	3,0
189,526	29,4	13,0	42,4	43,5	1,1
192,390	30,0	13,1	43,1	43,5	0,4
194,818	29,7	13,3	43,0	43,5	0,5
196,446	28,7	13,3	42,1	43,5	1,4
198,926	28,4	13,4	41,8	43,5	1,7
201,331	26,5	13,5	40,0	43,5	3,5
205,816	21,4	13,5	34,9	43,5	8,6
231,028	9,6	14,5	24,2	46,0	21,8
235,922	7,5	14,8	22,2	46,0	23,8
242,418	10,9	14,9	25,8	46,0	20,2

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,6 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,7	13,6	33,3	40,0	6,7
32,944	18,6	13,8	32,4	40,0	7,6
67,935	26,3	11,6	37,9	40,0	2,1
70,378	26,5	11,2	37,7	40,0	2,3
72,406	28,3	11,1	39,4	40,0	0,6
74,850	27,4	10,9	38,3	40,0	1,7
76,067	28,0	10,9	38,9	40,0	1,1
78,506	26,0	10,9	36,9	40,0	3,1
127,733	23,3	11,3	34,6	43,5	8,9
186,300	27,4	12,7	40,1	43,5	3,4
189,969	27,2	13,0	40,2	43,5	3,4
191,194	26,1	13,1	39,2	43,5	4,4
231,040	16,9	14,5	31,4	46,0	14,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-03-23  
 Tested by: Pessinger Jürgen

Result: PASS

horizontal



Minimum margin to limit: 0,9 dB


Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
137,865	14,3	10,6	24,9	43,5	18,6
183,019	25,3	12,4	37,7	43,5	5,8
186,274	28,1	12,7	40,8	43,5	2,7
189,526	29,0	13,0	42,0	43,5	1,5
192,390	29,5	13,1	42,6	43,5	0,9
194,818	28,8	13,3	42,1	43,5	1,4
196,446	28,4	13,3	41,7	43,5	1,8
198,926	29,1	13,4	42,5	43,5	1,0
201,331	26,0	13,5	39,5	43,5	4,0
205,816	21,2	13,5	34,7	43,5	8,8
231,028	9,9	14,5	24,5	46,0	21,6
235,922	6,9	14,8	21,7	46,0	24,3
242,418	10,5	14,9	25,4	46,0	20,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 2 active  
Date: 2012-03-23  
Tested by: Pessinger Jürgen

Result: PASS

vertical



Minimum margin to limit: 0,5 dB

Frequency [MHz]	Reading [dBµV] QP	Correction [dB]	Values [dBµV/m] QP	Limit [dBµV/m] QP	Margin [dB] QP
31,727	19,7	13,6	33,3	40,0	6,7
32,944	18,8	13,8	32,6	40,0	7,4
67,935	26,1	11,6	37,7	40,0	2,3
70,378	26,6	11,2	37,8	40,0	2,2
72,406	28,4	11,1	39,5	40,0	0,5
74,850	27,2	10,9	38,1	40,0	1,9
76,067	27,8	10,9	38,7	40,0	1,3
78,506	25,4	10,9	36,4	40,0	3,6
127,733	23,2	11,3	34,5	43,5	9,1
186,300	27,2	12,7	39,9	43,5	3,6
189,969	27,6	13,0	40,6	43,5	2,9
191,194	26,4	13,1	39,4	43,5	4,1
231,040	16,6	14,5	31,2	46,0	14,9

File No. T-0329-4305-00 JP

## 6.4 Radiated disturbance (1GHz – 40GHz)

For test instruments and accessories used see section 7 Part SER 3.

### 6.4.1 Description of the test location

Test location: Anechoic Chamber A4

Test distance: 3 metres

### 6.4.2 Photo documentation of the test set-up



### 6.4.3 Test specification

Environmental conditions: Temperature: 23 ° C Humidity: 34 % Atmospheric pressure: 96 kPa

Frequency range: 1 GHz – 40GHz

The test was carried out in the following operation mode(s):

- test software active, CH00 (5871MHz) adjusted
- test software active, CH27 (5755MHz) adjusted
- test software active, CH53 (5729MHz) adjusted

### 6.4.4 Test result

Minimal margin to limit 2,7 dB at 17,4 GHz

The requirements are **FULFILLED**.


Remarks: The test was performed with 4 sets of antenna types, refer to 4.3 EuT configuration.

File No. **T-0329-4305-00 JP**

### 6.4.5 Test protocol

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **12,2 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	50,4	35,6	-10,1	40,3	25,5	74,0	54,0	33,7	28,5
11511,000	52,6		8,8	61,4		74,0	54,0	12,6	
11763,000	52,8	32,2	9,0	61,8	41,2	74,0	54,0	12,2	12,8

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS



Minimum margin to limit: **4,9 dB**


Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	51,1	35,1	-10,5	40,6	24,6	74,0	54,0	33,4	29,4
11763,000	57,5	30,4	9,0	66,5	39,4	74,0	54,0	7,5	14,6
17601,000	50,0		19,0	69,1		74,0	54,0	4,9	

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 11,3 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1039,000	53,2		-11,8	41,4		74,0	54,0	32,6	
1481,000	50,5	35,0	-10,1	40,4	24,9	74,0	54,0	33,6	29,1
11511,000	53,9	32,3	8,8	62,7	41,1	74,0	54,0	11,3	12,9

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




		Minimum margin to limit:						7,9 dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]				
	PK	AV	PK	AV	PK	AV	PK	AV	
1325,000	51,5	35,3	41,0	24,8	74,0	54,0	33,0	29,2	
1494,000	51,2		41,2		74,0	54,0	32,8		
11511,000	55,7	32,1	64,5	40,9	74,0	54,0	9,5	13,1	
17265,000	51,1		66,1		74,0	54,0	7,9		

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 12,2 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	50,6	36,0	-10,1	40,5	25,9	74,0	54,0	33,5	28,1
1988,000	47,6		-7,1	40,5		74,0	54,0	33,4	
11427,000	52,3	30,8	8,9	61,1	39,6	74,0	54,0	12,9	14,3
11511,000	53,0		8,8	61,7		74,0	54,0	12,2	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




		Minimum margin to limit:						4,1 dB	
Frequency [MHz]	Reading [dBµV]	Correction [dB]	Values [dBµV/m]	Limit [dBµV/m]	Margin [dB]				
	PK	AV	PK	AV	PK	AV	PK	AV	
1325,000	51,1	36,7	40,6	26,2	74,0	54,0	33,4	27,8	
1988,000	49,7		42,6		74,0	54,0	31,4		
11427,000	55,3	31,6	64,2	40,5	74,0	54,0	9,8	13,5	
17790,000	50,6		69,8		74,0	54,0	4,1		

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 4,3 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	50,9	35,4	-10,1	40,8	25,3	74,0	54,0	33,2	28,7
11511,000	52,1		8,8	60,8		74,0	54,0	13,1	
11763,000	51,3	30,3	9,0	60,3	39,2	74,0	54,0	13,7	14,7
17643,000	50,4		19,2	69,6		74,0	54,0	4,3	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **4,9 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	51,0		-10,5	40,5		74,0	54,0	33,5	
1494,000	50,7	36,5	-10,1	40,6	26,4	74,0	54,0	33,4	27,6
1988,000	47,6		-7,1	40,5		74,0	54,0	33,5	
11511,000	53,6	30,0	8,8	62,4	38,8	74,0	54,0	11,6	15,2
11763,000	57,0	33,1	9,0	66,0	42,1	74,0	54,0	8,0	11,9
17622,000	49,9		19,1	69,1		74,0	54,0	4,9	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS



Minimum margin to limit: 5,0 dB


Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	50,7	35,1	-10,4	40,4	24,7	74,0	54,0	33,6	29,2
2001,000	48,2	28,3	-7,1	41,2	21,2	74,0	54,0	32,8	32,8
11490,000	52,8	32,5	8,8	61,5	41,3	74,0	54,0	12,4	12,7
11658,000	48,9		9,0	57,8		74,0	54,0	16,1	
17601,000	49,9		19,0	69,0		74,0	54,0	5,0	

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **4,8 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	51,3	35,4	-10,5	40,8	24,9	74,0	54,0	33,2	29,0
11490,000	54,2	30,1	8,8	63,0	38,9	74,0	54,0	11,0	15,1
11616,000	53,9		8,9	62,8		74,0	54,0	11,2	
17685,000	49,8		19,4	69,2		74,0	54,0	4,8	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **4,1 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	49,9	35,4	-10,4	39,5	25,0	74,0	54,0	34,5	29,0
1481,000	50,5		-10,1	40,4		74,0	54,0	33,6	
1884,000	48,5		-7,2	41,3		74,0	54,0	32,7	
11448,000	52,5	32,0	8,8	61,3	40,9	74,0	54,0	12,7	13,1
11511,000	53,8		8,8	62,6		74,0	54,0	11,4	
17622,000	50,8		19,1	69,9		74,0	54,0	4,1	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 3,6 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	50,3	34,8	-10,5	39,8	24,3	74,0	54,0	34,2	29,7
1650,000	53,1		-9,3	43,8		74,0	54,0	30,2	
11427,000	54,0	29,7	8,9	62,9	38,5	74,0	54,0	11,1	15,4
11616,000	54,0		8,9	63,0		74,0	54,0	11,0	
17643,000	51,2		19,2	70,4		74,0	54,0	3,6	

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 11,0 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1195,000	48,9	36,0	-10,9	38,0	25,0	74,0	54,0	36,0	28,9
1481,000	48,5	34,9	-10,1	38,4	24,8	74,0	54,0	35,6	29,1
1988,000	46,4		-7,1	39,3		74,0	54,0	34,7	
11511,000	49,9		8,8	58,6		74,0	54,0	15,3	
11763,000	54,0	31,4	9,0	62,9	40,4	74,0	54,0	11,0	13,6

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




		Minimum margin to limit: 5,0 dB							
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Marg	PK	AV	PK	AV
1325,000	51,2	-10,5	40,7	74,0	33,2	74,0	54,0	33,2	28,4
1962,000	48,8	-7,2	41,6	74,0	32,4	74,0	54,0	32,4	
11595,000	52,2	8,9	61,1	74,0	12,9	74,0	54,0	12,9	
11763,000	54,0	9,0	63,0	74,0	11,0	74,0	54,0	11,0	11,0
17601,000	50,0	19,0	69,0	74,0	5,0	74,0	54,0	5,0	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **8,4 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1195,000	50,0	36,1	-10,9	39,0	25,1	74,0	54,0	34,9	28,8
1481,000	49,8	35,2	-10,1	39,7	25,0	74,0	54,0	34,3	28,9
11500,000	51,2	31,4	8,8	59,9	40,2	74,0	54,0	14,0	13,8
11658,000	47,1		9,0	56,1		74,0	54,0	17,9	
17118,000	51,9		13,7	65,6		74,0	54,0	8,4	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




					Minimum margin to limit:		8,7 dB		
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	50,2	35,2	-10,5	39,7	24,7	74,0	54,0	34,3	29,3
1494,000	52,1		-10,1	42,0		74,0	54,0	32,0	
1884,000	54,9		-7,2	47,7		74,0	54,0	26,3	
11511,000	54,2	31,5	8,8	63,0	40,3	74,0	54,0	11,0	13,7
11616,000	48,6		8,9	57,5		74,0	54,0	16,5	
17307,000	50,0		15,3	65,3		74,0	54,0	8,7	

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **14,6 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	49,2	35,5	-10,1	39,1	25,4	74,0	54,0	34,9	28,6
2001,000	46,9		-7,1	39,8		74,0	54,0	34,2	
11427,000	49,1	30,6	8,9	57,9	39,4	74,0	54,0	16,0	14,6
11511,000	50,4		8,8	59,2		74,0	54,0	14,8	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **4,6 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	53,3	34,8	-10,1	43,2	24,7	74,0	54,0	30,8	29,2
1897,000	59,4		-7,1	52,3		74,0	54,0	21,7	
11427,000	51,5	30,7	8,9	60,4	39,5	74,0	54,0	13,6	14,4
11511,000	50,6		8,8	59,3		74,0	54,0	14,6	
17643,000	50,1		19,2	69,4		74,0	54,0	4,6	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 4,1 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	48,7	34,7	-10,4	38,3	24,3	74,0	54,0	35,7	29,7
2001,000	47,1		-7,1	40,0		74,0	54,0	34,0	
11511,000	49,9	29,5	8,8	58,7	38,3	74,0	54,0	15,3	15,7
11763,000	55,9	32,9	9,0	64,9	41,9	74,0	54,0	9,1	12,1
17622,000	50,8		19,1	69,9		74,0	54,0	4,1	

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




						Minimum margin to limit:		4,3 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	49,6	37,0	-10,1	39,4	26,9	74,0	54,0	34,5	27,1
1884,000	51,9		-7,2	44,7		74,0	54,0	29,3	
1988,000	48,2		-7,1	41,1		74,0	54,0	32,8	
11511,000	51,8	28,8	8,8	60,6	37,6	74,0	54,0	13,4	16,4
11763,000	56,7	34,6	9,0	65,7	43,6	74,0	54,0	8,3	10,4
17622,000	50,6		19,1	69,7		74,0	54,0	4,3	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **8,3 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	37,2	24,3	-10,4	26,8	13,9	74,0	54,0	47,2	40,1
1988,000	39,5		-7,1	32,4		74,0	54,0	41,6	
11490,000	56,7		8,8	65,5		74,0	54,0	8,5	
11511,000	56,1	36,9	8,8	64,8	45,7	74,0	54,0	9,1	8,3
11637,000	56,0		9,0	64,9		74,0	54,0	9,0	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit:								2,8 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	38,9	24,3	-10,5	28,4	13,8	74,0	54,0	45,6	40,1
1988,000	41,0	27,1	-7,1	33,9	20,0	74,0	54,0	40,1	33,9
11490,000	62,4		8,8	71,2		74,0	54,0	2,8	
11511,000	59,7	40,0	8,8	68,4	48,7	74,0	54,0	5,5	5,2
11616,000	60,5		8,9	69,4		74,0	54,0	4,6	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS



Minimum margin to limit: **14,3 dB**


Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1039,000	52,3		-11,8	40,5		74,0	54,0	33,5	
1390,000	48,8	35,0	-10,4	38,4	24,6	74,0	54,0	35,5	29,4
1988,000	46,3		-7,1	39,2		74,0	54,0	34,8	
11448,000	50,2	30,9	8,8	59,0	39,7	74,0	54,0	15,0	14,3
11574,000	50,5		8,9	59,3		74,0	54,0	14,6	

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




						Minimum margin to limit:		12,5 dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Marginal [dB]	PK	AV	PK	AV
1325,000	51,6	-10,5	41,1	74,0	32,9				
1494,000	51,6	-10,1	41,5	74,0	32,5				
1988,000	47,6	-7,1	40,5	74,0	33,4				
11427,000	52,6	8,9	61,5	74,0	12,5				
11658,000	52,3	9,0	61,2	74,0	12,7				

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 12,6 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	50,3	35,3	-10,1	40,2	25,2	74,0	54,0	33,8	28,8
1988,000	47,2		-7,1	40,1		74,0	54,0	33,8	
11511,000	52,6		8,8	61,4		74,0	54,0	12,6	
11763,000	50,0	30,0	9,0	59,0	39,0	74,0	54,0	15,0	15,0

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit:								7,8 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	50,7	35,0	-10,5	40,2	24,5	74,0	54,0	33,7	29,5
1988,000	48,7		-7,1	41,7		74,0	54,0	32,3	
11511,000	51,9	28,7	8,8	60,7	37,5	74,0	54,0	13,3	16,5
11763,000	57,2	31,2	9,0	66,2	40,2	74,0	54,0	7,8	13,8

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **4,0 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	47,9	36,8	-10,1	37,8	26,7	74,0	54,0	36,2	27,3
11511,000	53,2	33,0	8,8	61,9	41,8	74,0	54,0	12,0	12,2
11616,000	47,7		8,9	56,7		74,0	54,0	17,3	
17685,000	50,5		19,4	69,9		74,0	54,0	4,0	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




						Minimum margin to limit:		2,7 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	46,3	34,8	-10,5	35,8	24,3	74,0	54,0	38,2	29,7
11511,000	61,5	29,6	8,8	70,3	38,4	74,0	54,0	3,7	15,6
11595,000	60,1		8,9	69,1		74,0	54,0	4,9	
17391,000	55,1		16,2	71,3		74,0	54,0	2,7	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **4,6 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1481,000	50,7		-10,1	40,6		74,0	54,0	33,4	
1988,000	46,7		-7,1	39,6		74,0	54,0	34,3	
11427,000	51,8	30,1	8,9	60,6	39,0	74,0	54,0	13,4	15,0
11511,000	51,6		8,8	60,4		74,0	54,0	13,6	
17622,000	50,3		19,1	69,4		74,0	54,0	4,6	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




		Minimum margin to limit:						8,6 dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Margin [dB]				
	PK	AV	PK	AV	PK	AV	PK	AV	
1494,000	50,2		40,1		74,0	54,0	33,9		
1988,000	49,5	33,4	42,4	26,3	74,0	54,0	31,6	27,7	
11427,000	56,5	30,7	65,4	39,5	74,0	54,0	8,6	14,5	
11595,000	49,5		58,4		74,0	54,0	15,6		

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 12,6 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	49,1	36,5	-10,4	38,8	26,1	74,0	54,0	35,2	27,9
1481,000	51,1		-10,1	41,0		74,0	54,0	33,0	
11511,000	52,6		8,8	61,4		74,0	54,0	12,6	
11763,000	50,0	30,0	9,0	59,0	39,0	74,0	54,0	15,0	15,0

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit:								7,8 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1988,000	49,3		-7,1	42,2		74,0	54,0	31,8	
11511,000	51,9	28,7	8,8	60,7	37,5	74,0	54,0	13,3	16,5
11742,000	57,2	31,2	9,0	66,2	40,2	74,0	54,0	7,8	13,8

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 10,2 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	50,3	36,4	-10,4	39,9	26,0	74,0	54,0	34,1	28,0
1988,000	47,3		-7,1	40,2		74,0	54,0	33,7	
11490,000	51,1	28,3	8,8	59,9	37,0	74,0	54,0	14,1	16,9
14031,000	52,0		11,9	63,8		74,0	54,0	10,2	

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit:								2,9 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1494,000	52,0		-10,1	41,9		74,0	54,0	32,0	
1988,000	49,0		-7,1	41,9		74,0	54,0	32,1	
11511,000	60,5	32,0	8,8	69,2	40,8	74,0	54,0	4,7	13,2
17349,000	55,3		15,7	71,1		74,0	54,0	2,9	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 13,6 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	49,7	36,0	-10,4	39,3	25,6	74,0	54,0	34,7	28,4
11427,000	51,5	31,3	8,9	60,4	40,2	74,0	54,0	13,6	13,8
11511,000	50,9		8,8	59,7		74,0	54,0	14,3	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-15  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 5,3 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	50,4	35,0	-10,5	39,9	24,5	74,0	54,0	34,1	29,5
1988,000	48,7		-7,1	41,6		74,0	54,0	32,3	
11427,000	53,7	29,9	8,9	62,6	38,8	74,0	54,0	11,4	15,2
11637,000	52,5		9,0	61,4		74,0	54,0	12,6	
17496,000	51,4		17,3	68,7		74,0	54,0	5,3	

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 12,1 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1091,000	48,7	34,3	-11,4	37,3	22,9	74,0	54,0	36,7	31,0
1390,000	50,4	34,1	-10,4	40,0	23,7	74,0	54,0	34,0	30,2
11511,000	53,1		8,8	61,9		74,0	54,0	12,1	
11637,000	52,3		9,0	61,3		74,0	54,0	12,7	
11763,000	52,5	30,8	9,0	61,4	39,8	74,0	54,0	12,5	14,2
13779,000	50,7		11,0	61,7		74,0	54,0	12,3	
14995,000	50,9		8,6	59,4		74,0	54,0	14,5	

File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit:						6,5 dB			
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	51,1	34,9	-10,5	40,6	24,4	74,0	54,0	33,3	29,6
1494,000	49,7	35,1	-10,1	39,6	25,0	74,0	54,0	34,3	29,0
1897,000	49,7	33,2	-7,1	42,5	26,0	74,0	54,0	31,4	28,0
11511,000	50,2		8,8	59,0		74,0	54,0	15,0	
11595,000	52,2		8,9	61,1		74,0	54,0	12,9	
11637,000	52,0		9,0	60,9		74,0	54,0	13,0	
11763,000	57,9	28,7	9,0	66,9	37,6	74,0	54,0	7,1	16,3
14367,000	50,3		11,3	61,6		74,0	54,0	12,4	
17622,000	48,3		19,1	67,4		74,0	54,0	6,5	

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **8,1 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1091,000	50,6		-11,4	39,3		74,0	54,0	34,7	
1494,000	49,3	34,4	-10,1	39,2	24,3	74,0	54,0	34,8	29,7
8676,000	46,2		6,2	52,4		74,0	54,0	21,6	
11511,000	53,6	34,2	8,8	62,4	43,0	74,0	54,0	11,6	11,0
17349,000	50,1		15,7	65,8		74,0	54,0	8,1	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




					Minimum margin to limit:		4,1 dB		
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1234,000	52,7		-10,8	41,9		74,0	54,0	32,0	
1325,000	51,5	36,3	-10,5	41,0	25,7	74,0	54,0	33,0	28,2
1884,000	51,8		-7,2	44,6		74,0	54,0	29,4	
11511,000	54,0	31,8	8,8	62,8	40,6	74,0	54,0	11,2	13,4
11595,000	53,8		8,9	62,7		74,0	54,0	11,3	
17958,000	51,5		18,4	69,9		74,0	54,0	4,1	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 9,0 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	51,5	35,8	-10,4	41,2	25,4	74,0	54,0	32,8	28,6
1988,000	47,4		-7,1	40,4		74,0	54,0	33,6	
11472,000	50,0	27,6	8,8	58,8	36,4	74,0	54,0	15,2	17,6
11511,000	50,3		8,8	59,1		74,0	54,0	14,9	
17181,000	50,8		14,2	65,0		74,0	54,0	9,0	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 13,8 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1234,000	51,3		-10,8	40,5		74,0	54,0	33,5	
1325,000	50,3	35,1	-10,5	39,8	24,6	74,0	54,0	34,2	29,4
1988,000	49,6	33,5	-7,1	42,5	26,4	74,0	54,0	31,5	27,6
11472,000	51,3	31,3	8,8	60,1	40,1	74,0	54,0	13,8	13,9

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 12,1 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1091,000	51,3		-11,4	39,9		74,0	54,0	34,1	
1390,000	51,0	34,4	-10,4	40,6	24,0	74,0	54,0	33,4	29,9
1871,000	46,4		-7,4	39,0		74,0	54,0	35,0	
11763,000	52,9	27,0	9,0	61,9	36,0	74,0	54,0	12,1	18,0
16572,000	51,6		10,3	61,9		74,0	54,0	12,1	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




		Minimum margin to limit:						5,3 dB	
Frequency [MHz]	Reading [dBμV]	Correction [dB]	Values [dBμV/m]	Limit [dBμV/m]	Marg	PK	AV	PK	AV
	PK	AV	PK	AV					
1234,000	51,2		40,4	74,0	33,6				
1325,000	50,1	35,5	39,6	74,0	34,3				
1390,000	47,5	34,8	37,1	74,0	36,8				
1988,000	48,7	-7,1	41,6	74,0	32,4				
11511,000	50,4	8,8	59,2	74,0	14,8				
11742,000	51,8	9,0	60,8	74,0	13,2				
11763,000	57,8	30,1	66,8	74,0	7,2				
14661,000	50,0	10,5	60,4	74,0	13,5				
17622,000	49,6	29,2	68,7	74,0	5,3				

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: **8,9 dB**

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	51,5	36,1	-10,4	41,1	25,7	74,0	54,0	32,9	28,3
1481,000	50,0		-10,1	39,9		74,0	54,0	34,1	
11511,000	52,3	28,9	8,8	61,1	37,7	74,0	54,0	12,9	16,3
17265,000	50,1		14,9	65,0		74,0	54,0	8,9	

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS



Minimum margin to limit: 12,0 dB


Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	51,3	34,4	-10,5	40,8	23,9	74,0	54,0	33,2	30,1
1988,000	49,4		-7,1	42,3		74,0	54,0	31,7	
11511,000	52,6	32,5	8,8	61,4	41,3	74,0	54,0	12,6	12,7
11595,000	53,1		8,9	62,0		74,0	54,0	12,0	

File No. T-0329-4305-00 JP



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS




Minimum margin to limit: 12,8 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1390,000	50,0	35,3	-10,4	39,6	24,9	74,0	54,0	34,4	29,1
1988,000	47,1	32,3	-7,1	40,0	25,2	74,0	54,0	34,0	28,7
11448,000	52,4	29,0	8,8	61,2	37,8	74,0	54,0	12,8	16,2

File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-16  
 Tested by: Pessinger Jürgen

Result: PASS



						Minimum margin to limit:		10,8 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
1325,000	50,1	34,7	-10,5	39,6	24,2	74,0	54,0	34,4	29,8
1494,000	51,5		-10,1	41,4		74,0	54,0	32,5	
1988,000	48,4		-7,1	41,3		74,0	54,0	32,7	
11427,000	52,3	29,4	8,9	61,1	38,2	74,0	54,0	12,8	15,8
11637,000	54,2		9,0	63,2		74,0	54,0	10,8	

File No. **T-0329-4305-00 JP**

## 6.5 Bandedges


For test instruments and accessories used see section 7 Part SER 3.

### 6.5.1 Description of the test location

Test location: Anechoic Chamber A4

Test distance: 3 metres

### 6.5.2 Photo documentation of the test set-up



### 6.5.3 Test specification

Environmental conditions: Temperature: 23 ° C Humidity: 36 % Atmospheric pressure: 98 kPa

Frequency range: 5725MHz – 5875MHz

The test was carried out in the following operation mode(s):

- test software active, CH00 (5871MHz) adjusted
- test software active, CH27 (5755MHz) adjusted
- test software active, CH53 (5729MHz) adjusted

### 6.5.4 Test result

The requirements are **FULFILLED**.

**Remarks:** The test was performed with 4 sets of antenna types, refer to 4.3 EuT configuration.

The testing was performed in vertical polarization only, pretests show the highest

emission occurs in vertical polarization.


File No. **T-0329-4305-00 JP**

## 6.5.5 Test protocol

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 2 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 2 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 2 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000421 10dBi connected, adjustable  
attenuator set to 14dB, Antenna Port 1 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000421 10dBi connected, adjustable  
attenuator set to 14dB, Antenna Port 2 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000468 13dBi connected, adjustable  
attenuator set to 6dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000468 13dBi connected, adjustable  
attenuator set to 6dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000468 13dBi connected, adjustable  
attenuator set to 6dB, Antenna Port 2 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high




File No. T-0329-4305-00 JP

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low




File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH27 (5755MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 2 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge high





File No. T-0329-4305-00 JP

Operation mode: test software active, CH53 (5729MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 2 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS

### Band edge low





File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS

### Band edge high



File No. **T-0329-4305-00 JP**

## 6.6 Field strength of emission within band

For test instruments and accessories used see section 7 Part SER 3.

### 6.6.1 Description of the test location

Test location: Anechoic Chamber A4

Test distance: 3 metres

### 6.6.2 Photo documentation of the test set-up



### 6.6.3 Test specification

Environmental conditions: Temperature: 23 ° C Humidity: 30 % Atmospheric pressure: 97 kPa

Frequency range: 5725MHz – 5875MHz

The test was carried out in the following operation mode(s):

- test software active, CH00 (5871MHz) adjusted
- test software active, CH27 (5755MHz) adjusted
- test software active, CH53 (5729MHz) adjusted

### 6.6.4 Test result

Minimal margin to limit 1,4 dB

The requirements are **FULFILLED**.

**Remarks:** The test was performed with 4 sets of antenna types, refer to 4.3 EuT configuration.

The testing was performed in vertical polarization only, pretests show the highest


emission occurs in vertical polarization.

File No. **T-0329-4305-00 JP**

### 6.6.5 Test protocol

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:

						Minimum margin to limit:		7,0 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5775,6	66,2	--	37,4	103,6	--	114,0	--	10,4	--
5871,6	--	49,2	37,8	--	87,0	--	94,0	--	7,0

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

				Minimum margin to limit:				6,1 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5773,2	66,1	--	37,5	103,6	--	114,0	--	10,4	--
5755,2	--	50,3	37,6	--	87,9	--	94,0	--	6,1

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		5,9 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5728,8	65,7	--	37,6	103,3	--	114,0	--	10,7	--
5729,2	--	50,5	37,6	--	88,1	--	94,0	--	5,9

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000947 6dBi connected, adjustable  
attenuator set to 10dB, Antenna Port 2 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:

Minimum margin to limit: 4,7 dB


Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5871,2	65,6	51,5	37,8	103,4	89,3	114,0	94,0	10,6	4,7

File No. T-0329-4305-00 JP



Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		6,4 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5824,4	65,7	--	37,6	103,3	--	114,0	--	10,7	--
5754,8	--	50,0	37,6	--	87,6	--	94,0	--	6,4

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000947 6dBi connected, adjustable  
 attenuator set to 10dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		5,1 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5826,0	65,7	--	37,6	103,3	--	114,0	--	10,7	--
5728,8	--	51,3	37,6	--	88,9	--	94,0	--	5,1

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000421 10dBi connected, adjustable  
attenuator set to 14dB, Antenna Port 1 active  
Date: 2012-02-07  
Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		5,2 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5758,0	67,7	--	37,6	105,3	--	114,0	--	8,7	--
5871,2	--	51,0	37,8	--	88,8	--	94,0	--	5,2

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000421 10dBi connected, adjustable  
 attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		3,2 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5754,8	67,8	53,2	37,6	105,4	90,8	114,0	94,0	8,6	3,2

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Remarks: Antenna ANC000421 10dBi connected,  
 adjustable attenuator set to 14dB, Antenna Port 1 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		4,0 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5758,0	67,7	--	37,6	105,3	--	114,0	--	8,7	--
5728,8	--	52,4	37,6	--	90,0	--	94,0	--	4,0

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Remarks: Antenna ANC000421 10dBi connected,  
 adjustable attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:


Minimum margin to limit: 6,4 dB

Frequency [MHz]	Reading [dBμV] PK	AV	Correction [dB]	Values [dBμV/m] PK	AV	Limit [dBμV/m] PK	AV	Margin [dB] PK	AV
5758,8	65,4	--	37,6	103,0	--	114,0	--	11,0	--
5871,2	--	49,8	37,8	--	87,6	--	94,0	--	6,4

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Remarks: Antenna ANC000421 10dBi connected,  
 adjustable attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		5,6 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5758,4	65,4	--	37,6	103,0	--	114,0	--	11,0	--
5755,2	--	50,8	37,6	--	88,4	--	94,0	--	5,6

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Remarks: Antenna ANC000421 10dBi connected,  
 adjustable attenuator set to 14dB, Antenna Port 2 active  
 Date: 2012-02-07  
 Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:


						Minimum margin to limit:		6,9 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5758,0	65,3	--	37,6	102,9	--	114,0	--	11,1	--
5728,8	--	49,5	37,6	--	87,1	--	94,0	--	6,9

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		4,1 dB	
Frequency [MHz]	Reading [dBμV] PK	AV	Correction [dB]	Values [dBμV/m] PK	AV	Limit [dBμV/m] PK	AV	Margin [dB] PK	AV
5809,2	68,3	--	37,6	105,9	--	114,0	--	8,1	--
5870,8	--	52,1	37,8	--	89,9	--	94,0	--	4,1

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		2,1 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5754,8	68,5	54,3	37,6	106,1	91,9	114,0	94,0	7,9	2,1

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		1,4 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5728,8	69,3	55,0	37,6	106,9	92,6	114,0	94,0	7,1	1,4

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000468 13dBi connected, adjustable  
attenuator set to 6dB, Antenna Port 2 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:


Minimum margin to limit: 1,7 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5791,6	69,2	--	37,5	106,7	--	114,0	--	7,3	--
5871,2	--	54,5	37,8	--	92,3	--	94,0	--	1,7

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		2,4 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5791,2	69,2	--	37,5	106,7	--	114,0	--	7,3	--
5754,8	--	54,0	37,6	--	91,6	--	94,0	--	2,4

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000468 13dBi connected, adjustable  
 attenuator set to 6dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		1,5 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5728,8	69,2	54,9	37,6	106,8	92,6	114,0	94	7,2	1,5

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
Remarks: Antenna ANC000168 23dBi connected, adjustable  
attenuator set to 26dB, Antenna Port 1 active  
Date: 2012-02-14  
Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:


Minimum margin to limit: 3,6 dB

Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5758,0	67,1	--	37,6	104,7	--	114,0	--	9,3	--
5871,2	--	52,6	37,8	--	90,4	--	94,0	--	3,6

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:


						Minimum margin to limit:		3,8 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5754,8	66,9	52,6	37,6	104,5	90,2	114,0	94,0	9,5	3,8

File No. **T-0329-4305-00 JP**



Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 1 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		3,8 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5728,8	66,9	52,6	37,6	104,5	90,2	114,0	94,0	9,5	3,8

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH00 (5871MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:


Minimum margin to limit: 4,2 dB

Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5871,2	66,1	52,0	37,8	103,9	89,8	114,0	94,0	10,1	4,2

File No. T-0329-4305-00 JP

Operation mode: test software active, CH27 (5755MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS




Maximum field strength measured:

						Minimum margin to limit:		4,8 dB	
Frequency [MHz]	Reading [dBµV]		Correction [dB]	Values [dBµV/m]		Limit [dBµV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5754,8	65,9	51,6	37,6	103,5	89,2	114,0	94,0	10,5	4,8

File No. **T-0329-4305-00 JP**

Operation mode: test software active, CH53 (5729MHz) adjusted  
 Remarks: Antenna ANC000168 23dBi connected, adjustable  
 attenuator set to 26dB, Antenna Port 2 active  
 Date: 2012-02-14  
 Tested by: Pessinger Jürgen

Result: PASS



Maximum field strength measured:

						Minimum margin to limit:		4,8 dB	
Frequency [MHz]	Reading [dBμV]		Correction [dB]	Values [dBμV/m]		Limit [dBμV/m]		Margin [dB]	
	PK	AV		PK	AV	PK	AV	PK	AV
5728,8	65,8	51,6	37,6	103,4	89,2	114,0	94,0	10,6	4,8

File No. **T-0329-4305-00 JP**

## 7 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used, in addition to the test accessories, are calibrated and verified regularly.

Test ID	Model Type	Equipment No.	Next Calib.	Last Calib.	Next Verif.	Last Verif.
A 4	ESH 3	01-02/03-01-005	02/01/2013	02/01/2012		
	ESH 2 - Z 5	01-02/20-01-001	26/01/2014	26/01/2011	02/02/2013	02/02/2012
	ESH 3 - Z 2	01-02/50-02-020	29/12/2012	29/12/2011		
	BNC-3000-N	01-02/50-07-008				
	N-5000-N	01-02/50-07-009				
	Tile Version 3.4K20	01-02/68-09-001				
	emitel ESW V31	01-02/68-09-002				
SER 1	ESH 3	01-02/03-01-005	02/01/2013	02/01/2012		
	FMZB 1516	01-02/24-01-018			16/02/2013	16/02/2012
	N-40000-N	01-02/50-05-043				
	N-30000-N	01-02/50-05-044				
	Tile Version 3.4K20	01-02/68-09-001				
	emitel ESW V31	01-02/68-09-002				
SER 2	ESVP	01-02/03-01-002	27/02/2013	27/02/2012		
	HM 5012	01-02/11-01-001				
	VULB 9163	01-02/24-01-006	09/11/2014	09/11/2011		
	HCC	01-02/50-01-021				
	N-40000-N	01-02/50-05-043				
	N-30000-N	01-02/50-05-044				
	Tile Version 3.4K20	01-02/68-09-001				
	emitel ESW V31	01-02/68-09-002				
	RST 070	01-05/60-02-003				
SER 3	AMF-40-005-180-24-10P	01-02/17-02-009			12/12/2012	12/12/2011
	HCC	01-02/50-01-021				
	FA210A0020000000	01-02/50-06-065				
	FA210A0050000000	01-02/50-10-005				
	Tile Version 3.4K20	01-02/68-09-001				
	emitel ESW V31	01-02/68-09-002				
	RST 070	01-05/60-02-003				
	FSP 40	02-02/11-11-001	02/09/2012	02/09/2011		
	3117	02-02/24-05-009	16/02/2013	16/02/2012		
	R1 _ 18 - 40 GHz	02-02/30-09-002			19/12/2012	19/12/2011

File No. **T-0329-4305-00 JP**