

## FCC 47 CFR PART 15 SUBPART C

Product Type : Tobii I-15  
Applicant : Tobii Technology AB  
Address : Karlsrovägen 2D,182 53 Danderyd, SWEDEN  
Trade Name : Tobii  
Model Number : I-15 ETR  
Test Specification : FCC 47 CFR PART 15 SUBPART C: Oct., 2012  
Canada RSS-210 ISSUE 8: Dec., 2010  
Canada RSS-Gen ISSUE 3: Dec., 2010  
ANSI C63.4-2009  
Application Purpose : Original  
Receive Date : Feb. 19, 2013  
Test Period : Mar. 21 ~ Apr. 14, 2013  
Issue Date : May 20, 2013

### Issue by

A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade City,  
Taoyuan County 334, Taiwan R.O.C.  
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330



**Note:** This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

**Revision History**

Rev.	Issue Date	Revisions	Revised By
00	May 20, 2013	Initial Issue	


## Verification of Compliance

Issued Date: 05/20/2013

Product Type : Tobii I-15  
Applicant : Tobii Technology AB  
Address : Karlsrovägen 2D,182 53 Danderyd, SWEDEN  
Trade Name : Tobii  
Model Number : I-15 ETR  
FCC ID : W5M-TOBIII15A  
EUT Rated Voltage : DC 24V, 2.71A  
Test Voltage : 120 Vac / 60 Hz  
Applicable Standard : FCC 47 CFR PART 15 SUBPART C: Oct., 2012  
Canada RSS-210 ISSUE 8: Dec., 2010  
Canada RSS-Gen ISSUE 3: Dec., 2010  
ANSI C63.4-2009  
Test Result : Complied  
Application Purpose : Original  
Performing Lab. : A Test Lab Techno Corp.  
No. 140-1, Changan Street, Bade City,  
Taoyuan County 334, Taiwan R.O.C.  
Tel : +886-3-2710188 / Fax : +886-3-2710190  
  
Taiwan Accreditation Foundation accreditation number: 1330  
<http://www.atl-lab.com.tw/e-index.htm>

The above equipment was tested by A Test Lab Techno Corp. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2009 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247 .

The test results of this report relate only to the tested sample identified in this report.

Approved By : 

(Manager)

Reviewed By

(Testing Engineer)

: 

(Fly Lu)

## TABLE OF CONTENTS

<b>1</b>	<b>General Information .....</b>	<b>6</b>
<b>2</b>	<b>EUT Description .....</b>	<b>7</b>
<b>3</b>	<b>Test Methodology .....</b>	<b>8</b>
3.1.	Mode of Operation.....	8
3.2.	EUT Exercise Software .....	8
3.3.	Configuration of Test System Details .....	9
3.4.	Test Site Environment .....	10
<b>4</b>	<b>Conducted Emission Measurement .....</b>	<b>11</b>
4.1.	Limit .....	11
4.2.	Test Instruments .....	11
4.3.	Test Setup.....	11
4.4.	Test Procedure .....	12
4.5.	Test Result.....	13
<b>5</b>	<b>Radiated Emission Measurement.....</b>	<b>15</b>
5.1.	Limit .....	15
5.2.	Test Instruments .....	15
5.3.	Setup .....	16
5.4.	Test Procedure .....	17
5.5.	Test Result.....	19
<b>6</b>	<b>Maximum Conducted Output Power Measurement.....</b>	<b>27</b>
6.1.	Limit .....	27
6.2.	Test Setup.....	27
6.3.	Test Instruments .....	27
6.4.	Test Procedure .....	27
6.5.	Test Result.....	28
<b>7</b>	<b>6dB RF Bandwidth Measurement.....</b>	<b>30</b>
7.1.	Limit .....	30
7.2.	Test Setup.....	30
7.3.	Test Instruments .....	30
7.4.	Test Procedure .....	30
7.5.	Test Result.....	31
7.6.	Test Graphs .....	32

<b>8</b>	<b>Maximum Power Density Measurement .....</b>	<b>36</b>
8.1.	Limit .....	36
8.2.	Test Setup.....	36
8.3.	Test Instruments .....	36
8.4.	Test Procedure .....	36
8.5.	Test Result.....	37
8.6.	Test Graphs .....	38
<b>9</b>	<b>Out of Band Conducted Emissions Measurement .....</b>	<b>42</b>
9.1.	Limit .....	42
9.2.	Test Setup.....	42
9.3.	Test Instruments .....	42
9.4.	Test Procedure .....	42
9.5.	Test Graphs .....	43
<b>10</b>	<b>Band Edges Measurement .....</b>	<b>47</b>
10.1.	Limit .....	47
10.2.	Test Setup.....	47
10.3.	Test Instruments .....	47
10.4.	Test Procedure .....	48
10.5.	Test Result.....	49
<b>11</b>	<b>99 % Occupied Bandwidth Measurement.....</b>	<b>65</b>
11.1.	Limit .....	65
11.2.	Test Setup.....	65
11.3.	Test Instruments .....	65
11.4.	Test Procedure .....	65
11.5.	Test Result.....	66
11.6.	Test Graphs .....	67
<b>12</b>	<b>Antenna Measurement.....</b>	<b>71</b>
12.1.	Limit .....	71
12.2.	Antenna Connector Construction .....	71

## 1 General Information

### 1.1 Summary of Test Result

Standard		Item	Result	Remark
15.247	RSS-GEN			
15.207	7.2.2	AC Power Conducted Emission	PASS	-----
-----	6	Receiver Radiated Emissions	PASS	-----
Standard		Item	Result	Remark
15.247	RSS-210			
15.247(d)	A8.5	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	A8.4	Max. Output Power	PASS	-----
15.247(a)(2)	A8.2 (a)	6dB RF Bandwidth	PASS	-----
15.247(e)	A8.2 (b)	Power Spectral Density	PASS	-----
15.247(c)	A8.5	Out of Band Conducted Spurious Emission	PASS	-----
15.247(d)	A8.5	Band Edge Measurement	PASS	-----
15.247(c)	A8.5	Occupied Bandwidth Measurement	PASS	-----
15.203	-	Antenna Requirement	PASS	-----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

### 1.2 Measurement Uncertainty

#### Conducted Emission

The measurement uncertainty is evaluated as  $\pm 2.24$  dB.

#### Radiated Emission

The measurement uncertainty is evaluated as  $\pm 3.072$ dB.

## 2 EUT Description

Product	Tobii I-15				
Trade Name	Tobii				
Model No.	I-15 ETR				
Applicant	Tobii Technology AB Karlsrovägen 2D,182 53 Danderyd, SWEDEN				
Manufacturer	ONYX Healthcare 2F., No.135, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)				
FCC ID	W5M-TOBIII15A				
Frequency Range	IEEE 802.11b / 802.11g / 802.11n 2.4GHz 20MHz: 2412 ~ 2462 MHz IEEE 802.11n 2.4GHz 40MHz: 2422 ~ 2452 MHz				
Modulation Type	IEEE 802.11b:DSSS IEEE 802.11g:DSSS + OFDM IEEE 802.11n 2.4GHz 20MHz: OFDM IEEE 802.11n 2.4GHz 40MHz: OFDM				
Antenna Use	Item	Antenna	Model Number	Type	Max. Gain
	1	Main ANT (L)	151504-10	Folded Dipole Antenna	3.86 dBi
	2	Aux ANT (R)	151504-10	Folded Dipole Antenna	3.60 dBi
RF Output Power	IEEE 802.11b: 0.109 W / 20.39 dBm IEEE 802.11g: 0.177 W / 22.49 dBm IEEE 802.11n 2.4GHz 20MHz: 0.171 W / 22.33 dBm IEEE 802.11n 2.4GHz 40MHz: 0.168 W / 22.25 dBm				

### 3 Test Methodology

#### 3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Normal Operation Mode
Mode 2: IEEE 802.11b Link Mode
Mode 3: IEEE 802.11g Link Mode
Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode
Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode
Mode 6: Receiver Mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n 2.4GHz 20MHz mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

IEEE 802.11n 2.4GHz 40MHz mode:


Channel Low (2422MHz), Channel Mid (2437MHz) and Channel High (2452MHz) with 13.5Mbps data rate were chosen for full testing.


#### 3.2. EUT Exercise Software

1. Setup the EUT shown on 3.3.
2. Turn on the power of all equipment.
3. Turn on Wi-Fi function link to AP.
4. EUT run test program.



### 3.3. Configuration of Test System Details





### 3.4. Test Site Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

## 4 Conducted Emission Measurement

### 4.1. Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50


### 4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/18/2012	(1)
LISN	R&S	ENV216	101040	03/04/2013	(1)
LISN	R&S	ENV216	101041	03/04/2013	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 4.3. Test Setup



#### **4.4. Test Procedure**


The power line conducted emission measurements were performed in a shielded enclosure. The EUT was assembled on a wooden table which is 80 centimeters high, was placed 40 centimeters from the back wall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and EMCO Model 3162/2 SH Line Impedance Stabilization Networks (LISN). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.1.

#### 4.5. Test Result


Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	04/14/2013
		Test By:	Fly Lu
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.3300	35.40	22.01	9.62	45.02	31.63	59.45	49.45	-14.43	-17.82	Pass
2	0.3780	38.03	25.11	9.62	47.65	34.73	58.32	48.32	-10.67	-13.59	Pass
3	0.4020	38.55	24.86	9.62	48.17	34.48	57.81	47.81	-9.64	-13.33	Pass
4	0.4780	38.17	22.82	9.62	47.79	32.44	56.37	46.37	-8.58	-13.93	Pass
5	0.5220	35.81	20.98	9.62	45.43	30.60	56.00	46.00	-10.57	-15.40	Pass
6	0.5780	36.71	20.99	9.63	46.34	30.62	56.00	46.00	-9.66	-15.38	Pass
7	0.6060	37.54	21.48	9.64	47.18	31.12	56.00	46.00	-8.82	-14.88	Pass
8	0.7020	34.10	18.21	9.64	43.74	27.85	56.00	46.00	-12.26	-18.15	Pass
9	0.7180	33.35	16.91	9.64	42.99	26.55	56.00	46.00	-13.01	-19.45	Pass
10	2.7900	20.71	6.79	9.73	30.44	16.52	56.00	46.00	-25.56	-29.48	Pass
11	10.0020	32.72	32.24	10.08	42.80	42.32	60.00	50.00	-17.20	-7.68	Pass

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	1	Date:	04/14/2013
		Test By:	Fly Lu

Description:



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.2020	40.11	30.47	9.63	49.74	40.10	63.53	53.53	-13.79	-13.43	Pass
2	0.4020	38.52	24.87	9.63	48.15	34.50	57.81	47.81	-9.66	-13.31	Pass
3	0.4620	37.16	21.75	9.63	46.79	31.38	56.66	46.66	-9.87	-15.28	Pass
4	0.4860	39.13	20.61	9.63	48.76	30.24	56.24	46.24	-7.48	-16.00	Pass
5	0.5140	35.54	20.26	9.63	45.17	29.89	56.00	46.00	-10.83	-16.11	Pass
6	0.5300	35.31	19.84	9.63	44.94	29.47	56.00	46.00	-11.06	-16.53	Pass
7	0.5780	36.15	20.17	9.63	45.78	29.80	56.00	46.00	-10.22	-16.20	Pass
8	0.6260	37.84	23.79	9.64	47.48	33.43	56.00	46.00	-8.52	-12.57	Pass
9	0.6820	35.55	19.67	9.64	45.19	29.31	56.00	46.00	-10.81	-16.69	Pass
10	2.9140	24.60	11.62	9.73	34.33	21.35	56.00	46.00	-21.67	-24.65	Pass
11	10.0020	33.41	32.95	10.11	43.52	43.06	60.00	50.00	-16.48	-6.94	Pass

## 5 Radiated Emission Measurement

### 5.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ( $\mu\text{V/m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

### 5.2. Test Instruments


3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/16/2012	(2)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/21/2013	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/21/2013	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/21/2013	(1)
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	06/29/2012	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/15/2012	(1)
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	06/21/2012	(1)
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	08/14/2012	(3)
Test Site	ATL	TE01	888001	08/28/2012	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.


Note: N.C.R. = No Calibration Request.

### 5.3. Setup

Below 1GHz



Above 1GHz





## 5.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (mode VULB9163) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1)  $\text{Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2)  $\text{Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 5.5. Test Result

### Below 1GHz

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		I-15 ETR		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		1		Date:		03/21/2013	
				Test By:		Fly Lu	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
134.5000	50.89	-17.30	33.59	43.50	-9.91	QP	H
249.0000	50.38	-11.98	38.40	46.00	-7.60	QP	H
415.0000	45.36	-8.42	36.94	46.00	-9.06	QP	H
528.0000	44.07	-6.65	37.42	46.00	-8.58	QP	H
660.0000	41.70	-4.00	37.70	46.00	-8.30	QP	H
864.0000	36.90	-0.52	36.38	46.00	-9.62	QP	H
133.5000	50.98	-17.29	33.69	43.50	-9.81	QP	V
396.0000	45.76	-8.61	37.15	46.00	-8.85	QP	V
528.0000	44.92	-6.65	38.27	46.00	-7.73	QP	V
660.0000	41.86	-4.00	37.86	46.00	-8.14	QP	V
792.0000	39.81	-1.70	38.11	46.00	-7.89	QP	V
936.0000	36.54	0.88	37.42	46.00	-8.58	QP	V

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

**Above 1GHz**

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	2			Date:	03/21/2013		
Frequency:	2412MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2995.000	38.74	5.90	44.64	74.00	-29.36	peak	H
4465.000	36.32	10.75	47.07	74.00	-26.93	peak	H
5928.000	34.69	15.66	50.35	74.00	-23.65	peak	H
3135.000	38.37	6.21	44.58	74.00	-29.42	peak	V
4584.000	35.97	11.09	47.06	74.00	-26.94	peak	V
5879.000	34.66	15.52	50.18	74.00	-23.82	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	2			Date:	03/21/2013		
Frequency:	2437MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2953.000	37.71	5.79	43.50	74.00	-30.50	peak	H
4465.000	36.65	10.75	47.40	74.00	-26.60	peak	H
5886.000	34.71	15.53	50.24	74.00	-23.76	peak	H
2967.000	37.44	5.82	43.26	74.00	-30.74	peak	V
4584.000	36.37	11.09	47.46	74.00	-26.54	peak	V
5872.000	35.38	15.49	50.87	74.00	-23.13	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	2			Date:	03/21/2013		
Frequency:	2462MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2974.000	37.90	5.84	43.74	74.00	-30.26	peak	H
4479.000	35.82	10.81	46.63	74.00	-27.37	peak	H
5907.000	34.04	15.60	49.64	74.00	-24.36	peak	H
3114.000	38.22	6.16	44.38	74.00	-29.62	peak	V
4528.000	35.42	10.95	46.37	74.00	-27.63	peak	V
5928.000	34.72	15.66	50.38	74.00	-23.62	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	03/21/2013		
Frequency:	2412MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2918.000	38.00	5.70	43.70	74.00	-30.30	peak	H
4465.000	36.54	10.75	47.29	74.00	-26.71	peak	H
5900.000	34.83	15.58	50.41	74.00	-23.59	peak	H
2995.000	38.38	5.90	44.28	74.00	-29.72	peak	V
4514.000	35.60	10.92	46.52	74.00	-27.48	peak	V
5956.000	34.92	15.75	50.67	74.00	-23.33	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	03/21/2013		
Frequency:	2437MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2967.000	39.03	5.82	44.85	74.00	-29.15	peak	H
4584.000	36.20	11.09	47.29	74.00	-26.71	peak	H
5984.000	34.49	15.83	50.32	74.00	-23.68	peak	H
3079.000	39.81	6.08	45.89	74.00	-28.11	peak	V
4542.000	36.51	10.99	47.50	74.00	-26.50	peak	V
5844.000	35.91	15.40	51.31	74.00	-22.69	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	3			Date:	03/21/2013		
Frequency:	2462MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	38.57	5.93	44.50	74.00	-29.50	peak	H
4528.000	36.42	10.95	47.37	74.00	-26.63	peak	H
5795.000	35.18	15.25	50.43	74.00	-23.57	peak	H
3016.000	38.24	5.95	44.19	74.00	-29.81	peak	V
4472.000	35.97	10.79	46.76	74.00	-27.24	peak	V
5886.000	35.20	15.53	50.73	74.00	-23.27	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	4			Date:	03/21/2013		
Frequency:	2412MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3100.000	38.97	6.13	45.10	74.00	-28.90	peak	H
4507.000	35.78	10.89	46.67	74.00	-27.33	peak	H
6061.000	34.57	16.07	50.64	74.00	-23.36	peak	H
3086.000	38.46	6.10	44.56	74.00	-29.44	peak	V
4570.000	36.07	11.06	47.13	74.00	-26.87	peak	V
6145.000	34.41	16.32	50.73	74.00	-23.27	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	4			Date:	03/21/2013		
Frequency:	2437MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	37.41	5.93	43.34	74.00	-30.66	peak	H
4521.000	36.67	10.93	47.60	74.00	-26.40	peak	H
5837.000	34.69	15.38	50.07	74.00	-23.93	peak	H
2953.000	37.66	5.79	43.45	74.00	-30.55	peak	V
4486.000	36.34	10.83	47.17	74.00	-26.83	peak	V
5977.000	34.74	15.81	50.55	74.00	-23.45	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	4			Date:	03/21/2013		
Frequency:	2462MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2939.000	38.35	5.75	44.10	74.00	-29.90	peak	H
4514.000	35.40	10.92	46.32	74.00	-27.68	peak	H
5809.000	35.22	15.29	50.51	74.00	-23.49	peak	H
2841.000	38.26	5.49	43.75	74.00	-30.25	peak	V
4451.000	36.19	10.71	46.90	74.00	-27.10	peak	V
5837.000	34.92	15.38	50.30	74.00	-23.70	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	5			Date:	03/21/2013		
Frequency:	2422MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3072.000	38.76	6.07	44.83	74.00	-29.17	peak	H
4528.000	36.50	10.95	47.45	74.00	-26.55	peak	H
6124.000	34.21	16.26	50.47	74.00	-23.53	peak	H
3072.000	37.93	6.07	44.00	74.00	-30.00	peak	V
4500.000	37.11	10.88	47.99	74.00	-26.01	peak	V
5837.000	34.29	15.38	49.67	74.00	-24.33	peak	V



Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	5			Date:	03/21/2013		
Frequency:	2437MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2967.000	38.27	5.82	44.09	74.00	-29.91	peak	H
4514.000	36.23	10.92	47.15	74.00	-26.85	peak	H
6047.000	34.42	16.03	50.45	74.00	-23.55	peak	H
3128.000	38.75	6.19	44.94	74.00	-29.06	peak	V
4563.000	35.68	11.05	46.73	74.00	-27.27	peak	V
5977.000	34.27	15.81	50.08	74.00	-23.92	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	I-15 ETR			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	5			Date:	03/21/2013		
Frequency:	2452MHz			Test By:	Fly Lu		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	37.68	5.93	43.61	74.00	-30.39	peak	H
4521.000	35.03	10.93	45.96	74.00	-28.04	peak	H
5830.000	34.04	15.36	49.40	74.00	-24.60	peak	H
2918.000	38.07	5.70	43.77	74.00	-30.23	peak	V
4451.000	37.14	10.71	47.85	74.00	-26.15	peak	V
5886.000	35.10	15.53	50.63	74.00	-23.37	peak	V


Standard:		RSS-Gen			Test Distance:		3m	
Test item:		Radiated Emission			Power:		AC 120V/60Hz	
Model Number:		I-15 ETR			Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		6			Date:		03/21/2013	
Modulation:		IEEE 802.11b			Test By:		Fly Lu	
Frequency:		2437MHz						
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/	Peak (dBuV/m)	AVG. (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	36.96	5.91	42.87	74.00	54.00	-31.13	peak	H
4458.000	36.10	10.73	46.83	74.00	54.00	-27.17	peak	H
6026.000	33.60	15.95	49.55	74.00	54.00	-24.45	peak	H
2953.000	37.39	5.79	43.18	74.00	54.00	-30.82	peak	V
4549.000	35.63	11.01	46.64	74.00	54.00	-27.36	peak	V
6054.000	34.14	16.05	50.19	74.00	54.00	-23.81	peak	V

## 6 Maximum Conducted Output Power Measurement

### 6.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm.

### 6.2. Test Setup



### 6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Single Channel PK Power Sensor	Agilent	N1911A	MY45101619	12/19/2012	(1)
Wideband Power Meter	Agilent	N1921A	MY45241957	12/19/2012	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 6.4. Test Procedure

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum peak output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6)/3 dBm.

The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

## 6.5. Test Result

Model Number	I-15 ETR									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 2: IEEE 802.11b Link Mode									
Date of Test	03/21/2013						Test Site		TE05	
Frequency (MHz)	Data Rate	CON 1				CON 2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2412	1M	17.18	0.052	20.08	0.102	17.07	0.051	19.95	0.099	< 30
2437		17.28	0.053	20.14	0.103	17.18	0.052	20.01	0.100	< 30
2462		17.55	0.057	<b>20.39</b>	<b>0.109</b>	17.45	0.056	20.26	0.106	< 30
2437	2M	17.24	0.053	20.09	0.102	17.16	0.052	19.99	0.100	< 30
2437	5.5M	17.18	0.052	20.06	0.101	17.11	0.051	19.95	0.099	< 30
2437	11M	17.11	0.051	19.99	0.100	17.09	0.051	19.88	0.097	< 30

Model Number	I-15 ETR									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 3: IEEE 802.11g Link Mode									
Date of Test	03/21/2013						Test Site	TE05		
Frequency (MHz)	Data Rate	CON 1				CON 2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2412	6M	14.53	0.028	22.33	0.171	14.41	0.028	22.21	0.166	< 30
2437		14.66	0.029	22.42	0.175	14.52	0.028	22.28	0.169	< 30
2462		14.73	0.030	<b>22.49</b>	<b>0.177</b>	14.61	0.029	22.36	0.172	< 30
2437	9M	14.64	0.029	22.38	0.173	14.53	0.028	22.26	0.168	< 30
2437	12M	14.60	0.029	22.30	0.170	14.48	0.028	22.22	0.167	< 30
2437	18M	14.56	0.029	22.22	0.167	14.45	0.028	22.19	0.166	< 30
2437	24M	14.53	0.028	22.16	0.164	14.40	0.028	22.11	0.163	< 30
2437	36M	14.50	0.028	22.10	0.162	14.37	0.027	22.03	0.160	< 30
2437	48M	14.47	0.028	22.04	0.160	14.34	0.027	21.96	0.157	< 30
2437	54M	14.45	0.028	22.00	0.158	14.31	0.027	21.89	0.155	< 30

Model Number	I-15 ETR									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode									
Date of Test	03/21/2013						Test Site		TE05	
Frequency (MHz)	Data Rate	CON 1				CON 2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2412	6.5M	14.61	0.029	21.93	0.156	14.44	0.028	21.84	0.153	< 30
2437		14.77	0.030	22.13	0.163	14.61	0.029	22.06	0.161	< 30
2462		14.87	0.031	<b>22.33</b>	<b>0.171</b>	14.73	0.030	22.21	0.166	< 30
2437	13M	14.75	0.030	22.11	0.163	14.55	0.029	22.03	0.160	< 30
2437	19.5M	14.72	0.030	22.08	0.161	14.51	0.028	21.98	0.001	< 30
2437	26M	14.69	0.029	22.05	0.160	14.43	0.028	21.95	0.158	< 30
2437	39M	14.66	0.029	22.02	0.159	14.41	0.028	21.91	0.157	< 30
2437	52M	14.62	0.029	21.98	0.158	14.36	0.027	21.84	0.155	< 30
2437	58.5M	14.60	0.029	21.96	0.157	14.31	0.027	21.81	0.153	< 30
2437	65M	14.57	0.029	21.93	0.156	14.29	0.027	21.77	0.152	< 30


Model Number	I-15 ETR									
Test Item	Maximum Conducted Output Power									
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode									
Date of Test	03/21/2013						Test Site		TE05	
Frequency (MHz)	Data Rate	CON 1				CON 2				Limit (dBm)
		Average Power		Peak Power		Average Power		Peak Power		
		(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	(dBm)	(W)	
2422	13.5M	14.69	0.029	21.96	0.157	14.54	0.028	21.81	0.152	< 30
2437		14.78	0.030	22.03	0.160	14.63	0.029	21.88	0.154	< 30
2452		14.84	0.030	<b>22.25</b>	<b>0.168</b>	14.72	0.030	22.09	0.162	< 30
2437	27M	14.76	0.030	22.01	0.159	14.59	0.029	21.81	0.152	< 30
2437	40.5M	14.72	0.030	21.97	0.157	14.51	0.028	21.77	0.150	< 30
2437	54M	14.69	0.029	21.94	0.156	14.49	0.028	21.71	0.148	< 30
2437	81M	14.66	0.029	21.91	0.155	14.44	0.028	21.66	0.147	< 30
2437	108M	14.63	0.029	21.88	0.154	14.39	0.027	21.62	0.145	< 30
2437	121.5M	14.59	0.029	21.84	0.153	14.31	0.027	21.59	0.144	< 30
2437	135M	14.57	0.029	21.82	0.152	14.22	0.026	21.54	0.143	< 30

## 7 6dB RF Bandwidth Measurement

### 7.1. Limit

Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

### 7.2. Test Setup



### 7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Test Site	ATL	TE05	TE05	N.C.R.	-----

dRemark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 7.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of Oct 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel 1, 6, 11)

## 7.5. Test Result




Model Number	I-15 ETR		
Test Item	6dB RF Bandwidth		
Test Mode	Mode 2: IEEE 802.11b Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2412	10186	> 500	
2437	10194	> 500	
2462	10193	> 500	

Model Number	I-15 ETR		
Test Item	6dB RF Bandwidth		
Test Mode	Mode 3: IEEE 802.11g Link Mode		
Date of Test	03/30/2013	Test Site	TE06
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2412	16583	> 500	
2437	16532	> 500	
2462	16517	> 500	

Model Number	I-15 ETR		
Test Item	6dB RF Bandwidth		
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2412	17663	> 500	
2437	17677	> 500	
2462	17656	> 500	

Model Number	I-15 ETR		
Test Item	6dB RF Bandwidth		
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2422	36.392	> 500	
2437	36.402	> 500	
2452	36.167	> 500	


## 7.6. Test Graphs

Mode 2: IEEE 802.11b Link Mode	
2412	 <p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>Res BW 100 kHz VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 13.9552 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 14.684 kHz</p> <p>x dB Bandwidth 10.186 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>
2437	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>Res BW 100 kHz VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 13.9530 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -2.354 kHz</p> <p>x dB Bandwidth 10.194 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>
2462	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>Res BW 100 kHz VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 13.9418 MHz Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 1.310 kHz</p> <p>x dB Bandwidth 10.193 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>




## Mode 3: IEEE 802.11g Link Mode


2412






2437



2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode


2412	 <p>Agilent T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 20 dB</p> <p>Peak 10 dB/Offst 11.3 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>Res BW 100 kHz VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5003 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 1.201 kHz</p> <p>x dB Bandwidth 17.663 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2437	 <p>Agilent T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 20 dB</p> <p>Peak 10 dB/Offst 11.3 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>Res BW 100 kHz VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5123 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -7.558 kHz</p> <p>x dB Bandwidth 17.677 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2462	 <p>Agilent T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 20 dBm Atten 20 dB</p> <p>Peak 10 dB/Offst 11.3 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>Res BW 100 kHz VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5201 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -2.744 kHz</p> <p>x dB Bandwidth 17.656 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

## Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode


2422



2437



2452




## 8 Maximum Power Density Measurement

### 8.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 8.2. Test Setup



### 8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 8.4. Test Procedure

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

## 8.5. Test Result




Model Number	I-15 ETR		
Test Item	Maximum Power Density		
Test Mode	Mode 2: IEEE 802.11b Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Reading (dBm/100KHz)		Limit (dBm)
2412	2.89		< 8
2437	3.07		< 8
2462	3.07		< 8

Model Number	I-15 ETR		
Test Item	Maximum Power Density		
Test Mode	Mode 3: IEEE 802.11g Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Reading (dBm/100KHz)		Limit (dBm)
2412	-1.33		< 8
2437	-1.31		< 8
2462	-1.54		< 8

Model Number	I-15 ETR		
Test Item	Maximum Power Density		
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Reading (dBm/100KHz)		Limit (dBm)
2412	-3.53		< 8
2437	-3.64		< 8
2462	-3.28		< 8


Model Number	I-15 ETR		
Test Item	Maximum Power Density		
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Reading (dBm/100KHz)		Limit (dBm)
2422	-6.22		< 8
2437	-6.32		< 8
2452	-6.47		< 8

## 8.6. Test Graphs


Mode 2: IEEE 802.11b Link Mode	
2412	 <p>Agilent T Freq/Channel</p> <p>Ref 20 dBm Atten 20 dB Mkr1 2.412 99 GHz 2.89 dBm</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>LgAv</p> <p>M1 S2 S3 FC AL</p> <p>E(f): FTun Swp</p> <p>Center 2.412 00 GHz Span 16 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 1.56 ms (601 pts)</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.40400000 GHz</p> <p>Stop Freq 2.42000000 GHz</p> <p>CF Step 1.60000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2437	 <p>Agilent T Freq/Channel</p> <p>Ref 20 dBm Atten 20 dB Mkr1 2.437 99 GHz 3.07 dBm</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>LgAv</p> <p>M1 S2 S3 FC AL</p> <p>E(f): FTun Swp</p> <p>Center 2.437 00 GHz Span 16 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 1.56 ms (601 pts)</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42900000 GHz</p> <p>Stop Freq 2.44500000 GHz</p> <p>CF Step 1.60000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2462	 <p>Agilent T Freq/Channel</p> <p>Ref 20 dBm Atten 20 dB Mkr1 2.462 96 GHz 3.07 dBm</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>LgAv</p> <p>M1 S2 S3 FC AL</p> <p>E(f): FTun Swp</p> <p>Center 2.462 00 GHz Span 16 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 1.56 ms (601 pts)</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.45400000 GHz</p> <p>Stop Freq 2.47000000 GHz</p> <p>CF Step 1.60000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 3: IEEE 802.11g Link Mode


2412






2437



2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode

2412	 <p>Agilent T Freq/Channel</p> <p>Ref 20 dBm Atten 20 dB Mkr1 2.409 12 GHz -3.53 dBm</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>LgAv</p> <p>M1 S2 S3 FC AL</p> <p>E(f): FTun Swp</p> <p>Center 2.412 00 GHz Span 27 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.6 ms (601 pts)</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39850000 GHz</p> <p>Stop Freq 2.42550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2437	 <p>Agilent T Freq/Channel</p> <p>Ref 20 dBm Atten 20 dB Mkr1 2.434 12 GHz -3.64 dBm</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>LgAv</p> <p>M1 S2 S3 FC AL</p> <p>E(f): FTun Swp</p> <p>Center 2.437 00 GHz Span 27 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.6 ms (601 pts)</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42350000 GHz</p> <p>Stop Freq 2.45050000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2462	 <p>Agilent T Freq/Channel</p> <p>Ref 20 dBm Atten 20 dB Mkr1 2.459 12 GHz -3.28 dBm</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>LgAv</p> <p>M1 S2 S3 FC AL</p> <p>E(f): FTun Swp</p> <p>Center 2.462 00 GHz Span 27 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.6 ms (601 pts)</p> <p>Copyright 2000-2005 Agilent Technologies</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44850000 GHz</p> <p>Stop Freq 2.47550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>




Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode


2422



2437



2452




## 9 Out of Band Conducted Emissions Measurement

### 9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### 9.2. Test Setup



### 9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(2)
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/09/2012	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 9.4. Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.


All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band.

The test was performed at 3 channels (Channel 1, 6, 11)


## 9.5. Test Graphs

Mode 2: IEEE 802.11b Link Mode


2412



2437



2462



Mode 3: IEEE 802.11g Link Mode


2412



2437




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode


2412



2437



2462






Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode


2422



2437



2452




## 10 Band Edges Measurement

### 10.1.Limit

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 10.2.Test Setup



### 10.3.Test Instruments

3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/16/2012	(2)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/21/2013	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/21/2013	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/21/2013	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/15/2012	(1)
Test Site	ATL	TE01	888001	08/28/2012	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

#### **10.4. Test Procedure**

The EUT was setup to ANSI C63.4, 2009; tested to DTS test procedure of Oct 2012 KDB558074 for compliance to FCC 47CFR 15.247 requirements.

The emissions on the harmonics frequencies, the limits, and the margin of compliance are presented. These tests were made when the transmitter was in full radiated power. The additional test was performed to show compliance with the requirement at the band-edge frequency 2483.5 MHz and up to 2500 MHz and at 2390.0 MHz.

The transmitter was configured with the worst case antenna and setup to transmit at the highest channel. Then the field strength was measured at 2483.5 MHz.


The transmitter was then configured with the worst case antenna and setup to transmit at the lowest channel. Then the field strength was measured at 2390.0 MHz. These tests were performed at 4 different bit rates.

For measurements the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.




## 10.5.Test Result

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	03/21/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2381.720	52.77	3.83	56.60	74.00	-17.40	peak
2	2381.720	38.05	3.83	41.88	54.00	-12.12	AVG
3	2390.000	49.57	3.88	53.45	74.00	-20.55	peak
4	2390.000	40.27	3.88	44.15	54.00	-9.85	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	03/21/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2383.700	50.19	3.83	54.02	74.00	-19.98	peak
2	2383.700	38.30	3.83	42.13	54.00	-11.87	AVG
3	2390.000	47.55	3.88	51.43	74.00	-22.57	peak

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	03/21/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	49.74	4.50	54.24	74.00	-19.76	peak
2	2483.500	38.86	4.50	43.36	54.00	-10.64	AVG
3	2485.720	50.83	4.52	55.35	74.00	-18.65	peak
4	2485.720	37.70	4.52	42.22	54.00	-11.78	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	2	Date:	03/21/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	47.82	4.50	52.32	74.00	-21.68	peak
2	2483.500	37.68	4.50	42.18	54.00	-11.82	AVG
3	2484.520	49.03	4.51	53.54	74.00	-20.46	peak
4	2484.520	37.44	4.51	41.95	54.00	-12.05	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	03/21/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.530	53.60	3.88	57.48	74.00	-16.52	peak
2	2389.530	37.72	3.88	41.60	54.00	-12.40	AVG
3	2390.000	53.70	3.88	57.58	74.00	-16.42	peak
4	2390.000	37.76	3.88	41.64	54.00	-12.36	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	03/21/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2387.880	50.32	3.86	54.18	74.00	-19.82	peak
2	2387.880	36.90	3.86	40.76	54.00	-13.24	AVG
3	2390.000	49.25	3.88	53.13	74.00	-20.87	peak
4	2390.000	38.09	3.88	41.97	54.00	-12.03	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	03/21/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	49.78	4.50	54.28	74.00	-19.72	peak
2	2483.500	36.66	4.50	41.16	54.00	-12.84	AVG
3	2483.720	54.97	4.50	59.47	74.00	-14.53	peak
4	2483.720	36.59	4.50	41.09	54.00	-12.91	AVG


Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	3	Date:	03/21/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	50.89	4.50	55.39	74.00	-18.61	peak
2	2483.500	35.80	4.50	40.30	54.00	-13.70	AVG
3	2483.760	52.87	4.51	57.38	74.00	-16.62	peak
4	2483.760	35.55	4.51	40.06	54.00	-13.94	AVG




Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	4	Date:	03/21/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.980	50.89	3.88	54.77	74.00	-19.23	peak
2	2388.980	37.50	3.88	41.38	54.00	-12.62	AVG
3	2390.000	49.94	3.88	53.82	74.00	-20.18	peak
4	2390.000	37.67	3.88	41.55	54.00	-12.45	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	4	Date:	03/21/2013
Frequency:	2412 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.210	50.14	3.86	54.00	74.00	-20.00	peak
2	2388.210	37.61	3.86	41.47	54.00	-12.53	AVG
3	2390.000	48.36	3.88	52.24	74.00	-21.76	peak
4	2390.000	37.76	3.88	41.64	54.00	-12.36	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	4	Date:	03/21/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	48.06	4.50	52.56	74.00	-21.44	peak
2	2483.500	37.08	4.50	41.58	54.00	-12.42	AVG
3	2484.800	50.47	4.51	54.98	74.00	-19.02	peak
4	2484.800	36.63	4.51	41.14	54.00	-12.86	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	4	Date:	03/21/2013
Frequency:	2462 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	47.62	4.50	52.12	74.00	-21.88	peak
2	2483.500	36.70	4.50	41.20	54.00	-12.80	AVG
3	2484.080	49.09	4.51	53.60	74.00	-20.40	peak
4	2484.080	36.60	4.51	41.11	54.00	-12.89	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	5	Date:	03/21/2013
Frequency:	2422 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.720	52.32	3.87	56.19	74.00	-17.81	peak
2	2388.720	37.67	3.87	41.54	54.00	-12.46	AVG
3	2390.000	51.27	3.88	55.15	74.00	-18.85	peak
4	2390.000	37.83	3.88	41.71	54.00	-12.29	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	5	Date:	03/21/2013
Frequency:	2422 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2384.280	50.54	3.84	54.38	74.00	-19.62	peak
2	2384.280	37.29	3.84	41.13	54.00	-12.87	AVG
3	2390.000	48.34	3.88	52.22	74.00	-21.78	peak
4	2390.000	37.77	3.88	41.65	54.00	-12.35	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	5	Date:	03/21/2013
Frequency:	2452 MHz	Test By:	Fly Lu
Ant.Polar.:	Horizontal		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	48.34	4.50	52.84	74.00	-21.16	peak
2	2483.500	36.68	4.50	41.18	54.00	-12.82	AVG
3	2484.000	51.87	4.51	56.38	74.00	-17.62	peak
4	2484.000	36.63	4.51	41.14	54.00	-12.86	AVG

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	I-15 ETR	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	5	Date:	03/21/2013
Frequency:	2452 MHz	Test By:	Fly Lu
Ant.Polar.:	Vertical		



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	48.52	4.50	53.02	74.00	-20.98	peak
2	2483.500	36.81	4.50	41.31	54.00	-12.69	AVG
3	2484.200	49.76	4.51	54.27	74.00	-19.73	peak
4	2484.200	36.73	4.51	41.24	54.00	-12.76	AVG




## 11 99 % Occupied Bandwidth Measurement

### 11.1.Limit

N/A

### 11.2.Test Setup



### 11.3.Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/19/2012	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

### 11.4.Test Procedure

The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%.

The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

### 11.5. Test Result




Model Number	I-15 ETR		
Test Item	99 % Occupied Bandwidth		
Test Mode	Mode 2: IEEE 802.11b Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2412	13955.2	-----	
2437	13953.0	-----	
2462	13941.8	-----	

Model Number	I-15 ETR		
Test Item	99 % Occupied Bandwidth		
Test Mode	Mode 3: IEEE 802.11g Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2412	16422.5	-----	
2437	16410.6	-----	
2462	16404.0	-----	

Model Number	I-15 ETR		
Test Item	99 % Occupied Bandwidth		
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2412	17500.3	-----	
2437	17512.3	-----	
2462	17520.1	-----	


Model Number	I-15 ETR		
Test Item	99 % Occupied Bandwidth		
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode		
Date of Test	03/30/2013	Test Site	TE05
Frequency (MHz)	Measurement (kHz)	Limit (kHz)	
2422	35776.5	-----	
2437	35804.5	-----	
2452	35768.7	-----	

## 11.6. Test Graphs


Mode 2: IEEE 802.11b Link Mode	
2412	 <p>Agilent R T Freq/Channel</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 13.9552 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 14.684 kHz</p> <p>x dB Bandwidth 10.186 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>
2437	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 13.9530 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -2.354 kHz</p> <p>x dB Bandwidth 10.194 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>
2462	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 13.9418 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 1.310 kHz</p> <p>x dB Bandwidth 10.193 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>

## Mode 3: IEEE 802.11g Link Mode


2412






2437



2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz Link Mode


2412	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.412 00 GHz Span 30 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5003 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 1.201 kHz</p> <p>x dB Bandwidth 17.663 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>
2437	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.437 00 GHz Span 30 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5123 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -7.558 kHz</p> <p>x dB Bandwidth 17.677 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>
2462	 <p>Agilent T Freq/Channel</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Ref 20 dBm Atten 20 dB</p> <p>*Peak Log 10 dB/Offst 11.3 dB</p> <p>Center 2.462 00 GHz Span 30 MHz</p> <p>*Res BW 100 kHz *VBW 300 kHz Sweep 2.88 ms (601 pts)</p> <p>Occupied Bandwidth 17.5201 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error -2.744 kHz</p> <p>x dB Bandwidth 17.656 MHz</p> <p>Copyright 2000-2005 Agilent Technologies</p>

## Mode 5: IEEE 802.11n 2.4GHz 40MHz Link Mode


2422



2437



2452



## 12 Antenna Measurement

### 12.1.Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 12.2.Antenna Connector Construction

The antenna used in this product is below:

Item	Antenna	Model Number	Type	Max. Gain
1	Main ANT (L)	151504-10	Folded Dipole Antenna	3.86 dBi
2	Aux ANT (R)	151504-10	Folded Dipole Antenna	3.60 dBi