

FCC 47 CFR PART 15 SUBPART C

Product Type : Tobii Dynavox I-12+
Applicant : Tobii Technology AB
Address : Karlsrovagen 2D, 182 53 Danderyd, SWEDEN
Trade Name : tobii dynavox
Model Number : 12003611 I-12+ ETR-01, xxxxxxxx I-12+ ETR-xx (x=0~9, A~Z, a~z or blank or slash; for marketing purpose only and no impact safety related constructions and critical components)
Test Specification : FCC 47 CFR PART 15 SUBPART C: Oct., 2014
ANSI C63.10:2009
Receive Date : Dec. 27, 2014
Test Period : Feb. 07~Feb. 25, 2015
Issue Date : Mar. 27, 2015

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

Revision History

Rev.	Issue Date	Revisions	Revised By
00	Feb. 26, 2015	Initial Issue	
01	Mar. 27, 2015	Revised report Information.	Snow Wang

Verification of Compliance

Issued Date: 03/27/2015

Product Type : Tobii Dynavox I-12+
Applicant : Tobii Technology AB
Address : Karlsrovagen 2D, 182 53 Danderyd, SWEDEN
Trade Name : tobii dynavox
Model Number : 12003611 I-12+ ETR-01, xxxxxxxx I-12+ ETR-xx (x=0~9, A~Z, a~z or blank or slash; for marketing purpose only and no impact safety related constructions and critical components)
FCC ID : W5M-TDI12A
EUT Rated Voltage : DC 24V, 2.71A
Test Voltage : 120 Vac / 60 Hz
Applicable Standard : FCC 47 CFR PART 15 SUBPART C: Oct., 2014
ANSI C63.10:2009
Test Result : Complied

Performing Lab. : A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade City,
Taoyuan County 334, Taiwan R.O.C.
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
<http://www.atl-lab.com.tw/e-index.htm>

A Test Lab Techno Corp. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by A Test Lab Techno Corp. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By

: Fly Lu
(Manager) (Fly Lu)

Reviewed By

(Testing Engineer)

: Eric Ou Yang
(Eric Ou Yang)

TABLE OF CONTENTS

1	General Information.....	6
1.1.	Summary of Test Result	6
1.2.	Measurement Uncertainty	6
2	EUT Description	7
3	Test Methodology	8
3.1.	Mode of Operation	8
3.2.	EUT Exercise Software	8
3.3.	Configuration of Test System Details	9
3.4.	Test Site Environment	9
4	Maximum Conducted Output Power Measurement	11
4.1.	Limit.....	11
4.2.	Test Setup	11
4.3.	Test Instruments	11
4.4.	Test Procedure	11
4.5.	Test Result	12
5	Conducted Emission Measurement.....	14
5.1.	Limit.....	14
5.2.	Test Instruments	14
5.3.	Test Setup	14
5.4.	Test Procedure	15
5.5.	Test Result	16
6	Radiated Interference Measurement.....	18
6.1.	Limit.....	18
6.2.	Test Instruments	18
6.3.	Setup	19
6.4.	Test Procedure	21
6.5.	Test Result	22
7	20dB RF Bandwidth and 99 % Occupied Bandwidth Measurement.....	26
7.1.	Limit.....	26
7.2.	Test Setup	26
7.3.	Test Instruments	26
7.4.	Test Procedure	27
7.5.	Test Result	28
7.6.	Test Graphs	29

8	Carrier Frequency Separation Measurement	33
8.1.	Limit.....	33
8.2.	Test Setup	33
8.3.	Test Instruments	33
8.4.	Test Procedure	34
8.5.	Test Result	35
8.6.	Test Graphs	36
9	Number of Hopping Measurement	38
9.1.	Limit.....	38
9.2.	Test Setup	38
9.3.	Test Instruments	38
9.4.	Test Procedure	38
9.5.	Test Result	39
9.6.	Test Graphs	40
10	Time of Occupancy (Dwell Time) Measurement	42
10.1.	Limit.....	42
10.2.	Test Setup	42
10.3.	Test Instruments	42
10.4.	Test Procedure	42
10.5.	Test Result	43
10.6.	Test Graphs	45
11	Out of Band Conducted Emissions Measurement	47
11.1.	Limit.....	47
11.2.	Test Setup	47
11.3.	Test Instruments	47
11.4.	Test Procedure	47
11.5.	Test Graphs	48
12	Band Edges Measurement	52
12.1.	Limit.....	52
12.2.	Test Setup	52
12.3.	Test Instruments	52
12.4.	Test Procedure	53
12.5.	Test Result	54
13	Antenna Measurement	57
13.1.	Limit.....	57
13.2.	Antenna Connector Construction	57

1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.247			
15.207	AC Power Conducted Emission	PASS	-----
Standard	Item	Result	Remark
15.247			
15.247(b)(1)	Max. Output Power	PASS	-----
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(a)(1)	20dB RF Bandwidth	PASS	-----
15.247(a)(1)	Carrier Frequency Separation	PASS	-----
15.247(a)(1)(iii)	Number of Hopping	PASS	-----
15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.247(d)	Band Edge Measurement	PASS	-----
-	Occupied Bandwidth Measurement	PASS	-----
15.203	Antenna Requirement	PASS	-----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2. Measurement Uncertainty

Test Item	Frequency Range		Uncertainty (dB)
Conducted Emission	9kHz ~ 30MHz		± 2.02
Radiated Emission	30MHz ~ 1000MHz	Horizontal	± 3.98
		Vertical	± 3.62
	1000MHz ~ 18000MHz	Horizontal	± 3.11
		Vertical	± 3.07
	18000MHz ~ 40000MHz	Horizontal	± 3.66
		Vertical	± 3.54

2 EUT Description

Product	Tobii Dynavox I-12+				
Trade Name	tobii dynavox				
Model Number	12003611 I-12+ ETR-01, xxxxxxxx I-12+ ETR-xx (x=0~9, A~Z, a~z or blank or slash; for marketing purpose only and no impact safety related constructions and critical components)				
Applicant	Tobii Technology AB Karlsrovagen 2D, 182 53 Danderyd, SWEDEN				
Manufacturer	ONYX Healthcare 2F., No.135, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)				
FCC ID	W5M-TDI12A				
Frequency Range	2402 ~ 2480 MHz				
Modulation Type	GFSK for 1Mbps				
	$\pi/4$ -DQPSK for 2Mbps				
	8DPSK for 3Mbps				
Antenna Type	Internal antenna				
Antenna Gain	3.89 dBi				
RF Output Power (Conducted)	GFSK for 1Mbps	3.42	dBm /	0.002	W
	$\pi/4$ -DQPSK for 2Mbps	1.59	dBm /	0.001	W
	8DPSK for 3Mbps	1.76	dBm /	0.001	W
99 % Occupied Bandwidth	GFSK: 0.901MHz				
	8DPSK: 1.19MHz				
Emission Designator	GFSK: 901KF1D				
	8DPSK: 1M19G1D				

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test Mode
Mode 1: Normal Operation Mode
Mode 2: GFSK Link Mode
Mode 3: $\pi/4$ -DQPSK Link Mode
Mode 4: 8DPSK Link Mode

By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "X axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

Final-Test Mode
Mode 1: Normal Operation Mode
Mode 2: GFSK Link Mode
Mode 4: 8DPSK Link Mode

Description of Test Modes

Preliminary tests were performed in different modulation to find the worst case. The modulation has shown the worst-case in section 4.5. Investigation has been done on all the possible configurations for searching the worst cases.

Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:


	Product	Manufacturer	Model Number	Serial Number	Power Cord
1.	Bluetooth Tester	R & S	CBT	100350	NA

3.2. EUT Exercise Software


1	Setup the EUT and Bluetooth Tester (CBT) as shown on 3.3.
2	Turn on the power of all equipment.
3	EUT run test program.
4	Open Bluetooth function link to CBT.

3.3. Configuration of Test System Details

Conducted Emission



Radiated Emission



3.4. Test Site Environment


Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

4 Maximum Conducted Output Power Measurement

4.1. Limit

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels < 0.125 watt.

4.2. Test Setup



4.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Single Channel PK Power Sensor	Agilent	N1911A	MY45101619	12/15/2014	(1)
Wideband Power Meter	Agilent	N1921A	MY45241957	12/15/2014	(1)
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	03/03/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

4.4. Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum peak output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode. For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6)/3 dBm. The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

4.5. Test Result

Model Number	12003611 I-12+ ETR-01			
Test Item	Maximum Conducted Output Power			
Test Mode	Mode 2: GFSK Link Mode			
Date of Test	02/07/2015		Test Site	TE02
Frequency (MHz)	Packet Type	Peak Power		Limit (W)
		(dBm)	(W)	
2402	DH1	1.51	0.001	< 0.125
	DH3	1.54	0.001	< 0.125
	DH5	1.57	0.001	< 0.125
2441	DH1	2.18	0.002	< 0.125
	DH3	2.21	0.002	< 0.125
	DH5	2.27	0.002	< 0.125
2480	DH1	3.32	0.002	< 0.125
	DH3	3.35	0.002	< 0.125
	DH5	3.42	0.002	< 0.125

Model Number	12003611 I-12+ ETR-01			
Test Item	Maximum Conducted Output Power			
Test Mode	Mode 3: $\pi/4$ -DQPSK Mode			
Date of Test	02/07/2015		Test Site	TE02
Frequency (MHz)	Packet Type	Peak Power		Limit (W)
		(dBm)	(W)	
2402	DH1	0.17	0.001	< 0.125
	DH3	0.21	0.001	< 0.125
	DH5	0.36	0.001	< 0.125
2441	DH1	0.69	0.001	< 0.125
	DH3	0.77	0.001	< 0.125
	DH5	0.86	0.001	< 0.125
2480	DH1	1.48	0.001	< 0.125
	DH3	1.52	0.001	< 0.125
	DH5	1.59	0.001	< 0.125

Note: The relevant measured result has the offset with cable loss already.

Model Number	12003611 I-12+ ETR-01			
Test Item	Maximum Conducted Output Power			
Test Mode	Mode 4: 8DPSK Link Mode			
Date of Test	02/07/2015		Test Site	TE02
Frequency (MHz)	Packet Type	Peak Power		Limit (W)
		(dBm)	(W)	
2402	DH1	0.26	0.001	< 0.125
	DH3	0.31	0.001	< 0.125
	DH5	0.41	0.001	< 0.125
2441	DH1	0.81	0.001	< 0.125
	DH3	0.86	0.001	< 0.125
	DH5	0.95	0.001	< 0.125
2480	DH1	1.59	0.001	< 0.125
	DH3	1.69	0.001	< 0.125
	DH5	1.76	0.001	< 0.125

Note: The relevant measured result has the offset with cable loss already.

5 Conducted Emission Measurement

5.1. Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50


5.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/12/2014	(1)
LISN	R&S	ENV216	101040	03/07/2014	(1)
LISN	R&S	ENV216	101041	03/07/2014	(1)
RF Cable	EMCI	RG 214/U	TE-02	06/30/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

5.3. Test Setup



5.4. Test Procedure


The power line conducted emission measurements were performed in a shielded enclosure. The EUT was assembled on a wooden table which is 80 centimeters high, was placed 40 centimeters from the back wall and at least 1 meter from the sidewall.

Power was fed to the EUT from the public utility power grid through a line filter and EMCO Model 3162/2 SH Line Impedance Stabilization Networks (LISN). The LISN housing, measuring instrumentation case, ground plane, etc., were electrically bonded together at the same RF potential. The Spectrum analyzer was connected to the AC line through an isolation transformer. The 50-ohm output of the LISN was connected to the spectrum analyzer directly. Conducted emission levels were in the CISPR quasi-peak detection mode. The analyzer's 6 dB bandwidth was set to 9 KHz. No post-detector video filter was used.

The spectrum was scanned from 150 KHz to 30 MHz. The physical arrangement of the test system and associated cabling was varied (within the scope of arrangements likely to be encountered in actual use) to determine the effect on the unit's emanations in amplitude and frequency. All spurious emission frequencies were observed. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in paragraph 4.1.

5.5. Test Result

Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	12003611 I-12+ ETR-01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	02/07/2015
		Test By:	Eric Ou Yang
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1500	41.78	13.39	9.59	51.37	22.98	66.00	56.00	-14.63	-33.02	Pass
2	0.1620	40.10	11.34	9.60	49.70	20.94	65.36	55.36	-15.66	-34.42	Pass
3	0.1685	39.36	10.93	9.60	48.96	20.53	65.03	55.03	-16.07	-34.50	Pass
4	0.1900	38.79	26.21	9.60	48.39	35.81	64.04	54.04	-15.65	-18.23	Pass
5	0.1980	38.16	26.01	9.60	47.76	35.61	63.69	53.69	-15.93	-18.08	Pass
6	0.2180	33.95	7.71	9.60	43.55	17.31	62.89	52.89	-19.34	-35.58	Pass
7	1.7900	33.25	25.34	9.68	42.93	35.02	56.00	46.00	-13.07	-10.98	Pass
8	1.8820	35.47	25.41	9.69	45.16	35.10	56.00	46.00	-10.84	-10.90	Pass
9	1.9420	28.62	21.37	9.69	38.31	31.06	56.00	46.00	-17.69	-14.94	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	12003611 I-12+ ETR-01	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	02/07/2015
		Test By:	Eric Ou Yang
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1580	40.36	11.84	9.60	49.96	21.44	65.57	55.57	-15.61	-34.13	Pass
2	0.1700	38.95	10.57	9.60	48.55	20.17	64.96	54.96	-16.41	-34.79	Pass
3	0.1820	37.35	16.47	9.60	46.95	26.07	64.39	54.39	-17.44	-28.32	Pass
4	0.1980	38.06	25.90	9.60	47.66	35.50	63.69	53.69	-16.03	-18.19	Pass
5	0.2180	33.82	7.56	9.60	43.42	17.16	62.89	52.89	-19.47	-35.73	Pass
6	1.7580	28.69	21.30	9.69	38.38	30.99	56.00	46.00	-17.62	-15.01	Pass
7	1.8500	33.96	25.96	9.69	43.65	35.65	56.00	46.00	-12.35	-10.35	Pass
8	1.8980	36.67	25.74	9.70	46.37	35.44	56.00	46.00	-9.63	-10.56	Pass
9	1.9900	27.52	20.20	9.70	37.22	29.90	56.00	46.00	-18.78	-16.10	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

6 Radiated Interference Measurement

6.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


6.2. Test Instruments

3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/06/2015	(1)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/06/2015	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/24/2014	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/24/2014	(1)
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	07/22/2014	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/11/2014	(1)
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	06/13/2014	(1)
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	02/02/2015	(1)
Microwave Cable	EMCI	EMC-104-SM-S M-14000	140202	02/24/2015	(1)
Microwave Cable	EMCI	EMC104-SM-S M-600	140301	03/03/2014	(1)
Test Site	ATL	TE01	888001	08/28/2014	(1)


Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

NOTE: N.C.R. = No Calibration Request.


6.3. Setup



Below 1GHz



Above 1GHz



6.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (model VULB9163) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 26.5 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts per meter (uV/m).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Amplitude (dBuV/m) = FI (dBuV) + AF (dBuV) + CL (dBuV) - Gain (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

$$(2) \text{ Actual Amplitude (dBuV/m) = Amplitude (dBuV) - Dis(dB)}$$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

6.5. Test Result

Below 1GHz

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		Mode 1		Date:		02/10/2015	
				Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
130.5000	40.21	-13.53	26.68	43.50	-16.82	QP	H
258.0000	45.46	-12.96	32.50	46.00	-13.50	QP	H
386.5000	44.73	-8.78	35.95	46.00	-10.05	QP	H
562.5000	36.46	-5.30	31.16	46.00	-14.84	QP	H
715.0000	36.44	-2.25	34.19	46.00	-11.81	QP	H
844.0000	36.81	0.29	37.10	46.00	-8.90	QP	H
257.5000	41.42	-12.91	28.51	46.00	-17.49	QP	V
452.0000	39.99	-7.38	32.61	46.00	-13.39	QP	V
552.0000	36.75	-5.59	31.16	46.00	-14.84	QP	V
646.5000	34.22	-3.56	30.66	46.00	-15.34	QP	V
780.0000	35.33	-0.88	34.45	46.00	-11.55	QP	V
916.5000	34.94	1.96	36.90	46.00	-9.10	QP	V

Note: No emission found between lowest internal used/generated frequencies to 30MHz (9 kHz~30MHz).

Above 1GHz

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	12003611 I-12+ ETR-01			Temp.(℃)/Hum.(%RH):	26(℃)/60%RH		
Mode:	Mode 2			Date:	02/10/2015		
Frequency:	2402 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2974.000	37.46	-0.61	36.85	74.00	-37.15	peak	H
4570.000	33.84	3.97	37.81	74.00	-36.19	peak	H
6663.000	34.09	9.43	43.52	74.00	-30.48	peak	H
3002.000	36.99	-0.54	36.45	74.00	-37.55	peak	V
4654.000	33.64	4.19	37.83	74.00	-36.17	peak	V
6726.000	34.71	9.60	44.31	74.00	-29.69	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	12003611 I-12+ ETR-01			Temp.(℃)/Hum.(%RH):	26(℃)/60%RH		
Mode:	Mode 2			Date:	02/10/2015		
Frequency:	2441 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3023.000	36.68	-0.48	36.20	74.00	-37.80	peak	H
4577.000	33.97	3.98	37.95	74.00	-36.05	peak	H
6677.000	34.03	9.46	43.49	74.00	-30.51	peak	H
3051.000	36.84	-0.40	36.44	74.00	-37.56	peak	V
4577.000	34.15	3.98	38.13	74.00	-35.87	peak	V
6705.000	33.73	9.54	43.27	74.00	-30.73	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	12003611 I-12+ ETR-01			Temp.(℃)/Hum.(%RH):	26(℃)/60%RH		
Mode:	Mode 2			Date:	02/10/2015		
Frequency:	2480 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3023.000	36.84	-0.48	36.36	74.00	-37.64	peak	H
4570.000	34.29	3.97	38.26	74.00	-35.74	peak	H
6691.000	33.93	9.50	43.43	74.00	-30.57	peak	H
3037.000	36.57	-0.44	36.13	74.00	-37.87	peak	V
4591.000	34.30	4.01	38.31	74.00	-35.69	peak	V
6733.000	33.68	9.62	43.30	74.00	-30.70	peak	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(℃)/Hum.(%RH):		26(℃)/60%RH	
Mode:		Mode 4		Date:		02/10/2015	
Frequency:		2402 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3037.000	36.71	-0.44	36.27	74.00	-37.73	peak	H
4626.000	34.88	4.10	38.98	74.00	-35.02	peak	H
6670.000	33.92	9.45	43.37	74.00	-30.63	peak	H
3023.000	36.13	-0.48	35.65	74.00	-38.35	peak	V
4563.000	35.19	3.95	39.14	74.00	-34.86	peak	V
6663.000	33.63	9.43	43.06	74.00	-30.94	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	12003611 I-12+ ETR-01			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	02/10/2015		
Frequency:	2441 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	36.74	-0.51	36.23	74.00	-37.77	peak	H
4619.000	33.05	4.10	37.15	74.00	-36.85	peak	H
6698.000	33.94	9.53	43.47	74.00	-30.53	peak	H
3030.000	36.37	-0.45	35.92	74.00	-38.08	peak	V
4591.000	34.33	4.01	38.34	74.00	-35.66	peak	V
6719.000	32.69	9.58	42.27	74.00	-31.73	peak	V


Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	12003611 I-12+ ETR-01			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	02/10/2015		
Frequency:	2480 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	36.87	-0.51	36.36	74.00	-37.64	peak	H
4549.000	34.03	3.92	37.95	74.00	-36.05	peak	H
6670.000	33.86	9.45	43.31	74.00	-30.69	peak	H
3023.000	36.50	-0.48	36.02	74.00	-37.98	peak	V
4570.000	34.87	3.97	38.84	74.00	-35.16	peak	V
6649.000	33.15	9.39	42.54	74.00	-31.46	peak	V

7 20dB RF Bandwidth and 99 % Occupied Bandwidth Measurement

7.1. Limit

N/A

7.2. Test Setup



7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Microwave Cable	EMCI	EMC104-SM-SM-1 500	140303	03/03/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

7.4. Test Procedure

20dB RF Bandwidth

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer used the following settings:

1. Span = approx. 2 to 3 times the 20dB bandwidth, centered on a hopping frequency
2. RBW \geq 1% of the 20dB span
3. VBW \geq RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold

The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate. The marker-to-peak function was used to set the marker to the peak of the emission. The marker-delta function was used to measure 20dB down one side of the emission. The marker-delta function and marker was moved to the other side of the emission until it was even with the reference marker. The marker-delta reading at this point was the 20dB bandwidth of the emission.

99 % Occupied Bandwidth

The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.




7.5. Test Result




Model Number	12003611 I-12+ ETR-01		
Test Item	20dB RF Bandwidth and 99 % Occupied Bandwidth		
Test Mode	Mode 2: GFSK Link Mode		
Date of Test	02/07/2015	Test Site	TE02
Frequency (MHz)	20dB RF Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	Limit (MHz)
2402	0.957	0.893	-----
2441	1.020	0.901	-----
2480	0.946	0.881	-----

Model Number	12003611 I-12+ ETR-01		
Test Item	20dB RF Bandwidth and 99 % Occupied Bandwidth		
Test Mode	Mode 4: 8DPSK Link Mode		
Date of Test	02/07/2015	Test Site	TE02
Frequency (MHz)	20dB RF Bandwidth (MHz)	99 % Occupied Bandwidth (MHz)	Limit (MHz)
2402	1.263	1.195	-----
2441	1.253	1.183	-----
2480	1.300	1.196	-----




7.6. Test Graphs




20dB RF Bandwidth

Mode 2: GFSK Link Mode	
2402	 <p>Agilent R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offset 1.7 dB</p> <p>Center 2.402 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 893.2807 kHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -1.555 kHz</p> <p>x dB Bandwidth 957.375 kHz</p> <p>Freq/Channel</p> <p>Center Freq 2.4020000 GHz</p> <p>Start Freq 2.4005000 GHz</p> <p>Stop Freq 2.4035000 GHz</p> <p>CF Step 300.00000 kHz</p> <p>Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>
2441	 <p>Agilent R T</p> <p>Ch Freq 2.441 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offset 1.7 dB</p> <p>Center 2.441 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 901.1465 kHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -166.366 Hz</p> <p>x dB Bandwidth 1.020 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.4410000 GHz</p> <p>Start Freq 2.4395000 GHz</p> <p>Stop Freq 2.4425000 GHz</p> <p>CF Step 300.00000 kHz</p> <p>Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>
2480	 <p>Agilent R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offset 1.7 dB</p> <p>Center 2.48 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 881.3115 kHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -2.509 kHz</p> <p>x dB Bandwidth 946.331 kHz</p> <p>Freq/Channel</p> <p>Center Freq 2.4800000 GHz</p> <p>Start Freq 2.4785000 GHz</p> <p>Stop Freq 2.4815000 GHz</p> <p>CF Step 300.00000 kHz</p> <p>Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>

Mode 4: 8DPSK Link Mode	
2402	 <p>Agilent R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offst 1.7 dB</p> <p>Center 2.402 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1954 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -13.523 kHz</p> <p>x dB Bandwidth 1.263 MHz</p> <p>Signal Track Off</p>
2441	 <p>Agilent R T</p> <p>Ch Freq 2.441 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offst 1.7 dB</p> <p>Center 2.441 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1829 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -11.513 kHz</p> <p>x dB Bandwidth 1.253 MHz</p> <p>Signal Track Off</p>
2480	 <p>Agilent R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offst 1.7 dB</p> <p>Center 2.48 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1961 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -12.018 kHz</p> <p>x dB Bandwidth 1.300 MHz</p> <p>Signal Track Off</p>

99 % Occupied Bandwidth

Mode 2: GFSK Link Mode	
2402	 <p>Agilent R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/ Offst 1.7 dB</p> <p>Center 2.402 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 893.2807 kHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -1.555 kHz</p> <p>x dB Bandwidth 957.375 kHz</p> <p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.40050000 GHz</p> <p>Stop Freq 2.40350000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2441	 <p>Agilent R T</p> <p>Ch Freq 2.441 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/ Offst 1.7 dB</p> <p>Center 2.441 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 901.1465 kHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -166.366 Hz</p> <p>x dB Bandwidth 1.020 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.44100000 GHz</p> <p>Start Freq 2.43950000 GHz</p> <p>Stop Freq 2.44250000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2480	 <p>Agilent R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/ Offst 1.7 dB</p> <p>Center 2.48 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 881.3115 kHz</p> <p>Occ BW % Pwr 99.00 % x dB -20.00 dB</p> <p>Transmit Freq Error -2.509 kHz</p> <p>x dB Bandwidth 946.331 kHz</p> <p>Freq/Channel</p> <p>Center Freq 2.48000000 GHz</p> <p>Start Freq 2.47850000 GHz</p> <p>Stop Freq 2.48150000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>


Mode 4: 8DPSK Link Mode	
2402	 <p>Agilent R T</p> <p>Ch Freq 2.402 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offst 1.7 dB</p> <p>Center 2.402 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1954 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -13.523 kHz</p> <p>x dB Bandwidth 1.263 MHz</p> <p>Signal Track On Off</p>
2441	 <p>Agilent R T</p> <p>Ch Freq 2.441 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offst 1.7 dB</p> <p>Center 2.441 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1829 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -11.513 kHz</p> <p>x dB Bandwidth 1.253 MHz</p> <p>Signal Track On Off</p>
2480	 <p>Agilent R T</p> <p>Ch Freq 2.48 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 25 dB</p> <p>#Peak Log 10 dB/Offst 1.7 dB</p> <p>Center 2.48 GHz Span 3 MHz</p> <p>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</p> <p>Occupied Bandwidth 1.1961 MHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -20.00 dB</p> <p>Transmit Freq Error -12.018 kHz</p> <p>x dB Bandwidth 1.300 MHz</p> <p>Signal Track On Off</p>

8 Carrier Frequency Separation Measurement

8.1. Limit

Title 47 of the CFR, Part 15 Subpart (c) 15.247(a)(1) requires the measurement of the bandwidth of the transmission between the -20 dB points on the transmitted spectrum. The results of this test determine the limits for channel spacing. The channel spacing shall be a minimum of 25 kHz or the 20 dB bandwidth, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.

8.2. Test Setup



8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Microwave Cable	EMCI	EMC104-SM-SM-1 500	140303	03/03/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

8.4. Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth transmitter of the V6 had its hopping function enabled. The following spectrum analyzer settings were used:

1. Span = wide enough to capture the peaks of two adjacent channels
2. Resolution (or IF) Bandwidth (RBW) \geq 1% of the span
3. Video (or Average) Bandwidth (VBW) \geq RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


The trace was allowed to stabilize. The marker-delta function was used to determine the separation between the peaks of the adjacent channels.




**8.5. Test Result**

Model Number	12003611 I-12+ ETR-01		
Test Item	Carrier Frequency Separation		
Test Mode	Mode 2: GFSK Link Mode		
Date of Test	02/07/2015	Test Site	TE02
Frequency (MHz)	Measurement (MHz)	Limit (MHz)	
2402	1	> 0.638	
2441	1	> 0.680	
2480	1	> 0.631	

Model Number	12003611 I-12+ ETR-01		
Test Item	Carrier Frequency Separation		
Test Mode	Mode 4: 8DPSK Link Mode		
Date of Test	02/07/2015	Test Site	TE02
Frequency (MHz)	Measurement (MHz)	Limit (MHz)	
2402	1	> 0.842	
2441	1	> 0.835	
2480	1	> 0.867	

8.6. Test Graphs




Mode 4: 8DPSK Link Mode																					
2402	<div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm Atten 25 dB Mkr3 2.4040125 GHz 1.405 dBm</div><div>Peak Log 10 dB/Offset 1.7 dB</div><div></div><div>Center 2.403 GHz Span 3 MHz</div><div>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</div><div><table><tr><th>Marker</th><th>Trace</th><th>Type</th><th>X Axis</th><th>Amplitude</th></tr><tr><td>1</td><td>(1)</td><td>Freq</td><td>2.4020125 GHz</td><td>1.25 dBm</td></tr><tr><td>2</td><td>(1)</td><td>Freq</td><td>2.4030125 GHz</td><td>1.385 dBm</td></tr><tr><td>3</td><td>(1)</td><td>Freq</td><td>2.4040125 GHz</td><td>1.405 dBm</td></tr></table></div></div><div><div>Freq/Channel</div><div>Center Freq 2.40300000 GHz</div><div>Start Freq 2.40150000 GHz</div><div>Stop Freq 2.40450000 GHz</div><div>CF Step 300.000000 kHz Auto Man</div><div>Freq Offset 0.00000000 Hz</div><div>Signal Track On Off</div></div></div>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.4020125 GHz	1.25 dBm	2	(1)	Freq	2.4030125 GHz	1.385 dBm	3	(1)	Freq	2.4040125 GHz	1.405 dBm
Marker	Trace	Type	X Axis	Amplitude																	
1	(1)	Freq	2.4020125 GHz	1.25 dBm																	
2	(1)	Freq	2.4030125 GHz	1.385 dBm																	
3	(1)	Freq	2.4040125 GHz	1.405 dBm																	
2441	<div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm Atten 25 dB Mkr3 2.4420125 GHz -0.44 dBm</div><div>Peak Log 10 dB/Offset 1.7 dB</div><div></div><div>Center 2.441 GHz Span 3 MHz</div><div>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</div><div><table><tr><th>Marker</th><th>Trace</th><th>Type</th><th>X Axis</th><th>Amplitude</th></tr><tr><td>1</td><td>(1)</td><td>Freq</td><td>2.4400125 GHz</td><td>-0.27 dBm</td></tr><tr><td>2</td><td>(1)</td><td>Freq</td><td>2.4410125 GHz</td><td>-0.354 dBm</td></tr><tr><td>3</td><td>(1)</td><td>Freq</td><td>2.4420125 GHz</td><td>-0.44 dBm</td></tr></table></div></div><div><div>Freq/Channel</div><div>Center Freq 2.44100000 GHz</div><div>Start Freq 2.43950000 GHz</div><div>Stop Freq 2.44250000 GHz</div><div>CF Step 300.000000 kHz Auto Man</div><div>Freq Offset 0.00000000 Hz</div><div>Signal Track On Off</div></div></div>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.4400125 GHz	-0.27 dBm	2	(1)	Freq	2.4410125 GHz	-0.354 dBm	3	(1)	Freq	2.4420125 GHz	-0.44 dBm
Marker	Trace	Type	X Axis	Amplitude																	
1	(1)	Freq	2.4400125 GHz	-0.27 dBm																	
2	(1)	Freq	2.4410125 GHz	-0.354 dBm																	
3	(1)	Freq	2.4420125 GHz	-0.44 dBm																	
2480	<div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm Atten 25 dB Mkr3 2.4800125 GHz -1.15 dBm</div><div>Peak Log 10 dB/Offset 1.7 dB</div><div></div><div>Center 2.479 GHz Span 3 MHz</div><div>#Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts)</div><div><table><tr><th>Marker</th><th>Trace</th><th>Type</th><th>X Axis</th><th>Amplitude</th></tr><tr><td>1</td><td>(1)</td><td>Freq</td><td>2.4780125 GHz</td><td>-1.235 dBm</td></tr><tr><td>2</td><td>(1)</td><td>Freq</td><td>2.4790125 GHz</td><td>-1.249 dBm</td></tr><tr><td>3</td><td>(1)</td><td>Freq</td><td>2.4800125 GHz</td><td>-1.15 dBm</td></tr></table></div></div><div><div>Freq/Channel</div><div>Center Freq 2.47900000 GHz</div><div>Start Freq 2.47750000 GHz</div><div>Stop Freq 2.48050000 GHz</div><div>CF Step 300.000000 kHz Auto Man</div><div>Freq Offset 0.00000000 Hz</div><div>Signal Track On Off</div></div></div>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.4780125 GHz	-1.235 dBm	2	(1)	Freq	2.4790125 GHz	-1.249 dBm	3	(1)	Freq	2.4800125 GHz	-1.15 dBm
Marker	Trace	Type	X Axis	Amplitude																	
1	(1)	Freq	2.4780125 GHz	-1.235 dBm																	
2	(1)	Freq	2.4790125 GHz	-1.249 dBm																	
3	(1)	Freq	2.4800125 GHz	-1.15 dBm																	

9 Number of Hopping Measurement

9.1. Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

9.2. Test Setup



9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Microwave Cable	EMCI	EMC104-SM-SM-1 500	140303	03/03/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

9.4. Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer used the following settings:

1. Span = the frequency band of operation
2. RBW \geq 1% of the span
3. VBW \geq RBW
4. Sweep = auto
5. Detector function = peak
6. Trace = max hold


The trace was allowed to stabilize.


9.5. Test Result

Model Number	12003611 I-12+ ETR-01		
Test Item	Number of Hopping		
Test Mode	Mode 2: GFSK Link Mode		
Date of Test	02/08/2015	Test Site	TE02
Frequency Range (MHz)	Measurement (ch)	Limit (ch)	
2402 - 2480	79	> 15	

Model Number	12003611 I-12+ ETR-01		
Test Item	Number of Hopping		
Test Mode	Mode 4: 8DPSK Link Mode		
Date of Test	02/08/2015	Test Site	TE02
Frequency Range (MHz)	Measurement (ch)	Limit (ch)	
2402 - 2480	79	> 15	

9.6. Test Graphs






10 Time of Occupancy (Dwell Time) Measurement

10.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

10.2. Test Setup



10.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Microwave Cable	EMCI	EMC104-SM-SM-1500	140303	03/03/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

10.4. Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage. The Bluetooth hopping function of the EUT was enabled. The following spectrum analyzer settings were used:

1. Span = zero span, centered on a hopping channel
2. RBW = 1 MHz
3. VBW \geq RBW
4. Sweep = as necessary to capture the entire dwell time per hopping channel
5. Detector function = peak
6. Trace = max hold


The marker-delta function was used to determine the dwell time.


10.5. Test Result

Model Number	12003611 I-12+ ETR-01		
Test Item	Time of Occupancy (Dwell Time)		
Test Mode	Mode 2: GFSK Link Mode		
Date of Test	02/07/2015	Test Site	TE02
DH1			
Cycle Calculate	79CH * 0.4 = 31.6 (sec)		
The EUT Hopping Number per Sec	1600 times/sec		
Each Channel Dwell Times per Sec	800/79CH = 10.13(times/sec)		
Each Channel Dwell Times (1)	0.500 ms (sec)		
Each Channel Dwell Times on Cycle(2)	31.6 * 10.13 = 320.108(times)		
Dwell Times on Cycle (1) * (2)	160.0540 ms (sec)		
LIMIT(msec)	< = 400		
DH3			
Cycle Calculate	79CH * 0.4 = 31.6 (sec)		
The EUT Hopping Number per Sec	1600 times/sec		
Each Channel Dwell Times per Sec	400/79CH = 5.1(times/sec)		
Each Channel Dwell Times (1)	1.725 ms (sec)		
Each Channel Dwell Times on Cycle(2)	31.6 * 5.1 = 161.16(times)		
Dwell Times on Cycle (1) * (2)	278.0010 ms (sec)		
LIMIT(msec)	< = 400		
DH5			
Cycle Calculate	79CH * 0.4 = 31.6 (sec)		
The EUT Hopping Number per Sec	1600 times/sec		
Each Channel Dwell Times per Sec	266.7/79CH = 3.37(times/sec)		
Each Channel Dwell Times (1)	2.975 ms (sec)		
Each Channel Dwell Times on Cycle(2)	31.6 * 3.37 = 106.492(times)		
Dwell Times on Cycle (1) * (2)	316.8137 ms (sec)		
LIMIT(msec)	< = 400		

Model Number	12003611 I-12+ ETR-01		
Test Item	Time of Occupancy (Dwell Time)		
Test Mode	Mode 4: 8DPSK Link Mode		
Date of Test	02/07/2015	Test Site	TE02
3DH1			
Cycle Calculate	79CH * 0.4 = 31.6 (sec)		
The EUT Hopping Number per Sec	1600 times/sec		
Each Channel Dwell Times per Sec	800/79CH = 10.13(times/sec)		
Each Channel Dwell Times (1)	0.500 ms (sec)		
Each Channel Dwell Times on Cycle(2)	31.6 * 10.13 = 320.108(times)		
Dwell Times on Cycle (1) * (2)	160.0540 ms (sec)		
LIMIT(msec)	< = 400		
3DH3			
Cycle Calculate	79CH * 0.4 = 31.6 (sec)		
The EUT Hopping Number per Sec	1600 times/sec		
Each Channel Dwell Times per Sec	400/79CH = 5.1(times/sec)		
Each Channel Dwell Times (1)	1.725 ms (sec)		
Each Channel Dwell Times on Cycle(2)	31.6 * 5.1 = 161.16(times)		
Dwell Times on Cycle (1) * (2)	278.0010 ms (sec)		
LIMIT(msec)	< = 400		
3DH5			
Cycle Calculate	79CH * 0.4 = 31.6 (sec)		
The EUT Hopping Number per Sec	1600 times/sec		
Each Channel Dwell Times per Sec	266.7/79CH = 3.37(times/sec)		
Each Channel Dwell Times (1)	2.975 ms (sec)		
Each Channel Dwell Times on Cycle(2)	31.6 * 3.37 = 106.492(times)		
Dwell Times on Cycle (1) * (2)	316.8137 ms (sec)		
LIMIT(msec)	< = 400		

10.6. Test Graphs






11 Out of Band Conducted Emissions Measurement

11.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

11.2. Test Setup



11.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/24/2014	(1)
Microwave Cable	EMCI	EMC104-SM-SM-1 500	140303	03/03/2014	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----


Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.


NOTE: N.C.R. = No Calibration Request.

11.4. Test Procedure


Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function. All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band. The test was performed at 3 channels (Channel 0, 39, 78)

11.5. Test Graphs





Mode 4: 8DPSK Link Mode											
2402	<div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 15 dBm</div><div>Atten 25 dB</div><div>Mkr1 2.40 GHz</div><div>0.61 dBm</div></div><div><div>Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1.7</div><div>dB</div><div>DI</div><div>-19.4</div><div>dBm</div></div><div><div>Start 30 MHz</div><div>Stop 26.5 GHz</div></div><div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 2.742 s (401 pts)</div></div><div><table><tr><th>Marker</th><th>Trace</th><th>Type</th><th>X Axis</th><th>Amplitude</th></tr><tr><td>1</td><td>(1)</td><td>Freq</td><td>2.40 GHz</td><td>0.61 dBm</td></tr></table></div></div> <div><div>Freq/Channel</div><div>Center Freq 13.2650000 GHz</div><div>Start Freq 30.0000000 MHz</div><div>Stop Freq 26.5000000 GHz</div><div>CF Step 2.64700000 GHz Auto Man</div><div>Freq Offset 0.00000000 Hz</div><div>Signal Track On Off</div></div>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.40 GHz	0.61 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.40 GHz	0.61 dBm							
2441	<div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 15 dBm</div><div>Atten 25 dB</div><div>Mkr1 2.44 GHz</div><div>0.891 dBm</div></div><div><div>Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1.7</div><div>dB</div><div>DI</div><div>-19.2</div><div>dBm</div></div><div><div>Start 30 MHz</div><div>Stop 26.5 GHz</div></div><div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 2.742 s (401 pts)</div></div><div><table><tr><th>Marker</th><th>Trace</th><th>Type</th><th>X Axis</th><th>Amplitude</th></tr><tr><td>1</td><td>(1)</td><td>Freq</td><td>2.44 GHz</td><td>0.891 dBm</td></tr></table></div></div> <div><div>Freq/Channel</div><div>Center Freq 13.2650000 GHz</div><div>Start Freq 30.0000000 MHz</div><div>Stop Freq 26.5000000 GHz</div><div>CF Step 2.64700000 GHz Auto Man</div><div>Freq Offset 0.00000000 Hz</div><div>Signal Track On Off</div></div>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	0.891 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	0.891 dBm							
2480	<div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 15 dBm</div><div>Atten 25 dB</div><div>Mkr1 2.48 GHz</div><div>-0.519 dBm</div></div><div><div>Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1.7</div><div>dB</div><div>DI</div><div>-20.5</div><div>dBm</div></div><div><div>Start 30 MHz</div><div>Stop 26.5 GHz</div></div><div><div>#Res BW 100 kHz</div><div>#VBW 300 kHz</div><div>Sweep 2.742 s (401 pts)</div></div><div><table><tr><th>Marker</th><th>Trace</th><th>Type</th><th>X Axis</th><th>Amplitude</th></tr><tr><td>1</td><td>(1)</td><td>Freq</td><td>2.48 GHz</td><td>-0.519 dBm</td></tr></table></div></div> <div><div>Freq/Channel</div><div>Center Freq 13.2650000 GHz</div><div>Start Freq 30.0000000 MHz</div><div>Stop Freq 26.5000000 GHz</div><div>CF Step 2.64700000 GHz Auto Man</div><div>Freq Offset 0.00000000 Hz</div><div>Signal Track On Off</div></div>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.48 GHz	-0.519 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.48 GHz	-0.519 dBm							




12 Band Edges Measurement

12.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

12.2. Test Setup



12.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/24/2014	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/24/2015	(1)
Horn Antenna	SCHWARZBECK MESS-ELEKTRONIK	9120D	9120D-550	06/11/2014	(1)
Microwave Cable	EMCI	EMC-104-SM-SM-1 4000	140202	02/24/2015	(1)
Microwave Cable	EMCI	EMC104-SM-SM-6 00	140301	03/03/2014	(1)
Test Site	ATL	TE01	888001	08/28/2014	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years.

NOTE: N.C.R. = No Calibration Request.

12.4. Test Procedure

Testing must be done according to this procedure, FCC Public Notice DA 00-705 - Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems. This is the only method recognized by the FCC. The emissions on the harmonics frequencies, the limits, and the margin of compliance are presented. These tests were made when the transmitter was in full radiated power. The additional test was performed to show compliance with the requirement at the band-edge frequency 2483.5 MHz and up to 2500 MHz and at 2390.0 MHz.

The transmitter was configured with the worst case antenna and setup to transmit at the highest channel. Then the field strength was measured at 2483.5 MHz.

The transmitter was then configured with the worst case antenna and setup to transmit at the lowest channel. Then the field strength was measured at 2390.0 MHz. These tests were performed at 4 different bit rates.

For measurements the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

12.5. Test Result

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		Mode 2		Date:		02/10/2015	
Frequency:		2402 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2389.310	42.73	-2.25	40.48	74.00	-33.52	peak	H
2390.000	38.83	-2.24	36.59	74.00	-37.41	peak	H
2388.320	51.95	-2.25	49.70	74.00	-24.30	peak	V
2390.000	37.26	-2.24	35.02	74.00	-38.98	peak	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		Mode 2		Date:		02/10/2015	
Frequency:		2480 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	48.27	-1.83	46.44	74.00	-27.56	peak	H
2484.660	52.40	-1.82	50.58	74.00	-23.42	peak	H
2483.500	61.94	-1.83	60.11	74.00	-13.89	peak	V
2483.500	35.30	-1.83	33.47	54.00	-20.53	AVG	V
2483.800	62.56	-1.83	60.73	74.00	-13.27	peak	V
2483.800	35.24	-1.83	33.41	54.00	-20.59	AVG	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		Mode 4		Date:		02/10/2015	
Frequency:		2402 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2388.760	43.28	-2.25	41.03	74.00	-32.97	peak	H
2390.000	42.70	-2.24	40.46	74.00	-33.54	peak	H
2387.990	50.86	-2.25	48.61	74.00	-25.39	peak	V
2390.000	40.38	-2.24	38.14	74.00	-35.86	peak	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(℃)/Hum.(%RH):		26(℃)/60%RH	
Mode:		Mode 4		Date:		02/10/2015	
Frequency:		2480 MHz		Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	47.48	-1.83	45.65	74.00	-28.35	peak	H
2484.220	53.64	-1.82	51.82	74.00	-22.18	peak	H
2483.500	64.75	-1.83	62.92	74.00	-11.08	peak	V
2483.500	35.51	-1.83	33.68	54.00	-20.32	AVG	V
2483.780	62.32	-1.83	60.49	74.00	-13.51	peak	V
2483.780	35.46	-1.83	33.63	54.00	-20.37	AVG	V

Standard:		FCC Part 15C		Test Distance:		3m	
Test item:		Radiated Emission		Power:		AC 120V/60Hz	
Model Number:		12003611 I-12+ ETR-01		Temp.(°C)/Hum.(%RH):		26(°C)/60%RH	
Mode:		Hopping		Date:		02/10/2015	
				Test By:		Eric Ou Yang	
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2373.080	39.04	-2.31	36.73	74.00	-37.27	peak	H
2390.000	36.79	-2.24	34.55	74.00	-39.45	peak	H
2483.500	37.78	-1.83	35.95	74.00	-38.05	peak	H
2492.970	39.31	-1.78	37.53	74.00	-36.47	peak	H
2387.900	47.81	-2.25	45.56	74.00	-28.44	peak	V
2390.000	37.83	-2.24	35.59	74.00	-38.41	peak	V
2483.500	37.88	-1.83	36.05	74.00	-37.95	peak	V
2484.610	52.39	-1.82	50.57	74.00	-23.43	peak	V

13 Antenna Measurement

13.1. Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b)(4), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2. Antenna Connector Construction

The antenna used in this product is Internal antenna. And the maximum Gain of this antenna is only 3.89 dBi.