



## **Compliance Testing, LLC**

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

### **Test Report**

**Prepared for: Solid Technologies**

**Model: EXPRESS Public Safety**

**Description: Class B Part 90 Booster System**

**SC-MRU700PS800PS – 700/800 MHz Amplifier**

**FCC ID: W6U700P800P**

**To**

**FCC Part 90**

**Date of Issue: July 28, 2014**

**On the behalf of the applicant:**

**Solid Technologies  
4332 E Siesta Lane  
Phoenix, AZ 85050**

**Attention of:**

**Gregory Glenn  
(408) 649-4803  
E-Mail: [greg.glenn@solid.com](mailto:greg.glenn@solid.com)**

**Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p13a0005**

**Mike Graffeo  
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	April 29, 2014	Mike Graffeo	Original Document
2.0	May 7, 2014	Mike Graffeo	Updated Emission Designators
3.0	July 8, 2014	John Erhard	Add additional part 90 rule section information to test summary table
4.0	July 28, 2014	Mike Graffeo	Added noise figure tests to show compliance with 90.219(e)(2)



## Table of Contents

<b><u>Description</u></b>	<b><u>Page</u></b>
Standard Test Conditions and Engineering Practices	6
Test Result Summary	7
Out of Band Rejection	8
Carrier Output Power (Conducted)	10
Conducted Spurious Emissions	11
Emission Masks (Occupied Bandwidth)	15
Intermodulation	20
Noise Figure Test	22
Radiated Spurious Emissions	24
Test Equipment Utilized	26



## ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



**FCC Site Reg. #349717**

**IC Site Reg. #2044A-2**

**Non-accredited tests contained in this report:**

**N/A**



**The Applicant has been cautioned as to the following:**

**15.21: Information to the User**

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**15.27(a): Special Accessories**

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without an additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.



## Test and Measurement Data

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations Part 90.219, KDB 935210 D02, and FCC Part 2 where appropriate.

## Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing.

In accordance with ANSI/TIA 603C, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104°F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Environmental Conditions		
Temp (°C)	Humidity (%)	Pressure (mbar)
21.6 - 29.0	40.2 - 57.9	964.7 - 969.4

Measurement results, unless otherwise noted, are worst-case measurements.

### EUT Description

**Model:** EXPRESS Public Safety

**Description:** Multiple-Enclosure Booster System

**Firmware:** N/A

**Test Software:** DAS Management Ver12

**Accessories:** None

**Cables:** Customer Supplied

**Modifications:** None

### Additional Information:

The EUT is an industrial booster that amplifies the signal of cellular phone signals and data communication devices. The following frequency bands and emission types are utilized

Frequency Band (MHz)		
<b>Downlink</b>	758 to 775	851 to 869
<b>Emission Designator</b>	F3E F3D F1E	F3E F3D F1E

### EUT Operation during Tests

The EUT was in a normal operating condition.

**Accessories:** None

**Cables:** None

**Modifications:** None



## Test Result Summary

Specification	Test Name	Pass, Fail, N/A	Comments
KDB 935210-D03	Out of Band Rejection	Pass	
2.1046	Output Power (Conducted)	Pass	
90.210 2.1049	Occupied Bandwidth (Emission Masks)	Pass	
90.219(e)(2)	Noise Figure	Pass	
2.1051	Spurious Emissions (Transmitter Conducted)	Pass	
KDB 935210-D03	Intermodulation	Pass	
90.213	Frequency Stability (Temperature Variation)	N/A	The EUT does not perform frequency translation
90.213	Frequency Stability (Voltage Variation)	N/A	The EUT does not perform frequency translation
2.202	Necessary Bandwidth Calculation	N/A	The EUT does not perform frequency translation

The following Part 90 band specific rules apply

Frequency Band (MHz)	Test Name	Part 90 Specification	Comments
758-769	Operational band	90.531(f), 90.531(g)	It is noted that the guard band of 768-769 exists but is not used
758-769	Power Limits	90.542	
758-769		90.543(e), 90.543(f)	
769-775	Operational band	90.531(f), 90.531(g)	
769-775	Spectrum Efficiency	90.535	The EUT cannot generate a modulated signal therefore the host signal from an already certified device controls the spectrum efficiency.
769-775	Power Limits	90.541	
769-775		90.543(a)-(d), 90.543(f)	The ACPR requirements for 90.534(a)-(d) are for the licensed radios with which the EUT operates. Compliance to the emissions masks requirements proves linear operation thus compliance.
758 to 775 851 to 869	Noise Figure	90.219(e)(2)	



## Out of Band Rejection

**Name of Test:** Out of Band Rejection

**Test Equipment Utilized:** i00405, i00331


**Engineer:** Mike Graffeo

**Test Date:** 4/9/2014

### Test Procedure

The EUT was connected to a spectrum analyzer through a 20 dB power attenuator. A signal generator was utilized to produce a swept CW signal with the RF input level set to the level determined by the intermodulation testing requirements. The downlink filter response and bandwidth were measured. The marker table function of the spectrum analyzer was used to show the maximum power and the 20 dB bandwidth of the pass band filter.


### Test Setup








## 758 - 775 MHz Band



## 851 - 869 MHz Band





## Carrier Output Power (Conducted)

**Name of Test:**

Carrier Output Power (Conducted)

**Engineer:** Mike Graffeo

**Test Equipment Utilized:**


i00405, i00331

**Test Date:** 4/12/14

### Measurement Procedure

The EUT was connected to a spectrum analyzer through a 20 dB power attenuator. A signal generator was utilized to produce a CW input signal. The RF input level was increased while monitoring the output power. The input RF drive level was increased until the EUT output reached saturation (the output stopped increasing) whereby the maximum power level and gain was achieved. The output levels with the highest output power from Out of Band Rejection Test are recorded in the following tables to and then the gain was calculated.

### Test Setup



### Downlink Output Power and Gain

#### 758 to 775 MHz Band

Tuned Frequency (MHz)	Input Power (dBm)	Output Power (dBm)	Gain (dB)
762.00	-22.01	27	49.01

#### 851 to 869 MHz Band

Tuned Frequency (MHz)	Input Power (dBm)	Output Power (dBm)	Gain (dB)
863.15	-21.51	27	48.51



## Conducted Spurious Emissions

**Name of Test:**

Conducted Spurious Emissions

**Engineer:** Mike Graffeo

**Test Equipment Utilized:**

i00405, i00331

**Test Date:** 4/9/2014

### Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator, with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor as needed to ensure accurate readings. A signal generator was utilized to produce a maximum allowable power. The conducted spurious emissions from 9 kHz to 10 times the highest tunable frequency for each operational band were measured (excluding the band defined by the Out of band emissions test). The emissions were plotted and the highest level was recorded in the summary table.


The following formulas are used for calculating the limits.

Conducted Spurious Emissions Limit =  $P1 - (43 + 10\log(P2)) = -13 \text{ dBm}$

P1 = power in dBm

P2 = power in Watts

### Test Setup




**Conducted Spurious Emissions Summary Test Table**


Tuned Frequency (MHz)	Spurious Frequency (MHz)	Measured Spurious Level (dBm)	Specification Limit (dBm)	Result
758 to 775	21842.5	-29.55	-19	Pass
851 to 869	14966	-30.99	-19	Pass



Test Plots  
758 - 775 MHz Band  
30 MHz to 1 GHz




758 - 775 MHz Band  
1 GHz to 22 GHz






851 - 869 Band  
30 MHz to 1 GHz




851 - 869 Band  
1 GHz to 22 GHz





Part 90.543(f) Testing  
851 - 869 Band


1559 MHz to 1610 MHz with 1MHz RBW



Note1: -70dBW/MHz = -40dBm

Note2: DL = -40 plus and additional -12dB for antenna gain to account for EIRP

1559 MHz to 1610 MHz with 700Hz RBW



Note1: -80dBW/MHz = -50dBm

Note2: DL = -50 plus and additional -12dB for antenna gain to account for EIRP

The test is performed using a 1.0 kHz RBW. Since the limit is referenced to a 700 Hz BW, the following correction factor is applied to the measured data.

BW correction Factor =  $10\log B1/B2$

BW correction Factor =  $10\log 700 / 1000 = -1.55 \text{ dB}$

Final Value (dBm) = conducted measurement + BW correction factor

Final Value (dBm) =  $-85.30 - 1.55 = -86.85\text{dBm}$



## Emission Masks (Occupied Bandwidth)

**Name of Test:**

Emission Masks (Occupied Bandwidth)

**Engineer:** Mike Graffeo

**Test Equipment Utilized**


i00405, i00331

**Test Date:** 4/29/2014

### Measurement Procedure

The EUT was connected directly to a spectrum analyzer to verify that the EUT meets the required emissions mask. Bandwidth calculations are located in the final section of this report.


### Test Setup






## Emission Masks Plots

### 758 - 775 MHz Band Mask B




### 758 - 775 MHz Band Mask D








758 - 775 MHz Band  
Mask E




851 - 869 MHz Band  
Mask B






851 - 869 Band  
Mask D




851 - 869 Band  
Mask E





Agilent 15:49:19 Jul 8, 2014 R T





## Intermodulation

**Name of Test:**

Intermodulation

**Engineer:** Mike Graffeo

**Test Equipment Utilized:**

i00405, i00331


**Test Date:** 4/8/2014

### Test Procedure

The EUT was connected to a spectrum analyzer through a 20 dB power attenuator. Two signal generators were utilized to produce a two tone signal with the 12.5KHz channel spacing set so the intermodulation products fell within the operational band. Frequency at the maximum power from out of band rejection was utilized.

The input signal level was increased until the intermodulation products were as close as possible to the maximum allowable level of -19 dBm without being greater than that limit. The downlink intermodulation products within the operational band were examined. The input signal level, output power, intermodulation level and gain are listed in the summary tables.

### Test Setup



### Downlink Test Results

**758 to 775 MHz Band  
Tuned to 762.00 MHz**


Frequency Pair (MHz)	Input Power (dBm)	Intermodulation Level (dBm)	Output Power (dBm)	Gain (dB)
761.9938 - 762.0063	-22.01	-38.19	26.46	48.47

**851 to 869 MHz Band  
Tuned to 863.15 MHz**


Frequency Pair (MHz)	Input Power (dBm)	Intermodulation Level (dBm)	Output Power (dBm)	Gain (dB)
863.1438 - 863.1563	-21.51	-31.19	26.11	47.62



## 758 - 775 MHz Band



## 851 - 869 Band





## Noise Figure Test

**Name of Test:** Noise Figure  
**Test Equipment Utilized:** i00331

**Engineer:** Mike Graffeo  
**Test Date:** 7/23/2014

### Test Procedure

The EUT was tested using Agilent Application Note 57-1, gain method.

### Test Setup



$$NF = NP - G - BCF + PNAD + ECF$$

$$NF = NP - G - 60 + 174 + 1.74$$

$$NF = NP - G + 115.74$$

NF = Noise Figure (dB)

NP = Noise power measured (dBm/MHz)

G = Gain for the Frequency band (dB)


BCF = Bandwidth Correction Factor =  $10\log B1/B2 = 10\log(1\text{MHz}/1\text{Hz}) = 60$  (Where BW1 = 1MHz, BW2 = 1Hz)

PNAD = Noise Power Density = 174 dBm/Hz

ECF = band edge correction factor (1%) = 1.74 dBm/Hz




### 758 to 775 MHz Band



$$NF = -62.44 - 49.01 + 115.74 = 4.29 \text{ dB}$$

### 851 to 869 MHz Band



$$NF = -60.25 - 48.51 + 115.74 = 6.98 \text{ dB}$$



## Radiated Spurious Emissions

**Name of Test:**

Radiated Spurious

**Engineer:** Mike Graffeo

**Test Equipment Utilized:**

i00405, i00331, i00103

**Test Date:** 4/10/2014

### Test Procedure

The EUT was tested in an semi-anechoic chamber with the turntable set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Emissions. The EUT was tested by rotating it 360 degrees with the antenna in both the vertical and horizontal orientation while raised from 1 to 4 meters to ensure that the signal levels were maximized. All cable and antenna correction factors were input into the spectrum analyzer ensuring an accurate measurement in ERP/EIRP with the resultant power in dBm. A signal generator was used to provide a CW signal centered in each operational uplink and downlink band. The EUT output was terminated into a 50 Ohm non-radiating load.


The following formula was used for calculating the limits:

Radiated Spurious Emissions Limit =  $P1 - (43 + 10\log(P2)) = -13\text{dBm}$

P1 = power in dBm

P2 = power in Watts

### Test Setup







### Downlink Test Results

#### 758 to 775 MHz Band 766.5 MHz Tuned Frequency

Measured Frequency (MHz)	Measured Level (dBm)	Limit (dBm)	Result
1533.0	-74.39	-13	Pass
2299.5	-69.43	-13	Pass
3066.0	-52.82	-13	Pass

#### 851 to 869 MHz Band 860 MHz Tuned Frequency

Measured Frequency (MHz)	Measured Level (dBm)	Limit (dBm)	Result
1720	-73.15	-13	Pass
2580	-66.08	-13	Pass
3440	-50.88	-13	Pass



## Test Equipment Utilized

Description	Manufacturer	Model #	CT Asset #	Last Cal Date	Cal Due Date
Signal Generator	Rohde & Schwarz	SMU200A	i00405	12/11/13	12/11/14
Spectrum Analyzer	Tektronix	RSA5126A	i00424	9/22/13	9/22/14
Spectrum Analyzer	Agilent	E4407B	i00331	4/23/13	4/23/14*
Humidity / Temp Meter	Omega	RH81	i00408	4/15/13	4/15/15
Horn Antenna	EMCO	3115	i00103	12/11/12	12/11/14
Power Attenuator	Lucas Weinschel	24-40-12	S/N: AY3295	Verified on: 8/19/13	

\* Note: Equipment is under a 60 day calibration extension per Lab Manager

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT



Test Setup Photos  
FCC ID: W6U700P800P

**RF Conducted**



**RF Radiated**

