IslandLabs
EMC Certification and Consulting

RF Exposure Evaluation

Report Prepared for: Blackline GPS Inc.

Suite 101, 1215 – 13th Street SE

Calgary Alberta

T2G 3J4

Canada

Equipment Under Test (EUT):   Model: 101283

FCC ID: W77BCN

IC Certification number: 8225A-BCN

FCC Rule Part(s):   Part 15.249

Industry Canada Rule Part(s)   RSS-210

Tested by: Island Compliance Services Inc.

6454 Fitzgerald Road

Courtenay, BC

V9J 1N7

Authorized By
Andrew Eadie (Manager)
A. Eadie

Date: 28th May 2013

FCC OATS registration number: 386117

Industry Canada OATS registration number: 9578B-1

1.1 RF EXPOSURE EVALUATION

FCC 1.1310 states the criteria listed in the table below shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in Section 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of Section 2.1093. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation".

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Average Time (s)
(A) Limits for Occupational/Control Exposures				
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposures				
300-1500	-	-	F/1500	6
1500-100,000	-	-	1	30

TABLE 1 - POWER DENSITY LIMITS

1.2 EUT OPERATING CONDITION

Maximum antenna gain = 2.0 dBi.

1.3 RF EXPOSURE EVALUATION DISTANCE CALCULATION

Frequency (MHz)	Max Antenna Gain (dBi)	Max EIRP (W)	Power Density Limit (mW/cm^2)	R (cm)
2402	2.0	0.0085	1	0.82
2440	2.0	0.0227	1	1.34
2480	2.0	0.0022	1	0.41

TABLE 2 - DISTANCE CALCULATIONS

where: S   = Allowable Power density Limit (mW/cm^2)

       EIRP   = Equivalent (or effective) isotropically radiated power (mW)

       R   = Distance to the center of radiation of the antenna (cm)

$$R = \sqrt{\frac{EIRP}{4.\pi.S}}$$

As shown above, the minimum distance where the MPE limit is reached is 1.34 cm from the EUT with 2.0 dBi antenna.