SIGNALFIRE
— WIRELESS TELEMETRY —

S/N: 00000001

Model: GW-DIN

www.signal-fire.com Hudson, MA

ETL LISTED
C US
Intertek
4003827

**Class I, Division 2
Groups C, D T5**

FCC ID: W8V-GWDIN
IC: 8373A-GWDIN

Voltage: 6 – 36 VDC
Current: 200 mA Max
Temperature: –40ºC to +85ºC

1.25"

Certified to CSA C22.2 No. 142 and CSA C22.2 No. 213   Conforms to ISA 12.12.01 and UL 916

WARNING – EXPLOSION HAZARD Substitution of
components may impair suitability for Class I, Division 2

AVERTISSEMENT - RISQUE D'EXPLOSION. La
substitution de composants peut rendre ce materiel
inacceptable pour les emplacements de classe I, division 2

WARNING – EXPLOSION HAZARD
Do not connect while circuit is live unless area is know to be
nonhazardous

AVERTISSEMENT - RISQUE D'EXPLOSION. Ne pas
debrancher tant que le circuit est sous tension, a moins qu'il
ne s'agisse d'un emplacement non dangereux.

2.75"

Notes
1. Printing is Black on a Silver Background
2. Above Graphic Representative of Label Printing
3. All Text Must be Easily Readable
4. Label Adhesive – Extra aggressive acrylic adhesive
5. Serial Numbers Increment from Starting Number
   Defined on Purchase Order
6. Temperature Range -40 to + 140 deg C

SignalFire Telemetry

Part Name	Label, DIN-GW, ETL C1D2, FCC, IC	Date 2/26/16
Part Number	345-0031-01	Rev A
Material	Metalized Polyester	