

7. Radiated Spurious Emission

7.1. Test Equipment

The following test equipments are used during the test:


Radiated Emission / CB1

Instrument	Manufacturer	Model No.	Serial No	Cal. Date	Next Cal. Date
Bilog Antenna	SCHAFFNER	CBL6112B	2895	2011/08/15	2012/08/14
Double Ridged Guide Horn Antenna	Schwarzback	BBHA 9120D	743	2012/02/03	2013/02/02
Pre-Amplifier	MITEQ	AMF-4D-0051 80-24-10P	888003	2011/12/06	2012/12/05
Pre-Amplifier	QuieTek	AP-025C	CHM-0706049	2011/03/11	2012/03/10
Spectrum Analyzer	Agilent	E4440A	MY46187335	2012/01/09	2013/01/08
Coaxial Cable	Huber+Suhner AG	Sucoflex 102	25623/2	2011/03/22	2012/03/21


Note: 1. All equipments that need to calibrate are with calibration period of 1 year.

7.2. Test Setup


Under 1GHz Test Setup:



Above 1GHz Test Setup: RF Radiated Measurement:



Substitution Measurement Setup:



7.3. Limits

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or less, but at least one percent of the emission bandwidth of the fundamental emission of the transmitter, provided the measured energy is integrated over a 1 MHz bandwidth.

7.4. Test Procedure

For measuring E.I.R.P peak power, EUT was placed on the turn-table which was rotated around 360 degrees to search the maximum radiation power and receiver antenna was rotated vertical and horizontal polarization to find the maximum polarization radiated power.

The EUT is replaced by a horn antenna connected to a signal generator tuned to the frequency of emission and level of signal generator adjusted to same level of emission. Both horizontal and vertical polarization of the antenna are set on measurement.

On any frequency, the limits shown are based on measuring equipment employing a peak detector function. The resolution bandwidth of spectrum analyzer is 1MHz. and video bandwidth is 3MHz.

The radiated E.I.R.P power was calculated via the Correct factor, Reading Level, and Antenna gain as follows:

$$\text{E.I.R.P} = \text{Reading Level} + \text{Correct Factor} = \text{S.G.} - \text{Cable Loss} + \text{Antenna Gain}$$

7.5. Uncertainty

The measurement uncertainty


30MHz~1GHz as $\pm 3.19\text{dB}$

1GHz~27GHz as $\pm 3.9\text{dB}$

7.6. Test Result

30 MHz – 1 GHz Spurious:

Site : CB1	Time : 2011/12/28 - 19:43
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		70.417	2.820	-66.220	-63.401	-50.401	-13.000	PEAK
2		101.133	1.951	-66.878	-64.927	-51.927	-13.000	PEAK
3		335.550	0.677	-60.414	-59.737	-46.737	-13.000	PEAK
4		600.683	6.746	-66.871	-60.126	-47.126	-13.000	PEAK
5	*	799.533	8.102	-64.252	-56.150	-43.150	-13.000	PEAK
6		933.717	9.113	-70.622	-61.509	-48.509	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:43
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	70.417	1.613	-50.708	-49.095	-36.095	-13.000	PEAK
2		89.817	2.793	-52.763	-49.969	-36.969	-13.000	PEAK
3		338.783	2.682	-57.854	-55.173	-42.173	-13.000	PEAK
4		579.667	7.383	-62.608	-55.226	-42.226	-13.000	PEAK
5		600.683	7.541	-62.781	-55.240	-42.240	-13.000	PEAK
6		799.533	9.350	-64.544	-55.195	-42.195	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:43
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	89.817	2.552	-54.851	-52.299	-39.299	-13.000	PEAK
2		340.400	0.670	-55.825	-55.156	-42.156	-13.000	PEAK
3		600.683	6.746	-64.044	-57.299	-44.299	-13.000	PEAK
4		649.183	7.037	-63.201	-56.164	-43.164	-13.000	PEAK
5		799.533	8.102	-64.189	-56.087	-43.087	-13.000	PEAK
6		933.717	9.113	-67.013	-57.900	-44.900	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.082	-49.156	-36.156	-13.000	PEAK
2		99.517	3.108	-52.557	-49.449	-36.449	-13.000	PEAK
3		340.400	2.784	-57.940	-55.156	-42.156	-13.000	PEAK
4		574.817	7.333	-60.989	-53.655	-40.655	-13.000	PEAK
5		600.683	7.541	-62.253	-54.712	-41.712	-13.000	PEAK
6		799.533	9.350	-65.474	-56.125	-43.125	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:47
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	88.200	2.524	-54.794	-52.269	-39.269	-13.000	PEAK
2		340.400	0.670	-55.321	-54.652	-41.652	-13.000	PEAK
3		600.683	6.746	-64.715	-57.970	-44.970	-13.000	PEAK
4		649.183	7.037	-65.588	-58.551	-45.551	-13.000	PEAK
5		799.533	8.102	-63.537	-55.435	-42.435	-13.000	PEAK
6		933.717	9.113	-68.277	-59.164	-46.164	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:47
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.482	-49.556	-36.556	-13.000	PEAK
2		99.517	3.108	-53.569	-50.461	-37.461	-13.000	PEAK
3		340.400	2.784	-57.839	-55.055	-42.055	-13.000	PEAK
4		574.817	7.333	-60.914	-53.580	-40.580	-13.000	PEAK
5		600.683	7.541	-63.067	-55.526	-42.526	-13.000	PEAK
6		799.533	9.350	-64.877	-55.528	-42.528	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:48
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	36.467	10.316	-62.246	-51.930	-38.930	-13.000	PEAK
2		88.200	2.524	-55.228	-52.703	-39.703	-13.000	PEAK
3		280.583	-0.240	-59.261	-59.501	-46.501	-13.000	PEAK
4		338.783	0.673	-55.202	-54.530	-41.530	-13.000	PEAK
5		649.183	7.037	-64.643	-57.606	-44.606	-13.000	PEAK
6		799.533	8.102	-64.139	-56.037	-43.037	-13.000	PEAK

C

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:48
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-50.863	-48.937	-35.937	-13.000	PEAK
2		102.750	2.950	-53.584	-50.634	-37.634	-13.000	PEAK
3		338.783	2.682	-57.916	-55.235	-42.235	-13.000	PEAK
4		574.817	7.333	-61.976	-54.642	-41.642	-13.000	PEAK
5		600.683	7.541	-62.632	-55.091	-42.091	-13.000	PEAK
6		799.533	9.350	-65.644	-56.295	-43.295	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:48
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	88.200	2.524	-55.253	-52.728	-39.728	-13.000	PEAK
2		278.967	-0.311	-59.527	-59.837	-46.837	-13.000	PEAK
3		338.783	0.673	-54.585	-53.913	-40.913	-13.000	PEAK
4		599.067	6.745	-63.975	-57.231	-44.231	-13.000	PEAK
5		650.800	7.044	-64.398	-57.353	-44.353	-13.000	PEAK
6		799.533	8.102	-63.310	-55.208	-42.208	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:48
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.067	-49.141	-36.141	-13.000	PEAK
2		97.900	3.058	-52.276	-49.217	-36.217	-13.000	PEAK
3		338.783	2.682	-58.585	-55.904	-42.904	-13.000	PEAK
4		574.817	7.333	-62.056	-54.722	-41.722	-13.000	PEAK
5		600.683	7.541	-62.238	-54.697	-41.697	-13.000	PEAK
6		933.717	9.802	-65.896	-56.094	-43.094	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:48
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		68.800	3.235	-56.645	-53.411	-40.411	-13.000	PEAK
2	*	88.200	2.524	-55.311	-52.786	-39.786	-13.000	PEAK
3		338.783	0.673	-55.560	-54.888	-41.888	-13.000	PEAK
4		600.683	6.746	-63.967	-57.222	-44.222	-13.000	PEAK
5		649.183	7.037	-64.200	-57.163	-44.163	-13.000	PEAK
6		799.533	8.102	-63.651	-55.549	-42.549	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 19:49
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-50.841	-48.915	-35.915	-13.000	PEAK
2		99.517	3.108	-52.455	-49.347	-36.347	-13.000	PEAK
3		338.783	2.682	-57.678	-54.997	-41.997	-13.000	PEAK
4		576.433	7.350	-61.234	-53.884	-40.884	-13.000	PEAK
5		600.683	7.541	-62.325	-54.784	-41.784	-13.000	PEAK
6		799.533	9.350	-65.457	-56.108	-43.108	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		36.467	10.316	-71.834	-61.518	-48.518	-13.000	PEAK
2	*	335.550	0.677	-60.715	-60.038	-47.038	-13.000	PEAK
3		571.583	6.797	-71.244	-64.448	-51.448	-13.000	PEAK
4		600.683	6.746	-67.324	-60.579	-47.579	-13.000	PEAK
5		867.433	8.233	-72.001	-63.768	-50.768	-13.000	PEAK
6		933.717	9.113	-71.172	-62.059	-49.059	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	70.417	1.613	-50.847	-49.234	-36.234	-13.000	PEAK
2		89.817	2.793	-52.864	-50.070	-37.070	-13.000	PEAK
3		340.400	2.784	-58.472	-55.688	-42.688	-13.000	PEAK
4		579.667	7.383	-63.513	-56.131	-43.131	-13.000	PEAK
5		600.683	7.541	-62.839	-55.298	-42.298	-13.000	PEAK
6		799.533	9.350	-64.721	-55.372	-42.372	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2)' 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	89.817	2.552	-55.083	-52.531	-39.531	-13.000	PEAK
2		338.783	0.673	-56.207	-55.535	-42.535	-13.000	PEAK
3		600.683	6.746	-64.731	-57.986	-44.986	-13.000	PEAK
4		649.183	7.037	-64.079	-57.042	-44.042	-13.000	PEAK
5		799.533	8.102	-65.173	-57.071	-44.071	-13.000	PEAK
6		933.717	9.113	-67.179	-58.066	-45.066	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2)' 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.345	-49.419	-36.419	-13.000	PEAK
2		99.517	3.108	-53.168	-50.060	-37.060	-13.000	PEAK
3		340.400	2.784	-58.301	-55.517	-42.517	-13.000	PEAK
4		574.817	7.333	-61.334	-54.000	-41.000	-13.000	PEAK
5		600.683	7.541	-63.011	-55.470	-42.470	-13.000	PEAK
6		799.533	9.350	-66.294	-56.945	-43.945	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		36.467	10.316	-63.786	-53.470	-40.470	-13.000	PEAK
2	*	88.200	2.524	-55.036	-52.511	-39.511	-13.000	PEAK
3		338.783	0.673	-55.598	-54.926	-41.926	-13.000	PEAK
4		600.683	6.746	-65.307	-58.562	-45.562	-13.000	PEAK
5		649.183	7.037	-65.913	-58.876	-45.876	-13.000	PEAK
6		799.533	8.102	-63.994	-55.892	-42.892	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.566	-49.640	-36.640	-13.000	PEAK
2		107.600	2.645	-53.961	-51.316	-38.316	-13.000	PEAK
3		340.400	2.784	-58.183	-55.399	-42.399	-13.000	PEAK
4		574.817	7.333	-61.457	-54.123	-41.123	-13.000	PEAK
5		799.533	9.350	-65.265	-55.916	-42.916	-13.000	PEAK
6		933.717	9.802	-67.248	-57.446	-44.446	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	88.200	2.524	-55.257	-52.732	-39.732	-13.000	PEAK
2		280.583	-0.240	-59.515	-59.755	-46.755	-13.000	PEAK
3		340.400	0.670	-55.241	-54.572	-41.572	-13.000	PEAK
4		599.067	6.745	-65.440	-58.696	-45.696	-13.000	PEAK
5		649.183	7.037	-65.128	-58.091	-45.091	-13.000	PEAK
6		799.533	8.102	-65.194	-57.092	-44.092	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	70.417	1.613	-51.357	-49.744	-36.744	-13.000	PEAK
2		107.600	2.645	-54.414	-51.769	-38.769	-13.000	PEAK
3		338.783	2.682	-58.538	-55.857	-42.857	-13.000	PEAK
4		579.667	7.383	-62.803	-55.421	-42.421	-13.000	PEAK
5		600.683	7.541	-63.192	-55.651	-42.651	-13.000	PEAK
6		799.533	9.350	-66.232	-56.883	-43.883	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		36.467	10.316	-64.260	-53.944	-40.944	-13.000	PEAK
2	*	89.817	2.552	-56.021	-53.469	-40.469	-13.000	PEAK
3		338.783	0.673	-55.424	-54.752	-41.752	-13.000	PEAK
4		599.067	6.745	-64.850	-58.106	-45.106	-13.000	PEAK
5		799.533	8.102	-63.918	-55.816	-42.816	-13.000	PEAK
6		933.717	9.113	-68.479	-59.366	-46.366	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.487	-49.561	-36.561	-13.000	PEAK
2		97.900	3.058	-52.720	-49.661	-36.661	-13.000	PEAK
3		338.783	2.682	-58.868	-56.187	-43.187	-13.000	PEAK
4		571.583	7.302	-62.922	-55.621	-42.621	-13.000	PEAK
5		599.067	7.521	-62.627	-55.106	-42.106	-13.000	PEAK
6		933.717	9.802	-66.154	-56.352	-43.352	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		68.800	3.235	-57.457	-54.223	-41.223	-13.000	PEAK
2	*	88.200	2.524	-55.416	-52.891	-39.891	-13.000	PEAK
3		338.783	0.673	-56.508	-55.836	-42.836	-13.000	PEAK
4		600.683	6.746	-64.589	-57.844	-44.844	-13.000	PEAK
5		799.533	8.102	-64.457	-56.355	-43.355	-13.000	PEAK
6		933.717	9.113	-67.319	-58.206	-45.206	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/31 - 13:51
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_30-1G-1_0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1	*	68.800	1.926	-51.590	-49.664	-36.664	-13.000	PEAK
2		99.517	3.108	-53.232	-50.124	-37.124	-13.000	PEAK
3		338.783	2.682	-57.742	-55.061	-42.061	-13.000	PEAK
4		576.433	7.350	-61.525	-54.175	-41.175	-13.000	PEAK
5		600.683	7.541	-62.344	-54.803	-41.803	-13.000	PEAK
6		933.717	9.802	-66.410	-56.608	-43.608	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Harmonic & Spurious:

Site : CB1	Time : 2011/12/28 - 20:04
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3651.75MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7302.670	20.669	-62.580	-41.911	-28.911	-13.000	PEAK
2		10945.250	22.495	-69.010	-46.514	-33.514	-13.000	PEAK
3		14610.067	26.650	-69.370	-42.721	-29.721	-13.000	PEAK
4	*	18261.033	36.690	-71.340	-34.650	-21.650	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 20:10
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3651.75MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7303.100	20.123	-63.100	-42.976	-29.976	-13.000	PEAK
2		10957.000	21.157	-68.800	-47.643	-34.643	-13.000	PEAK
3		14611.117	24.850	-69.260	-44.411	-31.411	-13.000	PEAK
4	*	18254.517	36.650	-71.690	-35.040	-22.040	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 20:24
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7324.650	20.708	-63.510	-42.802	-29.802	-13.000	PEAK
2		10987.333	22.553	-68.450	-45.897	-32.897	-13.000	PEAK
3		14651.500	26.846	-69.230	-42.385	-29.385	-13.000	PEAK
4	*	18313.833	36.690	-72.090	-35.400	-22.400	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 20:30
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7324.217	20.234	-64.580	-44.347	-31.347	-13.000	PEAK
2		10989.083	21.159	-66.940	-45.781	-32.781	-13.000	PEAK
3		14648.733	25.014	-68.820	-43.806	-30.806	-13.000	PEAK
4	*	18315.750	36.650	-71.950	-35.300	-22.300	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 20:46
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3673.25MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7345.417	20.745	-63.420	-42.675	-29.675	-13.000	PEAK
2		11023.817	22.589	-68.670	-46.081	-33.081	-13.000	PEAK
3		14689.467	27.025	-69.860	-42.836	-29.836	-13.000	PEAK
4	*	18368.617	36.690	-71.140	-34.450	-21.450	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 21:15
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 1: Transmit (3.5MHz BW_QPSK1/2) 3673.25MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7345.550	20.343	-63.420	-43.077	-30.077	-13.000	PEAK
2		11024.833	21.249	-68.060	-46.811	-33.811	-13.000	PEAK
3		14698.333	25.232	-70.630	-45.397	-32.397	-13.000	PEAK
4	*	18362.800	36.650	-71.580	-34.930	-21.930	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 21:31
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3651.75MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7303.183	20.669	-65.090	-44.420	-31.420	-13.000	PEAK
2		10951.433	22.503	-68.350	-45.846	-32.846	-13.000	PEAK
3		14610.333	26.651	-69.080	-42.429	-29.429	-13.000	PEAK
4	*	18262.083	36.690	-72.798	-36.108	-23.108	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 21:36
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3651.75MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7305.300	20.135	-64.020	-43.885	-30.885	-13.000	PEAK
2		10957.050	21.157	-70.650	-49.493	-36.493	-13.000	PEAK
3		14603.550	24.816	-69.690	-44.874	-31.874	-13.000	PEAK
4	*	18257.617	36.650	-71.610	-34.960	-21.960	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 21:43
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7327.183	20.713	-65.650	-44.938	-31.938	-13.000	PEAK
2		10991.867	22.559	-67.910	-45.351	-32.351	-13.000	PEAK
3		14645.350	26.816	-70.020	-43.204	-30.204	-13.000	PEAK
4	*	18316.967	36.690	-70.780	-34.090	-21.090	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 21:47
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7348.400	20.357	-65.273	-44.915	-31.915	-13.000	PEAK
2		11015.500	21.215	-68.930	-47.715	-34.715	-13.000	PEAK
3		14693.683	25.212	-70.490	-45.278	-32.278	-13.000	PEAK
4	*	18366.050	36.650	-72.010	-35.360	-22.360	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 21:58
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3673.25MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7348.017	20.750	-65.230	-44.480	-31.480	-13.000	PEAK
2		11019.450	22.585	-68.340	-45.755	-32.755	-13.000	PEAK
3		14696.917	27.060	-69.880	-42.821	-29.821	-13.000	PEAK
4	*	18362.017	36.690	-71.941	-35.251	-22.251	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 22:02
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 2: Transmit (3.5MHz BW_16QAM1/2) 3673.25MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7348.418	20.357	-64.530	-44.172	-31.172	-13.000	PEAK
2		11023.533	21.244	-69.230	-47.986	-34.986	-13.000	PEAK
3		14695.483	25.220	-70.180	-44.960	-31.960	-13.000	PEAK
4	*	18368.283	36.650	-71.700	-35.050	-22.050	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 22:12
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3651.75MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7303.300	20.670	-64.480	-43.810	-30.810	-13.000	PEAK
2		10954.150	22.507	-68.290	-45.782	-32.782	-13.000	PEAK
3		14605.983	26.631	-69.670	-43.040	-30.040	-13.000	PEAK
4	*	18260.550	36.690	-71.040	-34.350	-21.350	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2011/12/28 - 22:16
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3651.75MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7303.533	20.126	-63.190	-43.064	-30.064	-13.000	PEAK
2		10958.833	21.157	-68.920	-47.762	-34.762	-13.000	PEAK
3		14603.767	24.816	-69.660	-44.843	-31.843	-13.000	PEAK
4	*	18261.283	36.650	-71.920	-35.270	-22.270	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:08
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7327.333	20.713	-66.310	-45.597	-32.597	-13.000	PEAK
2		10992.110	22.559	-67.820	-45.261	-32.261	-13.000	PEAK
3		14645.340	26.816	-69.013	-42.197	-29.197	-13.000	PEAK
4	*	18312.966	36.690	-70.630	-33.940	-20.940	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:28
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7348.300	20.357	-64.266	-43.909	-30.909	-13.000	PEAK
2		11015.340	21.215	-67.733	-46.518	-33.518	-13.000	PEAK
3		14692.333	25.206	-70.660	-45.454	-32.454	-13.000	PEAK
4	*	18366.112	36.650	-71.330	-34.680	-21.680	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:30
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3673.25MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7347.596	20.749	-64.330	-43.581	-30.581	-13.000	PEAK
2		11020.120	22.586	-67.960	-45.374	-32.374	-13.000	PEAK
3		14697.756	27.064	-70.120	-43.057	-30.057	-13.000	PEAK
4	*	18362.710	36.690	-70.120	-33.430	-20.430	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:31
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G-1-0901 - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 3: Transmit (3.5MHz BW_64QAM2/3) 3673.25MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7349.311	20.363	-63.530	-43.168	-30.168	-13.000	PEAK
2		11022.987	21.242	-70.110	-48.868	-35.868	-13.000	PEAK
3		14695.555	25.220	-70.200	-44.980	-31.980	-13.000	PEAK
4	*	18367.990	36.650	-72.500	-35.850	-22.850	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3652.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7305.171	20.175	-59.077	-38.901	-25.901	-13.000	PEAK
2	*	10958.295	25.373	-58.314	-32.940	-19.940	-13.000	PEAK
3		14606.246	28.335	-68.049	-39.714	-26.714	-13.000	PEAK
4		18256.707	31.900	-69.753	-37.853	-24.853	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3652.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7304.742	19.460	-61.791	-42.331	-29.331	-13.000	PEAK
2	*	10957.796	25.255	-57.894	-32.639	-19.639	-13.000	PEAK
3		14609.800	27.069	-69.170	-42.101	-29.101	-13.000	PEAK
4		18265.531	31.300	-70.357	-39.057	-26.057	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7326.049	20.206	-59.274	-39.068	-26.068	-13.000	PEAK
2	*	10987.533	25.525	-59.255	-33.730	-20.730	-13.000	PEAK
3		14649.056	28.345	-65.506	-37.161	-24.161	-13.000	PEAK
4		18314.156	31.900	-68.583	-36.683	-23.683	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7326.192	19.540	-57.614	-38.074	-25.074	-13.000	PEAK
2	*	10987.739	25.400	-56.270	-30.870	-17.870	-13.000	PEAK
3		14651.934	27.141	-70.467	-43.326	-30.326	-13.000	PEAK
4		18305.025	31.300	-69.780	-38.480	-25.480	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3672.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7345.726	20.235	-58.539	-38.304	-25.304	-13.000	PEAK
2	*	11016.090	25.611	-58.940	-33.327	-20.327	-13.000	PEAK
3		14690.715	28.356	-67.334	-38.978	-25.978	-13.000	PEAK
4		18365.545	31.900	-69.118	-37.218	-24.218	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 4: Transmit (5MHz BW_QPSK3/4) 3672.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7345.200	19.612	-60.298	-40.687	-27.687	-13.000	PEAK
2	*	11015.961	25.469	-59.067	-33.598	-20.598	-13.000	PEAK
3		14686.646	27.200	-70.950	-43.750	-30.750	-13.000	PEAK
4		18363.809	31.300	-70.358	-39.058	-26.058	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3652.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7304.079	20.173	-61.077	-40.903	-27.903	-13.000	PEAK
2	*	10957.438	25.369	-61.927	-36.558	-23.558	-13.000	PEAK
3		14614.061	28.337	-67.452	-39.115	-26.115	-13.000	PEAK
4		18254.047	31.900	-70.279	-38.379	-25.379	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3652.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7305.719	19.463	-60.455	-40.992	-27.992	-13.000	PEAK
2	*	10957.815	25.255	-58.396	-33.141	-20.141	-13.000	PEAK
3		14608.891	27.067	-68.658	-41.591	-28.591	-13.000	PEAK
4		18268.146	31.300	-71.155	-39.855	-26.855	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7325.559	20.206	-59.938	-39.733	-26.733	-13.000	PEAK
2	*	10987.813	25.526	-58.567	-33.040	-20.040	-13.000	PEAK
3		14647.360	28.345	-68.100	-39.755	-26.755	-13.000	PEAK
4		18303.408	31.900	-69.933	-38.033	-25.033	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:37
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7325.145	19.536	-62.041	-42.505	-29.505	-13.000	PEAK
2		10989.034	25.407	-63.631	-38.224	-25.224	-13.000	PEAK
3		14646.906	27.133	-70.299	-43.166	-30.166	-13.000	PEAK
4	*	18304.736	31.300	-69.342	-38.042	-25.042	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3672.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7345.718	20.235	-59.680	-39.445	-26.445	-13.000	PEAK
2	*	11016.793	25.613	-61.908	-36.295	-23.295	-13.000	PEAK
3		14686.949	28.355	-69.538	-41.183	-28.183	-13.000	PEAK
4		18367.041	31.900	-69.485	-37.585	-24.585	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 5: Transmit (5MHz BW_16QAM1/2) 3672.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7345.778	19.613	-60.010	-40.397	-27.397	-13.000	PEAK
2	*	11017.414	25.470	-59.644	-34.173	-21.173	-13.000	PEAK
3		14688.514	27.205	-68.899	-41.694	-28.694	-13.000	PEAK
4		18362.436	31.300	-70.770	-39.470	-26.470	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3652.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7304.469	20.175	-59.315	-39.140	-26.140	-13.000	PEAK
2	*	10955.584	25.360	-59.705	-34.345	-21.345	-13.000	PEAK
3		14612.296	28.337	-67.406	-39.069	-26.069	-13.000	PEAK
4		18253.695	31.900	-69.147	-37.247	-24.247	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3652.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7306.139	19.465	-60.365	-40.900	-27.900	-13.000	PEAK
2	*	10956.749	25.250	-61.070	-35.820	-22.820	-13.000	PEAK
3		14609.440	27.068	-69.301	-42.233	-29.233	-13.000	PEAK
4		18255.350	31.300	-69.007	-37.707	-24.707	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7324.132	20.203	-60.858	-40.655	-27.655	-13.000	PEAK
2	*	10987.255	25.524	-60.073	-34.549	-21.549	-13.000	PEAK
3		14651.828	28.346	-68.527	-40.181	-27.181	-13.000	PEAK
4		18308.059	31.900	-70.417	-38.517	-25.517	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7323.750	19.530	-59.683	-40.152	-27.152	-13.000	PEAK
2	*	10986.952	25.397	-61.015	-35.618	-22.618	-13.000	PEAK
3		14649.911	27.138	-69.004	-41.866	-28.866	-13.000	PEAK
4		18316.080	31.300	-68.944	-37.644	-24.644	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3672.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7343.315	20.230	-59.900	-39.669	-26.669	-13.000	PEAK
2	*	11017.112	25.614	-58.140	-32.527	-19.527	-13.000	PEAK
3		14690.544	28.355	-66.216	-37.861	-24.861	-13.000	PEAK
4		18367.785	31.900	-69.912	-38.012	-25.012	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:38
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 6: Transmit (5MHz BW_64QAM2/3) 3672.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7344.795	19.609	-61.692	-42.082	-29.082	-13.000	PEAK
2	*	11015.253	25.469	-61.299	-35.829	-22.829	-13.000	PEAK
3		14685.316	27.199	-69.629	-42.430	-29.430	-13.000	PEAK
4		18355.879	31.300	-69.875	-38.575	-25.575	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3653.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7307.414	20.179	-60.020	-39.841	-26.841	-13.000	PEAK
2	*	10960.345	25.384	-60.699	-35.314	-22.314	-13.000	PEAK
3		14621.756	28.339	-67.635	-39.296	-26.296	-13.000	PEAK
4		18260.211	31.900	-69.552	-37.652	-24.652	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3653.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7307.007	19.468	-60.031	-40.563	-27.563	-13.000	PEAK
2	*	10965.865	25.293	-59.725	-34.431	-21.431	-13.000	PEAK
3		14618.505	27.084	-70.210	-43.126	-30.126	-13.000	PEAK
4		18258.244	31.300	-69.085	-37.785	-24.785	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7326.553	20.207	-60.155	-39.948	-26.948	-13.000	PEAK
2	*	10988.495	25.530	-60.720	-35.190	-22.190	-13.000	PEAK
3		14648.920	28.345	-68.353	-40.008	-27.008	-13.000	PEAK
4		18309.980	31.900	-69.364	-37.464	-24.464	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7326.417	19.541	-60.694	-41.153	-28.153	-13.000	PEAK
2	*	10989.963	25.411	-60.826	-35.415	-22.415	-13.000	PEAK
3		14650.531	27.139	-70.101	-42.962	-29.962	-13.000	PEAK
4		18321.230	31.300	-69.652	-38.352	-25.352	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3671.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7343.463	20.232	-60.191	-39.960	-26.960	-13.000	PEAK
2	*	11012.226	25.607	-60.432	-34.826	-21.826	-13.000	PEAK
3		14684.175	28.354	-68.121	-39.767	-26.767	-13.000	PEAK
4		18365.621	31.900	-69.490	-37.590	-24.590	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 7: Transmit (7MHz BW_QPSK3/4) 3671.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7344.075	19.607	-59.346	-39.739	-26.739	-13.000	PEAK
2	*	11013.097	25.468	-59.975	-34.507	-21.507	-13.000	PEAK
3		14683.837	27.196	-70.356	-43.160	-30.160	-13.000	PEAK
4		18364.682	31.300	-70.650	-39.350	-26.350	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2) 3653.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7308.977	20.180	-60.071	-39.890	-26.890	-13.000	PEAK
2	*	10955.574	25.360	-60.104	-34.744	-21.744	-13.000	PEAK
3		14619.224	28.339	-69.210	-40.871	-27.871	-13.000	PEAK
4		18263.451	31.900	-69.335	-37.435	-24.435	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2) 3653.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7308.841	19.474	-59.669	-40.194	-27.194	-13.000	PEAK
2	*	10957.086	25.252	-60.990	-35.738	-22.738	-13.000	PEAK
3		14613.567	27.076	-70.426	-43.350	-30.350	-13.000	PEAK
4		18273.803	31.300	-69.753	-38.453	-25.453	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7323.271	20.202	-60.758	-40.556	-27.556	-13.000	PEAK
2	*	10987.388	25.525	-61.794	-36.269	-23.269	-13.000	PEAK
3		14654.156	28.347	-71.020	-42.673	-29.673	-13.000	PEAK
4		18316.936	31.900	-71.801	-39.901	-26.901	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7322.989	19.528	-61.518	-41.990	-28.990	-13.000	PEAK
2	*	10986.504	25.395	-61.409	-36.015	-23.015	-13.000	PEAK
3		14653.956	27.145	-72.590	-45.445	-32.445	-13.000	PEAK
4		18317.678	31.300	-71.430	-40.130	-27.130	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2) 3671.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7340.439	20.227	-60.343	-40.116	-27.116	-13.000	PEAK
2	*	11019.125	25.617	-60.138	-34.522	-21.522	-13.000	PEAK
3		14687.117	28.355	-69.156	-40.801	-27.801	-13.000	PEAK
4		18348.393	31.900	-70.056	-38.156	-25.156	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 8: Transmit (7MHz BW_16QAM1/2) 3671.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7343.290	19.603	-60.194	-40.590	-27.590	-13.000	PEAK
2	*	11015.536	25.469	-60.669	-35.200	-22.200	-13.000	PEAK
3		14678.133	27.186	-71.043	-43.857	-30.857	-13.000	PEAK
4		18348.934	31.300	-70.244	-38.944	-25.944	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:44
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3653.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7305.289	20.176	-58.223	-38.047	-25.047	-13.000	PEAK
2	*	10964.068	25.405	-58.696	-33.291	-20.291	-13.000	PEAK
3		14609.666	28.336	-70.210	-41.874	-28.874	-13.000	PEAK
4		18267.242	31.900	-69.619	-37.719	-24.719	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3653.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7305.444	19.462	-61.198	-41.736	-28.736	-13.000	PEAK
2	*	10960.828	25.270	-59.966	-34.696	-21.696	-13.000	PEAK
3		14620.231	27.087	-70.528	-43.441	-30.441	-13.000	PEAK
4		18266.383	31.300	-70.498	-39.198	-26.198	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7324.274	20.204	-59.100	-38.897	-25.897	-13.000	PEAK
2	*	10986.707	25.522	-61.185	-35.664	-22.664	-13.000	PEAK
3		14648.409	28.346	-68.579	-40.233	-27.233	-13.000	PEAK
4		18318.854	31.900	-70.145	-38.245	-25.245	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7324.077	19.533	-59.183	-39.650	-26.650	-13.000	PEAK
2	*	10981.992	25.373	-59.135	-33.762	-20.762	-13.000	PEAK
3		14644.483	27.128	-70.540	-43.412	-30.412	-13.000	PEAK
4		18320.352	31.300	-70.433	-39.133	-26.133	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3671.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7343.815	20.232	-58.965	-38.733	-25.733	-13.000	PEAK
2	*	11017.592	25.614	-60.416	-34.802	-21.802	-13.000	PEAK
3		14693.772	28.356	-69.879	-41.523	-28.523	-13.000	PEAK
4		18361.262	31.900	-69.995	-38.095	-25.095	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 9: Transmit (7MHz BW_64QAM5/6) 3671.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7341.532	19.597	-59.263	-39.666	-26.666	-13.000	PEAK
2	*	11012.947	25.468	-60.675	-35.208	-22.208	-13.000	PEAK
3		14695.822	27.218	-69.253	-42.035	-29.035	-13.000	PEAK
4		18351.934	31.300	-70.249	-38.949	-25.949	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3655MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7310.306	20.183	-58.982	-38.799	-25.799	-13.000	PEAK
2	*	10965.044	25.409	-59.954	-34.545	-21.545	-13.000	PEAK
3		14622.206	28.339	-70.208	-41.869	-28.869	-13.000	PEAK
4		18265.078	31.900	-69.746	-37.846	-24.846	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3655MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7310.237	19.480	-58.620	-39.140	-26.140	-13.000	PEAK
2	*	10965.697	25.293	-59.502	-34.209	-21.209	-13.000	PEAK
3		14610.356	27.070	-69.971	-42.901	-29.901	-13.000	PEAK
4		18250.434	31.300	-69.911	-38.611	-25.611	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7324.793	20.204	-59.049	-38.845	-25.845	-13.000	PEAK
2	*	10982.997	25.502	-59.513	-34.011	-21.011	-13.000	PEAK
3		14653.106	28.347	-70.412	-42.065	-29.065	-13.000	PEAK
4		18305.232	31.900	-69.619	-37.719	-24.719	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7325.290	19.536	-58.791	-39.254	-26.254	-13.000	PEAK
2	*	10986.680	25.396	-59.550	-34.155	-21.155	-13.000	PEAK
3		14654.970	27.147	-71.426	-44.279	-31.279	-13.000	PEAK
4		18288.025	31.300	-70.652	-39.352	-26.352	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3670MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7339.932	20.226	-60.238	-40.012	-27.012	-13.000	PEAK
2	*	11012.931	25.608	-60.337	-34.729	-21.729	-13.000	PEAK
3		14671.782	28.351	-71.544	-43.193	-30.193	-13.000	PEAK
4		18334.826	31.900	-70.536	-38.636	-25.636	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 10: Transmit (10MHz BW_QPSK3/4) 3670MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7338.611	19.587	-60.056	-40.470	-27.470	-13.000	PEAK
2	*	11010.952	25.464	-61.477	-36.013	-23.013	-13.000	PEAK
3		14684.602	27.198	-70.829	-43.631	-30.631	-13.000	PEAK
4		18340.061	31.300	-69.556	-38.256	-25.256	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3655MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7310.253	20.183	-59.307	-39.124	-26.124	-13.000	PEAK
2	*	10972.768	25.449	-59.838	-34.389	-21.389	-13.000	PEAK
3		14613.244	28.338	-70.159	-41.821	-28.821	-13.000	PEAK
4		18269.912	31.900	-69.760	-37.860	-24.860	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3655MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7309.772	19.479	-58.971	-39.492	-26.492	-13.000	PEAK
2	*	10962.569	25.278	-58.737	-33.459	-20.459	-13.000	PEAK
3		14597.458	27.048	-70.173	-43.125	-30.125	-13.000	PEAK
4		18278.799	31.300	-70.370	-39.070	-26.070	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7326.702	20.207	-59.557	-39.350	-26.350	-13.000	PEAK
2	*	10989.634	25.537	-60.851	-35.315	-22.315	-13.000	PEAK
3		14649.259	28.346	-70.017	-41.671	-28.671	-13.000	PEAK
4		18301.568	31.900	-70.246	-38.346	-25.346	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7326.767	19.543	-59.893	-40.350	-27.350	-13.000	PEAK
2	*	10988.614	25.404	-59.269	-33.865	-20.865	-13.000	PEAK
3		14662.879	27.161	-71.047	-43.886	-30.886	-13.000	PEAK
4		18327.977	31.300	-70.235	-38.935	-25.935	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3670MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7343.095	20.230	-59.035	-38.804	-25.804	-13.000	PEAK
2	*	11010.863	25.603	-60.611	-35.008	-22.008	-13.000	PEAK
3		14675.979	28.353	-70.873	-42.520	-29.520	-13.000	PEAK
4		18355.799	31.900	-69.889	-37.989	-24.989	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 11: Transmit (10MHz BW_16QAM1/2) 3670MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7336.222	19.578	-59.068	-39.491	-26.491	-13.000	PEAK
2	*	11013.785	25.469	-61.417	-35.949	-22.949	-13.000	PEAK
3		14686.352	27.200	-70.469	-43.269	-30.269	-13.000	PEAK
4		18347.963	31.300	-69.569	-38.269	-25.269	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3655MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7310.061	20.183	-58.403	-38.220	-25.220	-13.000	PEAK
2	*	10970.768	25.438	-58.143	-32.704	-19.704	-13.000	PEAK
3		14607.208	28.336	-70.161	-41.825	-28.825	-13.000	PEAK
4		18256.996	31.900	-69.820	-37.920	-24.920	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3655MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7307.133	19.469	-60.160	-40.691	-27.691	-13.000	PEAK
2	*	10966.692	25.299	-60.852	-35.554	-22.554	-13.000	PEAK
3		14610.727	27.071	-70.297	-43.226	-30.226	-13.000	PEAK
4		18264.662	31.300	-69.777	-38.477	-25.477	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7325.899	20.206	-60.344	-40.139	-27.139	-13.000	PEAK
2	*	10984.236	25.509	-59.769	-34.261	-21.261	-13.000	PEAK
3		14631.576	28.341	-70.240	-41.899	-28.899	-13.000	PEAK
4		18306.570	31.900	-70.046	-38.146	-25.146	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3662.5MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7320.854	19.521	-60.885	-41.364	-28.364	-13.000	PEAK
2	*	10986.812	25.396	-59.830	-34.434	-21.434	-13.000	PEAK
3		14669.410	27.171	-69.481	-42.310	-29.310	-13.000	PEAK
4		18334.670	31.300	-70.411	-39.111	-26.111	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - HORIZONTAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3670MHz




		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7340.839	20.228	-58.949	-38.721	-25.721	-13.000	PEAK
2	*	11009.354	25.600	-60.115	-34.515	-21.515	-13.000	PEAK
3		14675.901	28.353	-69.777	-41.424	-28.424	-13.000	PEAK
4		18340.775	31.900	-70.198	-38.298	-25.298	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

Site : CB1	Time : 2012/01/03 - 20:45
Limit : PART27(WiMAX)_00M_PK	Margin : 6
Probe : CB1_CE_Sub_1-18G(2011-08) - VERTICAL	Power : AC 120V/60Hz
EUT : CBS 3.65GHz	Note : Mode 12: Transmit (10MHz BW_64QAM5/6) 3670MHz



		Frequency (MHz)	Correct Factor (dB)	Reading Level (dBm)	Measure Level (dBm)	Margin (dB)	Limit (dBm)	Detector Type
1		7335.815	19.577	-61.509	-41.932	-28.932	-13.000	PEAK
2	*	11001.494	25.450	-59.612	-34.162	-21.162	-13.000	PEAK
3		14685.736	27.200	-70.409	-43.209	-30.209	-13.000	PEAK
4		18332.498	31.300	-69.114	-37.814	-24.814	-13.000	PEAK

Note:

1. All Reading Levels are Peak value.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Correct Factor.

8. Frequency Stability Over Temperatures Variation

8.1. Test Equipment


The following test equipments are used during the test:

Frequency Stability Over Temperatures Variation/ SR7

Instrument	Manufacturer	Model No.	Serial No	Next Cal. Date
Spectrum Analyzer	Agilent	N9010A	US47140172	2012/07/13
Standard Temperature & Humidity Chamber	WIT	TH-1S-B	1082101	2012/01/30

Note: 1. All equipments that need to calibrate are with calibration period of 1 year.

8.2. Test Setup



8.3. Limits

The frequency stability shall be measured with variation of ambient temperature as follows: From -30° to +50° centigrade for all equipment. Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range.

8.4. Test Procedure

Power must be turned off when changing from one temperature to another. Power warm up is at least 15 min and power applied should perform before recording frequency error. The temperature range step is 10 degrees in this test items. All temperature levels shall be holding the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

8.5. Test Specification

FCC CFR Title 47 Part 90 Subpart Z, KDB 965270

8.6. Uncertainty

The measurement uncertainty is defined as $\pm 100\text{KHz}$

8.7. Test Result

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal_3.5MHz_Ant 0		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3651.75 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3651.7450	-1.3692	Pass
-20		3651.7450	-1.3692	Pass
-10		3651.7450	-1.3692	Pass
0		3651.7450	-1.3692	Pass
20		3651.7440	-1.6430	Pass
30		3651.7450	-1.3692	Pass
40		3651.7450	-1.3692	Pass
50		3651.7450	-1.3692	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4950	-1.3652	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3673.25 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3673.2450	-1.3612	Pass
-20		3673.2450	-1.3612	Pass
-10		3673.2450	-1.3612	Pass
0		3673.2450	-1.3612	Pass
20		3673.2450	-1.3612	Pass
30		3673.2450	-1.3612	Pass
40		3673.2450	-1.3612	Pass
50		3673.2450	-1.3612	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal_3.5MHz_Ant 1		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3651.75 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3651.7450	-1.3692	Pass
-20		3651.7450	-1.3692	Pass
-10		3651.7450	-1.3692	Pass
0		3651.7500	0.0000	Pass
20		3651.7440	-1.6430	Pass
30		3651.7450	-1.3692	Pass
40		3651.7450	-1.3692	Pass
50		3651.7450	-1.3692	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.5000	0.0000	Pass
-20		3662.5000	0.0000	Pass
-10		3662.5000	0.0000	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3673.25 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3673.2450	-1.3612	Pass
-20		3673.2400	-2.7224	Pass
-10		3673.2500	0.0000	Pass
0		3673.2500	0.0000	Pass
20		3673.2450	-1.3612	Pass
30		3673.2450	-1.3612	Pass
40		3673.2450	-1.3612	Pass
50		3673.2450	-1.3612	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal_5MHz_Ant 0		
Date of Test	2012/02/03	Test Site	SR7

Centre Frequency: 3652.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3652.4950	-1.3689	Pass
-20		3652.4950	-1.3689	Pass
-10		3652.4950	-1.3689	Pass
0		3652.4950	-1.3689	Pass
20		3652.4950	-1.3689	Pass
30		3652.4950	-1.3689	Pass
40		3652.4950	-1.3689	Pass
50		3652.4950	-1.3689	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4950	-1.3652	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3672.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3672.4950	-1.3615	Pass
-20		3672.4950	-1.3615	Pass
-10		3672.4950	-1.3615	Pass
0		3672.4950	-1.3615	Pass
20		3672.4950	-1.3615	Pass
30		3672.4950	-1.3615	Pass
40		3672.4950	-1.3615	Pass
50		3672.4950	-1.3615	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal_5MHz_Ant 1		
Date of Test	2012/02/03	Test Site	SR7

Centre Frequency: 3652.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3652.4950	-1.3689	Pass
-20		3652.4950	-1.3689	Pass
-10		3652.4950	-1.3689	Pass
0		3652.4950	-1.3689	Pass
20		3652.5000	0.0000	Pass
30		3652.5000	0.0000	Pass
40		3652.4950	-1.3689	Pass
50		3652.4950	-1.3689	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4900	-2.7304	Pass
0		3662.4950	-1.3652	Pass
20		3662.4900	-2.7304	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4900	-2.7304	Pass

Centre Frequency: 3672.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3672.4950	-1.3615	Pass
-20		3672.4950	-1.3615	Pass
-10		3672.4950	-1.3615	Pass
0		3672.4950	-1.3615	Pass
20		3672.4950	-1.3615	Pass
30		3672.4950	-1.3615	Pass
40		3672.4950	-1.3615	Pass
50		3672.4950	-1.3615	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal 7MHz Ant 0		
Date of Test	2012/02/03	Test Site	SR7

Centre Frequency: 3653.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3653.4950	-1.3686	Pass
-20		3653.4950	-1.3686	Pass
-10		3653.4950	-1.3686	Pass
0		3653.4950	-1.3686	Pass
20		3653.4950	-1.3686	Pass
30		3653.4950	-1.3686	Pass
40		3653.4950	-1.3686	Pass
50		3653.4950	-1.3686	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4950	-1.3652	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3671.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3671.4950	-1.3618	Pass
-20		3671.4950	-1.3618	Pass
-10		3671.4950	-1.3618	Pass
0		3671.4950	-1.3618	Pass
20		3671.4950	-1.3618	Pass
30		3671.4950	-1.3618	Pass
40		3671.4950	-1.3618	Pass
50		3671.4950	-1.3618	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal 7MHz Ant 1		
Date of Test	2012/02/03	Test Site	SR7

Centre Frequency: 3653.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3653.4950	-1.3686	Pass
-20		3653.5000	0.0000	Pass
-10		3653.4950	-1.3686	Pass
0		3653.4950	-1.3686	Pass
20		3653.4950	-1.3686	Pass
30		3653.4950	-1.3686	Pass
40		3653.4950	-1.3686	Pass
50		3653.4900	-2.7371	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4950	-1.3652	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3671.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3671.4950	-1.3618	Pass
-20		3671.4950	-1.3618	Pass
-10		3671.4950	-1.3618	Pass
0		3671.4950	-1.3618	Pass
20		3671.4950	-1.3618	Pass
30		3671.4950	-1.3618	Pass
40		3671.4950	-1.3618	Pass
50		3671.4950	-1.3618	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal 10MHz Ant 0		
Date of Test	2012/02/03	Test Site	SR7

Centre Frequency: 3655.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3654.9950	-1.3680	Pass
-20		3654.9950	-1.3680	Pass
-10		3654.9950	-1.3680	Pass
0		3654.9950	-1.3680	Pass
20		3654.9950	-1.3680	Pass
30		3654.9950	-1.3680	Pass
40		3654.9950	-1.3680	Pass
50		3654.9950	-1.3680	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4950	-1.3652	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3670.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3669.9950	-1.3624	Pass
-20		3669.9950	-1.3624	Pass
-10		3669.9950	-1.3624	Pass
0		3669.9950	-1.3624	Pass
20		3669.9950	-1.3624	Pass
30		3669.9950	-1.3624	Pass
40		3669.9950	-1.3624	Pass
50		3669.9950	-1.3624	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Temperatures Variation		
Test Mode	Carrier Signal_10MHz_Ant 1		
Date of Test	2012/02/03	Test Site	SR7

Centre Frequency: 3655.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3654.9950	-1.3680	Pass
-20		3654.9950	-1.3680	Pass
-10		3654.9950	-1.3680	Pass
0		3654.9950	-1.3680	Pass
20		3654.9950	-1.3680	Pass
30		3654.9950	-1.3680	Pass
40		3654.9900	-2.7360	Pass
50		3654.9950	-1.3680	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3662.4950	-1.3652	Pass
-20		3662.4950	-1.3652	Pass
-10		3662.4950	-1.3652	Pass
0		3662.4950	-1.3652	Pass
20		3662.4950	-1.3652	Pass
30		3662.4950	-1.3652	Pass
40		3662.4950	-1.3652	Pass
50		3662.4950	-1.3652	Pass

Centre Frequency: 3670.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
-30	120	3669.9950	-1.3624	Pass
-20		3669.9950	-1.3624	Pass
-10		3669.9950	-1.3624	Pass
0		3669.9950	-1.3624	Pass
20		3669.9950	-1.3624	Pass
30		3669.9950	-1.3624	Pass
40		3669.9950	-1.3624	Pass
50		3669.9950	-1.3624	Pass

9. Frequency Stability Over Voltage Variation

9.1. Test Equipment


The following test equipments are used during the test:

Frequency Stability Over Temperatures Variation/ SR7

Instrument	Manufacturer	Model No.	Serial No	Next Cal. Date
Spectrum Analyzer	Agilent	N9010A	US47140172	2012/07/13
Standard Temperature & Humidity Chamber	WIT	TH-1S-B	1082101	2012/01/30

Note: 1. all equipments that need to calibrate are with calibration period of 1 year.

9.2. Test Setup



9.3. Limits

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

9.4. Test Procedure

Power must be removed when changing from one voltage to another voltage. Power warm up is at least 15 min and power applied should perform before recording frequency error.

EUT is connected the external power supply to control the AC input power. The various Volts set from the minimum 102 Volts to 138 Volts. Each step shall be record the frequency error rate.

9.5. Test Specification

FCC CFR Title 47 Part 90 Subpart Z, KDB 965270

9.6. Uncertainty

The measurement uncertainty is defined as $\pm 100\text{KHz}$.

9.7. Test Result

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_3.5MHz_Ant 0		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3651.75 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3651.7450	-1.3692	Pass
	120	3651.7450	-1.3692	Pass
	138	3651.7450	-1.3692	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4950	-1.3652	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3673.25 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3673.2450	-1.3612	Pass
	120	3673.2450	-1.3612	Pass
	138	3673.2450	-1.3612	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_3.5MHz_Ant 1		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3651.75 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3651.7440	-1.6430	Pass
	120	3651.7450	-1.3692	Pass
	138	3651.7450	-1.3692	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.5000	0.0000	Pass
	120	3662.5000	0.0000	Pass
	138	3662.5000	0.0000	Pass

Centre Frequency: 3673.25 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3673.2500	0.0000	Pass
	120	3673.2500	0.0000	Pass
	138	3673.2450	-1.3612	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_5MHz_Ant 0		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3652.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3652.4950	-1.3689	Pass
	120	3652.4950	-1.3689	Pass
	138	3652.4950	-1.3689	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4950	-1.3652	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3672.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3672.4950	-1.3615	Pass
	120	3672.4950	-1.3615	Pass
	138	3672.4950	-1.3615	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_5MHz_Ant 1		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3652.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3652.4950	-1.3689	Pass
	120	3652.4950	-1.3689	Pass
	138	3652.5000	0.0000	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4900	-2.7304	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3672.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3672.4950	-1.3615	Pass
	120	3672.4950	-1.3615	Pass
	138	3672.4950	-1.3615	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_7MHz_Ant 0		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3653.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3653.4950	-1.3686	Pass
	120	3653.4950	-1.3686	Pass
	138	3653.4950	-1.3686	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4950	-1.3652	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3671.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3671.4950	-1.3618	Pass
	120	3671.4950	-1.3618	Pass
	138	3671.4950	-1.3618	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_7MHz_Ant 1		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3653.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3653.5000	0.0000	Pass
	120	3653.4950	-1.3686	Pass
	138	3653.4950	-1.3686	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4950	-1.3652	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3671.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3671.4950	-1.3618	Pass
	120	3671.4950	-1.3618	Pass
	138	3671.4950	-1.3618	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_10MHz_Ant 0		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3655.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3654.9950	-1.3680	Pass
	120	3654.9950	-1.3680	Pass
	138	3654.9950	-1.3680	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4950	-1.3652	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3670.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3669.9950	-1.3624	Pass
	120	3669.9950	-1.3624	Pass
	138	3669.9950	-1.3624	Pass

Product	CBS 3.65GHz		
Test Item	Frequency Stability Over Voltage Variation		
Test Mode	Carrier Signal_10MHz_Ant 1		
Date of Test	2012/01/03	Test Site	SR7

Centre Frequency: 3655.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3654.9950	-1.3680	Pass
	120	3654.9950	-1.3680	Pass
	138	3654.9950	-1.3680	Pass

Centre Frequency: 3662.5 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3662.4950	-1.3652	Pass
	120	3662.4950	-1.3652	Pass
	138	3662.4950	-1.3652	Pass

Centre Frequency: 3670.0 MHz

Temperature Interval (°C)	AC Voltage (V)	Frequency (MHz)	Deviation (ppm)	Result
25	102	3669.9950	-1.3624	Pass
	120	3669.9950	-1.3624	Pass
	138	3669.9950	-1.3624	Pass