

	1	2	3	4	5	6
A	RSAG8.807.					
B						其余
C	<div><div>1.6</div><div>49-0.2</div><div><div>PROSCAN®</div><div>FCC ID: W9HLCDD0003 This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.</div><div><div>ETL</div><div>CONFORMS TO ANSI/UL STD. 60065 CERTIFIED TO CAN/CSA STD. C22.2 NO. 60065</div><div>Intertek 3100846</div></div><div><div>CAUTION</div><div>RISK OF ELECTRIC SHOCK DO NOT OPEN</div></div><div><div>MODEL NO.:42LC55S240V87</div><div>120VOLTS~ 60Hz</div><div>205WATTS</div><div>ON Corp US, Inc.</div><div>4370 La Jolla Village Drive, Suite 400</div><div>San Diego, CA 92122</div><div>ATTENTION: RISQUE DE CHOC ELECTRIQUE; NE PAS OUVRIR</div><div>Series No.:</div><div>Manufactured date:</div><div>MADE IN CHINA</div></div><div>2×R3</div><div>t0.12</div><div>99-0.2</div></div></div>					
D						
E						
F						
G						
H						
I						
J						

技术要求

1. 材料要求：采用不干胶纸（80克铜版纸）覆膜。

2. 材料及粘接剂符合Rohs指令的环保要求。

3. 未注尺寸公差按照GB/T1804-2000规定的M级精度。

4. 印刷内容严格按图示排列，铭牌印刷成黑底白字，图中所有字符内容、大小、位置严格按照电子版文件制作，印刷文字要求清晰，不易擦除，无污损、无划痕等缺陷。

5. 商标、标志严格按照图纸（电子版）制作。

6. “~”符号符合GB/T 5465.2-1996 的标准要求。

7. 制件边缘裁切光滑、无毛刺等缺陷。

8. 在恒温恒湿条件下（温度：40℃/湿度：60%）、在变温条件下（温度：55℃—零下20℃/湿度：90%）无褶皱、无气泡等不良缺陷。

		镀涂			
旧底图总号				铭牌	
				RSAG8.807.	
更改标记		数量	更改单号	签名	日期
底图总号		设计		42LC55S240V87	
		电路		(LTDN42V87XUS)	
		审核			
签名				阶段标记	
				质量	
				比例	
				1:1	
				第1页	
				共1页	
				80克铜版纸（覆膜）	
				青岛海信电器股份有限公司	

格式(1)

1

2

3

4

5

6幅面: A4