

FCC PART 15.247



MEASUREMENT AND TEST REPORT

For

Verykool USA Inc.

4350 Executive Dr. #100, San Diego, CA 92121, USA

FCC ID: WA6R80

Report Type: Original Report	Product Type: GSM/GPRS Quad-Band Mobile Phone
Test Engineer: Sula Huang 	
Report Number: RSZ10121603-15.247	
Report Date: 2011-01-10	
Reviewed By: Merry Zhao  EMC Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
CONFIGURATION OF TEST SETUP	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247(i) & §2.1093 – RF EXPOSURE INFORMATION.....	9
APPLICABLE STANDARD	9
RESULT	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP.....	12
EMI TEST RECEIVER SETUP.....	13
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST PROCEDURE	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) – RADIATED SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST PROCEDURE	17
CORRECTED AMPLITUDE & MARGIN CALCULATION	17
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	22
APPLICABLE STANDARD	22
TEST EQUIPMENT LIST AND DETAILS.....	22

TEST PROCEDURE	22
TEST DATA	22
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING	25
APPLICABLE STANDARD	25
TEST EQUIPMENT LIST AND DETAILS	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	28
APPLICABLE STANDARD	28
TEST EQUIPMENT LIST AND DETAILS	28
TEST PROCEDURE	28
TEST DATA	28
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)	30
APPLICABLE STANDARD	30
TEST EQUIPMENT LIST AND DETAILS	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	36
APPLICABLE STANDARD	36
TEST EQUIPMENT LIST AND DETAILS	36
TEST PROCEDURE	36
TEST DATA	36
FCC §15.247(d) - BAND EDGES TESTING	39
APPLICABLE STANDARD	39
TEST EQUIPMENT LIST AND DETAILS	39
TEST PROCEDURE	39
TEST DATA	40

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Verykool USA Inc.*'s product, model number: *R80 (FCC ID: WA6R80)* or the "EUT" as referred to in this report is a *GSM/GPRS Quad-Band Mobile Phone*, which measures approximately: 12.0 cm (L) x 5.5 cm (W) x 1.5 cm (H), rated input voltage: DC 3.7 V battery.

Frequency Range:

Cellular Band: 824-849 MHz (Tx), 869-894 MHz (Rx)
PCS Band: 1850-1910 MHz (Tx), 1930-1990 MHz (Rx)
Bluetooth: 2400-2483.5 MHz (Tx/Rx)

Modulation Mode: GMSK (GSM/PCS); GFSK (Bluetooth)

Transmitter Output Power:

Cellular Band: 33 dBm, PCS Band: 30 dBm
Bluetooth: 9 dBm

** All measurement and test data in this report was gathered from production sample serial number: 1012068 (Assigned by BACL, Shenzhen). The EUT was received on 2010-12-16.*

Objective

This Type approval report is prepared on behalf of *Verykool USA Inc.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H&24E submission with FCC ID: WA6R80.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which is provided by manufacture.

EUT Exercise Software

N/A

Equipment Modifications

No modification was made to the unit tested.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
R & S	Universal Radio CommutationTester	CMU200	1100 0008.02	DOC


External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable USB Cabel	1.2	EUT	Adapter

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 15.247 (i), § 2.1093	RF Exposure	Compliance
§ 15.203	Antenna Requirement	Compliance
§ 15.207 (a)	AC Line Conducted Emissions	Compliance
§ 15.205, § 15.209, § 15.247(d)	Radiated Spurious Emissions	Compliance
§ 15.247 (a)(1)	20 dB Bandwidth	Compliance
§ 15.247(a)(1)	Channel Separation Test	Compliance
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§ 15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§ 15.247(b)(1)	Peak Output Power Measurement	Compliance
§ 15.247(d)	Band Edges	Compliance

FCC §15.247(i) & §2.1093 – RF EXPOSURE INFORMATION

Applicable Standard

According to FCC §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Table 2 – Summary of SAR Evaluation Requirements for a Cell Phone with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	SAR not required: <u>Unlicensed only</u> <ul style="list-style-type: none"> when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas <u>Licensed & Unlicensed</u> <ul style="list-style-type: none"> when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3 SAR required: <u>Licensed & Unlicensed</u> antenna pairs with SAR to peak location separation ratio ≥ 0.3 ; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply
Unlicensed Transmitters	<p>When there is no simultaneous transmission –</p> <ul style="list-style-type: none"> output ≤ 60 f: SAR not required output > 60 f: stand-alone SAR required <p>When there is simultaneous transmission – <u>Stand-alone SAR not required when</u></p> <ul style="list-style-type: none"> output $\leq 2 \cdot P_{Ref}$ and antenna is ≥ 5.0 cm from other antennas output $\leq P_{Ref}$ and antenna is ≥ 2.5 cm from other antennas output $\leq P_{Ref}$ and antenna is < 2.5 cm from other antennas, each with either output power $\leq P_{Ref}$ or 1-g SAR < 1.2 W/kg <p><u>Otherwise stand-alone SAR is required</u></p> <p>When stand-alone SAR is required</p> <ul style="list-style-type: none"> test SAR on highest output channel for each wireless mode and exposure condition if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedures 	
Jaw, Mouth and Nose	<u>Flat phantom SAR required</u> <ul style="list-style-type: none"> when measurement is required in tight regions of SAM and it is not feasible or the results can be questionable due to probe tilt, calibration, positioning and orientation issues position rectangular and clam-shell phones according to flat phantom procedures and conduct SAR measurements for these specific locations 	When simultaneous transmission SAR testing is required, contact the FCC Laboratory for interim guidance.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

Result

Three antennas are available for the EUT, (GSM antenna, Bluetooth antenna, GPS antenna), The distance between Bluetooth antenna and GSM antenna is more than 5 cm, the Bluetooth power is 9.908 mW which is less than $2 \times P_{\text{ref}} = 24 \text{ mW}$. According to KDB 648474, stand-alone and simultaneous SAR measurement is not required.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has a PIFA antenna of Bluetooth, the gain is 2.0 dBi, which are in accordance to section 15.203, please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard


FCC §15.207

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is ± 2.4 dB.

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>IF B/W</i>
150 kHz – 30 MHz	9 kHz

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2010-03-03	2011-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2010-03-09	2011-03-08

* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

5.94 dB at 27.120 MHz in the Line conductor mode

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa


* The testing was performed by Sula Huang on 2010-12-29.

Test Mode: Adapter Charging & Transmitting

120 V, 60 Hz, Line:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Correction Factor (dB)	Cord. Result (dBμV)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
27.120	44.06	10.13	50.00	5.94	Ave
13.560	43.28	10.14	50.00	6.72	Ave
27.120	44.03	10.13	60.00	15.97	QP
0.300	29.64	10.00	51.71	22.07	Ave
8.750	26.31	10.10	50.00	23.69	Ave
1.445	31.44	10.14	56.00	24.56	QP
0.300	37.14	10.00	61.71	24.57	QP
0.525	20.98	10.19	46.00	25.02	Ave
0.525	30.45	10.19	56.00	25.55	QP
1.455	19.47	10.15	46.00	26.53	Ave
13.560	24.69	10.14	60.00	35.31	QP
8.745	21.95	10.10	60.00	38.05	QP

120V, 60 Hz, Neutral:

Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Correction Factor (dB)	Cord. Result (dBμV)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
27.120	43.71	10.13	50.00	6.29	Ave
27.120	45.86	10.13	60.00	14.14	QP
0.295	35.84	10.00	51.86	16.02	Ave
0.295	45.01	10.00	61.86	16.85	QP
8.875	28.84	10.10	50.00	21.16	Ave
8.920	37.91	10.10	60.00	22.09	QP
0.590	23.79	10.18	46.00	22.21	Ave
0.365	26.16	10.06	49.86	23.70	Ave
0.590	30.34	10.18	56.00	25.66	QP
15.870	33.32	10.16	60.00	26.68	QP
0.365	32.65	10.06	59.86	27.21	QP
15.880	22.30	10.16	50.00	27.70	Ave

FCC §15.209, §15.205 & §15.247(d) – RADIATED SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2010-08-02	2011-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-03-11	2011-03-10
HP	Amplifier	2VA-213+	T-E27H	2010-03-08	2011-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2010-05-05	2011-05-04
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2010-07-08	2011-07-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

Below 1 GHz:

10.0 dB at 30.735000 MHz in the Vertical polarization

Above 1 GHz:


1.53 dB at 4882 MHz in the Horizontal polarization (Middle Channel)

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Sula Huang on 2010-12-29.

Below 1 GHz:*Test Mode: Transmitting*

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Test Antenna		Turntable Position (degree)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polarity (H/V)				
30.735000	30.0	290.0	V	298.0	-5.9	40.0	10.0
819.059250	33.4	100.0	V	211.0	-1.6	46.0	12.6
41.665000	25.6	10.0	V	135.0	-13.1	40.0	14.4
75.606000	25.0	400.0	H	216.0	-18.2	40.0	15.0
43.412750	24.8	100.0	V	25.0	-14.2	40.0	15.2
698.294750	30.4	164.0	V	0.0	-3.1	46.0	15.6

Test Mode: Transmitting

Above 1 GHz (worst case):

Indicated		Detector (PK/Ave.)	Table Angle Degree	Test Antenna		Correction Factor			FCC Part 15.247/15.209			
Frequency (MHz)	Receiver Reading (dBμV)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
Low Channel (2402 MHz)												
4804	38.12	Ave.	0	2.2	H	36.3	4.30	26.75	51.97	54	2.03	harmonic
2560.2	40.59	Ave.	226	1.9	H	30.6	3.10	26.88	47.41	54	6.59	spurious
4804	34.80	Ave.	0	2.4	V	32.8	4.30	26.75	45.15	54	8.85	harmonic
4804	50.98	PK	0	2.2	H	36.3	4.30	26.75	64.83	74	9.17	harmonic
2560.2	36.58	Ave.	0	1.3	V	30.6	3.10	26.88	43.4	54	10.6	spurious
4804	46.01	PK	0	2.4	V	35.0	4.30	26.75	58.56	74	15.44	harmonic
7206	19.88	Ave.	360	1.5	H	39.0	5.22	26.64	37.46	54	16.54	harmonic
7206	19.91	Ave.	307	2.5	V	37.9	5.22	26.64	36.39	54	17.61	harmonic
2560.2	43.37	PK	226	1.9	H	30.6	3.10	26.88	50.19	74	23.81	spurious
7206	31.67	PK	360	1.5	H	39.0	5.22	26.64	49.25	74	24.75	harmonic
2560.2	42.38	PK	0	1.3	V	30.6	3.10	26.88	49.2	74	24.8	spurious
7206	31.71	PK	307	2.5	V	37.9	5.22	26.64	48.19	74	25.81	harmonic
Middle Channel (2441 MHz)												
4882	38.25	Ave.	328	1.2	H	36.6	4.37	26.75	52.47	54	1.53	harmonic
2560.2	41.35	Ave.	224	1.9	H	30.6	3.10	26.88	48.17	54	5.83	spurious
4882	33.51	Ave.	0	1.5	V	35.4	4.37	26.75	46.53	54	7.47	harmonic
4882	50.94	PK	328	1.2	H	36.6	4.37	26.75	65.16	74	8.84	harmonic
2560.2	37.64	Ave.	10	1.4	V	30.6	3.10	26.88	44.46	54	9.54	spurious
4882	45.76	PK	0	1.5	V	35.4	4.37	26.75	58.78	74	15.22	harmonic
7323	20.34	Ave.	358	1.4	H	39.0	5.21	26.64	37.91	54	16.09	harmonic
7323	20.13	Ave.	310	2.4	V	37.9	5.21	26.64	36.6	54	17.4	harmonic
2560.2	44.19	PK	224	1.9	H	30.6	3.10	26.88	51.01	74	22.99	spurious
2560.2	42.35	PK	10	1.4	V	30.6	3.10	26.88	49.17	74	24.83	spurious
7323	31.42	PK	358	1.4	H	39.0	5.21	26.64	48.99	74	25.01	harmonic
7323	31.58	PK	310	2.4	V	37.9	5.21	26.64	48.05	74	25.95	harmonic
High Channel (2480 MHz)												
4960	36.37	Ave.	360	1	H	36.6	4.37	26.75	50.59	54	3.41	harmonic
4960	32.28	Ave.	0	2.4	V	35.4	4.37	26.75	45.30	54	8.70	harmonic
2559.6	37.01	Ave.	275	1.4	V	30.6	2.72	26.88	43.45	54	10.55	spurious
2559.6	36.15	Ave.	0	1.4	H	30.6	3.10	26.88	42.97	54	11.03	spurious
4960	48.46	PK	360	1	H	36.6	4.37	26.75	62.68	74	11.32	harmonic
4960	43.57	PK	0	2.4	V	35.4	4.37	26.75	56.59	74	17.41	harmonic
7440	18.62	Ave.	360	1.4	H	39.0	5.20	26.64	36.18	54	17.82	harmonic
7440	18.13	Ave.	300	2.5	V	37.7	5.20	26.64	34.39	54	19.61	harmonic
2559.6	42.56	PK	0	1.4	H	30.6	3.10	26.88	49.38	74	24.62	spurious
2559.6	42.15	PK	275	1.4	V	30.6	2.72	26.88	48.59	74	25.41	spurious
7440	29.51	PK	360	1.4	H	39.0	5.20	26.64	47.07	74	26.93	harmonic
7440	29.88	PK	300	2.5	V	37.7	5.20	26.64	46.14	74	27.86	harmonic

Spurious Emissions in Restrict Bands:

Indicated		Detector (PK/Ave.)	Table Angle Degree	Test Antenna		Correction Factor			FCC Part 15.247/15.209/15.205			
Frequency (MHz)	Receiver Reading (dBμV)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Comment
2483.56	33.54	Ave.	360	1.8	H	31.0	3.04	27.54	40.04	54	13.96	spurious
2389.50	33.67	Ave.	20	2.0	H	30.8	3.03	27.54	39.96	54	14.04	spurious
2389.50	33.59	Ave.	21	2.0	V	30.2	3.03	27.54	39.28	54	14.72	spurious
2483.56	31.33	Ave.	0	2.0	V	30.4	3.04	27.54	37.23	54	16.77	spurious
2389.50	46.62	PK	20	2.0	H	30.8	3.03	27.54	52.91	74	21.09	spurious
2483.56	46.21	PK	360	1.8	H	31.0	3.04	27.54	52.71	74	21.29	spurious
2389.50	46.78	PK	21	2.0	V	30.2	3.03	27.54	52.47	74	21.53	spurious
2483.56	44.74	PK	0	2.0	V	30.4	3.04	27.54	50.64	74	23.36	spurious

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

* The testing was performed by Sula Huang on 2011-01-03.


Test Result: Compliant.

Please refer to following tables and plots

Test Mode: Transmitting


Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low	2402	1.004	0.699	Pass
Adjacent	2403			
Middle	2441	1.004	0.699	Pass
Adjacent	2442			
High	2480	1.004	0.699	Pass
Adjacent	2479			

Please refer to the following plots.

Low Channel


Date: 3.JAN.2011 12:46:11

Middle Channel



Date: 3.JAN.2011 12:47:26

High Channel



Date: 3.JAN.2011 12:49:19

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

* The testing was performed by Sula Huang on 2011-01-03.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2402	1.048
Middle	2441	1.048
High	2480	1.048

Please refer to the following plots.

Low Channel

Date: 3.JAN.2011 12:36:43

1 PK
MAXH

Ref 22.5 dBm *Att 30 dB RBW 30 kHz VBW 100 kHz SWT 2.5 ms Delta 1 [T1] 2.92 dB 1.04800000 MHz

Offset 3.5 dB

D1 9.67 dBm

Marker 1 [T1] -11.78 dBm 2.44047200 GHz

F1 F2

Center 2.441 GHz 200 kHz/ Span 2 MHz

3DB
AC

Date: 3.JAN.2011 12:34:58

Ref 22.5 dBm *Att 30 dB Delta 1 [T1] 0.96 dB
 *VBW 100 kHz 1.04800000 MHz
 SWT 2.5 ms

Offset 3.5 dB Marker 1 [T1] -11.43 dBm
 2.479476000 GHz

D1 9.24 dBm D2 -10.76 dBm

F1 F2

Center 2.48 GHz 200 kHz/ Span 2 MHz

Date: 3.JAN.2011 12:33:12

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa


The testing was performed by Sula Huang on 2011-01-03.

Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15

Number of Hopping Channels

Date: 3.JAN.2011 12:14:31

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 * channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s

Hop rate=1600/s

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

* The testing was performed by Sula Huang on 2011-01-03.


Test Result: Compliance.

Please refer to following tables and plots

Test Mode: Transmitting


Mode	Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
DH 1	Low	0.392	0.126	0.4	Pass
	Middle	0.392	0.126	0.4	Pass
	High	0.392	0.126	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600 \div 2 \div 79) \times 31.6 Second				
DH 3	Low	1.664	0.267	0.4	Pass
	Middle	1.656	0.265	0.4	Pass
	High	1.664	0.267	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600 \div 4 \div 79) \times 31.6 Second				
DH 5	Low	2.928	0.313	0.4	Pass
	Middle	2.928	0.313	0.4	Pass
	High	2.944	0.314	0.4	Pass
	Note: Dwell time=Pulse Time (ms) \times (1600 \div 6 \div 79) \times 31.6 Second				

Please refer to the following plots.

Low Channel for DH1


Date: 3.JAN.2011 12:51:41

Middle Channel for DH1




Date: 3.JAN.2011 12:53:30

High Channel for DH1




Date: 3.JAN.2011 12:55:13

Low Channel for DH3




Date: 3.JAN.2011 12:56:48

Middle Channel for DH3




Date: 3.JAN.2011 12:57:33

High Channel for DH3




Date: 3.JAN.2011 12:58:16

Low Channel for DH5




Date: 3.JAN.2011 13:00:53

Middle Channel for DH5



Date: 3.JAN.2011 13:01:40

High Channel for DH5



Date: 3.JAN.2011 13:04:05

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to FCC §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt, For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa


* The testing was performed by Sula Huang on 2011-01-03.

Test Result: Compliance.

Test Mode: Transmitting


Channel	Channel frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
Low	2402	9.96	9.908	125
Middle	2441	9.70	9.333	125
High	2480	9.25	8.414	125

Note: The data above was tested in conducted mode.

Low Channel


Date: 3.JAN.2011 12:39:32

Middle Channel



Date: 3.JAN.2011 12:41:27

High Channel



Date: 3.JAN.2011 12:43:28

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-24	2011-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

**The testing was performed by Sula Huang on 2011-01-03.*


Test Result: Compliance

Test Mode: Transmitting


Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2399.984	-48.86	20
2484.922	-54.10	20

Note: The point fall into the stricted band was in FCC 15.209, please refer to the restrict band testing.

Please refer to follow plots:

Band Edge: Left Side

Date: 3.JAN.2011 13:11:15

Band Edge: Right Side

Date: 3.JAN.2011 13:15:06

******* END OF REPORT *******