



RF TEST REPORT



Report No.: 16071294-FCC-R3-V1

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Mobile Phone	
Model No.	s5019	
Serial No.	s5021	
Test Standard	FCC Part 15.247: 2015, ANSI C63.10: 2013	
Test Date	November 11 to December 05&11, 2016	
Issue Date	December 12, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	16071294-FCC-R3-V1-V1
Page	3 of 57

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH	10
6.3 MAXIMUM OUTPUT POWER	16
6.4 POWER SPECTRAL DENSITY	20
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	24
6.6 AC POWER LINE CONDUCTED EMISSIONS	29
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND	35
ANNEX A. TEST INSTRUMENT	45
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	46
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	52
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	56
ANNEX E. DECLARATION OF SIMILARITY	57

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071294-FCC-R3	NONE	Original	December 06, 2016
16071294-FCC-R3-V1	V1	Added the camera photos	December 12, 2016

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States
Manufacturer	HUAWO TECHNOLOGY LIMITED
Manufacturer Add	3 floor west, B building, New world shopping plaza,Gushu 2nd road, Xixiang street, Baoan District, Shenzhen , China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	s5019
Serial Model:	s5021
Date EUT received:	November 10, 2016
Test Date(s):	November 11 to December 05&11, 2016
Equipment Category :	DTS
Antenna Gain:	GSM850: -0.83dBi PCS1900: -0.59dBi UMTS-FDD Band V: -0.81dBi UMTS-FDD Band II: -0.55dBi Bluetooth: 0.25dBi WIFI: 0.26dBi GPS: -0.55dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK GPS: BPSK

RF Operating Frequency (ies):	<p>GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz</p> <p>PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz</p> <p>UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz</p> <p>UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;</p> <p>RX: 1932.4 ~ 1987.6 MHz</p> <p>WIFI: 802.11b/g/n(20M): 2412-2462 MHz</p> <p>Bluetooth: 2402-2480 MHz</p> <p>GPS: 1575.42 MHz</p>
Max. Output Power:	<p>802.11b: 8.74dBm</p> <p>802.11g: 8.86dBm</p> <p>802.11n(20M): 8.36dBm</p>
Number of Channels:	<p>GSM 850: 124CH</p> <p>PCS1900: 299CH</p> <p>UMTS-FDD Band V: 102CH</p> <p>UMTS-FDD Band II: 277CH</p> <p>WIFI :802.11b/g/n(20M): 11CH</p> <p>Bluetooth: 79CH</p> <p>GPS:1CH</p>
Port:	<p>USB Port, Earphone Port</p>
Input Power:	<p>Adapter:</p> <p>Model: QU050070USB01</p> <p>Input: AC100-240V~50/60Hz,0.15A</p> <p>Output: DC 5.0V-700mA</p> <p>Battery:</p> <p>Model: 365778</p> <p>Spec: 3.7V, 2000mAh(7.4Wh)</p> <p>Limited charger voltage: 4.2V</p>
Trade Name :	verykool
GPRS/EGPRS Multi-slot class	8/10/12
FCC ID:	WA6S5019

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Spurious Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached PIFA antenna for Bluetooth/WIFI/GPS, the gain is 0.25dBi for Bluetooth, the gain is 0.26dBi for WIFI, the gain is -0.55dBi for GPS.


A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is -0.83dBi for GSM850, -0.59dBi for PCS1900, -0.81dBi for UMTS-FDD Band V, -0.55dBi for UMTS-FDD Band II.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	November 11, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW \geq 500kHz; 20dB BW \geq 500kHz;	<input checked="" type="checkbox"/>
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> Set RBW = 100 kHz. Set the video bandwidth (VBW) $\geq 3 \times$ RBW. Detector = Peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> Set RBW = 1%-5% OBW. Set the video bandwidth (VBW) $\geq 3 \times$ RBW. Set the span range between 2 times and 5 times of the OBW. Sweep time=Auto, Detector=PK, Trace=Max hold. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst- 		

Test Report No.	16071294-FCC-R3-V1-V1
Page	11 of 57

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.12	14.37	≥ 0.5
	Mid	2437	10.11	14.36	≥ 0.5
	High	2462	10.11	14.36	≥ 0.5
802.11g	Low	2412	16.35	18.50	≥ 0.5
	Mid	2437	16.31	18.83	≥ 0.5
	High	2462	16.33	18.83	≥ 0.5
802.11n (20M)	Low	2412	17.41	19.40	≥ 0.5
	Mid	2437	16.98	19.58	≥ 0.5
	High	2462	17.43	19.41	≥ 0.5

Test Plots

6dB Bandwidth measurement result






802.11n20 6dB Bandwidth - Low CH 2412




802.11n20 6dB Bandwidth - Mid CH 2437



802.11n20 6dB Bandwidth - High CH 2462


20 dB Bandwidth measurement result




802.11b 20dB Bandwidth - Low CH 2412




802.11b 20dB Bandwidth - Mid CH 2437




802.11b 20dB Bandwidth - High CH 2462




802.11g 20dB Bandwidth - Low CH 2412




802.11g 20dB Bandwidth - Mid CH 2437




802.11g 20dB Bandwidth - High CH 2462



802.11n20 20dB Bandwidth - Low CH 2412



802.11n20 20dB Bandwidth - Mid CH 2437




802.11n20 20dB Bandwidth - High CH 2462

6.3 Maximum Output Power

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	November 11, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <ul style="list-style-type: none"> - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW $\geq 3 \times$ RBW. - d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum 		

Test Report No.	16071294-FCC-R3-V1-V1
Page	17 of 57

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Output Power measurement result

Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	8.53	30	Pass
		Mid	2437	8.37	30	Pass
		High	2462	8.74	30	Pass
	802.11g	Low	2412	8.38	30	Pass
		Mid	2437	8.86	30	Pass
		High	2462	8.69	30	Pass
	802.11n (20M)	Low	2412	8.27	30	Pass
		Mid	2437	8.36	30	Pass
		High	2462	8.35	30	Pass

Test Plots


The Average Power



802.11b - AV Output power - Low CH 2412




802.11b - AV Output power - Mid CH 2437




802.11b - AV Output power - High CH 2462



802.11g - AV Output power - Low CH 2412



802.11g - AV Output power - Mid CH 2437



802.11g - AV Output power - High CH 2462



802.11n20 - AV Output power - Low CH 2412




802.11n20 - AV Output power - Mid CH 2437



802.11n20 - AV Output power - High CH 2462

6.4 Power Spectral Density

Temperature	24°C
Relative Humidity	53%
Atmospheric Pressure	1011mbar
Test date :	November 11, 2016
Tested By :	Loren Luo

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A
Test Plot ☒ Yes (See below) ☐ N/A

Power Spectral Density measurement result

Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-17.664	8	Pass
		Mid	2437	-16.011	8	Pass
		High	2462	-16.685	8	Pass
	802.11g	Low	2412	-21.556	8	Pass
		Mid	2437	-21.422	8	Pass
		High	2462	-21.192	8	Pass
	802.11n (20M)	Low	2412	-21.819	8	Pass
		Mid	2437	-21.740	8	Pass
		High	2462	-21.933	8	Pass

Test Plots

Power Spectral Density measurement result




PSD - Low CH 2412 - 802.11b




PSD - Mid CH 2437 - 802.11b




PSD - High CH 2462 - 802.11b



PSD - Low CH 2412 - 802.11g




PSD - Mid CH 2437 - 802.11g



PSD - High CH 2462 - 802.11g



PSD - Low CH 2412 - 802.11n20



PSD - Mid CH 2437 - 802.11n20




PSD - High CH 2472 - 802.11n20

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range. 		



Test Report No.	16071294-FCC-R3-V1-V1
Page	25 of 57


	<ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Test Plots

Band Edge measurement result

 <p> * Att 5 dB * RBW 1 MHz * VBW 3 MHz * Ref 102.0 dBμV * SWT 2.5ms M2[1] 50.44 dBμV 2.374510000 GHz Limit Check Line Limit 74 PASS M1[1] PASS 48.81 dBμV 2.400000000 GHz 1Pk Max 90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV Tdf CF 2.39 GHz Span 80.0 MHz Date: 16.NOV.2016 15:21:11 </p>	 <p> * Att 5 dB * RBW 1 MHz * VBW 3 MHz * Ref 102.0 dBμV * SWT 2.5ms M1[1] 49.48 dBμV 2.489090000 GHz Limit Check Line Limit 74 PASS PASS 1Pk Max 90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV Tdf CF 2.4835 GHz Span 80.0 MHz Date: 16.NOV.2016 15:32:34 </p>
<p>Band Edge, Left Side (Peak) - 802.11b</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Peak) - 802.11b</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Band Edge, Left Side (Average) - 802.11b</p>	<p>Band Edge, Right Side (Average) - 802.11b</p>






Band Edge, Left Side (Peak) - 802.11n20
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11n20
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n20
Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)


Band Edge, Right Side (Average) - 802.11n20
Note: F1 is frequency 2483.5MHz

6.6 AC Power Line Conducted Emissions

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<div><input checked="" type="checkbox"/></div>														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
0.5 ~ 5	56	46															
5 ~ 30	60	50															

Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	---

Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report No.	16071294-FCC-R3-V1-V1
Page	30 of 57

	<p>coaxial cable.</p> <ol style="list-style-type: none"> 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.1773	40.73	QP	13.10	53.83	64.61	-10.78
2	L1	0.1773	19.78	AVG	13.10	32.88	54.61	-21.73
3	L1	0.6024	38.63	QP	11.80	50.43	56.00	-5.57
4	L1	0.6024	28.44	AVG	11.80	40.24	46.00	-5.76
5	L1	1.1796	30.81	QP	11.40	42.21	56.00	-13.79
6	L1	1.1796	17.86	AVG	11.40	29.26	46.00	-16.74
7	L1	1.5696	29.44	QP	11.40	40.84	56.00	-15.16
8	L1	1.5696	16.26	AVG	11.40	27.66	46.00	-18.34
9	L1	2.2287	30.53	QP	11.40	41.93	56.00	-14.07
10	L1	2.2287	17.80	AVG	11.40	29.20	46.00	-16.80
11	L1	3.9126	28.89	QP	11.40	40.29	56.00	-15.71
12	L1	3.9126	16.24	AVG	11.40	27.64	46.00	-18.36

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.5829	34.72	QP	11.82	46.54	56.00	-9.46
2	N	0.5829	25.19	AVG	11.82	37.01	46.00	-8.99
3	N	1.1016	26.37	QP	11.41	37.78	56.00	-18.22
4	N	1.1016	15.55	AVG	11.41	26.96	46.00	-19.04
5	N	1.4175	23.13	QP	11.45	34.58	56.00	-21.42
6	N	1.4175	13.41	AVG	11.45	24.86	46.00	-21.14
7	N	2.1663	24.39	QP	11.55	35.94	56.00	-20.06
8	N	2.1663	14.77	AVG	11.55	26.32	46.00	-19.68
9	N	3.6357	23.39	QP	11.73	35.12	56.00	-20.88
10	N	3.6357	13.54	AVG	11.73	25.27	46.00	-20.73
11	N	4.8369	22.43	QP	11.88	34.31	56.00	-21.69
12	N	4.8369	13.14	AVG	11.88	25.02	46.00	-20.98

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.5829	31.51	QP	11.82	43.33	56.00	-12.67
2	L1	0.5829	22.82	AVG	11.82	34.64	46.00	-11.36
3	L1	1.4019	27.28	QP	11.40	38.68	56.00	-17.32
4	L1	1.4019	15.53	AVG	11.40	26.93	46.00	-19.07
5	L1	1.9557	28.22	QP	11.40	39.62	56.00	-16.38
6	L1	1.9557	15.60	AVG	11.40	27.00	46.00	-19.00
7	L1	2.4744	28.55	QP	11.40	39.95	56.00	-16.05
8	L1	2.4744	16.31	AVG	11.40	27.71	46.00	-18.29
9	L1	3.6357	27.29	QP	11.40	38.69	56.00	-17.31
10	L1	3.6357	14.00	AVG	11.40	25.40	46.00	-20.60
11	L1	4.7082	28.48	QP	11.40	39.88	56.00	-16.12
12	L1	4.7082	15.56	AVG	11.40	26.96	46.00	-19.04

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.5829	37.08	QP	11.82	48.90	56.00	-7.10
2	N	0.5829	27.34	AVG	11.82	39.16	46.00	-6.84
3	N	0.6882	32.49	QP	11.71	44.20	56.00	-11.80
4	N	0.6882	23.11	AVG	11.71	34.82	46.00	-11.18
5	N	0.8130	31.60	QP	11.59	43.19	56.00	-12.81
6	N	0.8130	22.21	AVG	11.59	33.80	46.00	-12.20
7	N	2.0649	31.78	QP	11.53	43.31	56.00	-12.69
8	N	2.0649	20.58	AVG	11.53	32.11	46.00	-13.89
9	N	2.8293	31.19	QP	11.63	42.82	56.00	-13.18
10	N	2.8293	17.75	AVG	11.63	29.38	46.00	-16.62
11	N	3.4641	28.89	QP	11.71	40.60	56.00	-15.40
12	N	3.4641	20.58	AVG	11.71	32.29	46.00	-13.71

6.7 Radiated Spurious Emissions & Restricted Band

Temperature	25°C
Relative Humidity	58%
Atmospheric Pressure	1016mbar
Test date :	November 16&December 05&11, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 (A8.5)	a)	<div>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</div> <table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 - 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 - 960	200	Above 960	500	<div><input checked="" type="checkbox"/></div>
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
	88 – 216	150											
216 - 960	200												
Above 960	500												
b)	<div>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</div> <div><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</div>	<div><input checked="" type="checkbox"/></div>											
c)	<div>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</div>	<div><input checked="" type="checkbox"/></div>											

Test Setup	
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Camera1: s5019

Test Mode:	Transmitting Mode
-------------------	--------------------------

(Below 1GHz)




Test Data

Vertical Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	H	30.6379	26.64	peak	-0.73	25.91	40.00	-14.09	100	113
2	H	204.2377	30.49	peak	-8.78	21.71	43.50	-21.79	200	76
3	H	278.0669	33.51	peak	-7.91	25.60	46.00	-20.40	100	48
4	H	706.6999	26.06	peak	1.51	27.57	46.00	-18.43	100	264
5	H	881.4067	30.42	peak	4.37	34.79	46.00	-11.21	100	33
6	H	958.7943	27.69	peak	5.24	32.93	46.00	-13.07	100	215

(Below 1GHz)



Test Data


Horizontal Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	V	30.7455	31.07	peak	-0.81	30.26	40.00	-9.74	100	135
2	V	49.1866	40.87	peak	-12.82	28.05	40.00	-11.95	100	223
3	V	67.9129	39.77	peak	-13.75	26.02	40.00	-13.98	100	294
4	V	94.0979	43.14	peak	-12.36	30.78	43.50	-12.72	100	261
5	V	194.4534	32.97	peak	-9.01	23.96	43.50	-19.54	100	147
6	V	854.0247	25.99	peak	3.88	29.87	46.00	-16.13	100	214

Camera 2: s5021

Test Mode: Transmitting Mode

(Below 1GHz)




Test Data

Vertical Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	H	30.0000	25.74	peak	-0.26	25.48	40.00	-14.52	100	137
2	H	47.8260	38.62	peak	-12.20	26.42	40.00	-13.58	100	99
3	H	68.8721	30.84	peak	-13.68	17.16	40.00	-22.84	100	162
4	H	99.1797	28.76	peak	-11.02	17.74	43.50	-25.76	100	41
5	H	580.7026	25.63	peak	-0.30	25.33	46.00	-20.67	100	205
6	H	893.8567	25.59	peak	4.58	30.17	46.00	-15.83	100	162

(Below 1GHz)



Test Data

Horizontal Polarity Plot @3m

No	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Height	Degree
1	V	30.0000	31.83	peak	-0.26	31.57	40.00	-8.43	100	248
2	V	48.3318	42.38	peak	-12.44	29.94	40.00	-10.06	100	41
3	V	67.9129	41.80	peak	-13.75	28.05	40.00	-11.95	100	39
4	V	95.4270	33.30	peak	-12.02	21.28	43.50	-22.22	100	286
5	V	152.6641	27.97	peak	-8.37	19.60	43.50	-23.90	100	119
6	V	896.9965	24.35	peak	4.64	28.99	46.00	-17.01	100	75

Camera1: s5019

Above 1GHz

Test Mode:	Transmitting Mode
-------------------	--------------------------

Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824	38.54	AV	V	33.8	6.86	32.69	46.51	54	-7.49
4824	38.21	AV	H	33.8	6.86	32.69	46.18	54	-7.82
4824	47.56	PK	V	33.8	6.86	32.69	55.53	74	-18.47
4824	47.33	PK	H	33.8	6.86	32.69	55.3	74	-18.7
17912	23.87	AV	V	45.12	11.57	32.11	48.45	54	-5.55
17912	23.46	AV	H	45.12	11.57	32.11	48.04	54	-5.96
17912	40.59	PK	V	45.12	11.57	32.11	65.17	74	-8.83
17912	40.14	PK	H	45.12	11.57	32.11	64.72	74	-9.28

Middle Channel (2437 MHz) (g mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874	39.01	AV	V	33.6	6.82	32.71	46.72	54	-7.28
4874	38.76	AV	H	33.6	6.82	32.71	46.47	54	-7.53
4874	47.85	PK	V	33.6	6.82	32.71	55.56	74	-18.44
4874	47.64	PK	H	33.6	6.82	32.71	55.35	74	-18.65
17904	23.96	AV	V	45.17	11.63	32.18	48.58	54	-5.42
17904	23.71	AV	H	45.17	11.63	32.18	48.33	54	-5.67
17904	40.87	PK	V	45.17	11.63	32.18	65.49	74	-8.51
17904	40.62	PK	H	45.17	11.63	32.18	65.24	74	-8.76

High Channel (2462 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4924	39.24	AV	V	33.83	6.95	32.79	47.23	54	-6.77
4924	38.92	AV	H	33.83	6.95	32.79	46.91	54	-7.09
4924	47.65	PK	V	33.83	6.95	32.79	55.64	74	-18.36
4924	47.51	PK	H	33.83	6.95	32.79	55.5	74	-18.5
17896	23.26	AV	V	45.19	11.61	32.24	47.82	54	-6.18
17896	22.96	AV	H	45.19	11.61	32.24	47.52	54	-6.48
17896	40.48	PK	V	45.19	11.61	32.24	65.04	74	-8.96
17896	40.23	PK	H	45.19	11.61	32.24	64.79	74	-9.21

Note:

1, The testing has been conformed to $10 \times 2462 \text{ MHz} = 24,620 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Camera 2: s5021

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4824	38.47	AV	V	33.8	6.86	32.69	46.44	54	-7.56
4824	38.06	AV	H	33.8	6.86	32.69	46.03	54	-7.97
4824	47.86	PK	V	33.8	6.86	32.69	55.83	74	-18.17
4824	47.53	PK	H	33.8	6.86	32.69	55.5	74	-18.5
17904	24.16	AV	V	45.12	11.57	32.11	48.74	54	-5.26
17904	23.84	AV	H	45.12	11.57	32.11	48.42	54	-5.58
17904	40.67	PK	V	45.12	11.57	32.11	65.25	74	-8.75
17904	40.23	PK	H	45.12	11.57	32.11	64.81	74	-9.19

Middle Channel (2437 MHz) (g mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4874	38.67	AV	V	33.6	6.82	32.71	46.38	54	-7.62
4874	38.45	AV	H	33.6	6.82	32.71	46.16	54	-7.84
4874	48.13	PK	V	33.6	6.82	32.71	55.84	74	-18.16
4874	47.85	PK	H	33.6	6.82	32.71	55.56	74	-18.44
17893	24.25	AV	V	45.17	11.63	32.18	48.87	54	-5.13
17893	24.13	AV	H	45.17	11.63	32.18	48.75	54	-5.25
17893	40.96	PK	V	45.17	11.63	32.18	65.58	74	-8.42
17893	40.73	PK	H	45.17	11.63	32.18	65.35	74	-8.65

High Channel (2462 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4924	39.05	AV	V	33.83	6.95	32.79	47.04	54	-6.96
4924	38.76	AV	H	33.83	6.95	32.79	46.75	54	-7.25
4924	48.24	PK	V	33.83	6.95	32.79	56.23	74	-17.77
4924	48.03	PK	H	33.83	6.95	32.79	56.02	74	-17.98
17885	24.51	AV	V	45.19	11.61	32.24	49.07	54	-4.93
17885	24.27	AV	H	45.19	11.61	32.24	48.83	54	-5.17
17885	40.82	PK	V	45.19	11.61	32.24	65.38	74	-8.62
17885	40.63	PK	H	45.19	11.61	32.24	65.19	74	-8.81

Note:

1, The testing has been conformed to $10 \times 2462 \text{ MHz} = 24,620 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>


Annex B. EUT and Test Setup Photographs

Annex B.i. Photograph: EUT External Photo





EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1




Cover Off - Top View 2



Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View



Mainboard without Shielding - Front View



Mainboard with Shielding – Rear View




Mainboard without Shielding - Rear View




LCD – Front View



LCD – Rear View




Camera 1 : s5019 – Front View




Camera 1 : s5019 – Rear View

Test Report No.	16071294-FCC-R3-V1-V1
Page	50 of 57



Camera 2: s5021 – Front View



Camera 2: s5021 – Rear View



GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/GPS- Antenna View


Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	QU050070USB01	SK052D13

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	SKS052D13

Test Report No.	16071294-FCC-R3-V1-V1
Page	56 of 57

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY



Declaration Letter

For our business issue and marketing requirements, we would like to list two models in the reports:s5019 and s5021.

We Verykool USA Inc, hereby declare that our products s5019 and s5021 using the same PCB and the only difference between them are as below:

Main Model No.	Serial Model No.	Difference
s5019	s5021	For s5019, the front camera is 2MP while the rear one is 5MP. For s5021, the front camera is 5MP while the rear one is 8MP.

Thank you!

Sincerely

Signature:

A handwritten signature in black ink, appearing to be "Sunny Choi".

Job Title: Sunny Choi/Manager