




RF TEST REPORT



Report No.: 16070803-FCC-R1

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Mobile Phone	
Model No.	s5007	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; FCC Part 27:2015; ANSI/TIA-603-D: 2010	
Test Date	July 08 to July 27, 2016	
Issue Date	July 29, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070803-FCC-R1
Page	3 of 102

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 RF EXPOSURE (SAR).....	10
6.2 RF OUTPUT POWER	11
6.3 PEAK-AVERAGE RATIO	23
6.4 OCCUPIED BANDWIDTH	28
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	43
6.6 SPURIOUS RADIATED EMISSIONS	59
6.7 BAND EDGE.....	66
6.8 FREQUENCY STABILITY	80
ANNEX A. TEST INSTRUMENT.....	91
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	93
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	98
ANNEX C.II. EUT OPERATING CONKITIONS	100
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	101
ANNEX E. DECLARATION OF SIMILARITY	102

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070803-FCC-R1	NONE	Original	July 29, 2016

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States
Manufacturer	Shenzhen Fortuneship Technology Co., Ltd
Manufacturer Add	6/F, Kanghesheng Building, No.1 Chuangsheng Road, Nanshan District, Shenzhen, Guangdong, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Mobile Phone

Main Model: s5007

Serial Model: N/A

Date EUT received: July 07, 2016

Test Date(s): July 08 to July 27, 2016

Equipment Category : PCE

Antenna Gain:

- GSM850: 0.68dBi
- PCS1900: 0.95dBi
- UMTS-FDD Band V: 0.92dBi
- UMTS-FDD Band IV: 0.95dBi
- UMTS-FDD Band II: 0.95dBi
- Bluetooth /WIFI:1.92dBi

Antenna Type: PIFA antenna

Type of Modulation:

- GSM / GPRS: GMSK
- EGPRS: GMSK
- UMTS-FDD: QPSK
- 802.11b/g/n: DSSS, OFDM
- Bluetooth: GFSK, π /4DQPSK, 8DPSK

RF Operating Frequency (ies):

- GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
- PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
- UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
- UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
- RX : 2112.4 ~ 2152.6 MHz
- UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
- RX: 1932.4 ~ 1987.6 MHz
- WIFI: 802.11b/g/n(20M): 2412-2462 MHz
- Bluetooth: 2402-2480 MHz

Number of Channels:	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band IV: 202CH
	UMTS-FDD Band II: 277CH
	WIFI :802.11b/g/n(20M): 11CH
	Bluetooth: 79CH
Port:	Earphone Port, USB Port
Input Power:	Adapter:
	Model: s5005
	Input: AC 100-240V,50/60Hz;0.2A
	Output: DC 5.0V,1A
	Battery:
	Model: s5005
	Spec: 3.7V,2000mAh(7.4Wh)
	Charge limited voltage: 4.2V
Maximum Conducted AV Power to Antenna:	GSM Vioce:GSM850: 32.29 dBm
	PCS1900: 29.77 dBm
	GPRS:GSM850: 32.22dBm
	PCS1900: 28.75 dBm
	MCS1:GSM850: 32.15 dBm
	PCS1900: 28.64 dBm
	RMC:UMTS-FDD Band V: 21.36 dBm
	UMTS-FDD Band II: 21.77 dBm
	UMTS-FDD Band IV: 21.00 dBm
	HSDPA:UMTS-FDD Band V: 21.79 dBm
	UMTS-FDD Band II: 21.85 dBm
	UMTS-FDD Band IV: 21.39 dBm
	HSUPA:UMTS-FDD Band V: 21.87 dBm
	UMTS-FDD Band II: 21.84 dBm
	UMTS-FDD Band IV: 21.63 dBm

Test Report	16070803-FCC-R1
Page	8 of 102

ERP/EIRP:

GSM Vioce:GSM850: 30.58 dBm / ERP
 PCS1900: 30.28 dBm / EIRP
 GPRS:GSM850: 30.26 dBm / ERP
 PCS1900: 29.96 dBm / EIRP
 MCS1:GSM850: 30.04 dBm / ERP
 PCS1900: 29.92 dBm / EIRP
 RMC:UMTS-FDD Band V: 19.75 dBm / ERP
 UMTS-FDD Band II: 22.54 dBm / ERP
 UMTS-FDD Band IV: 21.89 dBm / EIRP
 HSDPA:UMTS-FDD Band V: 19.69 dBm / ERP
 UMTS-FDD Band II: 22.42 dBm / ERP
 UMTS-FDD Band IV: 21.79 dBm / EIRP
 HSUPA:UMTS-FDD Band V: 19.61 dBm / ERP
 UMTS-FDD Band II: 22.26 dBm / ERP
 UMTS-FDD Band IV: 21.83 dBm / EIRP

Trade Name : verykool

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: WA6S5007

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 16070803-FCC-H.

6.2 RF Output Power

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>
§27.50 (c)	c)	EIRP: 30dBm	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---

Test Report	16070803-FCC-R1
Page	12 of 102

	<p>frequency was investigated.</p> <ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.29	32.19	32.14	32±1	29.77	29.56	29.66	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.22	32.14	32.08	32±1	28.73	28.74	28.75	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	30.3	30.24	30.15	30±1	26.3	26.37	26.56	26±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	26.51	26.44	26.34	26±1	22.75	22.74	22.75	22.7±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	32.15	32.11	31.98	32±1	28.56	28.53	28.64	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	30.22	30.12	30.08	30±1	26.28	26.30	26.46	26±1
EGPRS Multi-Slot Class 10 (4 uplink) GMSK MCS1	26.45	26.43	26.33	26±1	22.7	22.73	22.85	22±1

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	21.20	21±1
	4175	835	21.36	21±1
	4233	846.6	21.25	21±1
HSDPA Subtest1	4132	826.4	21.29	21.5±1
	4175	835	21.78	21.5±1
	4233	846.6	21.69	21.5±1
HSDPA Subtest2	4132	826.4	21.52	21.5±1
	4175	835	21.59	21.5±1
	4233	846.6	21.54	21.5±1
HSDPA Subtest3	4132	826.4	21.79	21.5±1
	4175	835	21.27	21.5±1
	4233	846.6	21.16	21.5±1
HSDPA Subtest4	4132	826.4	21.06	21.5±1
	4175	835	21.3	21.5±1
	4233	846.6	21.09	21.5±1
HSUPA Subtest1	4132	826.4	21.16	21.5±1
	4175	835	21.87	21.5±1
	4233	846.6	21.56	21.5±1
HSUPA Subtest2	4132	826.4	21.25	21.5±1
	4175	835	21.28	21.5±1
	4233	846.6	21.27	21.5±1
HSUPA Subtest3	4132	826.4	21.36	21.5±1
	4175	835	21.39	21.5±1
	4233	846.6	21.34	21.5±1
HSUPA Subtest4	4132	826.4	21.65	21.5±1
	4175	835	21.64	21.5±1
	4233	846.6	21.68	21.5±1
HSUPA Subtest5	4132	826.4	21.55	21.5±1
	4175	835	21.51	21.5±1
	4233	846.6	21.5	21.5±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	20.65	21±1
	9400	1880	21.77	21±1
	9538	1907.6	21.39	21±1
HSDPA Subtest1	9262	1852.4	21.53	21.5±1
	9400	1880	21.61	21.5±1
	9538	1907.6	21.65	21.5±1
HSDPA Subtest2	9262	1852.4	21.85	21.5±1
	9400	1880	21.78	21.5±1
	9538	1907.6	21.4	21.5±1
HSDPA Subtest3	9262	1852.4	21.56	21.5±1
	9400	1880	21.85	21.5±1
	9538	1907.6	21.56	21.5±1
HSDPA Subtest4	9262	1852.4	21.1	21.5±1
	9400	1880	21.62	21.5±1
	9538	1907.6	21.29	21.5±1
HSUPA Subtest1	9262	1852.4	21.33	21.5±1
	9400	1880	21.54	21.5±1
	9538	1907.6	21.56	21.5±1
HSUPA Subtest2	9262	1852.4	21.06	21.5±1
	9400	1880	21.55	21.5±1
	9538	1907.6	21.52	21.5±1
HSUPA Subtest3	9262	1852.4	21.29	21.5±1
	9400	1880	21.63	21.5±1
	9538	1907.6	21.24	21.5±1
HSUPA Subtest4	9262	1852.4	21.3	21.5±1
	9400	1880	21.62	21.5±1
	9538	1907.6	21.25	21.5±1
HSUPA Subtest5	9262	1852.4	21.05	21.5±1
	9400	1880	21.64	21.5±1
	9538	1907.6	21.84	21.5±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	20.86	21±1
	4175	835	21.00	21±1
	4233	846.6	20.80	21±1
HSDPA Subtest1	4132	826.4	21.35	21.3±1
	4175	835	21.39	21.3±1
	4233	846.6	21.36	21.3±1
HSDPA Subtest2	4132	826.4	21.06	21.3±1
	4175	835	21.05	21.3±1
	4233	846.6	21.39	21.3±1
HSDPA Subtest3	4132	826.4	21.26	21.3±1
	4175	835	21.28	21.3±1
	4233	846.6	21.29	21.3±1
HSDPA Subtest4	4132	826.4	21.17	21.3±1
	4175	835	21.09	21.3±1
	4233	846.6	21.18	21.3±1
HSUPA Subtest1	4132	826.4	21.26	21.3±1
	4175	835	21.35	21.3±1
	4233	846.6	21.29	21.3±1
HSUPA Subtest2	4132	826.4	21.42	21.3±1
	4175	835	21.53	21.3±1
	4233	846.6	21.35	21.3±1
HSUPA Subtest3	4132	826.4	21.52	21.3±1
	4175	835	21.58	21.3±1
	4233	846.6	21.25	21.3±1
HSUPA Subtest4	4132	826.4	21.16	21.3±1
	4175	835	21.18	21.3±1
	4233	846.6	21.35	21.3±1
HSUPA Subtest5	4132	826.4	21.43	21.3±1
	4175	835	21.63	21.3±1
	4233	846.6	21.59	21.3±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.18	V	6.8	0.53	30.45	38.45
824.2	23.33	H	6.8	0.53	29.60	38.45
836.6	24.25	V	6.8	0.53	30.52	38.45
836.6	23.39	H	6.8	0.53	29.66	38.45
848.8	24.21	V	6.9	0.53	30.58	38.45
848.8	23.35	H	6.9	0.53	29.72	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.18	V	7.88	0.85	30.21	33
1850.2	22.31	H	7.88	0.85	29.34	33
1880	23.25	V	7.88	0.85	30.28	33
1880	22.39	H	7.88	0.85	29.42	33
1909.8	23.11	V	7.86	0.85	30.12	33
1909.8	22.27	H	7.86	0.85	29.28	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	23.85	V	6.8	0.53	30.12	38.45
824.2	23.11	H	6.8	0.53	29.38	38.45
836.6	23.94	V	6.8	0.53	30.21	38.45
836.6	23.18	H	6.8	0.53	29.45	38.45
848.8	23.89	V	6.9	0.53	30.26	38.45
848.8	23.22	H	6.9	0.53	29.59	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.86	V	7.88	0.85	29.89	33
1850.2	22.15	H	7.88	0.85	29.18	33
1880	22.93	V	7.88	0.85	29.96	33
1880	22.18	H	7.88	0.85	29.21	33
1909.8	22.94	V	7.86	0.85	29.95	33
1909.8	22.25	H	7.86	0.85	29.26	33

EGPRS (MCS1):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	23.77	V	6.8	0.53	30.04	38.45
824.2	23.14	H	6.8	0.53	29.41	38.45
836.6	23.85	V	6.8	0.53	30.12	38.45
836.6	23.09	H	6.8	0.53	29.36	38.45
848.8	23.81	V	6.9	0.53	30.18	38.45
848.8	23.15	H	6.9	0.53	29.52	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	22.83	V	7.88	0.85	29.86	33
1850.2	22.08	H	7.88	0.85	29.11	33
1880	22.87	V	7.88	0.85	29.90	33
1880	22.11	H	7.88	0.85	29.14	33
1909.8	22.91	V	7.86	0.85	29.92	33
1909.8	22.16	H	7.86	0.85	29.17	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.41	V	6.8	0.53	19.68	38.45
826.4	12.69	H	6.8	0.53	18.96	38.45
835	13.35	V	6.8	0.53	19.62	38.45
835	12.62	H	6.8	0.53	18.89	38.45
846.6	13.38	V	6.9	0.53	19.75	38.45
846.6	12.66	H	6.9	0.53	19.03	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.48	V	7.88	0.85	21.51	33
1852.4	13.72	H	7.88	0.85	20.75	33
1880	15.51	V	7.88	0.85	22.54	33
1880	14.38	H	7.88	0.85	21.41	33
1907.6	15.46	V	7.86	0.85	22.47	33
1907.6	14.57	H	7.86	0.85	21.58	33

EIRP for UMTS-FDD Band IV (Part 27E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	14.89	V	7.76	0.82	21.83	30
1712.4	14.12	H	7.76	0.82	21.06	30
1740	14.95	V	7.76	0.82	21.89	30
1740	14.18	H	7.76	0.82	21.12	30
1752.6	14.84	V	7.74	0.82	21.76	30
1752.6	14.03	H	7.74	0.82	20.95	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.35	V	6.8	0.53	19.62	38.45
826.4	12.61	H	6.8	0.53	18.88	38.45
835	13.28	V	6.8	0.53	19.55	38.45
835	12.54	H	6.8	0.53	18.81	38.45
846.6	13.32	V	6.9	0.53	19.69	38.45
846.6	12.59	H	6.9	0.53	18.96	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.43	V	7.88	0.85	21.46	33
1852.4	13.68	H	7.88	0.85	20.71	33
1880	15.39	V	7.88	0.85	22.42	33
1880	14.71	H	7.88	0.85	21.74	33
1907.6	15.28	V	7.86	0.85	22.29	33
1907.6	14.45	H	7.86	0.85	21.46	33

EIRP for UMTS-FDD Band IV (Part 27E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	14.85	V	7.76	0.82	21.79	30
1712.4	14.06	H	7.76	0.82	21.00	30
1740	14.91	V	7.76	0.82	21.85	30
1740	14.12	H	7.76	0.82	21.06	30
1752.6	14.79	V	7.74	0.82	21.71	30
1752.6	14.05	H	7.74	0.82	20.97	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.29	V	6.8	0.53	19.56	38.45
826.4	12.56	H	6.8	0.53	18.83	38.45
835	13.22	V	6.8	0.53	19.49	38.45
835	12.47	H	6.8	0.53	18.74	38.45
846.6	13.24	V	6.9	0.53	19.61	38.45
846.6	12.51	H	6.9	0.53	18.88	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	14.38	V	7.88	0.85	21.41	33
1852.4	13.62	H	7.88	0.85	20.65	33
1880	15.23	V	7.88	0.85	22.26	33
1880	14.67	H	7.88	0.85	21.70	33
1907.6	15.14	V	7.86	0.85	22.15	33
1907.6	14.38	H	7.86	0.85	21.39	33

EIRP for UMTS-FDD Band IV (Part 27E)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	14.86	V	7.76	0.82	21.80	30
1712.4	14.13	H	7.76	0.82	21.07	30
1740	14.89	V	7.76	0.82	21.83	30
1740	14.15	H	7.76	0.82	21.09	30
1752.6	14.83	V	7.74	0.82	21.75	30
1752.6	14.16	H	7.74	0.82	21.08	30

6.3 Peak-Average Ratio

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13dB.	<input checked="" type="checkbox"/>

Test Setup	
------------	---

Test Procedure	<p>According with KDB 971168 v02r02</p> <p>5.7.2 Alternate procedure for PAPR</p> <p>5.1.2 Peak power measurements with a peak power meter</p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p>5.2.3 Average power measurement with average power meter</p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output</p>
----------------	---

Test Report	16070803-FCC-R1
Page	24 of 102

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.47	29.77	0.7
1880	30.62	29.56	1.06
1909.8	30.54	29.66	0.88

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.09	28.73	1.36
1880	30.26	28.74	1.52
1909.8	30.63	28.75	1.88

RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	21.59	21.13	0.46
1880	22.54	21.89	0.65
1907.6	21.96	21.39	0.57

UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	22.38	20.86	1.52
1732.6	22.46	21	1.46
1752.4	22.57	20.8	1.77

HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	22.67	21.73	0.94
1880	22.24	21.35	0.89
1907.6	22.23	21.44	0.79

UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	22.58	21.26	1.32
1732.6	22.94	21.35	1.59
1752.4	22.73	21.29	1.44

HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	22.64	21.53	1.11
1880	22.83	21.61	1.22
1907.6	22.95	21.78	1.17


UMTS-FDD Band 4 PK-AV POWER (PART 27)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.6	22.65	21.35	1.3
1732.6	22.65	21.39	1.26
1752.4	22.55	21.36	1.19

6.4 Occupied Bandwidth

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	244.3640	318.772
190	836.6	247.7876	322.048
251	848.8	246.6234	317.763

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.7001	318.965
661	1880.0	246.8456	315.201
810	1909.8	244.2487	318.258

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.2013	319.635
190	836.6	248.0870	322.109
251	848.8	246.0571	323.994

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	250.3008	322.937
661	1880.0	246.2737	318.189
810	1909.8	245.9169	319.224

EGPRS (MCS 1):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	245.2939	319.799
190	836.6	243.9207	318.571
251	848.8	248.0691	317.001

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	251.1781	326.188
661	1880.0	249.4570	325.000
810	1909.8	246.6173	323.240

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1052	4.694
4175	835.0	4.1006	4.702
4233	846.6	4.0919	4.694

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.1163	4.700
1413	1732.6	4.0847	4.676
1512	1752.4	4.1027	4.720

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1061	4.712
9400	1880.0	4.0956	4.690
9538	1907.6	4.1044	4.686

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1018	4.698
4175	835.0	4.1105	4.721
4233	846.6	4.0945	4.684

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.1011	4.684
1413	1732.6	4.1068	4.693
1512	1752.4	4.1068	4.695

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1065	4.717
9400	1880.0	4.0998	4.696
9538	1907.6	4.1023	4.699

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.1057	4.686
4175	835.0	4.1205	4.704
4233	846.6	4.0945	4.717

UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.0951	4.695
1413	1732.6	4.0948	4.689
1512	1752.4	4.1133	4.721

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1167	4.712
9400	1880.0	4.0848	4.676
9538	1907.6	4.1020	4.706

Test Plots


GMS Voice:




GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz




PCS 1900 BW - High CH 1909.8MHz


EGPRS (MCS 1):




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz





PCS 1900 BW - Mid CH 1880MHz





PCS 1900 BW - High CH 1909.8MHz



RMC:



Band V BW - Low CH 826.6 MHz



Band V BW - High CH 846.4 MHz




Band IV BW - Mid CH 1732.6 MHz

Band IV BW - High CH 1752.4 MHz

Agilent 13:30:34 Jul 21, 2016

R T



Center 1.853 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz


Occupied Bandwidth
4.1061 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -7.682 kHz
x dB Bandwidth 4.712 MHz

Agilent 13:29:50 Jul 21, 2016

R T



Center 1.88 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz

Occupied Bandwidth
4.0956 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error 748.520 Hz
x dB Bandwidth 4.690 MHz

Band II BW - Low CH 1852.4MHz

Band II BW - Mid CH 1880MHz

Agilent 13:28:55 Jul 21, 2016

R T



Center 1.907 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz


Occupied Bandwidth
4.1044 MHz

Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -6.335 kHz
x dB Bandwidth 4.686 MHz


Band II BW - High CH 1907.6MHz

HSDPA:



Agilent 13:35:39 Jul 21, 2016

R T




Center 1.853 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz
Occupied Bandwidth
4.1065 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -8.637 kHz
x dB Bandwidth 4.717 MHz

Agilent 13:34:43 Jul 21, 2016

R T



Center 1.88 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz
Occupied Bandwidth
4.0998 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error 4.014 kHz
x dB Bandwidth 4.696 MHz

Band II BW - Low CH 1852.4MHz

Band II BW - Mid CH 1880MHz

Agilent 13:33:41 Jul 21, 2016

R T





Center 1.907 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz
Occupied Bandwidth
4.1023 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -3.433 kHz
x dB Bandwidth 4.699 MHz

Band II BW - High CH 1907.6MHz


HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.4 MHz



Band IV BW - Low CH 1712.6MHz




Band IV BW - Mid CH 1732.6MHz

Band IV BW - High CH 1752.4MHz

Agilent 13:31:24 Jul 21, 2016

R T




Center 1.853 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz
Occupied Bandwidth
4.1167 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -6.171 kHz
x dB Bandwidth 4.712 MHz

Band II BW - Low CH 1852.4MHz

Agilent 13:31:49 Jul 21, 2016

R T




Center 1.88 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz
Occupied Bandwidth
4.0848 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB

Transmit Freq Error -8.448 kHz
x dB Bandwidth 4.676 MHz

Band II BW - Mid CH 1880MHz

Agilent 13:32:58 Jul 21, 2016

R T



Center 1.907 GHz
#Res BW 100 kHz
#VBW 300 kHz
#Sweep 10 ms (401 pts)
Span 10 MHz
Occupied Bandwidth
4.1020 MHz
Occ BW % Pwr 99.00 %
x dB -26.00 dB


Transmit Freq Error -8.169 kHz
x dB Bandwidth 4.706 MHz

Band II BW - High CH 1907.6MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2




PCS1900 - High Channel-1




PCS 1900 - High Channel-2

GPRS:

Cellular Band (Part 22H) result




PCS Band (Part24E) result




EGPRS (MCS 1):


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2

PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)




Band V - Low Channel-1




Band V - Low Channel-2




Band V - Middle Channel-1



Band V - Middle Channel-2




Band V - High Channel-1




Band V - High Channel-2


UMTS-FDD Band IV (Part 27)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSDPA:


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band IV (Part 27)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

HSUPA:


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band IV (Part 27)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2



Band II - High Channel-1




Band II - High Channel-2

6.6 Spurious Radiated Emissions

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	
------------	--

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	16070803-FCC-R1
Page	60 of 102

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-42.59	V	7.95	0.78	-35.42	-13	-22.42
1648.4	-43.25	H	7.95	0.78	-36.08	-13	-23.08
315.6	-51.71	V	6.4	0.26	-45.57	-13	-32.57
580.9	-52.38	H	6.8	0.37	-45.95	-13	-32.95

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-42.63	V	7.95	0.78	-35.46	-13	-22.46
1673.2	-43.18	H	7.95	0.78	-36.01	-13	-23.01
315.7	-51.62	V	6.4	0.26	-45.48	-13	-32.48
580.4	-52.44	H	6.8	0.37	-46.01	-13	-33.01

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-42.58	V	7.95	0.78	-35.41	-13	-22.41
1697.6	-43.21	H	7.95	0.78	-36.04	-13	-23.04
315.3	-51.47	V	6.4	0.26	-45.33	-13	-32.33
580.7	-52.34	H	6.8	0.37	-45.91	-13	-32.91

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-46.31	V	10.25	2.73	-38.79	-13	-25.79
3700.4	-45.85	H	10.25	2.73	-38.33	-13	-25.33
314.8	-52.19	V	6.4	0.26	-46.05	-13	-33.05
580.2	-52.64	H	6.8	0.37	-46.21	-13	-33.21

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-46.28	V	10.25	2.73	-38.76	-13	-25.76
3760	-45.73	H	10.25	2.73	-38.21	-13	-25.21
314.5	-52.24	V	6.4	0.26	-46.1	-13	-33.1
580.9	-52.79	H	6.8	0.37	-46.36	-13	-33.36

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-46.31	V	10.36	2.73	-38.68	-13	-25.68
3819.6	-45.98	H	10.36	2.73	-38.35	-13	-25.35
314.6	-52.45	V	6.4	0.26	-46.31	-13	-33.31
580.1	-52.89	H	6.8	0.37	-46.46	-13	-33.46

Note:

1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-47.51	V	7.95	0.78	-40.34	-13	-27.34
1652.8	-47.28	H	7.95	0.78	-40.11	-13	-27.11
315.3	-52.34	V	6.4	0.26	-46.2	-13	-33.2
581.7	-52.69	H	6.8	0.37	-46.26	-13	-33.26

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-47.48	V	7.95	0.78	-40.31	-13	-27.31
1670	-47.35	H	7.95	0.78	-40.18	-13	-27.18
315.8	-52.61	V	6.4	0.26	-46.47	-13	-33.47
581.2	-52.88	H	6.8	0.37	-46.45	-13	-33.45

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-47.59	V	7.95	0.78	-40.42	-13	-27.42
1693.2	-47.14	H	7.95	0.78	-39.97	-13	-26.97
315.6	-52.48	V	6.4	0.26	-46.34	-13	-33.34
581.7	-52.61	H	6.8	0.37	-46.18	-13	-33.18

Note:

- 1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.51	V	10.25	2.73	-40.99	-13	-27.99
3704.8	-47.64	H	10.25	2.73	-40.12	-13	-27.12
316.3	-52.48	V	6.4	0.26	-46.34	-13	-33.34
579.9	-53.11	H	6.8	0.37	-46.68	-13	-33.68

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.49	V	10.25	2.73	-40.97	-13	-27.97
3760	-47.55	H	10.25	2.73	-40.03	-13	-27.03
316.5	-52.61	V	6.4	0.26	-46.47	-13	-33.47
579.2	-53.23	H	6.8	0.37	-46.8	-13	-33.8

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.56	V	10.36	2.73	-40.93	-13	-27.93
3815.2	-47.81	H	10.36	2.73	-40.18	-13	-27.18
316.8	-52.89	V	6.4	0.26	-46.75	-13	-33.75
579.3	-53.12	H	6.8	0.37	-46.69	-13	-33.69

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

UMTS-FDD Band IV (Part 27E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-46.68	V	10.07	2.52	-39.13	-13	-26.13
3424.8	-47.51	H	10.07	2.52	-39.96	-13	-26.96
351.3	-52.26	V	6.4	0.26	-46.12	-13	-33.12
718.5	-52.52	H	7.1	0.42	-45.84	-13	-32.84

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-46.85	V	10.09	2.52	-39.28	-13	-26.28
3480	-47.39	H	10.09	2.52	-39.82	-13	-26.82
351.6	-52.51	V	6.4	0.26	-46.37	-13	-33.37
718.2	-52.48	H	7.1	0.42	-45.8	-13	-32.8

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-46.77	V	10.09	2.52	-39.2	-13	-26.2
3505.2	-47.43	H	10.09	2.52	-39.86	-13	-26.86
351.9	-52.38	V	6.4	0.26	-46.24	-13	-33.24
718.5	-52.61	H	7.1	0.42	-45.93	-13	-32.93

Note:

1, The testing has been conformed to $10 \times 1712.4 \text{ MHz} = 17,124 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

6.7 Band Edge

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup			
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.76	-13
849.0175	-15.15	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-16.05	-13
1910.0200	-15.74	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-14.69	-13
849.0250	-17.13	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-14.80	-13
1910.0200	-14.82	-13

EGPRS (MCS1):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.29	-13
849.0200	-17.67	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9800	-21.14	-13
1910.0200	-18.62	-13

RMC:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.675	-20.65	-13
849.225	-22.11	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-21.99	-13
1755.300	-22.13	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.675	-24.21	-13
1910.050	-25.91	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-18.06	-13
849.025	-21.02	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-21.69	-13
1755.025	-18.60	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.950	-22.24	-13
1910.075	-15.11	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-20.22	-13
849.225	-20.57	-13

UMTS-FDD Band IV (Part 27)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-22.06	-13
1755.025	-19.07	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.775	-22.86	-13
1910.150	-17.63	-13


GSM Voice:

Test Plots




Cellular Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.19/3)=4.0+0.3=4.3dB




Cellular Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.18/3)=4.0+0.3=4.3dB



PCS Band - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(3.19/3)=4.5+0.3=4.8dB




PCS Band - High Channel

Note: Offset=Cable loss (4.0) + 10log
(3.18/3)=4.5+0.3=4.8dB


GPRS:

Test Plots




EGPRS (MCS 1):

Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(46.94/30)=4.0+1.9=5.9dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(46.94/30)=4.0+1.9=5.9dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(46.98/30)=4.0+1.9=5.9dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(46.84/30)=4.0+2.0=6.0dB

Test Report	16070803-FCC-R1
Page	75 of 102



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(46.86/30)4.5+2.0=6.5dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.17/30)=4.5+1.9=6.4dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.00/30)=4.0+1.9=5.9dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(47.20/30)=4.0+1.9=5.9dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(46.84/30)=4.0+1.9=5.9dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(46.95/30)=4.0+1.9=5.9dB

Test Report	16070803-FCC-R1
Page	77 of 102



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(46.95/30)=4.5+2.0=6.5dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(47.21/30)=4.5+1.9=6.4dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(47.12/30)=4.0+1.9=5.9dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(46.86/30)=4.0+2.0=6.0dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(47.17/30)=4.0+1.9=5.9dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(46.99/30)=4.0+2.0=6.0dB

Test Report	16070803-FCC-R1
Page	79 of 102



UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(47.12/30)=4.5+2.0=6.5dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(47.06/30)=4.5+2.0=6.5dB

6.8 Frequency Stability

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	July 21, 2016
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup																																			

Test Report	16070803-FCC-R1
Page	81 of 102

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0239	2.5
0		18	0.0215	2.5
10		16	0.0191	2.5
20		16	0.0191	2.5
30		13	0.0155	2.5
40		19	0.0227	2.5
50		18	0.0215	2.5
55		21	0.0251	2.5
25	4.2	20	0.0239	2.5
	3.5	20	0.0239	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	10	0.0053	2.5
0		13	0.0069	2.5
10		12	0.0064	2.5
20		11	0.0059	2.5
30		15	0.0080	2.5
40		16	0.0085	2.5
50		14	0.0074	2.5
55		16	0.0085	2.5
25	4.2	16	0.0085	2.5
	3.5	20	0.0106	2.5

GPRS:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		16	0.0191	2.5
10		14	0.0167	2.5
20		13	0.0155	2.5
30		12	0.0143	2.5
40		15	0.0179	2.5
50		16	0.0191	2.5
55		20	0.0239	2.5
25	4.2	20	0.0239	2.5
	3.5	19	0.0227	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		17	0.0090	2.5
10		14	0.0074	2.5
20		13	0.0069	2.5
30		12	0.0064	2.5
40		17	0.0090	2.5
50		15	0.0080	2.5
55		16	0.0085	2.5
25	4.2	21	0.0112	2.5
	3.5	20	0.0106	2.5

EGPRS (MCS1):

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		15	0.0179	2.5
10		17	0.0203	2.5
20		11	0.0131	2.5
30		15	0.0179	2.5
40		17	0.0203	2.5
50		21	0.0251	2.5
55		20	0.0239	2.5
25	4.2	19	0.0227	2.5
	3.5	15	0.0179	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0112	2.5
0		18	0.0096	2.5
10		17	0.0090	2.5
20		11	0.0059	2.5
30		17	0.0090	2.5
40		15	0.0080	2.5
50		14	0.0074	2.5
55		21	0.0112	2.5
25	4.2	20	0.0106	2.5
	3.5	14	0.0074	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	17	0.0204	2.5
0		15	0.0180	2.5
10		12	0.0144	2.5
20		15	0.0180	2.5
30		13	0.0156	2.5
40		10	0.0120	2.5
50		15	0.0180	2.5
55		16	0.0192	2.5
25	4.2	11	0.0132	2.5
	3.5	19	0.0228	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		11	0.0059	2.5
10		12	0.0064	2.5
20		10	0.0053	2.5
30		13	0.0069	2.5
40		16	0.0085	2.5
50		12	0.0064	2.5
55		14	0.0074	2.5
25	4.2	15	0.0080	2.5
	3.5	17	0.0090	2.5

UMTS-FDD Band IV (Part 27E)

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	15	0.0180	2.5
0		14	0.0168	2.5
10		15	0.0180	2.5
20		17	0.0204	2.5
30		14	0.0168	2.5
40		11	0.0132	2.5
50		14	0.0168	2.5
55		15	0.0180	2.5
25	4.2	11	0.0132	2.5
	3.5	17	0.0204	2.5

HSUPA:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	17	0.0204	2.5
0		15	0.0180	2.5
10		14	0.0168	2.5
20		16	0.0192	2.5
30		15	0.0180	2.5
40		11	0.0132	2.5
50		19	0.0228	2.5
55		18	0.0216	2.5
25	4.2	21	0.0251	2.5
	3.5	22	0.0263	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	17	0.0090	2.5
0		14	0.0074	2.5
10		13	0.0069	2.5
20		11	0.0059	2.5
30		15	0.0080	2.5
40		14	0.0074	2.5
50		15	0.0080	2.5
55		18	0.0096	2.5
25	4.2	15	0.0080	2.5
	3.5	20	0.0106	2.5

UMTS-FDD Band IV (Part 27E)

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	16	0.0192	2.5
0		17	0.0204	2.5
10		11	0.0132	2.5
20		12	0.0144	2.5
30		11	0.0132	2.5
40		12	0.0144	2.5
50		15	0.0180	2.5
55		14	0.0168	2.5
25	4.2	20	0.0240	2.5
	3.5	19	0.0228	2.5

HSDPA:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0240	2.5
0		17	0.0204	2.5
10		16	0.0192	2.5
20		11	0.0132	2.5
30		15	0.0180	2.5
40		16	0.0192	2.5
50		14	0.0168	2.5
55		21	0.0251	2.5
25	4.2	20	0.0240	2.5
	3.5	20	0.0240	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0112	2.5
0		18	0.0096	2.5
10		12	0.0064	2.5
20		10	0.0053	2.5
30		10	0.0053	2.5
40		15	0.0080	2.5
50		16	0.0085	2.5
55		17	0.0090	2.5
25	4.2	14	0.0074	2.5
	3.5	15	0.0080	2.5

UMTS-FDD Band IV (Part 27E)

Middle Channel, $f_0 = 1732.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0251	2.5
0		16	0.0192	2.5
10		16	0.0192	2.5
20		13	0.0156	2.5
30		14	0.0168	2.5
40		15	0.0180	2.5
50		15	0.0180	2.5
55		20	0.0240	2.5
25	4.2	21	0.0251	2.5
	3.5	18	0.0216	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/16/2015	09/15/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>

Test Report	16070803-FCC-R1
Page	92 of 102


Tunable Notch Filter	3NF- 1000/2000-S	AM 4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs


Annex B.i. Photograph: EUT External Photo




Test Report	16070803-FCC-R1
Page	94 of 102




EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View



Mainboard with Shielding - Front View




Mainboard without Shielding - Front View



Mainboard - Rear View




LCD – Front View



LCD – Rear View




GSM/PCS/UMTS-FDD - Antenna View




WIFI/BT/ - Antenna View

Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	S5005	s-5

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	s-5

Test Report	16070803-FCC-R1
Page	100 of 102

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	16070803-FCC-R1
Page	101 of 102

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Test Report	16070803-FCC-R1
Page	102 of 102

Annex E. DECLARATION OF SIMILARITY

N/A