# FCC Part 22H & 24E Measurement and Test Report

# For

# VeryKool USA Inc

3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA

FCC ID: WA6R623

FCC Rules: FCC Part 22H, FCC Part 24E

Product Description: GSM/GPRS Dual-band Mobile Phone

Tested Model: R623

**Report No.:** <u>STR12098307I-1</u>

**Tested Date:** <u>2012-10-09 to 2012-10-25</u>

**Issued Date:** <u>2012-10-25</u>

**Tested By:** Seven Song / Engineer

Reviewed By: Lahm Peng / EMC Manager

Approved & Authorized By: <u>Jandy so / PSQ Manager</u>

**Prepared By:** 

SEM.Test Compliance Service Co., Ltd

3/F, Jinbao Commerce Building, Xin'an Fanshen Road,

Seven Song

Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd

# TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 TEST STANDARDS	
1.3 TEST METHODOLOGY	
1.4 Test Facility	
1.5 EUT SETUP AND TEST MODE	
2. SUMMARY OF TEST RESULTS	6
3. RF EXPOSURE	7
3.1 STANDARD APPLICABLE	7
3.2 Test Result	7
4. RF OUTPUT POWER	8
4.1 Standard Applicable	8
4.2 TEST EQUIPMENT LIST AND DETAILS	
4.3 Test Procedure	
4.4 Environmental Conditions	
4.5 SUMMARY OF TEST RESULTS/PLOTS	
5. EMISSION BANDWIDTH	12
5.1 STANDARD APPLICABLE	
5.2 TEST EQUIPMENT LIST AND DETAILS	12
5.3 TEST PROCEDURE	
5.4 Environmental Conditions	
5.5 SUMMARY OF TEST RESULTS/PLOTS	
6. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL	
6.1 STANDARD APPLICABLE	
6.2 TEST EQUIPMENT LIST AND DETAILS	
6.3 Test Procedure	
6.4 Environmental Conditions	
7. SPURIOUS RADIATED EMISSIONS	
7.1 MEASUREMENT UNCERTAINTY	
7.2 STANDARD APPLICABLE	
7.4 TEST PROCEDURE	
7.5 ENVIRONMENTAL CONDITIONS	
7.6 SUMMARY OF TEST RESULTS/PLOTS	
8. FREQUENCY STABILITY	64
8.1 Standard Applicable	
8.2 TEST EQUIPMENT LIST AND DETAILS	
8.3 TEST PROCEDURE	64
8.4 Environmental Conditions	
8 5 SUMMARY OF TEST RESULTS/PLOTS	65

### 1. GENERAL INFORMATION

# 1.1 Product Description for Equipment Under Test (EUT)

#### **Client Information**

Applicant: VeryKool USA Inc

Address of applicant: 3636 Nobel Drive, Suite 325, San Diego, CA 92122

USA

Manufacturer: Verykool Wireless Technology Ltd.

Address of manufacturer: Room 1701, Reward Building C, No.203, 2<sup>nd</sup> Section

of WangJing, Li Ze Zhong Yuan, ChaoYang District,

Beijing, P.R. of China 100102

General Description of EUT				
Product Name:	GSM/GPRS Dual-band Mobile Phone			
Trade Name:	verykool			
Model No.:	R623			
Rated Voltage:	DC 3.7V Li-ion Battery			
Davier Adapter Madel	CYSK05-050050			
Power Adapter Model:	(Input: AC 100-240V, Output: DC 5V)			
Note: The test data is gathered from a p	roduction sample, provided by the manufacturer.			

Technical Characteristics of EUT	
Cellular Network Protocol:	GSM/GPRS
Hardware Version:	R263_VK_HW_1.00
Software Version:	R263_VK_SW_0.28
Frequency Range:	GSM/GPRS 850: 824~849MHz
	GSM/GPRS 1900: 1850~1910MHz
Max. RF Power(Conducted):	GSM850: 32.52 dBm; PCS1900: 29.96 dBm
Max. RF Power(ERP/EIRP):	GSM850: 30.49 dBm; PCS1900: 28.74 dBm
Type of Modulation:	GMSK
Type of Emission:	GSM(GSM850): 254KGXW
	GPRS(GSM850): 254KG7W
	GSM(PCS1900): 256KGXW
	GPRS(PCS1900): 255KG7W
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM 850: 0 dBi GSM1900: 1 dBi
GPRS Class:	Class 12
Device Category:	Portable Device

#### 1.2 Test Standards

The following report is prepared on behalf of the VeryKool USA Inc in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

*Maintenance of compliance* is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

#### 1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603-C: 2004 and ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

#### 1.4 Test Facility

#### • FCC – Registration No.: 994117

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

#### • Industry Canada (IC) Registration No.: 7673A

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

#### • CNAS Registration No.: L4062

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

REPORT NO.: STR12098307I-1 PAGE 4 OF 67 FCC PART 22H&24E

# 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List						
Test Mode	Description	Remark				
TM1	GSM 850	Low, Middle, High Channels				
TM2	GPRS 850	Low, Middle, High Channels				
TM3	GSM 1900	Low, Middle, High Channels				
TM4	GPRS 1900	Low, Middle, High Channels				

<b>Testing Configure</b>			
Support Band	Support Standard	Channel Frequency	Channel Number
		824.2 MHz	128
GSM 850	GSM/GPRS	836.6 MHz	190
		848.8 MHz	251
		1850.2 MHz	512
PCS 1900	GSM/GPRS	1880.0 MHz	661
		1909.8 MHz	810

Note: the transmitter has been tested on the communications mode of GSM and GPRS, compliance test and record the worst case.

Special Cable List and Details							
Cable Description Length (m) Shielded/Unshielded With / Without Ferrite							
USB Cable	1.0	Shielded	Without Ferrite				

Auxiliary Equipment List and Details							
Description Manufacturer Model Serial Number							
/	/	/	/				

REPORT NO.: STR12098307I-1 PAGE 5 OF 67 FCC PART 22H&24E

# 2. SUMMARY OF TEST RESULTS

FCC Rules	FCC Rules Description of Test Item	
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

# 3. RF Exposure

# 3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### 3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

# 4. RF Output Power

# 4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232 (c), no any case may the peak output power of mobile or portable station transmitter exceed 2 Watt EIRP.

### 4.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2012-03-28	2013-03-27
Pre-amplifier	Agilent	8447F	3113A06717	2012-03-28	2013-03-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2012-03-28	2013-03-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2012-02-25	2013-02-24
Horn Antenna	ETS	3117	00086197	2012-02-25	2013-02-24
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2012-03-28	2013-03-27
Signal Generator	R&S	SMR20	100047	2012-03-28	2013-03-27

#### **4.3 Test Procedure**

Conducted output power test method:



Radiated power test method:

- $1. The\ setup\ of\ EUT\ is\ according\ with\ per\ TIA/EIA\ Standard\ 603C\ and\ ANSI\ C63.4-2003\ measurement\ procedure.$
- 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
- 4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

REPORT NO.: STR12098307I-1 PAGE 8 OF 67 FCC PART 22H&24E

### **4.4 Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

# **4.5 Summary of Test Results/Plots**

Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H/V	dB	dB	dBm	dBm
				Low Cha	nnel			
824.2	30.29	1.5	0	Н	1.5	0	28.79	38.45
824.2	31.73	1.5	0	V	1.5	0	30.23	38.45
			M	liddle Ch	annel			
836.6	29.90	1.5	0	Η	1.5	0	28.40	38.45
836.6	31.96	1.5	0	V	1.5	0	30.46	38.45
	High Channel							
848.8	29.44	1.5	0	Н	1.5	0	27.94	38.45
848.8	31.63	1.5	0	V	1.5	0	30.13	38.45

#### EIRP For GSM Mode PCS1900

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H/V	dB	dB	dBm	dBm
			ı	Low Cha	nnel			
1850.2	19.98	1.5	0	Η	1.9	7.7	25.78	33
1850.2	21.84	1.5	0	V	1.9	7.7	27.64	33
			M	liddle Ch	annel			
1880.0	20.22	1.5	0	Н	1.9	7.7	26.02	33
1880.0	22.06	1.5	0	V	1.9	7.7	27.86	33
	High Channel							
1909.8	19.78	1.5	0	Н	1.9	7.7	25.58	33
1909.8	22.94	1.5	0	V	1.9	7.7	28.74	33

### ERP For GPRS Mode GSM850

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H/V	dB	dB	dBm	dBm
	Low Channel							
824.2	28.24	1.5	0	Н	1.5	0	26.74	38.45
824.2	31.97	1.5	0	V	1.5	0	30.47	38.45
	Middle Channel							
836.6	28.60	1.5	0	Η	1.5	0	27.10	38.45
836.6	31.85	1.5	0	V	1.5	0	30.35	38.45
	High Channel							
848.8	29.04	1.5	0	Н	1.5	0	27.54	38.45
848.8	31.99	1.5	0	V	1.5	0	30.49	38.45

# EIRP For GPRS Mode PCS1900

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Corrected Ampl.	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H/V	dB	dB	DBm	dBm
	Low Channel							
1850.2	20.74	1.5	0	Η	1.9	7.7	26.54	33
1850.2	22.30	1.5	0	<b>V</b>	1.9	7.7	28.10	33
	Middle Channel							
1880.0	20.45	1.5	0	Н	1.9	7.7	26.25	33
1880.0	22.17	1.5	0	V	1.9	7.7	27.97	33
	High Channel							
1909.8	19.78	1.5	0	Η	1.9	7.7	25.58	33
1909.8	22.07	1.5	0	V	1.9	7.7	27.87	33

Max. Conducted Output Power For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Output Power (dBm)	FCC Part 22.913 Limit (dBm)
	Low Channel	824.2	32.46	38.45
GSM	Middle Channel	836.6	32.51	38.45
	High Channel	848.8	32.52	38.45
	Low Channel	824.2	32.47	38.45
GPRS	Middle Channel	836.6	32.45	38.45
	High Channel	848.8	32.47	38.45

# For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Output Power (dBm)	FCC Part 24.232 Limit (dBm)
	Low Channel	1850.2	29.81	33
GSM	Middle Channel	1880.0	29.79	33
	High Channel	1909.8	29.94	33
	Low Channel	1850.2	29.80	33
GPRS	Middle Channel	1880.0	29.80	33
	High Channel	1909.8	29.96	33

#### 5. Emission Bandwidth

### 5.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


# 5.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2012-03-28	2013-03-27
Rohde & Schwarz	Universal Radio	CMU200	112012	2012-03-28	2013-03-27
	Communication Tester				

#### **5.3 Test Procedure**

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



#### **5.4 Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

# **5.5 Summary of Test Results/Plots**

For Cellular Band


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
	128	824.2	253.9158	339.311
GSM	190	836.6	253.2502	336.964
	251	848.8	254.0297	337.758
	128	824.2	253.9023	339.634
GPRS	190	836.6	252.2885	335.480
	251	848.8	252.6061	337.587

For PCS Band


Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
	512	1850.2	255.5897	344.032
GSM	661	1880.0	255.4756	337.293
	810	1909.8	255.1545	338.111
	512	1850.2	254.5986	340.963
GPRS	661	1880.0	254.7238	332.138
	810	1909.8	250.6880	334.998

Please refer to the following test plots:


# For Cellular Band GSM Low Channel




#### **GSM Middle Channel**




#### GSM High channel




#### **GPRS** Low Channel




#### GPRS Middle Channel




#### **GPRS High Channel**




# For PCS Band GSM Low Channel




#### **GSM Middle Channel**




#### **GSM** High channel




#### **GPRS** Low Channel



#### GPRS Middle Channel



### **GPRS High Channel**



### 6. Out of Band Emissions at Antenna Terminal

### 6.1 Standard Applicable

According to  $\S22.917(a)$ , the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P) dB$ .

According to  $\S24.238(a)$ , the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P) dB$ .


### 6.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B	US41192821	2012-03-28	2013-03-27
Rohde & Schwarz	Spectrum Analyzer	FSP	836079/035	2012-03-28	2013-03-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	112012	2012-03-28	2013-03-27

#### **6.3 Test Procedure**

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic.

Test Configuration for the out of band emissions testing:





#### **6.4 Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


# 6.5 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band GSM Low Channel 30MHz to 1GHz







# GSM Middle Channel 30MHz to 1GHz









# GSM High Channel 30MHz to 1GHz







#### **GSM** Low Band Emission




# **GSM High Band Emission**




# GPRS Low Channel 30MHz to 1GHz







# GPRS Middle Channel 30MHz to 1GHz









# GPRS High Channel 30MHz to 1GHz







#### **GPRS** Low Band Emission




#### **GPRS** High Band Emission




For PCS Band GSM Low Channel 30MHz to 1GHz










# GSM Middle Channel 30MHz to 1GHz






# GSM High Channel 30MHz to 1GHz







#### **GSM** Low Band Emission




#### **GSM High Band Emission**





# GPRS Low Channel 30MHz to 1GHz







# GPRS Middle Channel 30MHz to 1GHz






# GPRS High Channel 30MHz to 1GHz






#### **GPRS** Low Band Emission



#### **GPRS** High Band Emission



### 7. Spurious Radiated Emissions

### 7.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ±5.20 dB.

#### 7.2 Standard Applicable

According to  $\S22.917(a)$ , the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P) dB$ .

According to  $\S24.238(a)$ , the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P) dB$ .

#### 7.3 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2012-03-28	2013-03-27
Pre-amplifier	Agilent	8447F	3113A06717	2012-03-28	2013-03-27
Pre-amplifier	Compliance Direction	PAP-0118	24002	2012-03-28	2013-03-27
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2012-02-25	2013-02-24
Horn Antenna	ETS	3117	00086197	2012-02-25	2013-02-24
Universal Radio Communication Tester	Rohde & Schwarz	CMU200	112012	2012-03-28	2013-03-27
Signal Generator	R&S	SMR20	100047	2012-03-28	2013-03-27

#### 7.4 Test Procedure

- 1. The setup of EUT is according with per TIA/EIA Standard 603C and ANSI C63.4-2003 measurement procedure.
- 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
- 4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB = $43+10 \text{ Log}_{10}$  (power out in Watts)

### 7.5 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 7.6 Summary of Test Results/Plots


According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

-16.73 at 900.1474 MHz in the Vertical polarization for PCS Band\_GPRS Mode High channel, 30MHz to 18 GHz.

Spurious Emission From 30MHz to 1GHz For Cellular Band\_GSM Mode Low channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	36.5092	-68.90	20.93	-47.97	-13.00	-34.97	ERP
2	106.7587	-68.30	17.98	-50.32	-13.00	-37.32	ERP
3	330.1949	-68.25	22.08	-46.17	-13.00	-33.17	ERP
4	578.6699	-66.45	25.92	-40.53	-13.00	-27.53	ERP
5	739.6605	-68.07	29.87	-38.20	-13.00	-25.20	




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.1616	-68.72	21.34	-47.38	-13.00	-34.38	ERP
2	106.7587	-67.85	17.98	-49.87	-13.00	-36.87	ERP
3	318.8170	-67.92	22.26	-45.66	-13.00	-32.66	ERP
4	739.6605	-66.51	29.87	-36.64	-13.00	-23.64	ERP
5	900.1474	-67.07	31.18	-35.89	-13.00	-22.89	ERP

### For Cellular Band\_GSM Mode Middle channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	97.4560	-68.43	20.03	-48.40	-13.00	-35.40	ERP
2	972.3374	-68.82	34.03	-34.79	-13.00	-21.79	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	138.3873	-63.72	15.86	-47.86	-13.00	-34.86	ERP
2	390.7226	-67.98	23.11	-44.87	-13.00	-31.87	ERP
3	919.2866	-65.76	33.06	-32.70	-13.00	-19.70	ERP

# $For \ Cellular \ Band\_GSM \ Mode \ High \ channel$




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	41.1320	-68.03	21.13	-46.90	-13.00	-33.90	ERP
2	106.7587	-67.85	17.98	-49.87	-13.00	-36.87	ERP
3	739.6605	-66.51	29.87	-36.64	-13.00	-23.64	ERP
4	912.8620	-65.97	30.73	-35.24	-13.00	-22.24	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	40.8446	-63.45	21.22	-42.23	-13.00	-29.23	ERP
2	100.2286	-63.45	18.61	-44.84	-13.00	-31.84	ERP
3	452.7197	-61.97	23.38	-38.59	-13.00	-25.59	ERP
4	887.6099	-61.38	30.95	-30.43	-13.00	-17.43	ERP

# $For \ Cellular \ Band\_GPRS \ Mode \ Low \ channel$




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	41.1320	-68.03	21.13	-46.90	-13.00	-33.90	ERP
2	106.7587	-67.85	17.98	-49.87	-13.00	-36.87	ERP
3	279.0436	-64.04	20.97	-43.07	-13.00	-30.07	ERP
4	739.6605	-66.51	29.87	-36.64	-13.00	-23.64	ERP
5	912.8620	-65.97	30.73	-35.24	-13.00	-22.24	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	670.4892	-68.11	29.06	-39.05	-13.00	-26.05	ERP
2	787.8513	-68.34	30.63	-37.71	-13.00	-24.71	ERP
3	979.1803	-70.29	34.16	-36.13	-13.00	-23.13	ERP

# For Cellular Band\_GPRS Mode Middle channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	41.1320	-68.03	21.13	-46.90	-13.00	-33.90	ERP
2	105.2718	-67.63	18.12	-49.51	-13.00	-36.51	ERP
3	739.6605	-66.51	29.87	-36.64	-13.00	-23.64	ERP
4	912.8620	-65.97	30.73	-35.24	-13.00	-22.24	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	49.7068	-62.49	18.50	-43.99	-13.00	-30.99	ERP
2	100.2286	-63.45	18.61	-44.84	-13.00	-31.84	ERP
3	734.4913	-60.89	29.48	-31.41	-13.00	-18.41	ERP
4	900.1474	-60.92	31.18	-29.74	-13.00	-16.74	ERP

# $For \ Cellular \ Band\_GPRS \ Mode \ High \ channel$




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	112.9196	-66.31	18.91	-47.40	-13.00	-34.40	ERP
2	531.9635	-65.89	26.92	-38.97	-13.00	-25.97	ERP
3	599.3213	-67.53	28.45	-39.08	-13.00	-26.08	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	562.6624	-68.54	27.63	-40.91	-13.00	-27.91	ERP
2	782.3452	-68.20	30.54	-37.66	-13.00	-24.66	ERP
3	965.5421	-70.08	33.90	-36.18	-13.00	-23.18	ERP

### For PCS Band\_GSM Mode Low channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	97.4560	-67.43	20.03	-47.40	-13.00	-34.40	ERP
2	112.9196	-66.81	18.91	-47.90	-13.00	-34.90	ERP
3	531.9634	-65.89	26.92	-38.97	-13.00	-25.97	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	562.6624	-70.04	27.63	-42.41	-13.00	-29.41	ERP
2	782.3452	-69.70	30.54	-39.16	-13.00	-26.16	ERP
3	965.5421	-70.58	33.90	-36.68	-13.00	-23.68	ERP

### For PCS Band\_GSM Mode Middle channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	102.3597	-69.05	20.03	-49.02	-13.00	-36.02	ERP
2	499.4247	-70.18	26.16	-44.02	-13.00	-31.02	ERP
3	750.1083	-68.75	30.06	-38.69	-13.00	-25.69	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	96.0986	-70.13	19.94	-50.19	-13.00	-37.19	ERP
2	528.2458	-68.98	26.86	-42.12	-13.00	-29.12	ERP
3	1000.0000	-69.34	34.54	-34.80	-13.00	-21.80	ERP

## For PCS Band\_GSM Mode High channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	89.5900	-68.46	18.75	-49.71	-13.00	-36.71	ERP
2	401.8385	-68.66	23.20	-45.46	-13.00	-32.46	ERP
3	554.8254	-69.43	27.45	-41.98	-13.00	-28.98	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	101.6443	-69.58	20.09	-49.49	-13.00	-36.49	ERP
2	366.8231	-69.48	22.79	-46.69	-13.00	-33.69	ERP
3	550.9480	-68.64	27.37	-41.27	-13.00	-28.27	ERP

### For PCS Band\_GPRS Mode Low channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	97.4560	-69.29	20.03	-49.26	-13.00	-36.26	ERP
2	510.0436	-68.85	26.44	-42.41	-13.00	-29.41	ERP
3	675.2080	-68.58	29.09	-39.49	-13.00	-26.49	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	96.7749	-70.04	19.99	-50.05	-13.00	-37.05	ERP
2	267.5455	-68.68	20.97	-47.71	-13.00	-34.71	ERP
3	972.3374	-68.46	34.03	-34.43	-13.00	-21.43	ERP

### For PCS Band\_GPRS Mode Middle channel




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	99.5281	-70.92	20.20	-50.72	-13.00	-37.72	ERP
2	112.9196	-70.04	18.91	-51.13	-13.00	-38.13	ERP
3	385.2805	-70.08	23.05	-47.03	-13.00	-34.03	ERP




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	101.6443	-70.30	20.09	-50.21	-13.00	-37.21	ERP
2	364.2595	-70.02	22.76	-47.26	-13.00	-34.26	ERP
3	633.9073	-69.89	28.75	-41.14	-13.00	-28.14	ERP

## For PCS Band\_GPRS Mode High channel



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	41.1320	-68.03	21.13	-46.90	-13.00	-33.90	ERP
2	103.8055	-67.74	18.26	-49.48	-13.00	-36.48	ERP
3	739.6605	-66.51	29.87	-36.64	-13.00	-23.64	ERP
4	912.8620	-65.97	30.73	-35.24	-13.00	-22.24	ERP



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	39.1616	-62.68	21.34	-41.34	-13.00	-28.34	ERP
2	52.9453	-62.64	18.14	-44.50	-13.00	-31.50	ERP
3	299.3158	-62.73	21.95	-40.78	-13.00	-27.78	ERP
4	900.1474	-60.91	31.18	-29.73	-13.00	-16.73	ERP

Spurious Emissions Above 1GHz For Cellular Band\_GSM Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar	
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V	
		Low	Channel (824.2	MHz)	•		
1648.4	-34.53	-1.84	-36.37	-13	-23.37	Н	
2472.6	-40.30	0.02	-40.28	-13	-27.28	Н	
1648.4	-32.85	-1.84	-34.69	-13	-21.69	V	
2472.6	-39.86	0.02	-39.84	-13	-26.84	V	
Middle Channel (836.6MHz)							
1673.2	-35.75	-1.70	-37.45	-13	-24.45	Н	
2509.8	-41.35	0.09	-41.26	-13	-28.26	Н	
1673.2	-34.91	-1.70	-36.61	-13	-23.61	V	
2509.8	-39.81	0.09	-39.72	-13	-26.72	V	
High Channel (848.8MHz)							
1697.6	-36.15	-1.55	-37.70	-13	-24.70	Н	
2546.4	-42.83	0.38	-42.45	-13	-29.45	Н	
1697.6	-34.46	-1.55	-36.01	-13	-23.01	V	
2546 4	-40 75	0.38	-40.37	-13	-27 37	V	

#### For Cellular Band\_GPRS Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar	
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V	
		Low	Channel (824.2	MHz)			
1648.4	-36.78	-1.84	-38.62	-13	-25.62	Н	
2472.6	-40.36	0.02	-40.34	-13	-27.34	Н	
1648.4	-34.79	-1.84	-36.63	-13	-23.63	V	
2472.6	-42.32	0.02	-42.30	-13	-29.30	V	
	Middle Channel (836.6MHz)						
1673.2	-35.94	-1.70	-37.64	-13	-24.64	Н	
2509.8	-40.36	0.09	-40.27	-13	-27.27	Н	
1673.2	-35.02	-1.70	-36.72	-13	-23.72	V	
2509.8	-42.30	0.09	-42.21	-13	-29.21	V	
		High	Channel (848.8	MHz)			
1697.6	-37.27	-1.55	-38.82	-13	-25.82	Н	
2546.4	-42.18	0.38	-41.80	-13	-28.80	Н	
1697.6	-35.73	-1.55	-37.28	-13	-24.28	V	
2546.4	-42.89	0.38	-42.51	-13	-29.51	<b>V</b>	

For PCS Band\_GSM Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar	
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V	
		Low (	Channel (1850.2	2MHz)			
3700.4	-45.62	5.92	-39.7	-13	-26.70	Н	
5550.6	-53.94	10.24	-43.7	-13	-30.70	Н	
3700.4	-44.82	5.92	-38.9	-13	-25.90	V	
5550.6	-52.84	10.24	-42.6	-13	-29.60	V	
	Middle Channel (1880MHz)						
3760.0	-45.83	6.11	-39.72	-13	-26.72	Н	
5640.0	-53.18	10.17	-43.01	-13	-30.01	Н	
3760.0	-44.65	6.11	-38.54	-13	-25.54	V	
5640.0	-52.04	10.17	-41.87	-13	-28.87	V	
		High (	Channel (1909.8	BMHz)			
3819.6	-45.28	6.28	-39.00	-13	-26.00	Н	
5729.4	-53.34	10.11	-43.23	-13	-30.23	Н	
3819.6	-44.36	6.28	-38.08	-13	-25.08	V	
5729.4	-51.43	10.11	-41.32	-13	-28.32	V	

For PCS Band GPRS Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
		Low C	Channel (1850.2	MHz)		
3700.4	-46.25	5.92	-40.33	-13	-27.33	Н
5550.6	-53.75	10.24	-43.51	-13	-30.51	Н
3700.4	-47.59	5.92	-41.67	-13	-28.67	V
5550.6	-55.04	10.24	-44.80	-13	-31.80	V
Middle Channel (1880MHz)						
3760.0	-45.83	6.11	-39.72	-13	-26.72	Н
5640.0	-51.91	10.17	-41.74	-13	-28.74	Н
3760.0	-46.14	6.11	-40.03	-13	-27.03	V
5640.0	-53.44	10.17	-43.27	-13	-30.27	V
		High (	Channel (1909.8	BMHz)		
3819.6	-46.90	6.28	-40.62	-13	-27.62	Н
5729.4	-53.32	10.11	-43.21	-13	-30.21	Н
3819.6	-47.10	6.28	-40.82	-13	-27.82	V
5729.4	-54.57	10.11	-44.46	-13	-31.46	V

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 10<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 8. Frequency Stability

### 8.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

### 8.2 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Date	Due. Date
Aglient	Spectrum Analyzer	E4402B-ESA	US41192821	2012-03-28	2013-03-27
Rohde &	Universal Radio	CMU200	112012	2012 02 29	2012 02 27
Schwarz	Communication	CMO200	112012	2012-03-28	2013-03-27
GONGWEN	Moisture Test Chamber	GDS-150	SEMT-0013	2012-03-28	2013-03-27

#### 8.3 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage			
20°C	85-115% of declared nominal voltage			
-30°C to +50°C	Normal			

REPORT NO.: STR12098307I-1 PAGE 64 OF 67 FCC PART 22H&24E

### **8.4 Environmental Conditions**

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

# **8.5 Summary of Test Results/Plots**

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm						
Environment	Power Supplied	Frequency Measure with Time Elapsed				
Temperature (°C)	(VDC)	MCF (Hz)	Error (ppm)			
50	3.7	-32	-0.03825			
40	3.7	-30	-0.03586			
30	3.7	-22	-0.02630			
20	3.7	-16	-0.01913			
10	3.7	-18	-0.02152			
0	3.7	-20	-0.02391			
-10	3.7	-28	-0.03347			
-20	3.7	-30	-0.03586			
-30	3.7	-38	-0.04542			

#### For PCS Band GSM Mode

Refe	Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm						
Environment Temperature	Power Supplied (VDC)	Frequency Measure  MCF (Hz)	e with Time Elapsed  Error (ppm)				
(°C)	3.7	50	0.02660				
40	3.7	45	0.02394				
30	3.7	42	0.02234				
20	3.7	39	0.02074				
10	3.7	43	0.02287				
0	3.7	52	0.02766				
-10	3.7	55	0.02926				
-20	3.7	58	0.03085				
-30	3.7	62	0.03298				

REPORT NO.: STR12098307I-1 PAGE 65 OF 67 FCC PART 22H&24E

### For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm					
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed			
		MCF (Hz)	Error (ppm)		
50	3.7	-28	-0.03347		
40	3.7	-25	-0.02988		
30	3.7	-22	-0.02630		
20	3.7	-15	-0.01793		
10	3.7	-16	-0.01913		
0	3.7	-22	-0.02630		
-10	3.7	-30	-0.03586		
-20	3.7	-33	-0.03945		
-30	3.7	-38	-0.04542		

### For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm					
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed			
		MCF (Hz)	Error (ppm)		
50	3.7	62	0.03298		
40	3.7	53	0.02819		
30	3.7	53	0.02819		
20	3.7	40	0.02128		
10	3.7	32	0.01702		
0	3.7	40	0.02128		
-10	3.7	45	0.02394		
-20	3.7	57	0.03032		
-30	3.7	66	0.03511		

## So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm							
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed					
		Frequency (Hz)	Error (ppm)				
20	3.3	-20	-0.02391				
	3.7	-16	-0.01913				
	4.2	-19	-0.02271				
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm							
Environment	Power Supplied	Frequency Measure with Time Elapsed					
Temperature (°C)	(VDC)	Frequency (Hz)	Error (ppm)				
	3.3	36	0.01915				
20	3.7	39	0.02074				
	4.2	42	0.02234				
Referen	Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm						
Environment	Dower Supplied	ironment Frequency Measure with Time Elapsed		with Time Elapsed			
Temperature (°C)	(VDC)	Frequency (Hz)	Error (ppm)				
20	3.3	-20	-0.02391				
	3.7	-15	-0.01793				
	4.2	-18	-0.02152				
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm							
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed					
		Frequency (Hz)	Error (ppm)				
20	3.3	45	0.02394				
	3.7	40	0.02128				
	4.2	48	0.02553				

### \*\*\*\*\* END OF REPORT \*\*\*\*\*