



RF TEST REPORT



Report No.: 17070159-FCC-R2

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Tablet	
Model No.	T7445	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	March 02 to April 05, 2017	
Issue Date	April 06, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070159-FCC-R2
Page	3 of 66

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 ANTENNA REQUIREMENT	10
6.2 CHANNEL SEPARATION	11
6.3 20DB BANDWIDTH.....	15
6.4 PEAK OUTPUT POWER.....	19
6.5 NUMBER OF HOPPING CHANNEL.....	23
6.6 TIME OF OCCUPANCY (DWEIL TIME).....	25
6.7 BAND EDGE & RESTRICTED BAND	29
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	37
6.9 RADIATED EMISSIONS & RESTRICTED BAND.....	43
ANNEX A. TEST INSTRUMENT	49
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	50
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	61
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	65
ANNEX E. DECLARATION OF SIMILARITY.....	66

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070159-FCC-R2	NONE	Original	April 06, 2017

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States
Manufacturer	Tench (HK) information CO.,Limited
Manufacturer Add	Room 901,Building 2,COFCO Business Park,BaoAn District,ShenZhen,China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT: Tablet

Main Model: T7445

Serial Model: N/A

Date EUT received: March 01, 2017

Test Date(s): March 02 to April 05, 2017

Equipment Category : DSS

Antenna Gain:

GSM850: -0.5dBi
 PCS1900: 1.0dBi
 UMTS-FDD Band V: -0.5dBi
 UMTS-FDD Band II: 0.9dBi
 WIFI: 0.8dBi
 Bluetooth/BLE: 0.8dBi
 GPS: 0.9dBi

Antenna Type: PIFA antenna

Type of Modulation:

GSM / GPRS: GMSK
 EGPRS: GMSK
 UMTS-FDD: QPSK
 802.11b/g/n: DSSS, OFDM
 Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
 BLE: GFSK
 GPS: BPSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
 UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
 UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
 RX: 1932.4 ~ 1987.6 MHz
 WIFI: 802.11b/g/n(20M): 2412-2462 MHz
 WIFI: 802.11n(40M): 2422-2452 MHz

Bluetooth& BLE: 2402-2480 MHz

GPS: 1575.42 MHz

Max. Output Power: 2.848dBm

Number of Channels: GSM 850: 124CH
PCS1900: 299CH
UMTS-FDD Band V: 102CH
UMTS-FDD Band II: 277CH
WIFI :802.11b/g/n(20M): 11CH
WIFI :802.11n(40M): 7CH
Bluetooth: 79CH
BLE: 40CH
GPS:1CH

Port: USB Port, Earphone Port

Input Power: Adapter:
Model: JWS664-501000
Input: AC100-240V~50/60Hz,0.2A
Output: DC 5.0V,1000mA
Battery:
Model: PR-308088N
Spec: 3.7V, 2500mAh

Trade Name : verykool

FCC ID: WA6T7445

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Parameter	Uncertainty
AC Power Line Conducted Emissions (150kHz~30MHz)	$\pm 3.71\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.12\text{dB}$
Radiated Emission(1GHz~6GHz)	$\pm 5.34\text{dB}$

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:

A permanently attached PIFA antenna for Bluetooth/WIFI/BLE/GPS, the gain is 0.8dBi for Bluetooth/WIFI/BLE, 0.9dBi for GPS.

A permanently attached PIFA antenna for GSM/PCS/UMTS-FDD Band V/ UMTS-FDD Band II, the gain is -0.5dBi for GSM/ UMTS-FDD Band V, 1.0dBi for PCS1900, 0.9dBi for UMTS-FDD Band II.



The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span - Video (or Average) Bandwidth (VBW) ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot. 		

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.686	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.689	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.688	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.863	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.863	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.861	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.005	0.862	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.861	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.005	0.869	Pass
	Adjacency Channel	2479			


Test Plots

Channel Separation measurement result






8DPSK - Low Channel



8DPSK - Middle Channel





8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings:</p> <ul style="list-style-type: none"> - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW \geq 1% of the 20 dB bandwidth - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference 		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.029	0.9089
	Mid	2441	1.034	0.9057
	High	2480	1.032	0.8999
$\pi/4$ DQPSK	Low	2402	1.295	1.1632
	Mid	2441	1.294	1.1743
	High	2480	1.291	1.1626
8-DPSK	Low	2402	1.293	1.1686
	Mid	2441	1.292	1.1675
	High	2480	1.303	1.1716


Test Plots

20dB Bandwidth measurement result






8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	<input type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
------------	--

Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	---

	<p>- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Peak Output Power measurement result

Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	2.647	125	Pass
		Mid	2441	2.848	125	Pass
		High	2480	2.732	125	Pass
	$\pi/4$ DQPSK	Low	2402	2.446	125	Pass
		Mid	2441	2.641	125	Pass
		High	2480	2.517	125	Pass
	8-DPSK	Low	2402	2.555	125	Pass
		Mid	2441	2.739	125	Pass
		High	2480	2.617	125	Pass


Test Plots

Output Power measurement result






8DPSK Output power - Low CH 2402



8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled.</p> <ul style="list-style-type: none"> - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.875	306.667	400	Pass
		Mid	2.875	306.667	400	Pass
		High	2.875	306.667	400	Pass
	π /4 DQPSK	Low	2.875	306.667	400	Pass
		Mid	2.875	306.667	400	Pass
		High	2.850	304.000	400	Pass
	8-DPSK	Low	2.875	306.667	400	Pass
		Mid	2.875	306.667	400	Pass
		High	2.850	304.000	400	Pass
Note: Dwell time=Pulse Time (ms) \times (1600 \div 6 \div 79) \times 31.6						


Test Plots

Dwell Time measurement result






8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	22 °C
Relative Humidity	53%
Atmospheric Pressure	1029mbar
Test date :	March 29, 2017
Tested By :	Loren Luo

Requirement(s):


Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, 		


	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☐ Yes ☒ N/A
Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GFSK Mode:





Date: 29.MAR.2017 09:59:27




Date: 29.MAR.2017 10:14:13

GFSK-Left Side-PK

Note: F1 is frequency 2400MHz

GFSK-Right Side-PK

Note: F1 is frequency 2483.5MHz





Date: 29.MAR.2017 10:05:08


Note: (no need if PK value less than the AV limit)

GFSK-Left Side-AV

GFSK-Right Side-AV

$\pi/4$ DQPSK Mode:


 <p>Start 2.31 GHz Stop 2.44 GHz</p> <p>Date: 29.MAR.2017 14:17:24</p>	 <p>Start 2.44 GHz Stop 2.5 GHz</p> <p>Date: 29.MAR.2017 14:24:34</p>
<p>$\pi/4$ DQPSK-Hopping Left Side-PK</p> <p>Note: F1 is frequency 2400MHz</p>	<p>$\pi/4$ DQPSK-Hopping Right Side-PK</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>$\pi/4$ DQPSK-Hopping Left-AV</p>	<p>$\pi/4$ DQPSK-Hopping Right-AV</p>



Date: 29.MAR.2017 10:02:53

$\pi/4$ DQPSK-Left Side-PK


Note: F1 is frequency 2400MHz



Date: 29.MAR.2017 10:14:51

$\pi/4$ DQPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz




Date: 29.MAR.2017 10:04:50


$\pi/4$ DQPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)

$\pi/4$ DQPSK-Right Side-AV

8-DPSK Mode:






Date: 29.MAR.2017 10:01:08

8DPSK-Left Side-PK


Note: F1 is frequency 2400MHz



Date: 29.MAR.2017 10:15:49

8DPSK-Right Side-PK

Note: F1 is frequency 2483.5MHz



Date: 29.MAR.2017 10:04:33

8DPSK-Left Side-AV

Note: (no need if PK value less than the AV limit)


8DPSK-Right Side-AV

6.8 AC Power Line Conducted Emissions

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable		
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<div><input checked="" type="checkbox"/></div>		
		Frequency ranges (MHz)		Limit (dBµV)	
				QP	Average
		0.15 ~ 0.5		66 – 56	56 – 46
		0.5 ~ 5		56	46
5 ~ 30	60	50			


Test Setup	 <p>Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>
------------	---

Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.1968	25.09	QP	10.03	35.12	63.74	-28.62
2	L1	0.1968	17.66	AVG	10.03	27.69	53.74	-26.05
3	L1	0.3918	27.28	QP	10.03	37.31	58.03	-20.72
4	L1	0.3918	17.87	AVG	10.03	27.90	48.03	-20.13
5	L1	0.6570	31.42	QP	10.03	41.45	56.00	-14.55
6	L1	0.6570	22.79	AVG	10.03	32.82	46.00	-13.18
7	L1	0.8559	32.29	QP	10.03	42.32	56.00	-13.68
8	L1	0.8559	23.26	AVG	10.03	33.29	46.00	-12.71
9	L1	1.1835	31.30	QP	10.03	41.33	56.00	-14.67
10	L1	1.1835	21.39	AVG	10.03	31.42	46.00	-14.58
11	L1	24.0249	31.87	QP	10.38	42.25	60.00	-17.75
12	L1	24.0249	22.72	AVG	10.38	33.10	50.00	-16.90

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.1968	34.10	QP	10.02	44.12	63.74	-19.62
2	N	0.1968	20.08	AVG	10.02	30.10	53.74	-23.64
3	N	0.6570	28.66	QP	10.02	38.68	56.00	-17.32
4	N	0.6570	20.08	AVG	10.02	30.10	46.00	-15.90
5	N	0.9222	31.13	QP	10.03	41.16	56.00	-14.84
6	N	0.9222	21.04	AVG	10.03	31.07	46.00	-14.93
7	N	1.1211	31.53	QP	10.03	41.56	56.00	-14.44
8	N	1.1211	20.73	AVG	10.03	30.76	46.00	-15.24
9	N	2.7045	21.29	QP	10.05	31.34	56.00	-24.66
10	N	2.7045	9.39	AVG	10.05	19.44	46.00	-26.56
11	N	24.0210	24.90	QP	10.32	35.22	60.00	-24.78
12	N	24.0210	20.70	AVG	10.32	31.02	50.00	-18.98

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2007	35.72	QP	10.03	45.75	63.58	-17.83
2	L1	0.2007	23.43	AVG	10.03	33.46	53.58	-20.12
3	L1	0.2319	37.67	QP	10.03	47.70	62.38	-14.68
4	L1	0.2319	29.07	AVG	10.03	39.10	52.38	-13.28
5	L1	0.8676	34.38	QP	10.03	44.41	56.00	-11.59
6	L1	0.8676	23.19	AVG	10.03	33.22	46.00	-12.78
7	L1	1.1991	33.05	QP	10.03	43.08	56.00	-12.92
8	L1	1.1991	22.55	AVG	10.03	32.58	46.00	-13.42
9	L1	4.5171	23.89	QP	10.07	33.96	56.00	-22.04
10	L1	4.5171	10.06	AVG	10.07	20.13	46.00	-25.87
11	L1	24.0210	29.69	QP	10.38	40.07	60.00	-19.93
12	L1	24.0210	20.39	AVG	10.38	30.77	50.00	-19.23

Test Mode: Bluetooth Mode



Test Data


Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB}	(dBuV)	(dBuV)	(dB)
1	N	0.2007	35.79	QP	10.02	45.81	63.58	-17.77
2	N	0.2007	25.06	AVG	10.02	35.08	53.58	-18.50
3	N	0.2280	41.09	QP	10.02	51.11	62.52	-11.41
4	N	0.2280	31.91	AVG	10.02	41.93	52.52	-10.59
5	N	0.3294	29.89	QP	10.02	39.91	59.47	-19.56
6	N	0.3294	22.47	AVG	10.02	32.49	49.47	-16.98
7	N	1.1952	30.93	QP	10.03	40.96	56.00	-15.04
8	N	1.1952	23.36	AVG	10.03	33.39	46.00	-12.61
9	N	4.5171	22.36	QP	10.07	32.43	56.00	-23.57
10	N	4.5171	9.07	AVG	10.07	19.14	46.00	-26.86
11	N	17.6952	23.68	QP	10.23	33.91	60.00	-26.09
12	N	17.6952	15.36	AVG	10.23	25.59	50.00	-24.41

6.9 Radiated Emissions & Restricted Band

Temperature	25 °C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	March 28, 2017
Tested By :	Loren Luo

Requirement(s):

Spec	Item	Requirement	Applicable											
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges												
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 - 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 - 960	200	Above 960	500	
		Frequency range (MHz)		Field Strength (µV/m)										
		30 – 88		100										
		88 – 216		150										
		216 - 960		200										
Above 960	500													

Test Setup	
------------	--

Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
-----------	---


	<p>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	30.5306	28.74	peak	20.99	22.28	0.63	28.08	40.00	-11.92	100	30
2	H	42.4508	30.81	peak	12.28	22.28	0.77	21.58	40.00	-18.42	200	269
3	H	87.4177	36.58	peak	7.90	22.35	1.01	23.14	40.00	-16.86	100	242
4	H	102.0014	30.76	peak	10.75	22.32	1.13	20.32	43.50	-23.18	100	311
5	H	202.8104	28.61	peak	12.06	22.37	1.55	19.85	43.50	-23.65	100	141
6	H	790.6188	28.72	peak	21.29	21.17	2.94	31.78	46.00	-14.22	100	57

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	30.0000	27.84	peak	21.40	22.28	0.62	27.58	40.00	-12.42	100	152
2	V	47.8260	40.29	peak	9.36	22.34	0.78	28.09	40.00	-11.91	100	218
3	V	89.5900	34.88	peak	7.98	22.32	0.96	21.50	43.50	-22.00	100	171
4	V	159.7844	30.98	peak	12.60	22.27	1.39	22.70	43.50	-20.80	100	43
5	V	566.6223	27.50	peak	18.63	21.66	2.48	26.95	46.00	-19.05	100	320
6	V	836.2443	30.34	peak	21.80	21.05	2.89	33.98	46.00	-12.02	200	150

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel: 8-DFSK Mode (Worst Case) (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	38.96	AV	V	33.67	6.86	32.66	46.83	54	-7.17
4804	38.75	AV	H	33.67	6.86	32.66	46.62	54	-7.38
4804	48.53	PK	V	33.67	6.86	32.66	56.4	74	-17.6
4804	45.71	PK	H	33.67	6.86	32.66	53.58	74	-20.42
17801	24.64	AV	V	45.03	11.21	32.38	48.5	54	-5.5
17801	24.82	AV	H	45.03	11.21	32.38	48.68	54	-5.32
17801	40.44	PK	V	45.03	11.21	32.38	64.3	74	-9.7
17801	42.31	PK	H	45.03	11.21	32.38	66.17	74	-7.83

Middle Channel: 8-DFSK Mode (Worst Case) (2441 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4882	38.93	AV	V	33.71	6.95	32.74	46.85	54	-7.15
4882	38.77	AV	H	33.71	6.95	32.74	46.69	54	-7.31
4882	48.87	PK	V	33.71	6.95	32.74	56.79	74	-17.21
4882	47.65	PK	H	33.71	6.95	32.74	55.57	74	-18.43
17822	24.88	AV	V	45.15	11.18	32.41	48.8	54	-5.2
17822	23.79	AV	H	45.15	11.18	32.41	47.71	54	-6.29
17822	41.21	PK	V	45.15	11.18	32.41	65.13	74	-8.87
17822	41.35	PK	H	45.15	11.18	32.41	65.27	74	-8.73

High Channel: 8-DFSK Mode (Worst Case) (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.43	AV	V	33.9	6.76	32.74	46.35	54	-7.65
4960	38.36	AV	H	33.9	6.76	32.74	46.28	54	-7.72
4960	47.95	PK	V	33.9	6.76	32.74	55.87	74	-18.13
4960	47.56	PK	H	33.9	6.76	32.74	55.48	74	-18.52
17816	24.22	AV	V	45.22	11.35	32.38	48.41	54	-5.59
17816	24.71	AV	H	45.22	11.35	32.38	48.9	54	-5.1
17816	41.97	PK	V	45.22	11.35	32.38	66.16	74	-7.84
17816	41.38	PK	H	45.22	11.35	32.38	65.57	74	-8.43

Note:

1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Front View



EUT - Front View




EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Small board - Front View




Small board - Rear View



Mainboard - Front View




LCD - Front View




LCD – Rear View



GSM/PCS/UMTS - Antenna View



BT/WIFI - Antenna View



Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	T7445	A025613

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	A025613

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A