

RF TEST REPORT



Report No.: 16070460-FCC-R1

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Tablet	
Model No.	TL8010	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2015 ;FCC Part 24(E):2015; FCC Part 27:2015; ANSI/TIA-603-D: 2010	
Test Date	April 25 to May 26, 2016	
Issue Date	May 26, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070460-FCC-R1
Page	3 of 102

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
6.1 RF EXPOSURE (SAR).....	10
6.2 RF OUTPUT POWER	11
6.3 PEAK-AVERAGE RATIO.....	23
6.4 OCCUPIED BANDWIDTH.....	28
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	43
6.6 SPURIOUS RADIATED EMISSIONS	59
6.7 BAND EDGE.....	66
6.8 FREQUENCY STABILITY	80
ANNEX A. TEST INSTRUMENT.....	91
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	93
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	98
ANNEX C.II. EUT OPERATING CONKITIONS	100
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	101
ANNEX E. DECLARATION OF SIMILARITY	102

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070460-FCC-R1	NONE	Original	May 26, 2016

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA
Manufacturer	Topwise
Manufacturer Add	5th floor,A8Music Building,No.1002,Keyuan Road,Hi-Teach Park,NanShan Districtt,Shenzhen

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Tablet
Main Model:	TL8010
Serial Model:	N/A
Date EUT received:	April 25, 2016
Test Date(s):	April 25 to May 26, 2016
Equipment Category :	PCE
Antenna Gain:	GSM850: 0.61 dBi PCS1900: 0.85 dBi UMTS-FDD Band 5: 0.61 dBi UMTS-FDD Band 2: 0.85 dBi UMTS-FDD Band 4: -0.84 dBi LTE Band 2: 0.85 dBi LTE Band 4: -0.84 dBi LTE Band 5: 0.61 dBi LTE Band 7: 1.11 dBi LTE Band 17: -4.77 dBi Bluetooth/BLE/WIFI: 2.16 dBi GPS: 1.74 dBi
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK, 8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK GPS: BPSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
 UMTS-FDD Band 5 TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
 UMTS-FDD Band 2 TX: 1852.4 ~ 1907.6 MHz;
 RX: 1932.4 ~ 1987.6 MHz
 UMTS-FDD Band 4 TX: 1712.4 ~ 1752.6 MHz;
 RX: 2112.4 ~ 2152.6 MHz
 LTE Band 2 TX: 1852.5 ~ 1907.5 MHz; RX: 1932.5 ~ 1987.5 MHz
 LTE Band 4 TX: 1712.5 ~ 1752.5 MHz; RX: 2112.5 ~ 2152.5 MHz
 LTE Band 5 TX: 826.5 ~ 846.5 MHz; RX: 871.5 ~ 891.5 MHz
 LTE Band 7 TX: 2502.5 ~ 2567.5 MHz; RX: 2622.5 ~ 2687.5 MHz
 LTE Band 17 TX: 706.5 ~ 713.5 MHz; RX: 736.5 ~ 743.5 MHz
 WIFI: 802.11b/g/n(20M): 2412-2462 MHz
 WIFI: 802.11n(40M): 2422-2452 MHz
 Bluetooth& BLE: 2402-2480 MHz
 GPS: 1575.42 MHz

Maximum Conducted

AV Power to Antenna:

GSM Voice: GSM850: 32.56 dBm
 PCS1900: 30.26 dBm
 GPRS: GSM850: 32.55 dBm
 PCS1900: 30.25 dBm
 EGPRS: GSM850: 26.13 dBm
 PCS1900: 26.32 dBm
 RMC: UMTS-FDD Band 5: 21.11 dBm
 UMTS-FDD Band 2: 22.84 dBm
 UMTS-FDD Band 4: 23.22 dBm
 HSUPA: UMTS-FDD Band 5: 21.16 dBm
 UMTS-FDD Band 2: 21.89 dBm
 UMTS-FDD Band 4: 21.44 dBm
 HSDPA: UMTS-FDD Band 5: 21.18 dBm
 UMTS-FDD Band 2: 21.89 dBm
 UMTS-FDD Band 2: 21.49 dBm

ERP/EIRP:

GSM Voice: GSM850: 30.86 dBm / ERP
 PCS1900: 30.87 dBm / EIRP
 GPRS: GSM850: 30.48 dBm / ERP
 PCS1900: 30.25 dBm / EIRP

Test Report	16070460-FCC-R1
Page	8 of 102

EGPRS:GSM850: 26.82 dBm / ERP

PCS1900: 27.42 dBm / EIRP

RMC:UMTS-FDD Band 5: 19.43 dBm / ERP

UMTS-FDD Band 2: 23.25 dBm / EIRP

UMTS-FDD Band 4: 22.35 dBm / EIRP

HSUPA:UMTS-FDD Band 5: 19.29 dBm / ERP

UMTS-FDD Band 2: 22.35 dBm / EIRP

UMTS-FDD Band 4: 20.39 dBm / EIRP

HSDPA:UMTS-FDD Band 5: 19.15 dBm / ERP

UMTS-FDD Band 2: 22.25 dBm / EIRP

UMTS-FDD Band 4: 20.48 dBm / EIRP

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band 5: 102CH

UMTS-FDD Band 4: 202CH

UMTS-FDD Band 2: 277CH

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Number of Channels:

Port:

Power Port, Earphone Port, USB Port

Adapter:

Model: JML050200A

Input: AC 100-240V; 50/60Hz;0.3A

Input Power:

Output: DC 5.0V,2.0A

Battery:

Capacity: 2030mAh

Voltage: 3.8V

Trade Name :

verykool

GPRS/EGPRS Multi-slot class

8/10/12

FCC ID:

WA6TL8010

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 16070460-FCC-H.

6.2 RF Output Power

Temperature	23°C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	May 18, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	<input checked="" type="checkbox"/>
§24.232 (c)	b)	EIRP:33dBm	<input checked="" type="checkbox"/>
§27.50 (c)	c)	EIRP: 30dBm	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>For Conducted Power:</p> <ul style="list-style-type: none"> - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. <p>For ERP/EIRP:</p> <p>According with KDB 971168 v02r02</p> <ul style="list-style-type: none"> - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---

Test Report	16070460-FCC-R1
Page	12 of 102

	<p>frequency was investigated.</p> <ul style="list-style-type: none"> - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	32.56	32.54	32.55	32±1	30.22	30.24	30.26	30±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	32.55	32.54	32.53	32±1	30.21	30.23	30.25	30±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.74	31.75	31.74	31.5±1	29.41	29.42	29.51	29.5±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	28.72	28.70	28.66	28.5±1	26.19	26.21	26.54	26.5±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	32.52	32.51	32.50	32±1	30.23	30.29	30.07	30±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.74	31.73	31.71	31.5±1	29.50	29.56	29.47	29.5±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	28.73	28.71	28.68	28.5±1	26.64	26.71	26.95	26.5±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	26.13	26.10	26.02	26±1	26.32	26.13	25.95	26±1
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	25.02	24.91	24.88	25±1	25.17	25.10	24.91	25±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	21.90	21.81	21.75	21±1	21.66	21.58	21.50	21±1

Test Report	16070460-FCC-R1
Page	14 of 102

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	21.11	21.3±1
	4175	835	21.06	21.3±1
	4233	846.6	21.07	21.3±1
HSDPA Subtest1	4132	826.4	21.03	21.3±1
	4175	835	21.06	21.3±1
	4233	846.6	21.15	21.3±1
HSDPA Subtest2	4132	826.4	21.08	21.3±1
	4175	835	21.05	21.3±1
	4233	846.6	21.16	21.3±1
HSDPA Subtest3	4132	826.4	21.13	21.3±1
	4175	835	21.08	21.3±1
	4233	846.6	21.04	21.3±1
HSDPA Subtest4	4132	826.4	21.14	21.3±1
	4175	835	21.13	21.3±1
	4233	846.6	21.05	21.3±1
HSUPA Subtest1	4132	826.4	21.00	21.3±1
	4175	835	21.03	21.3±1
	4233	846.6	21.16	21.3±1
HSUPA Subtest2	4132	826.4	21.13	21.3±1
	4175	835	21.15	21.3±1
	4233	846.6	21.12	21.3±1
HSUPA Subtest3	4132	826.4	21.15	21.3±1
	4175	835	21.18	21.3±1
	4233	846.6	21.09	21.3±1
HSUPA Subtest4	4132	826.4	21.04	21.3±1
	4175	835	21.04	21.3±1
	4233	846.6	21.05	21.3±1
HSUPA Subtest5	4132	826.4	21.03	21.3±1
	4175	835	21.04	21.3±1
	4233	846.6	21.04	21.3±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	22.74	22.5±1
	9400	1880	22.84	22.5±1
	9538	1907.6	22.55	22.5±1
HSDPA Subtest1	9262	1852.4	21.86	21.3±1
	9400	1880	21.89	21.3±1
	9538	1907.6	21.85	21.3±1
HSDPA Subtest2	9262	1852.4	21.83	21.3±1
	9400	1880	21.87	21.3±1
	9538	1907.6	21.89	21.3±1
HSDPA Subtest3	9262	1852.4	21.85	21.3±1
	9400	1880	21.83	21.3±1
	9538	1907.6	21.89	21.3±1
HSDPA Subtest4	9262	1852.4	21.85	21.3±1
	9400	1880	21.87	21.3±1
	9538	1907.6	21.86	21.3±1
HSUPA Subtest1	9262	1852.4	21.89	21.3±1
	9400	1880	21.84	21.3±1
	9538	1907.6	21.87	21.3±1
HSUPA Subtest2	9262	1852.4	21.83	21.3±1
	9400	1880	21.81	21.3±1
	9538	1907.6	21.88	21.3±1
HSUPA Subtest3	9262	1852.4	21.82	21.3±1
	9400	1880	21.84	21.3±1
	9538	1907.6	21.87	21.3±1
HSUPA Subtest4	9262	1852.4	21.86	21.3±1
	9400	1880	21.82	21.3±1
	9538	1907.6	21.86	21.3±1
HSUPA Subtest5	9262	1852.4	21.86	21.3±1
	9400	1880	21.89	21.3±1
	9538	1907.6	21.84	21.3±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	23.11	23±1
	1413	1732.6	23.14	23±1
	1512	1752.4	23.22	23±1
HSDPA Subtest1	1313	1712.6	21.23	21.3±1
	1413	1732.6	21.11	21.3±1
	1512	1752.4	21.44	21.3±1
HSDPA Subtest2	1313	1712.6	21.32	21.3±1
	1413	1732.6	21.21	21.3±1
	1512	1752.4	21.11	21.3±1
HSDPA Subtest3	1313	1712.6	20.67	21.3±1
	1413	1732.6	20.74	21.3±1
	1512	1752.4	20.79	21.3±1
HSDPA Subtest4	1313	1712.6	20.61	21.3±1
	1413	1732.6	20.68	21.3±1
	1512	1752.4	20.92	21.3±1
HSUPA Subtest1	1313	1712.6	21.44	21.3±1
	1413	1732.6	21.33	21.3±1
	1512	1752.4	21.29	21.3±1
HSUPA Subtest2	1313	1712.6	21.35	21.3±1
	1413	1732.6	21.22	21.3±1
	1512	1752.4	21.19	21.3±1
HSUPA Subtest3	1313	1712.6	20.56	21.3±1
	1413	1732.6	20.67	21.3±1
	1512	1752.4	20.78	21.3±1
HSUPA Subtest4	1313	1712.6	21.43	21.3±1
	1413	1732.6	21.49	21.3±1
	1512	1752.4	21.32	21.3±1
HSUPA Subtest5	1313	1712.6	20.78	21.3±1
	1413	1732.6	20.99	21.3±1
	1512	1752.4	20.22	21.3±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	24.51	V	6.8	0.53	30.78	38.45
824.2	23.75	H	6.8	0.53	30.02	38.45
836.6	24.59	V	6.8	0.53	30.86	38.45
836.6	23.72	H	6.8	0.53	29.99	38.45
848.8	24.48	V	6.9	0.53	30.85	38.45
848.8	23.65	H	6.9	0.53	30.02	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.83	V	7.88	0.85	30.86	33
1850.2	22.48	H	7.88	0.85	29.51	33
1880	23.79	V	7.88	0.85	30.82	33
1880	22.51	H	7.88	0.85	29.54	33
1909.8	23.86	V	7.86	0.85	30.87	33
1909.8	22.54	H	7.86	0.85	29.55	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	23.44	V	6.8	0.53	29.71	38.45
824.2	23.11	H	6.8	0.53	29.38	38.45
836.6	24.18	V	6.8	0.53	30.45	38.45
836.6	23.21	H	6.8	0.53	29.48	38.45
848.8	24.11	V	6.9	0.53	30.48	38.45
848.8	24.11	H	6.9	0.53	30.48	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	23.17	V	7.88	0.85	30.2	33
1850.2	22.11	H	7.88	0.85	29.14	33
1880	23.22	V	7.88	0.85	30.25	33
1880	22.01	H	7.88	0.85	29.04	33
1909.8	23.24	V	7.86	0.85	30.25	33
1909.8	22.13	H	7.86	0.85	29.14	33

EGPRS(MCS5):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	20.11	V	6.8	0.53	26.38	38.45
824.2	19.81	H	6.8	0.53	26.08	38.45
836.6	20.13	V	6.8	0.53	26.4	38.45
836.6	20.55	H	6.8	0.53	26.82	38.45
848.8	20.44	V	6.9	0.53	26.81	38.45
848.8	20.13	H	6.9	0.53	26.5	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	20.13	V	7.88	0.85	27.16	33
1850.2	19.88	H	7.88	0.85	26.91	33
1880	19.8	V	7.88	0.85	26.83	33
1880	20.32	H	7.88	0.85	27.35	33
1909.8	20.41	V	7.86	0.85	27.42	33
1909.8	19.88	H	7.86	0.85	26.89	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	13.08	V	6.8	0.53	19.35	38.45
826.4	12.34	H	6.8	0.53	18.61	38.45
835	13.11	V	6.8	0.53	19.38	38.45
835	12.29	H	6.8	0.53	18.56	38.45
846.6	13.06	V	6.9	0.53	19.43	38.45
846.6	12.32	H	6.9	0.53	18.69	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	16.17	V	7.88	0.85	23.2	33
1852.4	15.34	H	7.88	0.85	22.37	33
1880	16.22	V	7.88	0.85	23.25	33
1880	15.29	H	7.88	0.85	22.32	33
1907.6	16.14	V	7.86	0.85	23.15	33
1907.6	15.31	H	7.86	0.85	22.32	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	15.32	V	7.76	0.82	22.26	30
1712.4	15.19	H	7.76	0.82	22.13	30
1740	14.89	V	7.76	0.82	21.83	30
1740	15.41	H	7.76	0.82	22.35	30
1752.6	15.21	V	7.74	0.82	22.13	30
1752.6	14.67	H	7.74	0.82	21.59	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.88	V	6.8	0.53	19.15	38.45
826.4	12.17	H	6.8	0.53	18.44	38.45
835	13.02	V	6.8	0.53	19.29	38.45
835	12.11	H	6.8	0.53	18.38	38.45
846.6	12.89	V	6.9	0.53	19.26	38.45
846.6	12.11	H	6.9	0.53	18.48	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	15.02	V	7.88	0.85	22.05	33
1852.4	14.13	H	7.88	0.85	21.16	33
1880	15.32	V	7.88	0.85	22.35	33
1880	14.22	H	7.88	0.85	21.25	33
1907.6	15.07	V	7.86	0.85	22.08	33
1907.6	14.44	H	7.86	0.85	21.45	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	13.11	V	7.76	0.82	20.05	30
1712.4	13.21	H	7.76	0.82	20.15	30
1740	12.98	V	7.76	0.82	19.92	30
1740	13.45	H	7.76	0.82	20.39	30
1752.6	13.35	V	7.74	0.82	20.27	30
1752.6	12.45	H	7.74	0.82	19.37	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	12.88	V	6.8	0.53	19.15	38.45
826.4	12.11	H	6.8	0.53	18.38	38.45
835	12.78	V	6.8	0.53	19.05	38.45
835	12.02	H	6.8	0.53	18.29	38.45
846.6	12.78	V	6.9	0.53	19.15	38.45
846.6	12.13	H	6.9	0.53	18.5	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	15.02	V	7.88	0.85	22.05	33
1852.4	14.27	H	7.88	0.85	21.3	33
1880	15.19	V	7.88	0.85	22.22	33
1880	15.22	H	7.88	0.85	22.25	33
1907.6	15.02	V	7.86	0.85	22.03	33
1907.6	14.28	H	7.86	0.85	21.29	33

EIRP for UMTS-FDD Band IV (Part 27H)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	13.45	V	7.76	0.82	20.39	30
1712.4	13.25	H	7.76	0.82	20.19	30
1740	12.77	V	7.76	0.82	19.71	30
1740	13.54	H	7.76	0.82	20.48	30
1752.6	12.19	V	7.74	0.82	19.11	30
1752.6	12.18	H	7.74	0.82	19.1	30

6.3 Peak-Average Ratio

Temperature	23°C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	May 18, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	<input checked="" type="checkbox"/>

Test Setup	
------------	---

Test Procedure	<p>According with KDB 971168 v02r02</p> <p>5.7.2 Alternate procedure for PAPR</p> <p>5.1.2 Peak power measurements with a peak power meter</p> <p>The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector.</p> <p>5.2.3 Average power measurement with average power meter</p> <p>As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions</p> <p>If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output</p>
----------------	---

Test Report	16070460-FCC-R1
Page	24 of 102

	<p>power level, then a conventional wide-band RF power meter can be used.</p> <p>If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER(PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.56	30.22	1.34
1880	31.56	30.24	1.32
1909.8	31.42	30.26	1.16

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	31.44	30.13	1.31
1880	31.32	30.14	1.18
1909.8	31.29	30.14	1.15

EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	27.13	26.45	0.68
1880	27.21	26.37	0.84
1909.8	27.1	26.39	0.71

RMC : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	25.46	22.74	2.72
1880	25.38	22.84	2.54
1907.6	25.69	22.55	3.14

UMTS-FDD Band 4 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	26.14	23.17	2.97
1740	26.24	23.21	3.03
1752.6	26.31	23.19	3.12

HSUPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.35	21.88	2.47
1880	24.41	21.56	2.85
1907.6	24.62	21.65	2.97

UMTS-FDD Band 4 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	24.21	21.12	3.09
1740	24.22	21.22	3
1752.6	24.19	21.35	2.84

HSDPA : UMTS-FDD Band 2 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	24.56	21.55	3.01
1880	24.61	21.64	2.97
1907.6	24.49	21.48	3.01


UMTS-FDD Band 4 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1712.4	24.12	21.45	2.67
1740	24.31	21.41	2.9
1752.6	24.12	21.35	2.77

6.4 Occupied Bandwidth

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	May 16&26, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	<input checked="" type="checkbox"/>
	b)	26 dB Bandwidth(kHz)	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	250.8869	317.222
190	836.6	247.4303	315.732
251	848.8	246.5866	320.293

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	247.8755	318.299
661	1880.0	248.7363	323.271
810	1909.8	244.3058	318.082

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	248.1894	317.483
190	836.6	247.2879	324.903
251	848.8	245.7257	327.128

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	247.2829	317.991
661	1880.0	246.6682	319.570
810	1909.8	243.0612	322.205

EGPRS (MCS 5):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	249.1155	327.127
190	836.6	249.3738	328.396
251	848.8	244.2298	309.993

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	247.8128	320.455
661	1880.0	250.3645	323.688
810	1909.8	248.8804	325.581

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2012	4.894
4175	835.0	4.2164	4.910
4233	846.6	4.1934	4.882

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2112	4.869
9400	1880.0	4.2263	4.914
9538	1907.6	4.2048	4.909

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.2230	4.918
1413	1732.6	4.2233	4.913
1512	1752.4	4.2170	4.909

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2118	4.874
4175	835.0	4.2097	4.867
4233	846.6	4.2066	4.899

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2158	4.931
9400	1880.0	4.2158	4.913
9538	1907.6	4.2287	4.915

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.2244	4.945
1413	1732.6	4.2445	4.974
1512	1752.4	4.2346	4.897

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2225	4.898
4175	835.0	4.2099	4.878
4233	846.6	4.2026	4.872

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2103	4.907
9400	1880.0	4.2205	4.908
9538	1907.6	4.2181	4.895

UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1712.6	4.2263	4.895
1413	1732.6	4.2313	4.870
1512	1752.4	4.2161	4.914

Test Plots


GMS Voice:




GPRS:




EGPRS:




RMC:






Band IV BW - Low CH 1852.4MHz





Band IVBW - Mid CH 1880MHz




Band IV BW - High CH 1907.6MHz

HSUPA:






Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

HSDPA:






Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	May 17&26, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:


Cellular Band (Part 22H) result




GSM 850 - Low Channel-1




GSM 850 - Low Channel-2




GSM 850 Middle Channel-1



GSM 850 Middle Channel-2




GSM 850 - High Channel-1




GSM 850 - High Channel-2


PCS Band (Part24E) result




PCS1900 - Low Channel-1




PCS 1900 - Low Channel-2




PCS1900 - Middle Channel-1



PCS 1900 - Middle Channel-2





PCS1900 - High Channel-1





PCS 1900 - High Channel-2

GPRS:



Cellular Band (Part 22H) result



GSM 850 - Low Channel-1




GSM 850 Middle Channel-1



GSM 850 - High Channel-1


GSM 850 - High Channel-2

PCS Band (Part24E) result




EGPRS (MCS 5):

Cellular Band (Part 22H) result




PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)




UMTS-FDD Band II (Part 24E)




Band II - Low Channel-1




Band II - Low Channel-2




Band II - Middle Channel-1



Band II - Middle Channel-2




Band II - High Channel-1




Band II - High Channel-2

UMTS-FDD Band IV (Part 27)




HSUPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSDPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)



UMTS-FDD Band IV (Part 27)




6.6 Spurious Radiated Emissions

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	May 17, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	<input checked="" type="checkbox"/>

Test setup	 <p>The diagram illustrates the test setup. A turntable is placed on a ground plane, with EUT & Support Units on top. The turntable is 1.5m high. A measurement antenna is positioned 3m away from the turntable. The antenna is mounted on a tower with a 1-4m variable height. A test receiver is connected to the antenna.</p>
------------	---

Test Procedure	<ol style="list-style-type: none"> The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. <p>Sample Calculation:</p> <p>EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)</p>
----------------	---

Test Report	16070460-FCC-R1
Page	60 of 102

Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.51	V	7.95	0.78	-36.34	-13	-23.34
1648.4	-43.18	H	7.95	0.78	-36.01	-13	-23.01
148.7	-46.58	V	1.2	0.19	-45.57	-13	-32.57
382.5	-52.19	H	6.6	0.3	-45.89	-13	-32.89

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.28	V	7.95	0.78	-36.11	-13	-23.11
1673.2	43.61	H	7.95	0.78	50.78	-13	63.78
148.3	-46.37	V	1.2	0.19	-45.36	-13	-32.36
382.6	-52.13	H	6.6	0.3	-45.83	-13	-32.83

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-43.91	V	7.95	0.78	-36.74	-13	-23.74
1697.6	-43.65	H	7.95	0.78	-36.48	-13	-23.48
148.4	-46.72	V	1.2	0.19	-45.71	-13	-32.71
382.7	-52.34	H	6.6	0.3	-46.04	-13	-33.04

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.56	V	10.25	2.73	-41.04	-13	-28.04
3700.4	-49.21	H	10.25	2.73	-41.69	-13	-28.69
149.2	-47.38	V	1.2	0.19	-46.37	-13	-33.37
383.5	-51.83	H	6.6	0.3	-45.53	-13	-32.53

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.32	V	10.25	2.73	-40.8	-13	-27.8
3760	-49.05	H	10.25	2.73	-41.53	-13	-28.53
149.3	-47.41	V	1.2	0.19	-46.4	-13	-33.4
383.2	-51.56	H	6.6	0.3	-45.26	-13	-32.26

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.29	V	10.36	2.73	-40.66	-13	-27.66
3819.6	-48.55	H	10.36	2.73	-40.92	-13	-27.92
148.9	-47.38	V	1.2	0.19	-46.37	-13	-33.37
383.7	-51.94	H	6.6	0.3	-45.64	-13	-32.64

Note:

- 1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases
- 4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-46.59	V	7.95	0.78	-39.42	-13	-26.42
1652.8	-46.23	H	7.95	0.78	-39.06	-13	-26.06
148.4	-46.66	V	1.2	0.19	-45.65	-13	-32.65
382.1	-51.35	H	6.6	0.3	-45.05	-13	-32.05

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-47.13	V	7.95	0.78	-39.96	-13	-26.96
1670	-47.62	H	7.95	0.78	-40.45	-13	-27.45
148.7	-46.75	V	1.2	0.19	-45.74	-13	-32.74
382.3	-51.48	H	6.6	0.3	-45.18	-13	-32.18

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-48.36	V	7.95	0.78	-41.19	-13	-28.19
1693.2	-47.24	H	7.95	0.78	-40.07	-13	-27.07
148.5	-46.79	V	1.2	0.19	-45.78	-13	-32.78
382.7	-51.34	H	6.6	0.3	-45.04	-13	-32.04

Note:

1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.21	V	10.25	2.73	-40.69	-13	-27.69
3704.8	-49.39	H	10.25	2.73	-41.87	-13	-28.87
147.9	-46.88	V	1.2	0.19	-45.87	-13	-32.87
381.5	-51.45	H	6.6	0.3	-45.15	-13	-32.15

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.94	V	10.25	2.73	-41.42	-13	-28.42
3760	-49.89	H	10.25	2.73	-42.37	-13	-29.37
148.2	-46.08	V	1.2	0.19	-45.07	-13	-32.07
381.6	-51.67	H	6.6	0.3	-45.37	-13	-32.37

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.61	V	10.36	2.73	-40.98	-13	-27.98
3815.2	-47.74	H	10.36	2.73	-40.11	-13	-27.11
147.8	-45.56	V	1.2	0.19	-44.55	-13	-31.55
381.3	-51.86	H	6.6	0.3	-45.56	-13	-32.56

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-48.17	V	10.07	2.52	-40.62	-13	-27.62
3424.8	-48.25	H	10.07	2.52	-40.7	-13	-27.7
355.1	-53.17	V	6.4	0.26	-47.03	-13	-34.03
688.2	-54.22	H	7.1	0.42	-47.54	-13	-34.54

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-48.55	V	10.09	2.52	-40.98	-13	-27.98
3480	-49.1	H	10.09	2.52	-41.53	-13	-28.53
352.1	-54.11	V	6.4	0.26	-47.97	-13	-34.97
690.2	-54.05	H	7.1	0.42	-47.37	-13	-34.37

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-48.95	V	10.09	2.52	-41.38	-13	-28.38
3505.2	-48.58	H	10.09	2.52	-41.01	-13	-28.01
351.2	-55.02	V	6.4	0.26	-48.88	-13	-35.88
689.5	-55.19	H	7.1	0.42	-48.51	-13	-35.51

Note:

1, The testing has been conformed to $10 \times 1752.6 \text{ MHz} = 17.526 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

6.7 Band Edge

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	May 16&26, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	<input checked="" type="checkbox"/>
Test setup			
Procedure	<ul style="list-style-type: none"> - The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.8	-13
849.0200	-17.18	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9975	-18.45	-13
1909.9975	-23.95	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9750	-16.41	-13
849.0200	-16.66	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9925	-18.97	-13
1910.0050	-20.02	-13

EGPRS (MCS5):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9850	-16.85	-13
849.0050	-16.92	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9985	-18.96	-13
1910.0050	-20.04	-13

RCM:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.900	-30.65	-13
849.900	-26.18	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.050	-32.75	-13
1910.025	-32.98	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1708.825	-25.84	-13
1756.350	-31.33	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.675	-29.49	-13
849.750	-28.11	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.700	-35.35	-13
1910.850	-34.59	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-25.42	-13
1755.025	-27.09	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
822.950	-28.51	-13
849.225	-28.20	-13

UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-34.66	-13
1910.425	-35.75	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.950	-25.94	-13
1755.025	-27.05	-13


GSM Voice:

Test Plots




GPRS:

Test Plots




EGPRS (MCS5):

Test Plots




RMC:

<p>Agilent 17:14:25 May 16, 2016 T</p> <p>Ref 40 dBm Atten 45 dB Mkr1 823.900 MHz -30.65 dBm</p> <p>Marker 823.900000 MHz -30.65 dBm</p> <p>Center 824 MHz #Res BW 30 kHz #Sweep 22.64 ms (401 pts) Span 10 MHz</p> <p>Option not installed</p>	<p>Agilent 17:12:29 May 16, 2016 T</p> <p>Ref 40 dBm Atten 45 dB Mkr1 849.900 MHz -26.18 dBm</p> <p>Marker 849.900000 MHz -26.18 dBm</p> <p>Center 849 MHz #Res BW 30 kHz #Sweep 22.64 ms (401 pts) Span 10 MHz</p> <p>Option not installed</p>
UMTS-FDD Band V - Low Channel	UMTS-FDD Band V - High Channel
<p>Note: Offset=Cable loss (4.0) + 10log (48.94/30)=4.0+2.1=6.1 dB</p>	<p>Note: Offset=Cable loss (4.0) + 10log (48.82/30)=4.0+2.1=6.1 dB</p>
<p>Agilent 17:26:53 May 16, 2016 T</p> <p>Ref 40 dBm Atten 45 dB Mkr1 1.849050 GHz -32.75 dBm</p> <p>Marker 1.849050000 GHz -32.75 dBm</p> <p>Center 1.85 GHz #Res BW 30 kHz #Sweep 22.64 ms (401 pts) Span 10 MHz</p> <p>Option not installed</p>	<p>Agilent 17:24:56 May 16, 2016 T</p> <p>Ref 40 dBm Atten 45 dB Mkr1 1.910650 GHz -32.98 dBm</p> <p>Marker 1.910650000 GHz -32.98 dBm</p> <p>Center 1.91 GHz #Res BW 30 kHz #Sweep 22.64 ms (401 pts) Span 10 MHz</p> <p>Option not installed</p>
UMTS-FDD Band II - Low Channel	UMTS-FDD Band II - High Channel
<p>Note: Offset=Cable loss (4.5) + 10log (48.69/30)=4.5+2.1=6.6 dB</p>	<p>Note: Offset=Cable loss (4.5) + 10log (49.09/30)=4.5+2.1=6.6 dB</p>



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(49.18/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.0) + 10log
(49.09/30)=4.5+2.1=6.1 dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(48.74/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(48.99/30)=4.0+2.1=6.1 dB



UMTS-FDD Band II - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(49.31/30)=4.5+2.2=6.7 dB



UMTS-FDD Band II - High Channel


Note: Offset=Cable loss (4.5) + 10log
(49.15/30)=4.5+2.1=6.6 dB

Test Report	16070460-FCC-R1
Page	77 of 102



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(49.45/30)=4.5+2.2=6.6 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(48.97/30)=4.5+2.1=6.6 dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(48.98/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(48.72/30)=4.0+2.1=6.1 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(49.07/30)=4.5+2.1=6.6 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(48.95/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(48.95/30)=4.5+2.1=6.6 dB




UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log
(49.14/30)=4.5+2.1=6.6 dB

6.8 Frequency Stability

Temperature	24°C
Relative Humidity	51%
Atmospheric Pressure	1027mbar
Test date :	May 18, 2016
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	<p>According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:</p> <p>Frequency Tolerance for Transmitters in the Public Mobile Services</p> <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>45 to 512</td><td>2.5</td><td>5.0</td><td>.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 29.</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960.</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> <p>According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.</p>	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	45 to 512	2.5	5.0	.0	821 to 896	1.5	2.5	2.5	928 to 29.	5.0	N/A	N/A	929 to 960.	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	<input checked="" type="checkbox"/>
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
45 to 512	2.5	5.0	.0																																
821 to 896	1.5	2.5	2.5																																
928 to 29.	5.0	N/A	N/A																																
929 to 960.	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup																																			

Test Report	16070460-FCC-R1
Page	81 of 102

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0239	2.5
0		16	0.0191	2.5
10		15	0.0179	2.5
20		13	0.0155	2.5
30		10	0.0120	2.5
40		15	0.0179	2.5
50		20	0.0239	2.5
55		19	0.0227	2.5
25	4.2	19	0.0227	2.5
	3.5	20	0.0239	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0106	2.5
0		17	0.0090	2.5
10		14	0.0074	2.5
20		9	0.0048	2.5
30		10	0.0053	2.5
40		13	0.0069	2.5
50		19	0.0101	2.5
55		20	0.0106	2.5
25	4.2	19	0.0101	2.5
	3.5	17	0.0090	2.5

GPRS:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0227	2.5
0		18	0.0215	2.5
10		12	0.0143	2.5
20		11	0.0131	2.5
30		10	0.0120	2.5
40		16	0.0191	2.5
50		17	0.0203	2.5
55		21	0.0251	2.5
25	4.2	22	0.0263	2.5
	3.5	24	0.0287	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		12	0.0064	2.5
10		10	0.0053	2.5
20		4	0.0021	2.5
30		15	0.0080	2.5
40		18	0.0096	2.5
50		19	0.0101	2.5
55		20	0.0106	2.5
25	4.2	18	0.0096	2.5
	3.5	22	0.0117	2.5

EGPRS (MCS5):

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	22	0.0263	2.5
0		20	0.0239	2.5
10		17	0.0203	2.5
20		13	0.0155	2.5
30		14	0.0167	2.5
40		19	0.0227	2.5
50		17	0.0203	2.5
55		20	0.0239	2.5
25	4.2	25	0.0299	2.5
	3.5	23	0.0275	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	22	0.0117	2.5
0		21	0.0112	2.5
10		18	0.0096	2.5
20		12	0.0064	2.5
30		16	0.0085	2.5
40		17	0.0090	2.5
50		20	0.0106	2.5
55		22	0.0117	2.5
25	4.2	24	0.0128	2.5
	3.5	26	0.0138	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0240	2.5
0		19	0.0228	2.5
10		15	0.0180	2.5
20		10	0.0120	2.5
30		11	0.0132	2.5
40		12	0.0144	2.5
50		16	0.0192	2.5
55		25	0.0299	2.5
25	4.2	25	0.0299	2.5
	3.5	22	0.0263	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0112	2.5
0		18	0.0096	2.5
10		17	0.0090	2.5
20		10	0.0053	2.5
30		19	0.0101	2.5
40		22	0.0117	2.5
50		25	0.0133	2.5
55		26	0.0138	2.5
25	4.2	21	0.0112	2.5
	3.5	20	0.0106	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	18	0.0096	2.5
0		17	0.0090	2.5
10		15	0.0080	2.5
20		9	0.0048	2.5
30		10	0.0053	2.5
40		12	0.0064	2.5
50		13	0.0069	2.5
55		15	0.0080	2.5
25	4.2	22	0.0117	2.5
	3.5	26	0.0138	2.5

HSUPA:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	22	0.0263	2.5
0		17	0.0204	2.5
10		14	0.0168	2.5
20		13	0.0156	2.5
30		10	0.0120	2.5
40		12	0.0144	2.5
50		15	0.0180	2.5
55		22	0.0263	2.5
25	4.2	19	0.0228	2.5
	3.5	18	0.0216	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	19	0.0101	2.5
0		17	0.0090	2.5
10		16	0.0085	2.5
20		9	0.0048	2.5
30		18	0.0096	2.5
40		21	0.0112	2.5
50		27	0.0144	2.5
55		29	0.0154	2.5
25	4.2	22	0.0117	2.5
	3.5	25	0.0133	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	20	0.0106	2.5
0		19	0.0101	2.5
10		17	0.0090	2.5
20		8	0.0043	2.5
30		9	0.0048	2.5
40		11	0.0059	2.5
50		15	0.0080	2.5
55		17	0.0090	2.5
25	4.2	24	0.0128	2.5
	3.5	27	0.0144	2.5

HSDPA:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	23	0.0275	2.5
0		18	0.0216	2.5
10		15	0.0180	2.5
20		11	0.0132	2.5
30		8	0.0096	2.5
40		12	0.0144	2.5
50		16	0.0192	2.5
55		21	0.0251	2.5
25	4.2	20	0.0240	2.5
	3.5	19	0.0228	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0112	2.5
0		18	0.0096	2.5
10		15	0.0080	2.5
20		10	0.0053	2.5
30		16	0.0085	2.5
40		20	0.0106	2.5
50		15	0.0080	2.5
55		17	0.0090	2.5
25	4.2	21	0.0112	2.5
	3.5	22	0.0117	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.7	21	0.0112	2.5
0		16	0.0085	2.5
10		15	0.0080	2.5
20		10	0.0053	2.5
30		11	0.0059	2.5
40		12	0.0064	2.5
50		16	0.0085	2.5
55		15	0.0080	2.5
25	4.2	23	0.0122	2.5
	3.5	25	0.0133	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/16/2015	09/15/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Temperature/Humidity Chamber	UHL-270	001	10/09/2015	10/08/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/24/2016	03/23/2017	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Amplifier	SMC150D	R1553-0313	03/09/2016	03/08/2017	<input checked="" type="checkbox"/>
Power Amplifier	S41-25D	R1553-0314	05/28/2015	05/27/2016	<input checked="" type="checkbox"/>
Tunable Notch Filter	3NF-800/1000-S	AA4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>

Test Report	16070460-FCC-R1
Page	92 of 102


Tunable Notch Filter	3NF- 1000/2000-S	AM 4	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo



Whole Package View



Adapter - Front View



EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View




EUT - Right View


Annex B.ii. Photograph: EUT Internal Photo



Cover Off - Top View 1



Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard - Rear View



LCD – Front View



LCD – Rear View



GSM/PCS/UMTS-FDD Antenna View




LTE - Antenna View




WIFI/BT/BLE/GPS - Antenna View

Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	JML050200A	Y11243578

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	Y1124222

Test Report	16070460-FCC-R1
Page	100 of 102

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Test Report	16070460-FCC-R1
Page	101 of 102

Annex D. User Manual / Block Diagram / Schematics / Partlist

N/A

Test Report	16070460-FCC-R1
Page	102 of 102

Annex E. DECLARATION OF SIMILARITY

N/A