

**FCC PART 15B**  
**MEASUREMENT AND TEST REPORT**  
**FOR**

**Verykool USA Inc**

**4350 Executive Dr. #100, San Diego**

**FCC ID: WA6R620**

<b>Report Concerns:</b> Original Report	<b>Equipment Type:</b> GSM/GPRS Dual-band Mobile Phone
<b>Model:</b>	<u>R620</u>
<b>Report No.:</b>	<u>STR11088125I-3</u>
<b>Test Date:</b>	<u>2011-08-16 to 2011-08-22</u>
<b>Issue Date:</b>	<u>2011-09-01</u>
<b>Tested By:</b>	<u>Susan Su / Engineer</u> <i>Susan Su</i>
<b>Reviewed By:</b>	<u>Lahm Peng / EMC Manager</u> <i>Lahm peng</i>
<b>Approved &amp; Authorized By:</b>	<u>Jandy so / PSQ Manager</u> <i>Jandyso</i>
<b>Prepared By:</b>	<b>SEM.Test Compliance Service Co., Ltd</b> 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd.

**TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	3
1.3 TEST METHODOLOGY.....	3
1.4 TEST FACILITY.....	4
1.5 EUT EXERCISE SOFTWARE.....	4
1.6 ACCESSORIES EQUIPMENT LIST AND DETAILS.....	4
1.7 EUT CABLE LIST AND DETAILS.....	4
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>5</b>
<b>3. §15.107 (A)- CONDUCTED EMISSION.....</b>	<b>6</b>
3.1 MEASUREMENT UNCERTAINTY.....	6
3.2 TEST EQUIPMENT LIST AND DETAILS.....	6
3.3 TEST PROCEDURE.....	6
3.4 BASIC TEST SETUP BLOCK DIAGRAM.....	6
3.5 ENVIRONMENTAL CONDITIONS.....	7
3.6 TEST RECEIVER SETUP.....	7
3.7 SUMMARY OF TEST RESULTS/PLOTS.....	7
3.8 CONDUCTED EMISSIONS TEST DATA.....	7
<b>4. §15.109(A)- RADIATED EMISSION.....</b>	<b>10</b>
4.1 MEASUREMENT UNCERTAINTY.....	10
4.2 TEST EQUIPMENT LIST AND DETAILS.....	10
4.3 TEST PROCEDURE.....	10
4.4 TEST RECEIVER SETUP.....	11
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	11
4.6 ENVIRONMENTAL CONDITIONS.....	11
4.7 SUMMARY OF TEST RESULTS/PLOTS.....	11

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Verykool USA Inc  
Address of applicant: 4350 Executive Dr. #100, San Diego

Manufacturer: Verykool Wireless Technology Ltd.  
Address of manufacturer: Room 1701, Reward Building C, No.203, 2nd Section of Wangjing, Li Ze Zhong Yuan, ChaoYang District, Beijing, P.R. of China 100102

#### General Description of E.U.T

Items	Description
EUT Description:	GSM/GPRS Dual-band Mobile Phone
Trade Name:	verykool
Model No.:	R620
Rated Voltage:	Battery DC 3.7V with Power adaptor
Rated Current:	2A
For more information refer to the circuit diagram form and the user's manual.	

*The test data is gathered from a production sample, provided by the manufacturer.*

### 1.2 Test Standards

The following report is prepared on behalf of the Verykool USA Inc in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15.107, and 15.109 rules.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

### 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible susceptibility against the tested phenomena. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the system components. The test software, provided by the customer, is started while the EUT is on to simulate the normal work. under the Windows XP terminal.

## 1.6 Accessories Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	ASUS	X50R	/

## 1.7 EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.1	Shielded	Without Core
Earphone Cable	1.5	Unshielded	Without Core

---

## 2. SUMMARY OF TEST RESULTS

---

Description of Test	Result
§15.107 (a) Conducted Emission	Compliant
§15.109(a) Radiated Emission	Compliant

### 3. §15.107 (a)- CONDUCTED EMISSION

#### 3.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is  $\pm 2.88$  dB.

#### 3.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2010-12-20	2011-12-19
L.I.S.N	Schwarz beck	NSLK8126	8126-224	2010-12-20	2011-12-19
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2010-12-20	2011-12-19


#### 3.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.107 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

#### 3.4 Basic Test Setup Block Diagram



### 3.5 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 3.6 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:


Start Frequency ..... 150 kHz  
Stop Frequency..... 30 MHz  
Sweep Speed ..... Auto  
IF Bandwidth..... 10 kHz  
Quasi-Peak Adapter Bandwidth ..... 9 kHz  
Quasi-Peak Adapter Mode ..... Normal

### 3.7 Summary of Test Results/Plots

According to the data in section 3.8, the EUT complied with the FCC Part 15B Conducted margin for a Class B device, with the *worst* margin reading of:


**-2.69 dB $\mu$ V at 1.250 MHz in the Line, Average detector, 0.15-30MHz**

### 3.8 Conducted Emissions Test Data

**Plot of Conducted Emissions Test Data***Conducted Disturbance**EUT: GSM/GPRS Dual-band Mobile Phone**M/N: R620**Operating Condition: Charging**Test Specification: N**Comment: 120V/60Hz*

EDIT PEAK LIST (Prescan Results)			
Trace1:	-QP		
Trace2:	-AV		
Trace3:	---		
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Max Peak	314 kHz	49.09	-10.76
2 Average	466 kHz	38.90	-7.68
1 Max Peak	474 kHz	47.50	-8.94
2 Average	1.25 MHz	33.11	-12.88
1 Max Peak	1.258 MHz	45.02	-10.97
1 Max Peak	8.286 MHz	47.64	-12.35
2 Average	9.254 MHz	33.79	-16.20
1 Max Peak	12.706 MHz	51.53	-8.46



**Plot of Conducted Emissions Test Data***Conducted Disturbance**EUT: GSM/GPRS Dual-band Mobile Phone**M/N: R620**Operating Condition: Charging**Test Specification: L**Comment: 120V/60Hz*

EDIT PEAK LIST (Prescan Results)				
Trace1:	-QP			
Trace2:	-AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBμV	DELTA	LIMIT dB
2 Average	314 kHz	41.56	-8.29	
1 Max Peak	466 kHz	49.62	-6.96	
2 Average	626 kHz	43.12	-2.87	
1 Max Peak	1.25 MHz	49.85	-6.14	
2 Average	1.25 MHz	43.30	-2.69	
2 Average	6.246 MHz	40.44	-9.55	
1 Max Peak	10.138 MHz	50.53	-9.46	
1 Max Peak	13.126 MHz	53.98	-6.02	
2 Average	14.034 MHz	40.35	-9.64	

## 4. §15.109(a)- RADIATED EMISSION

### 4.1 Measurement Uncertainty

Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any radiation emissions measurement is  $\pm 5.10$  dB.

### 4.2 Test Equipment List and Details


Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Spectrum Analyzer	R&S	FSP	836079/035	2010-12-20	2011-12-19
EMI Test Receiver	R&S	ESVB	825471/005	2010-12-20	2011-12-19
Positioning Controller	C&C	CC-C-1F	N/A	2010-12-20	2011-12-19
RF Switch	EM	EMSW18	SW060023	2010-12-20	2011-12-19
Pre-amplifier	Agilent	8447F	3113A06717	2010-12-20	2011-12-19
Pre-amplifier	Compliance Direction	PAP-0118	24002	2010-12-20	2011-12-19
Trilog Broadband Antenna	SCHWARZBECK	VULB9163	9163-333	2011-01-09	2012-01-08
Horn Antenna	ETS	3117	00086197	2011-01-09	2012-01-08

### 4.3 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 and FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



#### 4.4 Test Receiver Setup

During the radiated emission test, the test receiver was set with the following configurations:

Start Frequency ..... 30 MHz  
 Stop Frequency..... 1000 MHz  
 Sweep Speed ..... Auto  
 IF Bandwidth..... 100 kHz  
 Quasi-Peak Adapter Bandwidth ..... 120 kHz  
 Quasi-Peak Adapter Mode ..... Normal

#### 4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15B Limit}$$

#### 4.6 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### 4.7 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC Part 15B Class B standards, and had the worst margin of:


**-3.91 dBμV at 919.2866 MHz in the Horizontal polarization, Reading and Writing mode, 30 MHz to 1 GHz, 3Meters**

**-4.90 dBμV at 33.3279 MHz in the Vertical polarization, Charging mode, 30 MHz to 1 GHz, 3Meters**


**Plot of Radiation Emissions Test Data***Radiated Disturbance**EUT: GSM/GPRS Dual-band Mobile Phone**M/N: R620**Operating Condition: Reading and Writing**Test Specification: Horizontal & Vertical**Comment: AC 120V/60Hz connect to PC, USB 5V**Horizontal*

No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( ° )	Height (cm)	Remark
1	482.2156	27.79	12.67	40.46	46.00	-5.54	58	100	peak
2	535.7073	24.93	15.21	40.14	46.00	-5.86	75	100	peak
3	919.2866	20.83	21.26	42.09	46.00	-3.91	301	100	peak

Vertical




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	155.9101	30.38	4.35	34.73	43.50	-8.77	330	100	peak
2	499.4247	22.57	14.36	36.93	46.00	-9.07	55	100	peak
3	535.7073	24.08	15.21	39.29	46.00	-6.71	43	100	peak

*Radiated Disturbance**EUT: GSM/GPRS Dual-band Mobile Phone**M/N: R620**Operating Condition: Charging**Test Specification: Horizontal & Vertical**Comment: AC 120V/60Hz, DC 5V by adapter**Horizontal*

No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	33.0950	19.45	6.77	26.22	40.00	-13.78	305	100	peak
2	70.5836	24.87	3.52	28.39	40.00	-11.61	79	100	peak
3	76.7808	28.06	3.12	31.18	40.00	-8.82	61	100	peak

Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( ° )	(cm)	
1	33.3279	28.33	6.77	35.10	40.00	-4.90	114	100	peak
2	38.0783	26.37	7.61	33.98	40.00	-6.02	69	100	peak
3	63.0916	26.16	6.32	32.48	40.00	-7.52	56	100	peak

\*\*\*\*\* END OF REPORT \*\*\*\*\*