

# RF EXPOSURE REPORT



Report No.: 16070460-FCC-H2

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Tablet	
Model No.	TL8010	
Serial No.	N/A	
Test Standard	FCC 2.1093:2015	
Test Date	April 25 to May 25, 2016	
Issue Date	May 25, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
<i>Winnie Zhang</i>	<i>David Huang</i>	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

**SIEMIC (SHENZHEN-CHINA) LABORATORIES**

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070460-FCC-H2
Page	3 of 10

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	8
5.1 RF EXPOSURE.....	8
5.2 TEST RESULT .....	9

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070460-FCC-H2	NONE	Original	May 25, 2016

## 2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, CA 92122 USA
Manufacturer	Topwise
Manufacturer Add	5th floor,A8Music Building,No.1002,Keyuan Road,Hi-Teach Park,NanShan Districtt,Shenzhen

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

## 4. Equipment under Test (EUT) Information

Description of EUT: Tablet

Main Model: TL8010

Serial Model: N/A

Date EUT received: April 25, 2016

Test Date(s): April 25 to May 25, 2016

Antenna Gain:

GSM850: 0.61 dBi  
 PCS1900: 0.85 dBi  
 UMTS-FDD Band 5: 0.61 dBi  
 UMTS-FDD Band 2: 0.85 dBi  
 UMTS-FDD Band 4: -0.84 dBi  
 LTE Band 2: 0.85 dBi  
 LTE Band 4: -0.84 dBi  
 LTE Band 5: 0.61 dBi  
 LTE Band 7: 1.11 dBi  
 LTE Band 17: -4.77 dBi  
 Bluetooth/BLE/WIFI: 2.16 dBi  
 GPS: 1.74 dBi

Type of Modulation:

GSM / GPRS: GMSK  
 EGPRS: GMSK, 8PSK  
 UMTS-FDD: QPSK  
 LTE Band: QPSK, 16QAM  
 802.11b/g/n: DSSS, OFDM  
 Bluetooth: GFSK,  $\pi/4$ DQPSK, 8DPSK  
 BLE: GFSK  
 GPS: BPSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz  
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz  
 UMTS-FDD Band 5 TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz  
 UMTS-FDD Band 2 TX: 1852.4 ~ 1907.6 MHz;  
 RX: 1932.4 ~ 1987.6 MHz

Test Report	16070460-FCC-H2
Page	7 of 10

UMTS-FDD Band 4 TX :1712.4 ~ 1752.6 MHz;

RX : 2112.4 ~ 2152.6 MHz

LTE Band 2 TX: 1852.5 ~ 1907.5 MHz; RX : 1932.5 ~ 1987.5 MHz

LTE Band 4 TX: 1712.5 ~ 1752.5 MHz; RX : 2112.5 ~ 2152.5 MHz

LTE Band 5 TX: 826.5 ~ 846.5 MHz; RX : 871.5 ~ 891.5 MHz

LTE Band 7 TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz

LTE Band 17 TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz

WIFI: 802.11b/g/n(20M): 2412-2462 MHz

WIFI: 802.11n(40M): 2422-2452 MHz

Bluetooth& BLE: 2402-2480 MHz

GPS: 1575.42 MHz

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band 5: 102CH

UMTS-FDD Band 4: 202CH

UMTS-FDD Band 2: 277CH

Number of Channels:

WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Port:

Power Port, Earphone Port, USB Port

Adapter:

Model: JML050200A

Input: AC 100-240V; 50/60Hz;0.3A

Input Power:

Output: DC 5.0V,2.0A

Battery:

Capacity: 2030mAh

Voltage: 3.8V

Trade Name :

verykool

GPRS/EGPRS Multi-slot class

8/10/12

FCC ID:

WA6TL8010

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,<sup>16</sup> where

- $f_{\text{(GHz)}}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



## 5.2 Test Result

### Bluetooth Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	3.508	3.5±1	4.5	2.818	0.87	3
	Mid	2441	<b>5.03</b>	5±1	6	3.981	1.24	3
	High	2480	2.995	3.5±1	4.5	2.818	0.89	3
π /4 DQPSK	Low	2402	2.894	2±1	3.0	1.995	0.62	3
	Mid	2441	<b>4.497</b>	4.5±1	5.5	3.548	1.11	3
	High	2480	2.046	2±1	3.0	1.995	0.63	3
8-DPSK	Low	2402	3.102	2.5±1	3.5	2.239	0.69	3
	Mid	2441	<b>4.569</b>	4.5±1	5.5	3.548	1.11	3
	High	2480	2.272	2.5±1	3.5	2.239	0.71	3

### WIFI Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	9.27	8.5±1	9.5	8.913	2.77	3
	Mid	2442	<b>9.39</b>	8.5±1	9.5	8.913	2.79	3
	High	2472	8.68	8.5±1	9.5	8.913	2.80	3
802.11g	Low	2412	8.74	8.5±1	9.5	8.913	2.77	3
	Mid	2442	<b>8.78</b>	8.5±1	9.5	8.913	2.79	3
	High	2472	8.63	8.5±1	9.5	8.913	2.80	3
802.11n (20M)	Low	2412	<b>8.93</b>	8.5±1	9.5	8.913	2.77	3
	Mid	2442	8.48	8.5±1	9.5	8.913	2.79	3
	High	2472	8.31	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	7.95	8.5±1	9.5	8.913	2.77	3
	Mid	2442	<b>8.43</b>	8.5±1	9.5	8.913	2.79	3
	High	2462	7.55	8.5±1	9.5	8.913	2.80	3

### BLE Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-3.5	-3.5±1	-2.5	0.562	0.17	3
	Mid	2440	<b>-2.612</b>	-2.5±1	-1.5	0.708	0.22	3
	High	2480	-4.377	-3.5±1	-2.5	0.562	0.18	3

**Result:** Compliance

No SAR measurement is required.