

FCC PART 15.247

TEST REPORT

For

Zhongshan K-mate General Electronics Co.,Ltd.

NO.2, 5th Xinsheng Street, Gangkou Town, Zhongshan City, Guangdong, China

FCC ID: WAD-BTT004B

| | |
|---|---|
| Report Type: Original Report | Product Type: Bluetooth Dongle |
| Test Engineer: Leon Chen | leon chen |
| Report Number: R2DG140606008-00A | |
| Report Date: 2014-06-23 | |
| Reviewed By: Sula Huang RF Engineer | Sula Huang |
| Test Laboratory: | Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn |

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

| | |
|---|-----------|
| GENERAL INFORMATION..... | 4 |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) | 4 |
| OBJECTIVE | 4 |
| RELATED SUBMITTAL(S)/GRANT(S)..... | 4 |
| TEST METHODOLOGY | 4 |
| TEST FACILITY | 4 |
| SYSTEM TEST CONFIGURATION..... | 5 |
| DESCRIPTION OF TEST CONFIGURATION | 5 |
| EUT EXERCISE SOFTWARE | 5 |
| EQUIPMENT MODIFICATIONS | 5 |
| SUPPORT EQUIPMENT LIST AND DETAILS | 5 |
| EXTERNAL CABLE..... | 5 |
| BLOCK DIAGRAM OF TEST SETUP | 6 |
| SUMMARY OF TEST RESULTS | 7 |
| FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)..... | 8 |
| APPLICABLE STANDARD | 8 |
| FCC §15.203 - ANTENNA REQUIREMENT..... | 9 |
| APPLICABLE STANDARD | 9 |
| ANTENNA CONNECTOR CONSTRUCTION | 9 |
| FCC §15.207 – AC LINE CONDUCTED EMISSIONS..... | 10 |
| MEASUREMENT UNCERTAINTY..... | 10 |
| EUT SETUP | 10 |
| EMI TEST RECEIVER SETUP..... | 11 |
| TEST PROCEDURE | 11 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 11 |
| TEST EQUIPMENT LIST AND DETAILS..... | 12 |
| TEST RESULTS SUMMARY | 12 |
| TEST DATA | 12 |
| FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS..... | 15 |
| APPLICABLE STANDARD | 15 |
| MEASUREMENT UNCERTAINTY | 15 |
| EUT SETUP | 15 |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP | 16 |
| TEST PROCEDURE | 16 |
| TEST EQUIPMENT LIST AND DETAILS..... | 17 |
| CORRECTED AMPLITUDE & MARGIN CALCULATION | 17 |
| TEST RESULTS SUMMARY | 17 |
| TEST DATA | 17 |
| FCC §15.247(a) (1) - CHANNEL SEPARATION TEST | 26 |
| APPLICABLE STANDARD | 26 |
| TEST EQUIPMENT LIST AND DETAILS..... | 26 |
| TEST PROCEDURE | 26 |
| TEST DATA | 26 |
| FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING | 32 |

| | |
|--|-----------|
| APPLICABLE STANDARD | 32 |
| TEST PROCEDURE | 32 |
| TEST EQUIPMENT LIST AND DETAILS..... | 32 |
| TEST DATA | 32 |
| FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST | 38 |
| APPLICABLE STANDARD | 38 |
| TEST PROCEDURE | 38 |
| TEST EQUIPMENT LIST AND DETAILS..... | 38 |
| TEST DATA | 38 |
| FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)..... | 42 |
| APPLICABLE STANDARD | 42 |
| TEST PROCEDURE | 42 |
| TEST EQUIPMENT LIST AND DETAILS..... | 42 |
| TEST DATA | 42 |
| FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT | 58 |
| APPLICABLE STANDARD | 58 |
| TEST PROCEDURE | 58 |
| TEST EQUIPMENT LIST AND DETAILS..... | 58 |
| TEST DATA | 58 |
| FCC §15.247(d) - BAND EDGES TESTING | 64 |
| APPLICABLE STANDARD | 64 |
| TEST PROCEDURE | 64 |
| TEST EQUIPMENT LIST AND DETAILS..... | 64 |
| TEST DATA | 64 |

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Zhongshan K-mate General Electronics Co.,Ltd's product, model number: BTT004B(FCC ID: WAD-BTT004B) (the "EUT") in this report was a *Bluetooth Dongle*, which was measured approximately: 3.2cm (L) x 1.7 cm (W) x 0.6 cm(H), rated input voltage: DC5V from system.

All measurement and test data in this report was gathered from production sample serial number: 140606008. (Assigned by BACL, Dongguan). The EUT was received on 2014-06-09.

Objective

This report is prepared on behalf of Zhongshan K-mate General Electronics Co., Ltd. in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the Bluetooth BDR and EDR mode of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part15C JBP submissions with FCC ID: WAD-BTT004B.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

EUT Exercise Software

The software “CSR Bluesuite 2.5.0” was used, which was provided by manufacturer. The maximum power was set by default configuration.

| Test Software Version | | CSR Bluesuite 2.5.0 | | |
|-----------------------|---------------|---------------------|---------|---------|
| Test Frequency | | 2402MHz | 2441MHz | 2480MHz |
| Power Level Setting | GFSK | 63 | 63 | 63 |
| | $\pi/4$ DQPSK | 100 | 100 | 100 |
| | 8DPSK | 100 | 100 | 100 |

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

| Manufacturer | Description | Model | Serial Number |
|--------------|-------------|----------|----------------------|
| DELL | Laptop | PP11L | QDS-BRCM1017 |
| HP | Printer | C3941A | JPTVOB2337 |
| DELL | Keyboard | L100 | CNORH656658907BL05DC |
| SAST | Modem | AEM-2100 | 0293 |

External Cable

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port | To |
|-------------------|----------------|--------------|------------|------------------------|----------|
| Serial Cable | yes | No | 1.2 | Serial Port of Laptop | Modem |
| Parallel Cable | yes | No | 1.2 | ParallelPort of Laptop | Printer |
| USB Cable | Yes | No | 1.5 | USB Port of Laptop | Keyborad |

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test | Result |
|-------------------------------------|------------------------------------|------------|
| FCC §15.247 (i) & §1.1310 & §2.1091 | Maximum Permissible Exposure (MPE) | Compliance |
| §15.203 | Antenna Requirement | Compliance |
| §15.207 (a) | Conducted Emissions | Compliance |
| §15.205, §15.209, §15.247(d) | Radiated Emissions | Compliance |
| §15.247 (a)(1) | 20 dB Bandwidth | Compliance |
| §15.247(a)(1) | Channel Separation Test | Compliance |
| §15.247(a)(1)(iii) | Time of Occupancy (Dwell Time) | Compliance |
| §15.247(a)(1)(iii) | Quantity of hopping channel Test | Compliance |
| §15.247(b)(1) | Peak Output Power Measurement | Compliance |
| §15.247(d) | Band Edges | Compliance |

FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure | | | | |
|---|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | / | / | f/1500 | 30 |
| 1500–100,000 | / | / | 1.0 | 30 |

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

| Mode | Frequency (MHz) | Antenna Gain | | Conducted Power | | Evaluation Distance (cm) | Power Density (mW/cm ²) | MPE Limit (mW/cm ²) |
|------|-----------------|--------------|-----------|-----------------|------|--------------------------|-------------------------------------|---------------------------------|
| | | (dBi) | (numeric) | (dBm) | (mW) | | | |
| GFSK | 2441 | 0 | 1 | 4.84 | 3.05 | 20 | 0.0006 | 1.0 |

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one integral antenna arrangement, which was permanently attached and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 – AC LINE CONDUCTED EMISSIONS

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

| Measurement | U_{cisp} |
|---|------------|
| Conducted disturbance at mains port using AMN (150 kHz to 30 MHz) | 3.4 dB |

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 Class B limits.

The spacing between the peripherals was 10 cm.

The adapter of laptop was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz |

Test Procedure

During the conducted emission test, the adapter of laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|--------------------|---------|---------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESCS 30 | 830245/006 | 2013-11-20 | 2014-11-19 |
| R&S | Two-line V-network | ENV216 | 3560.6550.12 | 2014-01-22 | 2015-01-21 |
| R&S | L.I.S.N | ESH3-Z5 | 100113 | N/A | N/A |
| R&S | Test Software | EMC32 | Version8.53.0 | N/A | N/A |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

25.3 dB at 0.915445 MHz in the Neutral conducted mode


Test Data**Environmental Conditions**

| | |
|---------------------------|----------|
| Temperature: | 28 °C |
| Relative Humidity: | 60% |
| ATM Pressure: | 99.6 kPa |

The testing was performed by Leon Chen on 2014-06-11.


Test mode: Transmitting

AC120 V, 60 Hz, Line:



| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.253797 | 30.1 | 9.000 | L1 | 10.7 | 31.6 | 61.6 | Compliance |
| 0.297644 | 29.5 | 9.000 | L1 | 10.7 | 30.8 | 60.3 | Compliance |
| 0.515791 | 26.5 | 9.000 | L1 | 10.4 | 29.5 | 56.0 | Compliance |
| 0.604902 | 23.9 | 9.000 | L1 | 10.5 | 32.1 | 56.0 | Compliance |
| 0.624492 | 22.6 | 9.000 | L1 | 10.5 | 33.4 | 56.0 | Compliance |
| 0.799472 | 22.1 | 9.000 | L1 | 10.5 | 33.9 | 56.0 | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.243884 | 22.7 | 9.000 | L1 | 10.7 | 29.3 | 52.0 | Compliance |
| 0.487810 | 17.2 | 9.000 | L1 | 10.4 | 29.0 | 46.2 | Compliance |
| 0.726569 | 14.0 | 9.000 | L1 | 10.6 | 32.0 | 46.0 | Compliance |
| 0.915445 | 19.7 | 9.000 | L1 | 10.5 | 26.3 | 46.0 | Compliance |
| 0.937592 | 15.8 | 9.000 | L1 | 10.5 | 30.2 | 46.0 | Compliance |
| 0.952654 | 15.8 | 9.000 | L1 | 10.5 | 30.2 | 46.0 | Compliance |

AC120 V, 60 Hz, Neutral:

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|------------|
| 0.240029 | 28.3 | 9.000 | N | 11.3 | 33.8 | 62.1 | Compliance |
| 0.304845 | 32.9 | 9.000 | N | 11.1 | 27.2 | 60.1 | Compliance |
| 0.499611 | 27.9 | 9.000 | N | 10.4 | 28.1 | 56.0 | Compliance |
| 0.614619 | 22.9 | 9.000 | N | 10.5 | 33.1 | 56.0 | Compliance |
| 0.629488 | 20.4 | 9.000 | N | 10.5 | 35.6 | 56.0 | Compliance |
| 0.720803 | 21.1 | 9.000 | N | 10.6 | 34.9 | 56.0 | Compliance |

| Frequency (MHz) | Average (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) | Comment |
|-----------------|----------------|-----------------|------|------------|-------------|--------------|------------|
| 0.240029 | 22.9 | 9.000 | N | 11.3 | 29.2 | 52.1 | Compliance |
| 0.472507 | 12.7 | 9.000 | N | 10.5 | 33.8 | 46.5 | Compliance |
| 0.786832 | 14.1 | 9.000 | N | 10.5 | 31.9 | 46.0 | Compliance |
| 0.915445 | 20.7 | 9.000 | N | 10.6 | 25.3 | 46.0 | Compliance |
| 0.937592 | 17.5 | 9.000 | N | 10.6 | 28.5 | 46.0 | Compliance |
| 0.952654 | 16.0 | 9.000 | N | 10.5 | 30.0 | 46.0 | Compliance |

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB

Table 1 – Values of U_{cisp}

| Measurement | U_{cisp} |
|--|------------|
| Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz) | 6.3 dB |
| Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz) | 5.2 dB |
| Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz) | 5.5 dB |

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range | RBW | Video B/W | IF B/W | Detector |
|-------------------|---------|-----------|---------|----------|
| 30 MHz – 1000 MHz | 120 kHz | 300 kHz | 120 kHz | QP |
| Above 1 GHz | 1MHz | 3 MHz | / | PK |
| | 1MHz | 10 Hz | / | Ave. |

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|-----------------------|-------------------|-------------|--------------------|------------------|----------------------|
| R&S | EMI Test Receiver | ESCI | 100224 | 2014-05-09 | 2015-05-08 |
| Sunol Sciences | Antenna | JB3 | A060611-1 | 2011-09-06 | 2014-09-05 |
| HP | Amplifier | 8447E | 2434A02181 | 2013-09-06 | 2014-09-05 |
| R&S | Spectrum Analyzer | FSEM | DE31388 | 2014-05-09 | 2015-05-08 |
| ETS LINDGREN | Horn Antenna | 3115 | 000 527 35 | 2012-09-06 | 2015-09-05 |
| Mini-Circuit | Amplifier | ZVA-213-S+ | 054201245 | 2014-02-19 | 2015-02-18 |
| Ducommun Technologies | Horn Antenna | ARH-4223-02 | 1007726-01 1304 | 2013-06-16 | 2014-06-15 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

11.92 dB at 4804 MHz in the Horizontal polarization of BDR Mode (GFSK)

Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 28.6 °C |
| Relative Humidity: | 67% |
| ATM Pressure: | 99.6 kPa |

The testing was performed by Leon Chen on 2014-06-16.

Mode: Transmitting

BDR Mode (GFSK):

| Frequency | Receiver | | Rx Antenna | | Cable loss (dB) | Amplifier Gain (dB) | Corrected Amplitude (dBμV/m) | FCC 15.247 | |
|--------------------------|----------------|---------------------|-------------|-------------|-----------------|---------------------|------------------------------|----------------|-------------|
| (MHz) | Reading (dBμV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB) | | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel: 2402 MHz | | | | | | | | | |
| 2402 | 92.59 | PK | H | 25.65 | 4.42 | 27.32 | 95.34 | N/A | N/A |
| 2402 | 82.43 | AV | H | 25.65 | 4.42 | 27.32 | 85.18 | N/A | N/A |
| 2402 | 92.47 | PK | V | 25.65 | 4.42 | 27.32 | 95.22 | N/A | N/A |
| 2402 | 82.97 | AV | V | 25.65 | 4.42 | 27.32 | 85.72 | N/A | N/A |
| 2376 | 37.99 | PK | H | 25.58 | 4.35 | 27.32 | 40.60 | 74.00 | 33.40 |
| 2376 | 27.29 | AV | H | 25.58 | 4.35 | 27.32 | 29.90 | 54.00 | 24.10 |
| 4804 | 44.08 | PK | H | 30.59 | 5.98 | 27.41 | 53.24 | 74.00 | 20.76 |
| 4804 | 32.92 | AV | H | 30.59 | 5.98 | 27.41 | 42.08 | 54.00 | 11.92 |
| 7206 | 30.96 | PK | H | 34.09 | 7.45 | 25.91 | 46.59 | 74.00 | 27.41 |
| 7206 | 18.86 | AV | H | 34.09 | 7.45 | 25.91 | 34.49 | 54.00 | 19.51 |
| 9608 | 28.81 | PK | H | 35.96 | 8.80 | 27.55 | 46.02 | 74.00 | 27.98 |
| 9608 | 17.74 | AV | H | 35.96 | 8.80 | 27.55 | 34.95 | 54.00 | 19.05 |
| 7315 | 31.26 | PK | H | 34.36 | 7.51 | 25.88 | 47.25 | 74.00 | 26.75 |
| 7315 | 19.85 | AV | H | 34.36 | 7.51 | 25.88 | 35.84 | 54.00 | 18.16 |
| 159.9 | 33.20 | QP | H | 12.78 | 1.53 | 21.44 | 26.07 | 43.50 | 17.43 |
| Middle Channel: 2441 MHz | | | | | | | | | |
| 2441 | 93.70 | PK | H | 25.75 | 4.40 | 27.34 | 96.51 | N/A | N/A |
| 2441 | 83.85 | AV | H | 25.75 | 4.40 | 27.34 | 86.66 | N/A | N/A |
| 2441 | 91.31 | PK | V | 25.75 | 4.40 | 27.34 | 94.12 | N/A | N/A |
| 2441 | 81.50 | AV | V | 25.75 | 4.40 | 27.34 | 84.31 | N/A | N/A |
| 4882 | 44.01 | PK | H | 30.79 | 6.08 | 27.42 | 53.46 | 74.00 | 20.54 |
| 4882 | 30.26 | AV | H | 30.79 | 6.08 | 27.42 | 39.71 | 54.00 | 14.29 |
| 7323 | 31.02 | PK | H | 34.38 | 7.51 | 25.88 | 47.03 | 74.00 | 26.97 |
| 7323 | 19.64 | AV | H | 34.38 | 7.51 | 25.88 | 35.65 | 54.00 | 18.35 |
| 9764 | 28.97 | PK | H | 36.33 | 8.83 | 27.20 | 46.93 | 74.00 | 27.07 |
| 9764 | 17.99 | AV | H | 36.33 | 8.83 | 27.20 | 35.95 | 54.00 | 18.05 |
| 7315 | 31.87 | PK | H | 34.36 | 7.51 | 25.88 | 47.86 | 74.00 | 26.14 |
| 7315 | 20.07 | AV | H | 34.36 | 7.51 | 25.88 | 36.06 | 54.00 | 17.94 |
| 1062 | 32.02 | PK | H | 22.46 | 2.63 | 26.59 | 30.52 | 74.00 | 43.48 |
| 1062 | 18.63 | AV | H | 22.46 | 2.63 | 26.59 | 17.13 | 54.00 | 36.87 |
| 159.9 | 32.68 | QP | H | 12.78 | 1.53 | 21.44 | 25.55 | 43.50 | 17.95 |
| High Channel: 2480 MHz | | | | | | | | | |
| 2480 | 94.21 | PK | H | 25.85 | 4.48 | 27.36 | 97.18 | N/A | N/A |
| 2480 | 84.41 | AV | H | 25.85 | 4.48 | 27.36 | 87.38 | N/A | N/A |
| 2480 | 92.72 | PK | V | 25.85 | 4.48 | 27.36 | 95.69 | N/A | N/A |
| 2480 | 82.93 | AV | V | 25.85 | 4.48 | 27.36 | 85.90 | N/A | N/A |
| 2483.5 | 46.96 | PK | H | 25.86 | 4.49 | 27.36 | 49.95 | 74.00 | 24.05 |
| 2483.5 | 29.59 | AV | H | 25.86 | 4.49 | 27.36 | 32.58 | 54.00 | 21.42 |
| 4960 | 43.87 | PK | H | 31.00 | 5.90 | 27.43 | 53.34 | 74.00 | 20.66 |
| 4960 | 30.10 | AV | H | 31.00 | 5.90 | 27.43 | 39.57 | 54.00 | 14.43 |
| 7440 | 31.30 | PK | H | 34.66 | 7.58 | 25.97 | 47.57 | 74.00 | 26.43 |
| 7440 | 19.78 | AV | H | 34.66 | 7.58 | 25.97 | 36.05 | 54.00 | 17.95 |
| 9920 | 28.81 | PK | H | 36.71 | 8.87 | 26.66 | 47.73 | 74.00 | 26.27 |
| 9920 | 17.90 | AV | H | 36.71 | 8.87 | 26.66 | 36.82 | 54.00 | 17.18 |
| 7315 | 31.67 | PK | H | 34.36 | 7.51 | 25.88 | 47.66 | 74.00 | 26.34 |
| 7315 | 19.95 | AV | H | 34.36 | 7.51 | 25.88 | 35.94 | 54.00 | 18.06 |
| 159.9 | 33.11 | QP | H | 12.78 | 1.53 | 21.44 | 25.98 | 43.50 | 17.52 |

EDR Mode ($\pi/4$ -DQPSK):

| Frequency | Receiver | | Rx Antenna | | Cable loss (dB) | Amplifier Gain (dB) | Corrected Amplitude (dBμV/m) | FCC 15.247 | |
|--------------------------|-------------------|------------------------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
| (MHz) | Reading (dBμV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB) | | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel: 2402 MHz | | | | | | | | | |
| 2402 | 91.21 | PK | H | 25.65 | 4.42 | 27.32 | 93.96 | N/A | N/A |
| 2402 | 79.86 | AV | H | 25.65 | 4.42 | 27.32 | 82.61 | N/A | N/A |
| 2402 | 90.72 | PK | V | 25.65 | 4.42 | 27.32 | 93.47 | N/A | N/A |
| 2402 | 79.06 | AV | V | 25.65 | 4.42 | 27.32 | 81.81 | N/A | N/A |
| 2376 | 38.29 | PK | H | 25.58 | 4.35 | 27.32 | 40.90 | 74.00 | 33.10 |
| 2376 | 26.94 | AV | H | 25.58 | 4.35 | 27.32 | 29.55 | 54.00 | 24.45 |
| 4804 | 40.19 | PK | H | 30.59 | 5.98 | 27.41 | 49.35 | 74.00 | 24.65 |
| 4804 | 24.29 | AV | H | 30.59 | 5.98 | 27.41 | 33.45 | 54.00 | 20.55 |
| 7206 | 30.90 | PK | H | 34.09 | 7.45 | 25.91 | 46.53 | 74.00 | 27.47 |
| 7206 | 19.63 | AV | H | 34.09 | 7.45 | 25.91 | 35.26 | 54.00 | 18.74 |
| 9608 | 28.68 | PK | H | 35.96 | 8.80 | 27.55 | 45.89 | 74.00 | 28.11 |
| 9608 | 16.90 | AV | H | 35.96 | 8.80 | 27.55 | 34.11 | 54.00 | 19.89 |
| 7315 | 31.96 | PK | H | 34.36 | 7.51 | 25.88 | 47.95 | 74.00 | 26.05 |
| 7315 | 20.78 | AV | H | 34.36 | 7.51 | 25.88 | 36.77 | 54.00 | 17.23 |
| 159.9 | 32.74 | QP | H | 12.78 | 1.53 | 21.44 | 25.61 | 43.50 | 17.89 |
| Middle Channel: 2441 MHz | | | | | | | | | |
| 2441 | 90.96 | PK | H | 25.75 | 4.40 | 27.34 | 93.77 | N/A | N/A |
| 2441 | 79.22 | AV | H | 25.75 | 4.40 | 27.34 | 82.03 | N/A | N/A |
| 2441 | 90.40 | PK | V | 25.75 | 4.40 | 27.34 | 93.21 | N/A | N/A |
| 2441 | 78.89 | AV | V | 25.75 | 4.40 | 27.34 | 81.70 | N/A | N/A |
| 4882 | 42.98 | PK | H | 30.79 | 6.08 | 27.42 | 52.43 | 74.00 | 21.57 |
| 4882 | 29.86 | AV | H | 30.79 | 6.08 | 27.42 | 39.31 | 54.00 | 14.69 |
| 7323 | 30.47 | PK | H | 34.38 | 7.51 | 25.88 | 46.48 | 74.00 | 27.52 |
| 7323 | 19.36 | AV | H | 34.38 | 7.51 | 25.88 | 35.37 | 54.00 | 18.63 |
| 9764 | 28.78 | PK | H | 36.33 | 8.83 | 27.20 | 46.74 | 74.00 | 27.26 |
| 9764 | 16.68 | AV | H | 36.33 | 8.83 | 27.20 | 34.64 | 54.00 | 19.36 |
| 7315 | 31.88 | PK | H | 34.36 | 7.51 | 25.88 | 47.87 | 74.00 | 26.13 |
| 7315 | 20.64 | AV | H | 34.36 | 7.51 | 25.88 | 36.63 | 54.00 | 17.37 |
| 1062 | 32.15 | PK | H | 22.46 | 2.63 | 26.59 | 30.65 | 74.00 | 43.35 |
| 1062 | 31.72 | AV | H | 22.46 | 2.63 | 26.59 | 30.22 | 54.00 | 23.78 |
| 159.9 | 32.79 | QP | H | 12.78 | 1.53 | 21.44 | 25.66 | 43.50 | 17.84 |
| High Channel: 2480 MHz | | | | | | | | | |
| 2480 | 92.71 | PK | H | 25.85 | 4.48 | 27.36 | 95.68 | N/A | N/A |
| 2480 | 81.57 | AV | H | 25.85 | 4.48 | 27.36 | 84.54 | N/A | N/A |
| 2480 | 90.25 | PK | V | 25.85 | 4.48 | 27.36 | 93.22 | N/A | N/A |
| 2480 | 78.65 | AV | V | 25.85 | 4.48 | 27.36 | 81.62 | N/A | N/A |
| 2483.5 | 43.43 | PK | H | 25.86 | 4.49 | 27.36 | 46.42 | 74.00 | 27.58 |
| 2483.5 | 29.43 | AV | H | 25.86 | 4.49 | 27.36 | 32.42 | 54.00 | 21.58 |
| 4960 | 39.70 | PK | H | 31.00 | 5.90 | 27.43 | 49.17 | 74.00 | 24.83 |
| 4960 | 20.80 | AV | H | 31.00 | 5.90 | 27.43 | 30.27 | 54.00 | 23.73 |
| 7440 | 30.55 | PK | H | 34.66 | 7.58 | 25.97 | 46.82 | 74.00 | 27.18 |
| 7440 | 19.04 | AV | H | 34.66 | 7.58 | 25.97 | 35.31 | 54.00 | 18.69 |
| 9920 | 28.97 | PK | H | 36.71 | 8.87 | 26.66 | 47.89 | 74.00 | 26.11 |
| 9920 | 17.31 | AV | H | 36.71 | 8.87 | 26.66 | 36.23 | 54.00 | 17.77 |
| 7315 | 31.86 | PK | H | 34.36 | 7.51 | 25.88 | 47.85 | 74.00 | 26.15 |
| 7315 | 20.54 | AV | H | 34.36 | 7.51 | 25.88 | 36.53 | 54.00 | 17.47 |
| 159.9 | 32.55 | QP | H | 12.78 | 1.53 | 21.44 | 25.42 | 43.50 | 18.08 |


EDR Mode (8DPSK):

| Frequency | Receiver | | Rx Antenna | | Cable loss (dB) | Amplifier Gain (dB) | Corrected Amplitude (dBμV/m) | FCC 15.247 | |
|--------------------------|----------------|---------------------|-------------|-------------|-----------------|---------------------|------------------------------|----------------|-------------|
| (MHz) | Reading (dBμV) | Detector (PK/QP/AV) | Polar (H/V) | Factor (dB) | | | | Limit (dBμV/m) | Margin (dB) |
| Low Channel: 2402 MHz | | | | | | | | | |
| 2402 | 91.87 | PK | H | 25.65 | 4.42 | 27.32 | 94.62 | N/A | N/A |
| 2402 | 79.78 | AV | H | 25.65 | 4.42 | 27.32 | 82.53 | N/A | N/A |
| 2402 | 91.63 | PK | V | 25.65 | 4.42 | 27.32 | 94.38 | N/A | N/A |
| 2402 | 79.61 | AV | V | 25.65 | 4.42 | 27.32 | 82.36 | N/A | N/A |
| 2376 | 38.27 | PK | H | 25.58 | 4.35 | 27.32 | 40.88 | 74.00 | 33.12 |
| 2376 | 26.73 | AV | H | 25.58 | 4.35 | 27.32 | 29.34 | 54.00 | 24.66 |
| 4804 | 45.63 | PK | H | 30.59 | 5.98 | 27.41 | 54.79 | 74.00 | 19.21 |
| 4804 | 31.56 | AV | H | 30.59 | 5.98 | 27.41 | 40.72 | 54.00 | 13.28 |
| 7206 | 30.91 | PK | H | 34.09 | 7.45 | 25.91 | 46.54 | 74.00 | 27.46 |
| 7206 | 18.97 | AV | H | 34.09 | 7.45 | 25.91 | 34.60 | 54.00 | 19.40 |
| 9608 | 29.53 | PK | H | 35.96 | 8.80 | 27.55 | 46.74 | 74.00 | 27.26 |
| 9608 | 17.86 | AV | H | 35.96 | 8.80 | 27.55 | 35.07 | 54.00 | 18.93 |
| 7315 | 31.94 | PK | H | 34.36 | 7.51 | 25.88 | 47.93 | 74.00 | 26.07 |
| 7315 | 19.64 | AV | H | 34.36 | 7.51 | 25.88 | 35.63 | 54.00 | 18.37 |
| 159.9 | 33.26 | QP | H | 12.78 | 1.53 | 21.44 | 26.13 | 43.50 | 17.37 |
| Middle Channel: 2441 MHz | | | | | | | | | |
| 2441 | 91.57 | PK | H | 25.75 | 4.40 | 27.34 | 94.38 | N/A | N/A |
| 2441 | 79.78 | AV | H | 25.75 | 4.40 | 27.34 | 82.59 | N/A | N/A |
| 2441 | 90.12 | PK | V | 25.75 | 4.40 | 27.34 | 92.93 | N/A | N/A |
| 2441 | 78.49 | AV | V | 25.75 | 4.40 | 27.34 | 81.30 | N/A | N/A |
| 4882 | 46.26 | PK | H | 30.79 | 6.08 | 27.42 | 55.71 | 74.00 | 18.29 |
| 4882 | 32.60 | AV | H | 30.79 | 6.08 | 27.42 | 42.05 | 54.00 | 11.95 |
| 7323 | 32.91 | PK | H | 34.38 | 7.51 | 25.88 | 48.92 | 74.00 | 25.08 |
| 7323 | 20.20 | AV | H | 34.38 | 7.51 | 25.88 | 36.21 | 54.00 | 17.79 |
| 9764 | 28.34 | PK | H | 36.33 | 8.83 | 27.20 | 46.30 | 74.00 | 27.70 |
| 9764 | 17.89 | AV | H | 36.33 | 8.83 | 27.20 | 35.85 | 54.00 | 18.15 |
| 7315 | 32.09 | PK | H | 34.36 | 7.51 | 25.88 | 48.08 | 74.00 | 25.92 |
| 7315 | 19.85 | AV | H | 34.36 | 7.51 | 25.88 | 35.84 | 54.00 | 18.16 |
| 1062 | 32.15 | PK | H | 22.46 | 2.63 | 26.59 | 30.65 | 74.00 | 43.35 |
| 1062 | 31.71 | AV | H | 22.46 | 2.63 | 26.59 | 30.21 | 54.00 | 23.79 |
| 159.9 | 32.69 | QP | H | 12.78 | 1.53 | 21.44 | 25.56 | 43.50 | 17.94 |
| High Channel: 2480 MHz | | | | | | | | | |
| 2480 | 92.26 | PK | H | 25.85 | 4.48 | 27.36 | 95.23 | N/A | N/A |
| 2480 | 80.47 | AV | H | 25.85 | 4.48 | 27.36 | 83.44 | N/A | N/A |
| 2480 | 89.49 | PK | V | 25.85 | 4.48 | 27.36 | 92.46 | N/A | N/A |
| 2480 | 79.80 | AV | V | 25.85 | 4.48 | 27.36 | 82.77 | N/A | N/A |
| 2483.5 | 41.36 | PK | H | 25.86 | 4.49 | 27.36 | 44.35 | 74.00 | 29.65 |
| 2483.5 | 28.03 | AV | H | 25.86 | 4.49 | 27.36 | 31.02 | 54.00 | 22.98 |
| 4960 | 45.87 | PK | H | 31.00 | 5.90 | 27.43 | 55.34 | 74.00 | 18.66 |
| 4960 | 31.74 | AV | H | 31.00 | 5.90 | 27.43 | 41.21 | 54.00 | 12.79 |
| 7440 | 31.07 | PK | H | 34.66 | 7.58 | 25.97 | 47.34 | 74.00 | 26.66 |
| 7440 | 19.56 | AV | H | 34.66 | 7.58 | 25.97 | 35.83 | 54.00 | 18.17 |
| 9920 | 28.74 | PK | H | 36.71 | 8.87 | 26.66 | 47.66 | 74.00 | 26.34 |
| 9920 | 18.02 | AV | H | 36.71 | 8.87 | 26.66 | 36.94 | 54.00 | 17.06 |
| 7315 | 31.59 | PK | H | 34.36 | 7.51 | 25.88 | 47.58 | 74.00 | 26.42 |
| 7315 | 19.88 | AV | H | 34.36 | 7.51 | 25.88 | 35.87 | 54.00 | 18.13 |
| 159.9 | 33.12 | QP | H | 12.78 | 1.53 | 21.44 | 25.99 | 43.50 | 17.51 |

Conducted Spurious Emissions at Antenna Port


BDR Mode (GFSK):

Low Channel




Date: 16.JUN.2014 18:49:34

Middle Channel



Date: 16.JUN.2014 18:50:40


High Channel



Date: 16.JUN.2014 18:51:25


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 16.JUN.2014 18:54:45

Middle Channel



Date: 16.JUN.2014 18:53:58


High Channel



Date: 16.JUN.2014 18:52:51


EDR Mode (8DPSK):

Low Channel




Date: 16.JUN.2014 18:55:58

Middle Channel



Date: 16.JUN.2014 18:56:41

High Channel



Date: 16.JUN.2014 18:57:31

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2014-05-09 | 2015-05-08 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 30 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Data**Environmental Conditions**

| | |
|---------------------------|----------|
| Temperature: | 28.6 °C |
| Relative Humidity: | 67% |
| ATM Pressure: | 99.6 kPa |

The testing was performed by Leon Chen on 2014-06-16.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

| Mode | Channel | Frequency (MHz) | Channel Separation (MHz) | Limit (MHz) | Result |
|-----------------------------|----------|-----------------|--------------------------|-------------|--------|
| BDR Mode (GFSK) | Low | 2402 | 1.000 | 0.58 | Pass |
| | Adjacent | 2403 | | | |
| | Middle | 2441 | 1.004 | 0.58 | Pass |
| | Adjacent | 2442 | | | |
| | High | 2480 | 1.000 | 0.57 | Pass |
| | Adjacent | 2479 | | | |
| EDR Mode (($\pi/4$ -DQPSK) | Low | 2402 | 1.000 | 0.81 | Pass |
| | Adjacent | 2403 | | | |
| | Middle | 2441 | 1.004 | 0.82 | Pass |
| | Adjacent | 2442 | | | |
| | High | 2480 | 1.000 | 0.82 | Pass |
| | Adjacent | 2479 | | | |
| EDR Mode (8DPSK) | Low | 2402 | 1.000 | 0.81 | Pass |
| | Adjacent | 2403 | | | |
| | Middle | 2441 | 1.004 | 0.80 | Pass |
| | Adjacent | 2442 | | | |
| | High | 2480 | 1.000 | 0.83 | Pass |
| | Adjacent | 2479 | | | |


BDR Mode (GFSK):

Low Channel




Date: 16.JUN.2014 17:50:14

Middle Channel



Date: 16.JUN.2014 17:49:00


High Channel



Date: 16.JUN.2014 17:48:20


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 16.JUN.2014 17:51:15

Middle Channel



Date: 16.JUN.2014 17:51:46


High Channel



Date: 16.JUN.2014 17:52:20


EDR Mode (8DPSK):

Low Channel




Date: 16.JUN.2014 17:54:16

Middle Channel



Date: 16.JUN.2014 17:53:49

High Channel



Date: 16.JUN.2014 17:53:11

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2014-05-09 | 2015-05-08 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|---------------------------|----------|
| Temperature: | 28.6 °C |
| Relative Humidity: | 67% |
| ATM Pressure: | 99.6 kPa |


The testing was performed by Leon Chen on 2014-06-16.

Test Result: Compliance.


Please refer to following tables and plots

| Mode | Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |
|----------------------------|---------|-----------------|-----------------------|
| BDR Mode (GFSK) | Low | 2402 | 0.868 |
| | Middle | 2441 | 0.864 |
| | High | 2480 | 0.848 |
| EDR Mode ($\pi/4$ -DQPSK) | Low | 2402 | 1.212 |
| | Middle | 2441 | 1.224 |
| | High | 2480 | 1.228 |
| EDR Mode (8DPSK) | Low | 2402 | 1.208 |
| | Middle | 2441 | 1.204 |
| | High | 2480 | 1.248 |

BDR Mode (GFSK):




Middle Channel



Date: 16.JUN.2014 17:45:18


High Channel



Date: 16.JUN.2014 17:47:20


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 17.JUN.2014 18:19:28

Middle Channel



Date: 16.JUN.2014 17:34:07


High Channel



Date: 16.JUN.2014 17:36:03


EDR Mode (8DPSK):

Low Channel




Date: 16.JUN.2014 17:39:47

Middle Channel



Date: 16.JUN.2014 17:38:45

High Channel



Date: 16.JUN.2014 17:37:31

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2014-05-09 | 2015-05-08 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

| | |
|--------------------|----------|
| Temperature: | 28.6 °C |
| Relative Humidity: | 67% |
| ATM Pressure: | 99.6 kPa |

The testing was performed by Leon Chen on 2014-06-16.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|-----------------------|---------------------------|-----------|
| 2400-2483.5 | 79 | ≥ 15 |


Number of Hopping Channels



Date: 16.JUN.2014 18:07:05

EDR Mode (($\pi/4$ -DQPSK):

| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|-----------------------|---------------------------|-----------|
| 2400-2483.5 | 79 | ≥ 15 |



Date: 16.JUN.2014 18:05:29

| Frequency Range (MHz) | Number of Hopping Channel | Limit |
|-----------------------|---------------------------|-----------|
| 2400-2483.5 | 79 | ≥ 15 |



Date: 16.JUN.2014 18:03:45

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as $0.4 \times \text{channel no. (s)}$, the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= time slot length * hope rate/ number of hopping channels * 31.6s
Hop rate=1600/s

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2014-05-09 | 2015-05-08 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| | |
|---------------------------|----------|
| Temperature: | 28.6 °C |
| Relative Humidity: | 67% |
| ATM Pressure: | 99.6 kPa |

The testing was performed by Leon Chen on 2014-06-16.

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


| Mode | Channel | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result |
|------|---|------------------|----------------|-----------|--------|
| DH1 | Low | 0.534 | 0.171 | 0.4 | Pass |
| | Middle | 0.534 | 0.171 | 0.4 | Pass |
| | High | 0.534 | 0.171 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s | | | | |
| DH3 | Low | 1.818 | 0.291 | 0.4 | Pass |
| | Middle | 1.818 | 0.291 | 0.4 | Pass |
| | High | 1.818 | 0.291 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s | | | | |
| DH5 | Low | 3.068 | 0.327 | 0.4 | Pass |
| | Middle | 3.068 | 0.327 | 0.4 | Pass |
| | High | 3.068 | 0.327 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s | | | | |

DH1: Low Channel




Date: 16.JUN.2014 18:14:30

DH1: Middle Channel




Date: 16.JUN.2014 18:14:18

DH1: High Channel




Date: 16.JUN.2014 18:14:08

DH3: Low Channel




Date: 16.JUN.2014 18:40:28

DH3: Middle Channel




Date: 16.JUN.2014 18:40:14

DH3: High Channel




Date: 16.JUN.2014 18:40:05

DH5: Low Channel




Date: 16.JUN.2014 18:41:08

DH5: Middle Channel



Date: 16.JUN.2014 18:41:25

DH5: High Channel




Date: 16.JUN.2014 18:41:43

EDR Mode ($\pi/4$ -DQPSK):


| Mode | Channel | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result |
|------|---|------------------|----------------|-----------|--------|
| DH1 | Low | 0.548 | 0.175 | 0.4 | Pass |
| | Middle | 0.548 | 0.175 | 0.4 | Pass |
| | High | 0.548 | 0.175 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s | | | | |
| DH3 | Low | 1.822 | 0.292 | 0.4 | Pass |
| | Middle | 1.822 | 0.292 | 0.4 | Pass |
| | High | 1.822 | 0.292 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s | | | | |
| DH5 | Low | 3.088 | 0.329 | 0.4 | Pass |
| | Middle | 3.088 | 0.329 | 0.4 | Pass |
| | High | 3.088 | 0.329 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s | | | | |

DH1: Low Channel




Date: 16.JUN.2014 18:20:29

DH1: Middle Channel




Date: 16.JUN.2014 18:20:51

DH1: High Channel




Date: 16.JUN.2014 18:21:17

DH3: Low Channel




Date: 16.JUN.2014 18:25:35

DH3: Middle Channel




Date: 16.JUN.2014 18:25:42

DH3: High Channel




Date: 16.JUN.2014 18:25:51

DH5: Low Channel




Date: 16.JUN.2014 18:43:13

DH5: Middle Channel



Date: 16.JUN.2014 18:43:05


DH5: High Channel



Date: 16.JUN.2014 18:42:57


EDR Mode (8DPSK):

| Mode | Channel | Pulse Width (ms) | Dwell Time (s) | Limit (s) | Result |
|------------|---|------------------|----------------|-----------|--------|
| DH1 | Low | 0.548 | 0.175 | 0.4 | Pass |
| | Middle | 0.548 | 0.175 | 0.4 | Pass |
| | High | 0.548 | 0.175 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s | | | | |
| DH3 | Low | 1.822 | 0.292 | 0.4 | Pass |
| | Middle | 1.822 | 0.292 | 0.4 | Pass |
| | High | 1.822 | 0.292 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s | | | | |
| DH5 | Low | 3.088 | 0.329 | 0.4 | Pass |
| | Middle | 3.088 | 0.329 | 0.4 | Pass |
| | High | 3.088 | 0.329 | 0.4 | Pass |
| | Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s | | | | |

DH1: Low Channel


Date: 16.JUN.2014 18:23:38

DH1: Middle Channel




Date: 16.JUN.2014 18:23:08

DH1: High Channel




Date: 16.JUN.2014 18:23:47

DH3: Low Channel




Date: 16.JUN.2014 18:25:01

DH3: Middle Channel




Date: 16.JUN.2014 18:24:53

DH3: High Channel




Date: 16.JUN.2014 18:24:44

DH5: Low Channel




Date: 16.JUN.2014 18:43:50

DH5: Middle Channel



Date: 16.JUN.2014 18:44:00

DH5: High Channel



Date: 16.JUN.2014 18:44:08

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2014-05-09 | 2015-05-08 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 28.6 °C |
| Relative Humidity: | 67% |
| ATM Pressure: | 99.6 kPa |

The testing was performed by Leon Chen on 2014-06-16.


Test Result: Compliance.

Test Mode: Transmitting

| Mode | Channel | Frequency (MHz) | Peak Output Power (dBm) | Limit (dBm) |
|----------------------------|---------|-----------------|-------------------------|-------------|
| BDR Mode (GFSK) | Low | 2402 | 4.58 | 30 |
| | Middle | 2441 | 4.84 | 30 |
| | High | 2480 | 3.80 | 30 |
| EDR Mode ($\pi/4$ -DQPSK) | Low | 2402 | 2.87 | 30 |
| | Middle | 2441 | 3.41 | 30 |
| | High | 2480 | 2.22 | 30 |
| EDR Mode (8DPSK) | Low | 2402 | 3.27 | 30 |
| | Middle | 2441 | 3.68 | 30 |
| | High | 2480 | 2.68 | 30 |


Note: The data above was tested in conducted mode.

BDR Mode (GFSK):




Date: 16.JUN.2014 17:24:37

Output Power, Middle Channel



Date: 16.JUN.2014 17:24:58


Output Power, High Channel



Date: 16.JUN.2014 17:25:29


EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low Channel




Date: 16.JUN.2014 17:29:16

Output Power, Middle Channel



Date: 16.JUN.2014 17:29:00


Output Power, High Channel



Date: 16.JUN.2014 17:28:42


EDR Mode (8DPSK):

Output Power, Low Channel




Date: 16.JUN.2014 17:27:10

Output Power, Middle Channel



Date: 16.JUN.2014 17:27:41

Output Power, High Channel



Date: 16.JUN.2014 17:27:58

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

| Manufacturer | Description | Model | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-------------------|--------|---------------|------------------|----------------------|
| R&S | Spectrum Analyzer | FSP 38 | 100478 | 2014-05-09 | 2015-05-08 |

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data

Environmental Conditions

| | |
|--------------------|----------|
| Temperature: | 28.8 °C |
| Relative Humidity: | 61% |
| ATM Pressure: | 99.7 kPa |

The testing was performed by Leon Chen on 2014-06-13.

Band Edge, Left Side



Ref 16 dBm Att 50 dB

*RBW 100 kHz Marker 1 [T1] 2.65 dBm
 *VBW 300 kHz 2.479988000 GHz
 SWT 5 ms

Offset 0.5 dB

Marker 2 [T1] 44.80 dBm
 2.483500000 GHz
 Marker 3 [T1] -44.32 dBm
 2.500000000 GHz

1 PK MAXH

D1 2.65 dBm
 D2 -17.35 dBm


F1 F2

Start 2.4795 GHz 3.05 MHz/ Stop 2.51 GHz

Date: 13.JUN.2014 16:49:09


EDR Mode (π 4-DQPSK):

Band Edge, Left Side



Date: 13.JUN.2014 16:44:43


Band Edge, Right Side



Date: 13.JUN.2014 16:48:17


EDR Mode (8DPSK):

Band Edge, Left Side



Date: 13.JUN.2014 16:45:28

Band Edge, Right Side



Date: 13.JUN.2014 16:47:30

***** END OF REPORT *****