RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: WAK-RINUHF5239U

EUT Specification

EUT	BLUEBOX UHF 1CH Mid Range Controller					
Frequency band	☐ WLAN: 2.412GHz ~ 2.462GHz					
(Operating)	☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz					
	☐ WLAN: 5.745GHz ~ 5825GHz					
	⊠ Others 902-928MHz					
Device category	☐ Portable (<20cm separation)					
	⊠ Mobile (>20cm separation)					
	☐ Others					
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm2)					
	□ General Population/Uncontrolled exposure					
	(S=1mW/cm2)					
Antenna diversity	⊠ Single antenna					
	☐ Multiple antennas					
	☐ Tx diversity					
	☐ Rx diversity					
	☐ Tx/Rx diversity					
Max. output power	19.167dBm (0.0825W)					
Antenna gain (Max)	8 dBi					
Evaluation applied	⊠MPE Evaluation					
	☐ SAR Evaluation					

Limits for Maximum Permissible Exposure(MPE)

Frequency	Electric Field	Magnetic Field	tic Field Power						
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)	Time					
(A) Limits for Occupational/Control Exposures									
300-1500			F/300	6					
1500-100000			5	6					
(B) Limits for General Population/Uncontrol Exposures									
300-1500		F/1500		6					
1500-100000			1	30					

Friis transmission formula: Pd=(Pout*G)\(4*pi*R2)

Where

Pd= Power density in mW/cm²
Pout=output power to antenna in Mw

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel Frequency (MHz)	Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Antenna Gain (dBi)	Power density at 20cm (mW/ cm²)	Power density Limits (mW/cm²)
902.75	19.095	19.095±1	20.10	8	0.1283	0.6018
914.75	19.167	19.167±1	20.17	8	0.1304	0.6098
927.25	19.095	19.095±1	20.10	8	0.1283	0.6182