



# Test Report

## FCC Part15 Subpart C& RSS-247 Issue 2

Product Name : EZ-BT WICED Module

Model No. : CYBT-353027-02

FCC ID : WAP3027

IC : 7922A-3027

Applicant : Cypress Semiconductor

Address : 198 Champion Ct, San Jose, California 95134  
United States

Date of Receipt : Jan. 31, 2018

Test Date : Feb. 01, 2018~ Apr. 19, 2018

Issued Date : Apr. 20, 2018

Report No. : 1812155R-RF-US-P06V03

Report Version : V 1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by A2LA, TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing & Certification (Suzhou) Co., Ltd.


# Test Report Certification


Issued Date : Apr. 20, 2018


Report No. : 1812155R-RF-US-P06V03



Product Name : EZ-BT WICED Module  
Applicant : Cypress Semiconductor  
Address : 198 Champion Ct, San Jose, California 95134  
United States  
Manufacturer : Cypress Semiconductor  
Address : 198 Champion Ct, San Jose, California 95134  
United States  
Model No. : CYBT-353027-02  
FCC ID : WAP3027  
IC : 7922A-3027  
EUT Voltage : DC 2.3-3.6V  
Test Voltage : AC120V/60Hz  
Applicable Standard : FCC CFR Title 47 Part 15 Subpart C  
KDB DA 00-705 Released March 30, 2000  
ANSI C63.10: 2013  
RSS-Gen Issue 4/RSS-247 Issue 2  
Test Result : Complied  
Performed Location : DEKRA Testing & Certification (Suzhou) Co., Ltd.  
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou, 215006,  
Jiangsu, China  
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098  
FCC Designation Number: CN1199; ISED Lab Code: 4075B

Documented By :   
(Adm. Specialist: Kathy Feng)

Reviewed By :   
(Senior Engineer: Frank He )

Approved By :   
(Engineering Manager: Harry Zhao )

## TABLE OF CONTENTS

Description	Page
1. General Information .....	7
1.1. EUT Description .....	7
1.2. Antenna information .....	9
1.3. Mode of Operation .....	10
1.4. Tested System Details .....	11
1.5. Configuration of Tested System .....	12
1.6. EUT Exercise Software .....	13
2. Technical Test .....	14
2.1. Summary of Test Result .....	14
2.2. Test Environment .....	16
3. Conducted Emission .....	17
3.1. Test Equipment .....	17
3.2. Test Setup .....	17
3.3. Limit .....	18
3.4. Test Procedure .....	18
3.5. Uncertainty .....	18
3.6. Test Result .....	19
4. Emissions in restricted frequency bands .....	19
4.1. Test Equipment .....	21
4.2. Test Setup .....	22
4.3. Limit .....	23
4.4. Test Procedure .....	26
4.5. Uncertainty .....	26
4.6. Test Result .....	27
5. 20dB Bandwidth .....	47
5.1. Test Equipment .....	47
5.2. Test Setup .....	47
5.3. Limit .....	47
5.4. Test Procedure .....	48
5.5. Uncertainty .....	48
5.6. Test Result .....	49
6. Carrier Frequency Separation .....	55
6.1. Test Equipment .....	55
6.2. Test Setup .....	55
6.3. Limit .....	56
6.4. Test Procedure .....	56
6.5. Uncertainty .....	56

6.6.	Test Result .....	57
7.	Number of Hopping Frequencies .....	63
7.1.	Test Equipment .....	63
7.2.	Test Setup .....	63
7.3.	Limit.....	63
7.4.	Test Procedure .....	64
7.5.	Uncertainty .....	64
7.6.	Test Result .....	65
8.	Time of Occupancy (Dwell Time) .....	68
8.1.	Test Equipment .....	68
8.2.	Test Setup .....	68
8.3.	Limit.....	68
8.4.	Test Procedure .....	69
8.5.	Uncertainty .....	69
8.6.	Test Result .....	70
9.	Peak Output Power .....	76
9.1.	Test Equipment .....	76
9.2.	Test Setup .....	76
9.3.	Limit.....	77
9.4.	Test Procedure .....	77
9.5.	Uncertainty .....	77
9.6.	Test Result .....	78
10.	Emissions in non-restricted frequency bands .....	81
10.1.	Test Equipment .....	81
10.2.	Test Setup .....	81
10.3.	Limit.....	82
10.4.	Test Procedure .....	82
10.5.	Uncertainty .....	82
10.6.	Test Result .....	83
11.	Radiated Emission Band Edge .....	84
11.1.	Test Equipment .....	84
11.2.	Test Setup .....	84
11.3.	Limit.....	85
11.4.	Test Procedure .....	85
11.5.	Uncertainty .....	85
11.6.	Duty Factor.....	86
11.7.	Test Result .....	87
12.	Antenna Requirement .....	99

12.1. Limit.....	99
12.2. Antenna Connector Construction .....	99

**History of This Test Report**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
1812155R-RF-US-P06V03	V1.0	Initial Issued Report	Apr. 20, 2018

## 1. General Information

### 1.1. EUT Description

Product Name	EZ-BT WICED Module
Model No.	CYBT-353027-02
Working Voltage	DC 2.3-3.6V
Test Voltage	AC120V/60Hz
Bluetooth Specification	V3.0
Frequency Range	2402- 2480 MHz
Channel Number	V3.0: 79
Channel Separation	V3.0: 1MHz
Type of Modulation	V3.0: GFSK, Pi/4 DQPSK, 8DPSK
Data Rate	V3.0: 1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps(8DPSK)
Antenna Type	Reference to Antenna List
Peak Antenna Gain	Reference to Antenna List

Bluetooth Working Frequency of Each Channel: (For V3.0)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz	03	2405 MHz
04	2406 MHz	05	2407 MHz	06	2408 MHz	07	2409 MHz
08	2410 MHz	09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz	15	2417 MHz
16	2418 MHz	17	2419 MHz	18	2420 MHz	19	2421 MHz
20	2422 MHz	21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz	27	2429 MHz
28	2430 MHz	29	2431 MHz	30	2432 MHz	31	2433 MHz
32	2434 MHz	33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz	39	2441 MHz
40	2442 MHz	41	2443 MHz	42	2444 MHz	43	2445 MHz
44	2446 MHz	45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz	51	2453 MHz
52	2454 MHz	53	2455 MHz	54	2456 MHz	55	2457 MHz
56	2458 MHz	57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz	63	2465 MHz
64	2466 MHz	65	2467 MHz	66	2468 MHz	67	2469 MHz
68	2470 MHz	69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz	75	2477 MHz
76	2478 MHz	77	2479 MHz	78	2480 MHz	N/A	N/A



## 1.2 Antenna information

Model No.	N/A					
Antenna manufacturer	N/A					
Antenna Delivery	<input checked="" type="checkbox"/>	1*TX+1*RX	<input type="checkbox"/>	2*TX+2*RX	<input type="checkbox"/>	3*TX+3*RX
Antenna technology	<input checked="" type="checkbox"/>	SISO				
	<input type="checkbox"/>	MIMO	<input type="checkbox"/>	Basic		
			<input type="checkbox"/>	CDD		
			<input type="checkbox"/>	Sectorized		
			<input type="checkbox"/>	Beam-forming		
Antenna Type	<input type="checkbox"/>	External	<input type="checkbox"/>	Dipole		
			<input type="checkbox"/>	Sectorized		
	<input checked="" type="checkbox"/>	Internal	<input type="checkbox"/>	PIFA		
			<input type="checkbox"/>	PCB		
			<input checked="" type="checkbox"/>	Ceramic Chip Antenna		
			<input type="checkbox"/>	Monopole Antenna		
Antenna Technology	Ant Gain (dBi)					
<input checked="" type="checkbox"/> SISO	-1					

### 1.3 Mode of Operation

DEKRA has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmitter-1Mbps(GFSK_DH5)
Mode 2: Transmitter-2Mbps(Pi/4 DQPSK_DH5)
Mode 3: Transmitter-3Mbps(8DPSK_DH5)
Mode 4: Transmitter-Hopping

Note:

1. For portable device, radiated spurious emission was verified over X, Y, Z Axis, and shown the worst case on this report.
2. Regards to the frequency band operation for systems using FHSS modulation: normal operation (hopping) was selected to test for conducted spurious test.
3. The extreme test condition for voltage and temperature were declared by the manufacturer.
4. The reading values of all the test items contain cable loss.


#### 1.4 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:


Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook	Think Pad	2526	LV-A3285	Power by adapter
A	USB Cable	N/A	N/A	N/A	Shield, 0.5m
B	USB Cable	N/A	N/A	N/A	Shield, 10m

## 1.5 Configuration of Tested System

Test setup Diagram- AC Line Conducted Emission Test



Test setup Diagram- Radiated Emission



## 1.6 EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of all equipment.
3	Run RF software [Bluetool], and set the test mode and channel, then press OK to start to continue transmit.

## 2. Technical Test

### 2.1. Summary of Test Result

- ☒ No deviations from the test standards
- ☐ Deviations from the test standards as below description:

#### For FCC

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.207	Yes	No
Emissions in restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.209	Yes	No
20dB Bandwidth	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)	Yes	No
Carrier Frequency Separation	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)	Yes	No
Number of Hopping Frequencies	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)(iii)	Yes	No
Time of Occupancy (Dwell Time)	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(a)(1)(iii)	Yes	No
Peak Output Power	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.247(b)(1)	Yes	No
Emissions in non-restricted frequency bands	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.215(c), 15.247(d)	Yes	No
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart C: 2015 15.247(d)	Yes	No
Antenna Requirement	FCC CFR Title 47 Part 15 Subpart C: 2015 Section 15.203	Yes	No

**For ISED**

Performed Test Item	Normative References	Test Performed	Deviation
Conducted Emission	RSS-Gen Issue 4 Section 8.8	Yes	No
Radiated Emission	RSS-Gen Issue 4 Section 8.9	Yes	No
20dB Bandwidth	RSS-247 Issue 2 Section 5.1	Yes	No
Carrier Frequency Separation	RSS-247 Issue 2 Section 5.1	Yes	No
Number of Hopping Frequencies	RSS-247 Issue 2 Section 5.1	Yes	No
Time of Occupancy (Dwell Time)	RSS-247 Issue 2 Section 5.1	Yes	No
Peak Output Power	RSS-247 Issue 2 Section 5.4	Yes	No
Emissions in non-restricted frequency bands	RSS-247 Issue 2 Section 5.5	Yes	No
Radiated Emission Band Edge	RSS-Gen Issue 4 Section 8.10	Yes	No
Antenna Requirement	RSS-Gen Issue 4 Section 8.3	Yes	No

## 2.2. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000




### 3. Conducted Emission

#### 3.1. Test Equipment

AC Power Line Conducted Emission / TR-1					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100906	2017.03.05	2018.03.04
Two-Line V-Network	R&S	ENV 216	101189	2017.07.16	2018.07.15
Two-Line V-Network	R&S	ENV 216	101044	2017.09.15	2018.09.15
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	N/A	N/A
50ohm Termination	SHX	TF2	07081402	2017.09.15	2018.09.15
Temperature/Humidity Meter	Zhichen	ZC1-2	TR1-TH	2018.01.05	2019.01.04
Quietek EMI V3(test software)	Quietek	N/A	N/A	N/A	N/A

Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

#### 3.2. Test Setup



### 3.3. Limit

Frequency of Emission (MHz)	Conducted Limit	
	Quasi-peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50
Note 1: The lower limit shall apply at the transition frequencies.		
Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.		

### 3.4. Test Procedure


Test Method			
	References Rule	Chapter	Item
<input checked="" type="checkbox"/>	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

### 3.5. Uncertainty

The measurement uncertainty is defined as  $\pm 2.02$  dB


### 3.6. Test Result

Engineer: CptJack	
Site: TR1	Time: 2018/02/02 - 17:24
Limit: FCC_Part15.207_CE	Margin: 0
Probe: ENV216_101190(0.009-30MHz)	Polarity: Line
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.166	41.484	31.851	-23.674	65.158	9.607	0.027	0.000	QP
2		0.166	24.070	14.437	-31.088	55.158	9.607	0.027	0.000	AV
3		0.254	37.589	27.958	-24.036	61.625	9.600	0.031	0.000	QP
4		0.254	19.893	10.262	-31.732	51.625	9.600	0.031	0.000	AV
5		0.342	30.244	20.608	-28.911	59.155	9.600	0.035	0.000	QP
6		0.342	13.201	3.566	-35.953	49.155	9.600	0.035	0.000	AV
7		0.801	32.623	22.966	-23.377	56.000	9.603	0.053	0.000	QP
8	*	0.801	25.974	16.318	-20.026	46.000	9.603	0.053	0.000	AV
9		2.402	23.190	13.476	-32.810	56.000	9.617	0.096	0.000	QP
10		2.402	17.321	7.608	-28.679	46.000	9.617	0.096	0.000	AV
11		5.110	25.012	15.206	-34.988	60.000	9.662	0.144	0.000	QP
12		5.110	18.884	9.078	-31.116	50.000	9.662	0.144	0.000	AV

Engineer: CptJack	
Site: TR1	Time: 2018/02/02 - 17:30
Limit: FCC_Part15.207_CE	Margin: 0
Probe: ENV216_101190(0.009-30MHz)	Polarity: Neutral
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.170	40.605	30.984	-24.356	64.960	9.594	0.027	0.000	QP
2		0.170	22.202	12.580	-32.759	54.960	9.594	0.027	0.000	AV
3		0.250	37.225	27.596	-24.532	61.757	9.598	0.031	0.000	QP
4		0.250	20.053	10.424	-31.704	51.757	9.598	0.031	0.000	AV
5		0.802	32.886	23.243	-23.114	56.000	9.590	0.053	0.000	QP
6	*	0.802	26.034	16.391	-19.966	46.000	9.590	0.053	0.000	AV
7		3.402	24.449	14.704	-31.551	56.000	9.629	0.116	0.000	QP
8		3.402	18.738	8.993	-27.262	46.000	9.629	0.116	0.000	AV
9		4.270	24.601	14.830	-31.399	56.000	9.640	0.131	0.000	QP
10		4.270	19.180	9.409	-26.820	46.000	9.640	0.131	0.000	AV
11		5.058	24.598	14.803	-35.402	60.000	9.651	0.143	0.000	QP
12		5.058	18.988	9.194	-31.012	50.000	9.651	0.143	0.000	AV

## 4. Emissions in restricted frequency bands


### 4.1. Test Equipment

Radiated Emission(Below 1GHz) / AC-2					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2017.03.29	2018.03.28
Loop Antenna	R&S	HFH2-Z2	833799/003	2017.11.16	2018.11.15
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2017.10.16	2018.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2017.03.02	2018.03.01
Temperature/Humidity Meter	Zhichen	ZC1-2	AC2-TH	2018.01.04	2019.01.03
Quietek EMI V3(test software)	Quietek	N/A	N/A	N/A	N/A
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					


Radiated Emission(Above 1GHz) / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2018.01.04	2019.01.03
Preamplifier	Miteq	NSP1800-25	1364185	2017.05.06	2018.05.05
Preamplifier	QuieTek	AP-040G	CHM-0906001	2017.05.06	2018.05.05
DRG Horn	ETS-Lindgren	3117	00123988	2018.01.22	2019.01.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2017.11.25	2018.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2018.03.02	2019.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2018.03.02	2019.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2018.03.02	2019.03.01
EMI Receiver	Agilent	N9038A	MY51210196	2017.06.10	2018.06.09
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2018.01.04	2019.01.03
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

## 4.2. Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



### 4.3. Limit

#### For FCC:

Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

**For ISED:**

## Restricted Bands of operation

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090-0.110	13.36-13.41	1645.5-1646.5	13.25-13.4
2.1735-2.1905	16.42-16.423	1660-1710	14.47-14.5
3.020-3.026	16.69475-16.69525	1718.8-1722.2	15.35-16.2
4.125-4.128	16.80425-16.80475	2200-2300	17.7-21.4
4.17725-4.17775	25.5-25.67	2310-2390	22.01-23.12
4.20725-4.20775	37.5-38.25	2655-2900	23.6-24.0
5.677-5.683	73-74.6	3260-3267	31.2-31.8
6.215-6.218	74.8-75.2	3332-3339	36.43-36.5
6.26775-6.26825	108-138	3345.8-3358	Above 38.6
6.31175-6.31225	156.52475-156.52525	3500-4400	
8.291-8.294	156.7-156.9	4500-5150	
8.362-8.366	240-285	5350-5460	
8.37625-8.38675	322-335.4	7250-7750	
8.41425-8.41475	399.9-410	8025-8500	
12.29-12.293	608-614	9.0-9.2	
12.51975-12.52025	960-1427	9.3-9.5	
12.57675-12.57725	1435-1626.5	10.6-12.7	



Restricted Band Emissions Limit			
Frequency (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 <sub>(Note 1)</sub>
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 <sub>(Note 1)</sub>
1.705 - 30	30	29.5	30 <sub>(Note 1)</sub>
30 - 88	100	40	3 <sub>(Note 2)</sub>
88 - 216	150	43.5	3 <sub>(Note 2)</sub>
216 - 960	200	46	3 <sub>(Note 2)</sub>
Above 960	500	54	3 <sub>(Note 2)</sub>

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

#### 4.4. Test Procedure


Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

#### 4.5. Uncertainty

The measurement uncertainty above 1G is defined as  $\pm 3.9$  dB  
below 1G is defined as  $\pm 3.8$  dB


## 4.6. Test Result

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:34
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3847.500	51.718	53.648	-22.282	74.000	-1.930	PK
2		4804.000	40.359	40.878	-33.641	74.000	-0.519	PK
3		7206.000	43.098	39.082	-30.902	74.000	4.016	PK
4		9608.000	42.635	36.817	-31.365	74.000	5.817	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3839.000	51.282	53.395	-22.718	74.000	-2.113	PK
2		4804.000	40.164	40.683	-33.836	74.000	-0.519	PK
3		7206.000	43.142	39.126	-30.858	74.000	4.016	PK
4		9608.000	42.724	36.906	-31.276	74.000	5.817	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2441MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3907.000	51.016	53.636	-22.984	74.000	-2.620	PK
2		4882.000	39.791	40.304	-34.209	74.000	-0.514	PK
3		7323.000	42.403	38.476	-31.597	74.000	3.927	PK
4		9764.000	43.020	37.890	-30.980	74.000	5.131	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2441MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3907.000	49.735	52.355	-24.265	74.000	-2.620	PK
2		4882.000	40.171	40.684	-33.829	74.000	-0.514	PK
3		7323.000	42.228	38.301	-31.772	74.000	3.927	PK
4		9764.000	42.981	37.851	-31.019	74.000	5.131	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3966.500	52.650	54.392	-21.350	74.000	-1.742	PK
2		4960.000	39.309	40.186	-34.691	74.000	-0.877	PK
3		7440.000	42.845	39.206	-31.155	74.000	3.638	PK
4		9920.000	41.941	35.975	-32.059	74.000	5.966	PK


Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3966.500	50.745	52.487	-23.255	74.000	-1.742	PK
2		4960.000	40.900	41.777	-33.100	74.000	-0.877	PK
3		7440.000	42.743	39.104	-31.257	74.000	3.638	PK
4		9920.000	42.723	36.757	-31.277	74.000	5.966	PK




Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3847.500	51.203	53.133	-22.797	74.000	-1.930	PK
2		4804.000	39.889	40.408	-34.111	74.000	-0.519	PK
3		7206.000	42.627	38.611	-31.373	74.000	4.016	PK
4		9608.000	42.602	36.784	-31.398	74.000	5.817	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3847.500	50.420	52.350	-23.580	74.000	-1.930	PK
2		4804.000	39.799	40.318	-34.201	74.000	-0.519	PK
3		7206.000	43.002	38.986	-30.998	74.000	4.016	PK
4		9608.000	42.940	37.122	-31.060	74.000	5.817	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2441MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3907.000	51.628	54.248	-22.372	74.000	-2.620	PK
2		4882.000	39.757	40.270	-34.243	74.000	-0.514	PK
3		7323.000	42.184	38.257	-31.816	74.000	3.927	PK
4		9764.000	42.710	37.580	-31.290	74.000	5.131	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2441MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3907.000	50.227	52.847	-23.773	74.000	-2.620	PK
2		4882.000	40.135	40.648	-33.865	74.000	-0.514	PK
3		7323.000	42.769	38.842	-31.231	74.000	3.927	PK
4		9764.000	43.024	37.894	-30.976	74.000	5.131	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3966.500	52.579	54.321	-21.421	74.000	-1.742	PK
2		4960.000	38.795	39.672	-35.205	74.000	-0.877	PK
3		7440.000	42.388	38.749	-31.612	74.000	3.638	PK
4		9920.000	42.525	36.559	-31.475	74.000	5.966	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3966.500	50.972	52.714	-23.028	74.000	-1.742	PK
2		4960.000	38.777	39.654	-35.223	74.000	-0.877	PK
3		7440.000	42.021	38.382	-31.979	74.000	3.638	PK
4		9920.000	42.658	36.692	-31.342	74.000	5.966	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3847.500	51.317	53.247	-22.683	74.000	-1.930	PK
2		4804.000	39.968	40.487	-34.032	74.000	-0.519	PK
3		7206.000	43.698	39.682	-30.302	74.000	4.016	PK
4		9608.000	42.510	36.692	-31.490	74.000	5.817	PK


Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3847.500	51.070	53.000	-22.930	74.000	-1.930	PK
2		4804.000	39.589	40.108	-34.411	74.000	-0.519	PK
3		7206.000	42.716	38.700	-31.284	74.000	4.016	PK
4		9608.000	43.453	37.635	-30.547	74.000	5.817	PK




Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2441MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3907.000	51.338	53.958	-22.662	74.000	-2.620	PK
2		4882.000	39.601	40.114	-34.399	74.000	-0.514	PK
3		7323.000	42.479	38.552	-31.521	74.000	3.927	PK
4		9764.000	41.979	36.849	-32.021	74.000	5.131	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2441MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3907.000	49.823	52.443	-24.177	74.000	-2.620	PK
2		4882.000	39.648	40.161	-34.352	74.000	-0.514	PK
3		7323.000	42.090	38.163	-31.910	74.000	3.927	PK
4		9764.000	42.295	37.165	-31.705	74.000	5.131	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3966.500	52.387	54.129	-21.613	74.000	-1.742	PK
2		4960.000	38.703	39.580	-35.297	74.000	-0.877	PK
3		7440.000	42.631	38.992	-31.369	74.000	3.638	PK
4		9920.000	41.821	35.855	-32.179	74.000	5.966	PK

Engineer: Tommie	
Site: AC5	Time: 2018/03/13 - 11:37
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2480MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	3966.500	50.440	52.182	-23.560	74.000	-1.742	PK
2		4960.000	38.729	39.606	-35.271	74.000	-0.877	PK
3		7440.000	42.507	38.868	-31.493	74.000	3.638	PK
4		9920.000	42.211	36.245	-31.789	74.000	5.966	PK

Note:

1. Measured Level = Reading Level + Factor.
2. The test frequency range, 9kHz~30MHz, 18GHz~26GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
4. As the radiated emission was performed, so conducted emission was not tested.


### The worst case of Radiated Emission below 1GHz:

Site: AC3	Time: 2018/02/05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1	*	30.925	30.226	2.800	-9.774	40.000	20.966	6.460	0.000	100	94	QP
2		36.521	26.971	1.800	-13.029	40.000	18.668	6.503	0.000	200	349	QP
3		278.956	31.329	10.800	-14.671	46.000	12.980	7.548	0.000	200	121	QP
4		421.497	31.402	4.200	-14.598	46.000	19.242	7.960	0.000	100	198	QP
5		624.864	33.795	3.900	-12.205	46.000	21.406	8.489	0.000	100	269	QP
6		878.916	35.044	3.800	-10.956	46.000	22.186	9.058	0.000	100	244	QP

Site: AC3	Time: 2018/02/05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Probe (dB/m)	Cable (dB)	Amp (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		30.156	28.255	4.200	-11.745	40.000	17.601	6.454	0.000	100	69	QP
2		56.764	25.121	8.900	-14.879	40.000	9.594	6.627	0.000	200	169	QP
3		142.059	26.692	7.500	-16.808	43.500	12.147	7.046	0.000	100	336	QP
4		212.818	30.503	7.400	-12.997	43.500	15.775	7.328	0.000	100	244	QP
5		863.862	36.890	4.100	-9.110	46.000	23.765	9.026	0.000	100	263	QP
6	*	949.464	38.123	3.800	-7.877	46.000	25.121	9.201	0.000	200	344	QP

## 5. 20dB Bandwidth

### 5.1 Test Equipment

20dB Occupied Bandwidth / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

### 5.2 Test Setup



### 5.3 Limit

Carrier Frequency Separation	
<input checked="" type="checkbox"/>	For frequency hopping systems operating in 2400-2483.5 MHz band, within frequency range.
<input type="checkbox"/>	For frequency hopping systems operating in 902-928 MHz band, the maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
<input type="checkbox"/>	For frequency hopping systems operating in 5725-5850 MHz band, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

## 5.4 Test Procedure

Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	DA 00-705	N/A	20 dB Bandwidth

## 5.5 Uncertainty

The measurement uncertainty is defined as  $\pm 1$  kHz




## 5.6 Test Result


Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	927.2	887.66
39	2441	922.5	887.08
78	2480	924.4	888.79


Channel 00 (2402MHz)



## Channel 39 (2441MHz)




## Channel 78 (2480MHz)




Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 2	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1388	1235.3
39	2441	1386	1231.2
78	2480	1385	1232.3


### Channel 00 (2402MHz)



## Channel 39 (2441MHz)




## Channel 78 (2480MHz)




Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 3	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Channel No.	Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
00	2402	1371	1230.6
39	2441	1369	1230.3
78	2480	1367	1229.1


### Channel 00 (2402MHz)



## Channel 39 (2441MHz)



## Channel 78 (2480MHz)



## 6. Carrier Frequency Separation


### 6.1. Test Equipment

Carrier Frequency Separation / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 6.2. Test Setup

Carrier Frequency Separation test setup:



### 6.3. Limit

Carrier Frequency Separation	
<input type="checkbox"/>	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
<input checked="" type="checkbox"/>	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.
<input type="checkbox"/>	The 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period;
<input type="checkbox"/>	The 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.
<input type="checkbox"/>	Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz.

### 6.4. Test Procedure

Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	7.8.2	Carrier frequency separation

### 6.5. Uncertainty

The measurement uncertainty is defined as  $\pm 1$  kHz




## 6.6. Test Result


Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	618.1	Pass
39	2441	1000	615.0	Pass
78	2480	1000	616.3	Pass


Channel 00 (2402MHz)



## Channel 39 (2441MHz)




## Channel 78 (2480MHz)




Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 2	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	925.3	Pass
39	2441	1000	924.0	Pass
78	2480	1000	923.3	Pass


### Channel 00 (2402MHz)



## Channel 39 (2441MHz)




## Channel 78 (2480MHz)



Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 3	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Channel No.	Frequency (MHz)	Carrier Frequency Separation (kHz)	Limit (kHz)	Result
00	2402	1000	914.0	Pass
39	2441	1000	912.7	Pass
78	2480	1000	911.3	Pass


### Channel 00 (2402MHz)



## Channel 39 (2441MHz)



## Channel 78 (2480MHz)




## 7. Number of Hopping Frequencies

### 7.1. Test Equipment

Number of Hopping Frequencies / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

### 7.2. Test Setup



### 7.3. Limit

Carrier Frequency Separation	
<input checked="" type="checkbox"/>	For frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies.
<input type="checkbox"/>	For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is less than 250 kHz, shall use at least 50 hopping frequencies.
<input type="checkbox"/>	For frequency hopping systems operating in 902-928 MHz band, if the 20 dB bandwidth of the hopping channel is higher than 250 kHz, shall use at least 25 hopping frequencies.
<input type="checkbox"/>	For frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

## 7.4. Test Procedure

Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	7.8.3	Number of Hopping Frequencies

## 7.5. Uncertainty

The measurement uncertainty is defined as  $\pm 1$  kHz




## 7.6. Test Result

Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


### 2402 - 2480MHz



Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 2	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass


### 2402 - 2480 MHz



Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 3	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Frequency Band (MHz)	Number of Hopping Frequencies	Limit	Result
2400 - 2483.5	79	>15	Pass

### 2402 - 2480 MHz




## 8. Time of Occupancy (Dwell Time)

### 8.1. Test Equipment

Time of Occupancy (Dwell Time) / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2018.02.04	2019.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2018.04.09	2019.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2018.04.09	2019.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2018.04.10	2019.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

### 8.2. Test Setup



### 8.3. Limit

Time of Occupancy (Dwell Time)	
<input checked="" type="checkbox"/>	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
<input type="checkbox"/>	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period
<input type="checkbox"/>	For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping

	frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.
<input type="checkbox"/>	Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies. The maximum 20 dB bandwidth of the hopping channel is 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

#### 8.4. Test Procedure

Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	7.8.4	Time of Occupancy (Dwell Time)

#### 8.5. Uncertainty

The measurement uncertainty is defined as  $\pm 0.1 \text{ us}$

## 8.6. Test Result

Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1(GFSK_DH1)	Test Site	: TR-8
Test Date	: 2018.04.19	Test Engineer	: Tommie


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	118.11	< 400	Pass


Note1: Test Time Period:  $0.4 \times 79 = 31.6 \text{ sec}$

Note2: Time of Occupancy =  $0.381 \times 31 \times 31.6 / 3.16 = 117.6 \text{ ms}$

Note3: We have evaluated different packet type, shown in the report is the worst data.

### Channel 39 (2441MHz)-(DH1)





Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1(GFSK_DH3)	Test Site	: TR-8
Test Date	: 2018.04.19	Test Engineer	: Tommie


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	260.64	< 400	Pass

Note1: Test Time Period:  $0.4 \times 79 = 31.6 \text{ sec}$


Note2: Time of Occupancy =  $1.629 \times 16 \times 31.6 / 3.16$

Note3: We have evaluated different packet type, shown in the report is the worst data.

### Channel 39 (2441MHz) - (DH3)







Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1(GFSK_DH5)	Test Site	: TR-8
Test Date	: 2018.04.19	Test Engineer	: Tommie


Channel No.	Frequency (MHz)	Time of Occupancy (ms)	Limit (ms)	Result
39	2441	346.08	< 400	Pass


Note1: Test Time Period:  $0.4 \times 79 = 31.6 \text{ sec}$

Note2: Time of Occupancy =  $2.884 \times 12 \times 31.6 / 3.16$

Note3: We have evaluated different packet type, shown in the report is the worst data.

### Channel 39 (2441MHz) - (DH5)






## 9. Peak Output Power

### 9.1. Test Equipment

Peak Output Power / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2018.02.04	2019.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09

Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

### 9.2. Test Setup



### 9.3. Limit

Peak Output Power	
<input type="checkbox"/>	Frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
<input checked="" type="checkbox"/>	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
<input type="checkbox"/>	For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels

### 9.4. Test Procedure

Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	7.8.5	Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices

### 9.5. Uncertainty

The measurement uncertainty is defined as  $\pm 1.0$  dB

## 9.6. Test Result

Product Name	:	EZ-BT WICED Module	Power	:	AC 120V/60Hz
Test Mode	:	Mode 1	Test Site	:	TR-8
Test Date	:	2018.02.06	Test Engineer	:	Tommie

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
00	2402	9.06	21.00	Pass
39	2441	9.83	21.00	Pass
78	2480	9.89	21.00	Pass

Product Name	:	EZ-BT WICED Module	Power	:	AC 120V/60Hz
Test Mode	:	Mode 2	Test Site	:	TR-8
Test Date	:	2018.02.06	Test Engineer	:	Tommie

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
00	2402	7.63	21.00	Pass
39	2441	7.92	21.00	Pass
78	2480	7.38	21.00	Pass

Product Name	:	EZ-BT WICED Module	Power	:	AC 120V/60Hz
Test Mode	:	Mode 3	Test Site	:	TR-8
Test Date	:	2018.02.06	Test Engineer	:	Tommie

Channel No.	Frequency (MHz)	Measurement Power Output (dBm)	Limit (dBm)	Result
00	2402	7.86	21.00	Pass
39	2441	8.15	21.00	Pass
78	2480	7.61	21.00	Pass




## 10. Emissions in non-restricted frequency bands

### 10.1. Test Equipment

Emissions in non-restricted frequency bands / TR-8					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2017.02.04	2018.02.03
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2017.04.09	2018.04.08
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2017.04.09	2018.04.08
Temperature/Humidity Meter	zhichen	ZC1-2	TR8-TH	2017.04.10	2018.04.09
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

### 10.2. Test Setup



### 10.3. Limit

Un-Restricted Band Emissions Limit	
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30c(Note1)
RF Output power(PK detector)	20c(Note2)
<p>Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).</p> <p>Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).</p>	

### 10.4. Test Procedure

Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	7.8.6	Band-edge Compliance of RF Conducted Emissions

### 10.5. Uncertainty

The measurement uncertainty is defined as  $\pm 1.0$  dB

## 10.6. Test Result


Product Name	: EZ-BT WICED Module	Power	: AC 120V/60Hz
Test Mode	: Mode 1~4	Test Site	: TR-8
Test Date	: 2018.02.02	Test Engineer	: Tommie

Mode	Channel	Test Frequency (MHz)	In-Band PSD[a] (dBm/100kHz)	Frequency (MHz)	Out-Band PSD[b] (dBm/100kHz)	[a]-[b] (dB)	Limit (dB)	Result
1	00	2402	7.775	2400.00	-47.763	55.538	>20	Pass
1	78	2480	8.654	2500.00	-46.084	54.738	>20	Pass
2	00	2402	3.433	2400.00	-50.539	53.972	>20	Pass
2	78	2480	3.251	2500.00	-50.891	54.142	>20	Pass
3	00	2402	3.591	2400.00	-45.784	49.375	>20	Pass
3	78	2480	3.518	2500.00	-51.138	54.656	>20	Pass
4	00~78	00~78	3.785	2400.00	-51.216	55.001	>20	Pass

Note1: The worst case of Emissions in non-restricted frequency bands as below:

2: Mode 1-3, The In-Band PSD is the highest PSD of All channels.

Mode3 CH00(2402MHz)




## 11. Radiated Emission Band Edge

### 11.1. Test Equipment

Radiated Emission(Above 1GHz) / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Receiver	Agilent	N9038A	MY51210196	2017.07.16	2018.07.15
Pre-Amplifier	Miteq	NSP1800-25	1364185	2017.05.03	2018.05.02
DRG Horn Antenna	ETS-Lindgren	3117	00167055	2017.07.12	2018.07.11
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2017.09.18	2018.09.17
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.02.28	2018.02.27
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.02.28	2018.02.27
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2018.01.05	2019.01.04

### 11.2. Test Setup



### 11.3. Limit

Band edge Limit				
Frequency bands (MHz)	Detector	Limit (dB $\mu$ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

### 11.4. Test Procedure


Test Method			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	DA 00-705	N/A	duty cycle correction factor
<input checked="" type="checkbox"/>	ANSI C63.10	6.10	Band-edge testing
<input checked="" type="checkbox"/>	ANSI C63.10	6.10.5	Restricted-band band-edge measurements
<input type="checkbox"/>	ANSI C63.10	6.10.6	Marker-delta method
<input type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

### 11.5. Uncertainty

The measurement uncertainty above 1G is defined as  $\pm 3.9$  dB  
below 1G is defined as  $\pm 3.8$  dB


## 11.6. Duty Factor

Test Mode	Pluse Time (ms)	Pluse Number	Accumulated Transmit Time (ms)	Duty Factor (dB)
Mode 4	2.9	1	2.9	-30.752



## 11.7. Test Result


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 20:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.970	14.640	-23.030	74.000	36.329	PK
2	*	2401.770	89.896	53.567	N/A	N/A	36.328	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.970	20.218	-33.782	54.000	-30.752	AV
2	*	2401.770	89.896	59.144	N/A	N/A	-30.752	AV

Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:04
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.558	15.228	-22.442	74.000	36.329	PK
2	*	2402.198	79.175	42.846	N/A	N/A	36.329	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.558	20.806	-33.194	54.000	-30.752	AV
2	*	2402.198	79.175	48.423	N/A	N/A	-30.752	AV




Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.947	84.773	48.359	N/A	N/A	36.414	PK
2		2483.500	51.192	14.725	-22.808	74.000	36.467	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2479.947	84.773	54.021	N/A	N/A	-30.752	AV
2	*	2483.500	51.192	20.440	-33.560	54.000	-30.752	AV


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:09
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2479.837	75.438	39.026	N/A	N/A	36.412	PK
2		2483.500	51.680	15.213	-22.320	74.000	36.467	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2479.837	75.438	44.686	N/A	N/A	-30.752	AV
2	*	2483.500	51.680	20.928	-33.072	54.000	-30.752	AV


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.665	14.335	-23.335	74.000	36.329	PK
2	*	2402.103	87.901	51.572	N/A	N/A	36.329	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.665	19.913	-34.087	54.000	-30.752	AV
2	*	2402.103	87.901	57.149	N/A	N/A	-30.752	AV


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:13
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.072	14.742	-22.928	74.000	36.329	PK
2	*	2401.913	77.394	41.065	N/A	N/A	36.328	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.072	20.320	-33.680	54.000	-30.752	AV
2	*	2401.913	77.394	46.642	N/A	N/A	-30.752	AV


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:16
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.079	82.662	46.246	N/A	N/A	36.416	PK
2		2483.500	51.511	15.044	-22.489	74.000	36.467	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2480.079	82.662	51.910	N/A	N/A	-30.752	AV
2	*	2483.500	51.511	20.759	-33.241	54.000	-30.752	AV


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:18
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.035	73.454	37.039	N/A	N/A	36.415	PK
2		2483.500	50.956	14.489	-23.044	74.000	36.467	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2480.035	73.454	42.702	N/A	N/A	-30.752	AV
2	*	2483.500	50.956	20.204	-33.796	54.000	-30.752	AV


Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.898	14.568	-23.102	74.000	36.329	PK
2	*	2401.865	88.232	51.903	N/A	N/A	36.328	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	50.898	20.146	-33.854	54.000	-30.752	AV
2	*	2401.865	88.232	57.480	N/A	N/A	-30.752	AV

Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by 3DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.044	14.714	-22.956	74.000	36.329	PK
2	*	2401.913	77.641	41.312	N/A	N/A	36.328	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2390.000	51.044	20.292	-33.708	54.000	-30.752	AV
2	*	2401.913	77.641	46.889	N/A	N/A	-30.752	AV




Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.035	83.261	46.846	N/A	N/A	36.415	PK
2		2483.500	51.200	14.733	-22.800	74.000	36.467	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2480.035	83.261	52.509	N/A	N/A	-30.752	AV
2	*	2483.500	51.200	20.448	-33.552	54.000	-30.752	AV

Engineer: Tommie	
Site: AC5	Time: 2018/02/06 - 21:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: EZ-BT WICED Module	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2480MHz by 3DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2480.068	73.665	37.249	N/A	N/A	36.416	PK
2		2483.500	52.563	16.096	-21.437	74.000	36.467	PK

No	Mark	Frequency (MHz)	PK Level (dBuV/m)	AV Level (dBuV/m)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2480.068	73.665	42.913	N/A	N/A	-30.752	AV
2	*	2483.500	52.563	21.811	-32.189	54.000	-30.752	AV

## 12. Antenna Requirement

### 12.1. Limit

Antenna Requirement Limit	
<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.</p>	

### 12.2. Antenna Connector Construction

Antenna Connector Construction	
<input checked="" type="checkbox"/>	The use of a permanently attached antenna
<input type="checkbox"/>	The antenna use of a unique coupling to the intentional radiator
<input type="checkbox"/>	The use of a nonstandard antenna jack or electrical connector
Please refer to the attached document "Internal Photograph" to show the antenna connector.	

\_\_\_\_\_ The End \_\_\_\_\_