



C2PC Test Report

FCC Part15 Subpart E

Product Name : Wireless Access point

Model No. : AP122, AP122X

FCC ID : WBV-AP122

Applicant : Aerohive Networks, Inc.

Address : Aerohive Networks, 1011 McCarthy Boulevard,
Milpitas, CA 95035, United States

Date of Receipt : Oct. 10, 2017

Test Date : Oct. 10, 2017~ Nov. 24, 2017

Issued Date : Dec.13, 2017

Report No. : 17A2003R-RF-US-P09V01

Report Version : V1.0

The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF, A2LA or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.

Test Report Certification

Issued Date : Dec. 13, 2017

Report No. : 17A2003R-RF-US-P09V01



Product Name : Wireless Access point
Applicant : Aerohive Networks, Inc.
Address : Aerohive Networks, 1011 McCarthy Boulevard, Milpitas, CA
95035, United States
Manufacturer : Aerohive Networks, Inc.
Address : Aerohive Networks, 1011 McCarthy Boulevard, Milpitas, CA
95035, United States
Model No. : AP122, AP122X
FCC ID : WBV-AP122
EUT Voltage : PoE 48V
Test Voltage : AC 120V/60Hz
Brand Name : Aerohive
Applicable Standard : FCC CFR Title 47 Part 15 Subpart E
ANSI C63.10:2013;
789033 D02 General UNII Test Procedures New Rules
v01r04
KDB 662911 D01 Multiple Transmitter Output v02r01
Test Result : Complied
Performed Location : DEKRA Testing and Certification (Suzhou) Co., Ltd.
No.99 Hongye Rd., Suzhou Industrial Park, Suzhou,215006,
Jiangsu, China
TEL: +86-512-6251-5088 / FAX: +86-512-6251-5098
FCC Designation Number: CN1199

Documented By : Kathy Feng
(Project Assistant: Kathy Feng)

Reviewed By : Frank He
(Senior Engineer: Frank He)

Approved By : Harry Zhao
(Engineering Manager: Harry Zhao)

TABLE OF CONTENTS

Description	Page
1. General Information	6
1.1. EUT Description	6
1.2. Antenna information	6
1.3. Working Frequency of Each Channel:	8
1.4. Mode of Operation	9
1.5. Tested System Details	10
1.6. Configuration of Tested System	11
1.7. EUT Exercise Software	12
2. Technical Test	13
2.1. Summary of Test Result	13
2.2. Test Frequency configuration:	13
2.3. Power Parameter Value of the test software	14
2.4. Power vs Data Rate	18
2.5. Duty Cycle	20
2.6. Test Environment	22
2.7. Uncertainty	22
3. Conducted Emission	23
3.1. Test Equipment	23
3.2. Test Setup	23
3.3. Limit	24
3.4. Test Procedure	24
3.5. Test Result	25
4. Radiated Emission	29
4.1. Test Equipment	29
4.2. Test Setup	30
4.3. Limit	31
4.4. Test Procedure	34

4.5.	EUT test Axis definition	35
4.6.	Test Result	36
5.	Power Output.....	255
5.1.	Test Equipment	255
5.2.	Test Setup	255
5.3.	Limit.....	256
5.4.	Test Procedure	257
5.5.	EUT test Axis definition	259
5.6.	Test Result	260
6.	Peak Power Spectral Density.....	267
6.1.	Test Equipment	267
6.2.	Test Setup	267
6.3.	Limit.....	268
6.4.	Test Procedure	269
6.5.	EUT test Axis definition	270
6.6.	Test Result	271
7.	Radiated Emission Band Edge	282
7.1.	Test Equipment	282
7.2.	Test Setup	282
7.3.	Limit.....	283
7.4.	Test Procedure	286
7.5.	EUT test Axis definition	287
7.6.	Test Result	288
8.	Antenna Requirement.....	486
8.1.	Limit.....	486
8.2.	Antenna Connector Construction	486

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
17A2003R-RF-US-P09V01	V1.0	Initial Issued Report	Dec. 13, 2017

1. General Information

1.1. EUT Description

Product Name	Wireless Access point					
Brand Name	Aerohive					
Model No.	AP122, AP122X					
EUT Voltage	PoE 48V					
Type of Modulation	OFDM-BPSK, QPSK, 16QAM, 64QAM, 128QAM, 256QAM					
Data Rate	802.11a: 6/9/12/18/24/36/48/54Mbps					
	802.11n: up to 300Mbps					
	802.11ac: up to 866.6Mbps					
Channel Control	Auto					
Transmit modes	<input checked="" type="checkbox"/>	802.11a	<input checked="" type="checkbox"/>	802.11n(20MHz)	<input checked="" type="checkbox"/>	802.11n(40MHz)
	<input checked="" type="checkbox"/>	802.11ac(20MHz)	<input checked="" type="checkbox"/>	802.11ac(40MHz)	<input checked="" type="checkbox"/>	802.11ac(80MHz)
Support Bands	<input checked="" type="checkbox"/>	5150MHz~5250MHz	<input type="checkbox"/>	Outdoor AP		
			<input checked="" type="checkbox"/>	Indoor AP		
			<input type="checkbox"/>	Fixed point-to-point AP		
			<input type="checkbox"/>	Mobile and Portable Client		
	<input type="checkbox"/>	5250MHz~5350MHz				
	<input type="checkbox"/>	5470MHz~5725MHz	<input type="checkbox"/>	With TDWR Channels		
			<input type="checkbox"/>	Without TDWR Channels		
	<input checked="" type="checkbox"/>	5725MHz~5850MHz				

Note:

1. Adding a model AP122X, the difference is as below:

	Antenna Type	Max Antenna Gain(2.4G)	Max Antenna Gain(5G)
AP122	Internal PIFA Antenna	3.8 dBi	5.44 dBi
AP122X	External Dipole Antenna	4 dBi	4 dBi

1.2. Antenna information

Antenna Model No.	N/A			
Antenna Manufacturer	N/A			
Antenna Delivery	<input checked="" type="checkbox"/> 1*TX+1*RX	<input checked="" type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+4*RX	
Antenna Technology	<input checked="" type="checkbox"/> SISO <input type="checkbox"/> Basic methodology <input type="checkbox"/> Sectorized antenna systems <input type="checkbox"/> Cross-polarized antennas <input type="checkbox"/> Unequal antenna gains, with equal transmit powers <input type="checkbox"/> Spatial Multiplexing <input checked="" type="checkbox"/> Cyclic Delay Diversity (CDD)			
Antenna Type	Dipole Antenna			
Antenna Technology	Ant Gain (dBi)		Directional Gain (dBi)	
			For Power	For PSD
<input checked="" type="checkbox"/> CDD	Ant1:4 Ant2: 4		4	7.01
<input checked="" type="checkbox"/> Beam-forming	Ant1:4 Ant2: 4		7.01	7.01

1.3. Working Frequency of Each Channel:

802.11a/n/ac(20MHz) Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
36	5180 MHz	40	5200 MHz	44	5220 MHz	48	5240 MHz
149	5745 MHz	153	5765 MHz	157	5785 MHz	161	5805 MHz
165	5825MHz	N/A	N/A	N/A	N/A	N/A	N/A
802.11n/ac(40MHz) Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz	151	5755 MHz	159	5795 MHz
802.11ac(80MHz) Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
42	5210 MHz	155	5775 MHz	N/A	N/A	N/A	N/A

1.4. Mode of Operation

DEKRA Testing and Certification (Suzhou) Co., Ltd. has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Transmit by 802.11a with SISO
Mode 2: Transmit by 802.11n(20MHz) with SISO
Mode 3: Transmit by 802.11n(40MHz) with SISO
Mode 4: Transmit by 802.11ac(20MHz) with SISO
Mode 5: Transmit by 802.11ac(40MHz) with SISO
Mode 6: Transmit by 802.11ac(80MHz) with SISO
Mode 7: Transmit by 802.11a with CDD
Mode 8: Transmit by 802.11n(20MHz) with CDD
Mode 9: Transmit by 802.11n(40MHz) with CDD
Mode 10: Transmit by 802.11ac(20MHz) with CDD
Mode 11: Transmit by 802.11ac(40MHz) with CDD
Mode 12: Transmit by 802.11ac(80MHz) with CDD
Mode 13: Transmit by 802.11n(20MHz) with Beam-forming
Mode 14: Transmit by 802.11n(40MHz) with Beam-forming
Mode 15: Transmit by 802.11ac(20MHz) with Beam-forming
Mode 16: Transmit by 802.11ac(40MHz) with Beam-forming
Mode 17: Transmit by 802.11ac(80MHz) with Beam-forming

Note 1: Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report.

Note 2: For portable device, radiated tests was verified over X, Y, Z axis, and shown the worst case on this report.


1.5. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:


Product		Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook	Lenovo	Think pad x220	SUA0600195	Non-shielded
A	USB cable	N/A	N/A	N/A	Shielded, 0.5m
B	USB cable	N/A	N/A	N/A	Shielded, 10m

1.6. Configuration of Tested System

Test setup Diagram- AC Line Conducted Emission Test



Test setup Diagram- Radiated Emission



1.7. EUT Exercise Software

1	Setup the EUT and simulators as shown on above.
2	Turn on the power of equipment.
3	Run RF software [MTool], and set the test mode and channel, then press OK to start to continue transmit.

2. Technical Test

2.1. Summary of Test Result

- ☒ No deviations from the test standards
☐ Deviations from the test standards as below description:

Performed Test Item	Normative References	Limit	Result
Conducted Emission	FCC CFR Title 47 Part 15 Subpart E: 2015 Section 15.207	FCC 15.207	PASS
Radiated Emission	FCC CFR Title 47 Part 15 Subpart E: 2015 Section 15.209	FCC 15.209	PASS
Power Output	FCC CFR Title 47 Part 15 Subpart E: 2015 Section 15.407(a)	FCC 15.407(a)	PASS
Peak Power Spectral Density	FCC CFR Title 47 Part 15 Subpart E: 2015 Section 15.407(a)	FCC 15.407(a)	PASS
Radiated Emission Band Edge	FCC CFR Title 47 Part 15 Subpart E: 2015 Section 15.205, 15.407(b)	FCC 15.407(b)	PASS
Antenna Requirement	FCC CFR Title 47 Part 15 Subpart C: Section 15.203	FCC 15.203	PASS

2.2. Test Frequency configuration:

Modulation Mode	Channel	Frequency	Channel	Frequency	Channel	Frequency
802.11a/n(20MHz)/ac(20MHz)	36	5180MHz	44	5220MHz	48	5240MHz
	149	5745MHz	157	5785MHz	165	5825MHz
802.11n(40MHz)/ac(40MHz)	38	5190MHz	46	5230MHz	151	5755MHz
	159	5795MHz	N/A	N/A	N/A	N/A
802.11ac(80MHz)	42	5210MHz	155	5775MHz	N/A	N/A

2.3. Power Parameter Value of the test software

Test Mode	Frequency	Power Setting		
		Ant 1	Ant 2	Ant 1+2
802.11a with SISO	5180	70	70	-
	5220	70	70	-
	5240	70	70	-
	5745	82	82	-
	5785	82	82	-
	5825	82	82	-
802.11n(20MHz) with SISO	5180	68	68	-
	5220	68	68	-
	5240	68	68	-
	5745	82	82	-
	5785	82	82	-
	5825	82	82	-
802.11n(40MHz) with SISO	5190	62	58	-
	5230	62	58	-
	5755	82	82	-
	5795	82	82	-

802.11ac(20MHz) with SISO	5180	70	69	-
	5220	70	69	-
	5240	70	69	-
	5745	82	82	-
	5785	82	82	-
	5825	82	82	-
802.11ac(40MHz) with SISO	5190	60	56	-
	5230	60	56	-
	5755	82	82	-
	5795	82	82	-
802.11ac(80MHz) with SISO	5210	62	58	-
	5775	64	64	-
802.11a with CDD	5180	-	-	66
	5220	-	-	66
	5240	-	-	66
	5745	-	-	82
	5785	-	-	82
	5825	-	-	82
802.11n(20MHz) with CDD	5180	-	-	66
	5220	-	-	66
	5240	-	-	66
	5745	-	-	82
	5785	-	-	82
	5825	-	-	82
802.11n(40MHz) with CDD	5190	-	-	56
	5230	-	-	56
	5755	-	-	82
	5795	-	-	82

802.11ac(20MHz) with CDD	5180	-	-	68
	5220	-	-	68
	5240	-	-	68
	5745	-	-	82
	5785	-	-	82
	5825	-	-	82
802.11ac(40MHz) with CDD	5190	-	-	55
	5230	-	-	55
	5755	-	-	82
	5795	-	-	82
802.11ac(80MHz) with CDD	5210	-	-	56
	5290	-	-	59
	5530	-	-	53
	5775	-	-	63
802.11n(20MHz) with Beam-forming	5180	-	-	16
	5220	-	-	16
	5240	-	-	16
	5745	-	-	19
	5785	-	-	19
	5825	-	-	19
802.11n(40MHz) with Beam-forming	5190	-	-	13
	5230	-	-	13
	5755	-	-	19
	5795	-	-	19

802.11ac(20MHz) with Beam-forming	5180	-	-	16
	5220	-	-	16
	5240	-	-	16
	5745	-	-	19
	5785	-	-	19
	5825	-	-	19
802.11ac(40MHz) with Beam-forming	5190	-	-	13
	5230	-	-	13
	5755	-	-	19
	5795	-	-	19
802.11ac(80MHz) with Beam-forming	5210	-	-	13
	5775	-	-	15

2.4. Power vs Data Rate

MCS Index for 802.11n	Spatial Streams	Data Rate (Mbps)						
		802.11b	802.11g	802.11a	20MHz Bandwidth		40MHz Bandwidth	
					800ns GI	400ns GI	800ns GI	400ns GI
0	1	1	6	6	6.5	7.2	13.5	15.0
1	1	2	9	9	13.0	14.4	27.0	30.0
2	1	5.5	12	12	19.5	21.7	40.5	45.0
3	1	11	18	18	26.0	28.9	54.0	60.0
4	1	---	24	24	39.0	43.3	81.0	90.0
5	1	---	36	36	52.0	57.8	108.0	120.0
6	1	---	48	48	58.5	65.0	121.5	135.0
7	1	---	54	54	65.0	72.2	135.0	150.0
8	2	---	---	---	13.0	14.4	27.0	30.0
9	2	---	---	---	26.0	28.9	54.0	60.0
10	2	---	---	---	39.0	43.3	81.0	90.0
11	2	---	---	---	52.0	57.8	108.0	120.0
12	2	---	---	---	78.0	86.7	162.0	180.0
13	2	---	---	---	104.0	115.6	216.0	240.0
14	2	---	---	---	117.0	130.0	243.0	270.0
15	2	---	---	---	130.0	144.0	270.0	300.0

Note 1 : The blue form is the maximum power data rate

2: The EUT supports two spatial streams.

Spatial Streams (Note1)	MCS Index	Modulation type	Coding rate	Data Rate(Mb/s)					
				20MHz		40MHz		80MHz	
				Guard Interval		Guard Interval		Guard Interval	
				800ns	400ns	800ns	400ns	800ns	400ns
1	0	BPSK	1/2	6.5	7.2	13.5	15	29.3	32.5
	1	QPSK	1/2	13	14.4	27	30	58.5	65
	2	QPSK	3/4	19.5	21.7	40.5	45	87.8	97.5
	3	16-QAM	1/2	26	28.9	54	60	117	130
	4	16-QAM	3/4	39	43.3	81	90	175.5	195
	5	64-QAM	2/3	52	57.8	108	120	234	260
	6	64-QAM	3/4	58.5	65	121.5	135	263.3	292.5
	7	64-QAM	5/6	65	72.2	135	150	292.5	325
	8	256-QAM	3/4	78	86.7	162	180	351	390
	9	256-QAM	5/6	N/A	N/A	180	200	390	433.3
2	0	BPSK	1/2	13	14.4	27	30	58.6	65
	1	QPSK	1/2	26	28.8	54	60	117	130
	2	QPSK	3/4	39	43.4	81	90	175.6	195
	3	16-QAM	1/2	52	57.8	108	120	234	260
	4	16-QAM	3/4	78	86.6	162	180	351	390
	5	64-QAM	2/3	104	115.6	216	240	468	520
	6	64-QAM	3/4	117	130	243	270	526.6	585
	7	64-QAM	5/6	130	144.4	270	300	585	650
	8	256-QAM	3/4	156	173.4	324	360	702	780
	9	256-QAM	5/6	N/A	N/A	360	400	780	866.6
Note 1: The blue form is the maximum power data rate.									
2: The EUT supports two spatial streams.									


2.5. Duty Cycle

Test Mode	Tx On (ms)	Tx Off (ms)	VBW	Tx On + Tx Off (ms)	Duty Cycle
802.11a	2.058	0.12	510Hz	2.178	94.49%
802.11n(20MHz)	1.908	0.108	560Hz	2.016	94.64%
802.11n(40MHz)	0.915	0.114	1.1kHz	1.029	88.92%
802.11ac(20MHz)	1.915	0.045	560Hz	1.960	97.70%
802.11ac(40MHz)	0.936	0.045	1.1kHz	0.981	95.41%
802.11ac(80MHz)	0.4447	0.046	2.4kHz	0.4907	90.63%


Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note 2: According to KDB 789033 , when test for Radiated Emission Band Edge and Radiated Emission, VBW 1/T will be used.


802.11a




802.11n(20MHz)




802.11n(40MHz)




802.11ac(20MHz)



802.11ac(40MHz)

802.11ac(80MHz)



2.6. Test Environment

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	21
Humidity (%RH)	25-75	50
Barometric pressure (mbar)	860-1060	950-1000

2.7. Uncertainty

Test Items	Uncertainty
AC Power Line Conducted Emission	$\pm 2.02\text{dB}$
Radiated Emission	Below 1GHz $\pm 3.8\text{ dB}$
	Above 1GHz $\pm 3.9\text{ dB}$
RF Antenna Port Conducted Emission	$\pm 1.27\text{dB}$
Radiated Emission Band Edge	$\pm 3.9\text{dB}$
Occupied Bandwidth	$\pm 1\text{kHz}$
Power Spectral Density	$\pm 1.27\text{dB}$
Frequency Stability	$\pm 100\text{ Hz}$


3. Conducted Emission

3.1. Test Equipment

Conducted Emission / TR-1					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100906	2017.03.05	2018.03.04
Two-Line V-Network	R&S	ENV 216	101189	2017.06.16	2018.06.15
Two-Line V-Network	R&S	ENV 216	101044	2017.09.16	2018.09.15
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	N/A	N/A
50ohm Termination	SHX	TF2	07081402	2017.09.16	2018.09.15
Temperature/Humidity Meter	Zhichen	ZC1-2	TR1-TH	2017.01.05	2018.01.04

Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

3.2. Test Setup



3.3. Limit

Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 – 56	56 – 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

3.4. Test Procedure

Test Method			
	References Rule	Chapter	Item
<input checked="" type="checkbox"/>	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

3.5. Test Result

Engineer: Lucas	
Site: TR1	Time: 2017/10/13 - 09:24
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101190(0.009-30MHz)	Polarity: Line
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5180MHz by 802.11a ANT 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.154	44.155	34.520	-21.627	65.781	9.609	0.025	0.000	QP
2	*	0.154	43.182	33.548	-12.599	55.781	9.609	0.025	0.000	AV
3		0.242	39.628	29.997	-22.400	62.027	9.600	0.030	0.000	QP
4		0.242	38.827	29.196	-13.201	52.027	9.600	0.030	0.000	AV
5		0.330	33.288	23.653	-26.163	59.451	9.600	0.035	0.000	QP
6		0.330	31.770	22.135	-17.682	49.451	9.600	0.035	0.000	AV
7		0.630	30.644	20.996	-25.356	56.000	9.600	0.048	0.000	QP
8		0.630	29.525	19.877	-16.475	46.000	9.600	0.048	0.000	AV
9		0.982	27.217	17.548	-28.783	56.000	9.609	0.060	0.000	QP
10		0.982	24.690	15.021	-21.310	46.000	9.609	0.060	0.000	AV
11		1.478	23.908	14.224	-32.092	56.000	9.610	0.073	0.000	QP
12		1.478	22.668	12.985	-23.332	46.000	9.610	0.073	0.000	AV


Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.

2. " * ", means this data is the worst emission level.

3. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

Engineer: Lucas	
Site: TR1	Time: 2017/10/13 - 09:27
Limit: FCC_Part15.107_CE_AC Power_ClassB	Margin: 0
Probe: ENV216_101190(0.009-30MHz)	Polarity: Neutral
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5180MHz by 802.11a ANT 1	



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.150	39.570	29.952	-26.430	66.000	9.594	0.025	0.000	QP
2	*	0.150	38.820	29.201	-17.180	56.000	9.594	0.025	0.000	AV
3		0.210	35.242	25.614	-27.964	63.205	9.599	0.029	0.000	QP
4		0.210	34.462	24.834	-18.743	53.205	9.599	0.029	0.000	AV
5		0.354	25.958	16.327	-32.910	58.868	9.594	0.036	0.000	QP
6		0.354	24.862	15.231	-24.006	48.868	9.594	0.036	0.000	AV
7		0.582	25.533	15.898	-30.467	56.000	9.590	0.045	0.000	QP
8		0.582	24.399	14.764	-21.601	46.000	9.590	0.045	0.000	AV
9		1.022	21.461	11.810	-34.539	56.000	9.591	0.060	0.000	QP
10		1.022	19.738	10.087	-26.262	46.000	9.591	0.060	0.000	AV
11		1.446	17.876	8.204	-38.124	56.000	9.599	0.073	0.000	QP
12		1.446	16.669	6.997	-29.331	46.000	9.599	0.073	0.000	AV

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.

3. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

4. Radiated Emission


4.1. Test Equipment

Radiated Emission / AC-2					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	R&S	ESCI	100573	2017.03.29	2018.03.28
Loop Antenna	R&S	HFH2-Z2	833799/003	2017.11.16	2018.11.15
Bilog Antenna	Teseq GmbH	CBL6112D	27611	2017.10.16	2018.10.15
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2017.03.02	2018.03.01
Temperature/Humidity Meter	Zhichen	ZC1-2	AC2-TH	2017.01.04	2018.01.03


Radiated Emission / AC-5					
Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4446A	MY45300103	2017.01.04	2018.01.03
Preamplifier	Miteq	NSP1800-25	1364185	2017.05.06	2018.05.05
Preamplifier	DEKRA Testing and Certification (Suzhou) Co., Ltd.	AP-040G	CHM-0906001	2017.05.06	2018.05.05
DRG Horn	ETS-Lindgren	3117	00123988	2017.01.22	2018.01.21
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2016.11.25	2017.11.24
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C1	2017.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2017.03.02	2018.03.01
Coaxial Cable	Huber+Suhner	SUCOFLEX 102	AC5-C3	2017.03.02	2018.03.01
EMI Receiver	Agilent	N9038A	MY51210196	2017.06.10	2018.06.09
Temperature/Humidity Meter	Zhichen	ZC1-2	AC5-TH	2017.01.04	2018.01.03
Note: All equipment are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.					

4.2. Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




4.3. Limit

FCC Part 15 Subpart C Paragraph 15.209 (Restricted Band Emissions Limit)		
Frequency (MHz)	Distance (m)	Level (dB μ V/m)
0.009-0.490	300	2400/F(kHz)
0.490-1.705	30	24000/F(kHz)
1.705-30.0	30	30
30-88	3	100**
88-216	3	150**
216-960	3	200**
Above 960	3	500

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).







FCC Part 15 Subpart C Paragraph 15.205 (Restricted Band)			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

FCC Part 15 Subpart C Paragraph 15.407(5)(b) (Unrestricted Band Emissions Limit)		
Operating Frequency Band (MHz)	EIRP Limit (dBm/MHz)	Equivalent Field Strength at 3m (dB μ V/m)
5150 - 5250	-27	68.3
5250 - 5350	-27	68.3
5470 - 5725	-27	68.3
Operating Frequency Band (MHz)	EIRP Limit (dBm/MHz)	
5725 - 5850	 <p>U-NII-3 band (5725-5850 MHz)</p>	

4.4. Test Procedure

Test Method				
	References Rule		Chapter	Description
<input type="checkbox"/>	ANSI C63.10		12.7.3	Emissions in non-restricted frequency bands
<input checked="" type="checkbox"/>	ANSI C63.10		12.7.2	Emissions in restricted frequency bands
	<input checked="" type="checkbox"/>	ANSI C63.10	12.7.5	Radiated emission measurements
	<input checked="" type="checkbox"/>	ANSI C63.10	12.7.6	Procedure for peak unwanted emissions measurements above 1000 MHz
	<input checked="" type="checkbox"/>	ANSI C63.10	12.7.7	Procedures for average unwanted emissions measurements above 1000 MHz
	<input type="checkbox"/>	ANSI C63.10	12.7.7.2	Method AD (average detection)—primary method
	<input checked="" type="checkbox"/>	ANSI C63.10	12.7.7.3	Method VB-A (Alternative)
	<input checked="" type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	<input checked="" type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
<input type="checkbox"/>	FCC KDB 789033 D02v01r04		G.2	Unwanted Emissions that fall Outside of the Restricted Bands
<input type="checkbox"/>	FCC KDB 789033 D02v01r04		G.1	Unwanted Emissions in the Restricted Bands
	<input type="checkbox"/>	FCC KDB 789033 D02v01r04	G.4	Procedure for Unwanted Emissions Measurements below 1000 MHz
	<input type="checkbox"/>	FCC KDB 789033 D02v01r04	G.5	Procedure for Unwanted Maximum Emissions Measurements above 1000 MHz
	<input type="checkbox"/>	FCC KDB 789033 D02v01r04	G.6	Procedures for Average Unwanted Emissions Measurements above 1000 MHz
	<input type="checkbox"/>	FCC KDB 789033 D02v01r04	G.6.c	Method AD (Average detection)—primary method
	<input type="checkbox"/>	FCC KDB 789033 D02v01r04	G.6.d	Method VB (Averaging using reduced video bandwidth): Alternative method.


4.5. EUT test Axis definition

Item	Radiated Emission			
Device Category	<input type="checkbox"/>	Indoor use		
	<input type="checkbox"/>	Outdoor use		
	<input type="checkbox"/>	Fix position use		
	<input checked="" type="checkbox"/>	Client use		
Test mode	Mode 1-17			
Test method	<input checked="" type="checkbox"/>	Radiated		
		X Axis	Y Axis	Z Axis
				
		Worst Axis <input checked="" type="checkbox"/>	Worst Axis <input type="checkbox"/>	Worst Axis <input type="checkbox"/>
	<input type="checkbox"/>	Conducted		
	<input type="checkbox"/>	Chain 1		
				
	<input type="checkbox"/>	Chain 1	Chain 2	
				
	<input type="checkbox"/>	Chain 1	Chain 2	Chain 3
				

4.6. Test Result


Ant 1:

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5180MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10360.000	49.629	50.683	-24.371	74.000	-1.054	PK
2		15540.000	48.378	45.998	-25.622	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5180MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10360.000	47.814	48.868	-26.186	74.000	-1.054	PK
2	*	15540.000	48.047	45.667	-25.953	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5220MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	47.534	47.954	-26.466	74.000	-0.420	PK
2	*	15660.000	50.012	45.622	-23.988	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5220MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	47.518	47.938	-26.482	74.000	-0.420	PK
2	*	15660.000	50.122	45.732	-23.878	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5240MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	47.361	47.781	-26.639	74.000	-0.420	PK
2	*	15720.000	48.748	44.358	-25.252	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:05
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5240MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	46.087	46.507	-27.913	74.000	-0.420	PK
2	*	15720.000	48.684	44.294	-25.316	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5745MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	45.249	46.239	-28.751	74.000	-0.990	PK
2	*	17235.000	50.688	45.388	-23.312	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5745MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	45.278	46.268	-28.722	74.000	-0.990	PK
2	*	17235.000	48.744	43.444	-25.256	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5785MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.112	45.102	-29.888	74.000	-0.990	PK
2	*	17355.000	48.345	43.045	-25.655	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5785MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	43.913	44.903	-30.087	74.000	-0.990	PK
2	*	17355.000	48.544	43.244	-25.456	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:07
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5825MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	45.240	46.230	-28.760	74.000	-0.990	PK
2	*	17475.000	50.496	45.196	-23.504	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5825MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	45.338	46.328	-28.662	74.000	-0.990	PK
2	*	17475.000	48.807	43.507	-25.193	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5180MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10360.000	46.370	47.424	-27.630	74.000	-1.054	PK
2	*	15540.000	47.297	44.917	-26.703	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5180MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10360.000	46.027	47.081	-27.973	74.000	-1.054	PK
2	*	15540.000	46.604	44.224	-27.396	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5220MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	46.644	47.064	-27.356	74.000	-0.420	PK
2	*	15660.000	50.544	46.154	-23.456	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5220MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	45.473	45.893	-28.527	74.000	-0.420	PK
2	*	15660.000	48.586	44.196	-25.414	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5240MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	46.880	47.300	-27.120	74.000	-0.420	PK
2	*	15720.000	48.864	44.474	-25.136	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:08
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5240MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	46.111	46.531	-27.889	74.000	-0.420	PK
2	*	15720.000	47.798	43.408	-26.202	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5745MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	44.082	45.072	-29.918	74.000	-0.990	PK
2	*	17235.000	48.846	43.546	-25.154	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5745MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	44.506	45.496	-29.494	74.000	-0.990	PK
2	*	17235.000	48.739	43.439	-25.261	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5785MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	43.416	44.406	-30.584	74.000	-0.990	PK
2	*	17355.000	47.957	42.657	-26.043	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5785MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.314	45.304	-29.686	74.000	-0.990	PK
2	*	17355.000	48.159	42.859	-25.841	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:11
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5825MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	45.153	46.143	-28.847	74.000	-0.990	PK
2	*	17475.000	49.394	44.094	-24.606	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5825MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	45.351	46.341	-28.649	74.000	-0.990	PK
2	*	17475.000	51.175	45.875	-22.825	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5190MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	46.122	46.542	-27.878	74.000	-0.420	PK
2	*	15570.000	47.353	44.973	-26.647	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:12
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5190MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	44.752	45.172	-29.248	74.000	-0.420	PK
2	*	15570.000	46.560	44.180	-27.440	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:14
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5230MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	44.946	45.366	-29.054	74.000	-0.420	PK
2	*	15690.000	48.144	43.754	-25.856	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5230MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	46.284	46.704	-27.716	74.000	-0.420	PK
2	*	15690.000	50.297	45.907	-23.703	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5755MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	43.381	44.371	-30.619	74.000	-0.990	PK
2	*	17265.000	48.883	43.583	-25.117	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5755MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	43.707	44.697	-30.293	74.000	-0.990	PK
2	*	17265.000	48.494	43.194	-25.506	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5795MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	45.619	46.609	-28.381	74.000	-0.990	PK
2	*	17385.000	47.959	42.659	-26.041	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5795MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	43.997	44.987	-30.003	74.000	-0.990	PK
2	*	17385.000	48.825	43.525	-25.175	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5180MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10360.000	45.502	46.556	-28.498	74.000	-1.054	PK
2	*	15540.000	46.078	43.698	-27.922	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5180MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10360.000	45.157	46.211	-28.843	74.000	-1.054	PK
2	*	15540.000	45.330	42.950	-28.670	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5220MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	46.395	46.815	-27.605	74.000	-0.420	PK
2	*	15660.000	50.091	45.701	-23.909	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5220MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	45.070	45.490	-28.930	74.000	-0.420	PK
2	*	15660.000	49.057	44.667	-24.943	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5240MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	46.182	46.602	-27.818	74.000	-0.420	PK
2	*	15720.000	50.182	45.792	-23.818	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:20
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5240MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	46.295	46.715	-27.705	74.000	-0.420	PK
2	*	15720.000	47.767	43.377	-26.233	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5745MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	45.237	46.227	-28.763	74.000	-0.990	PK
2	*	17235.000	47.584	42.284	-26.416	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5745MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	44.163	45.153	-29.837	74.000	-0.990	PK
2	*	17235.000	48.812	43.512	-25.188	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5785MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.750	45.740	-29.250	74.000	-0.990	PK
2	*	17355.000	49.188	43.888	-24.812	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5785MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.471	45.461	-29.529	74.000	-0.990	PK
2	*	17355.000	49.212	43.912	-24.788	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5825MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	44.697	45.687	-29.303	74.000	-0.990	PK
2	*	17475.000	49.000	43.700	-25.000	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5825MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	45.207	46.197	-28.793	74.000	-0.990	PK
2	*	17475.000	48.760	43.460	-25.240	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5190MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	46.103	46.523	-27.897	74.000	-0.420	PK
2	*	15570.000	47.583	45.203	-26.417	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5190MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	44.879	45.299	-29.121	74.000	-0.420	PK
2	*	15570.000	46.206	43.826	-27.794	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5230MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	46.476	46.896	-27.524	74.000	-0.420	PK
2	*	15690.000	48.080	43.690	-25.920	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5230MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	45.300	45.720	-28.700	74.000	-0.420	PK
2	*	15690.000	46.807	42.417	-27.193	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5755MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	45.899	46.889	-28.101	74.000	-0.990	PK
2	*	17265.000	49.344	44.044	-24.656	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5755MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	43.672	44.662	-30.328	74.000	-0.990	PK
2	*	17265.000	48.677	43.377	-25.323	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5795MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	44.116	45.106	-29.884	74.000	-0.990	PK
2	*	17385.000	48.699	43.399	-25.301	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5795MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	43.767	44.757	-30.233	74.000	-0.990	PK
2	*	17385.000	47.909	42.609	-26.091	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5210MHz by 802.11ac80	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10420.000	44.847	45.267	-29.153	74.000	-0.420	PK
2	*	15630.000	46.071	42.509	-27.929	74.000	3.562	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5210MHz by 802.11ac80	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10420.000	45.364	45.784	-28.636	74.000	-0.420	PK
2	*	15630.000	46.487	42.925	-27.513	74.000	3.562	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5775MHz by 802.11ac80	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11550.000	44.243	45.233	-29.757	74.000	-0.990	PK
2	*	17325.000	48.338	43.038	-25.662	74.000	5.300	PK


Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5775MHz by 802.11ac80	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11550.000	43.413	44.403	-30.587	74.000	-0.990	PK
2	*	17325.000	48.987	43.687	-25.013	74.000	5.300	PK


Ant 2:

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:46
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5180MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10367.000	50.908	51.328	-23.092	74.000	-0.420	PK
2		15540.000	48.319	45.939	-25.681	74.000	2.380	PK

Profile: 5G Ant 1	Page No.: 218
Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:46
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5180MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10367.000	51.459	51.879	-22.541	74.000	-0.420	PK
2		15540.000	47.917	45.537	-26.083	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:46
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5220MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	50.424	50.844	-23.576	74.000	-0.420	PK
2	*	15660.000	51.947	47.557	-22.053	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:46
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5220MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	48.356	48.776	-25.644	74.000	-0.420	PK
2	*	15660.000	50.704	46.314	-23.296	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:47
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5240MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10477.500	53.275	53.695	-20.725	74.000	-0.420	PK
2		15720.000	50.458	46.068	-23.542	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:47
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5240MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	49.294	49.714	-24.706	74.000	-0.420	PK
2	*	15720.000	50.301	45.911	-23.699	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5745MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	43.906	44.896	-30.094	74.000	-0.990	PK
2	*	17235.000	51.011	45.711	-22.989	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5745MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	43.922	44.912	-30.078	74.000	-0.990	PK
2	*	17235.000	49.844	44.544	-24.156	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5785MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.368	45.358	-29.632	74.000	-0.990	PK
2	*	17355.000	49.453	44.153	-24.547	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5785MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	45.211	46.201	-28.789	74.000	-0.990	PK
2	*	17355.000	47.661	42.361	-26.339	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5825MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	46.246	47.236	-27.754	74.000	-0.990	PK
2	*	17475.000	49.079	43.779	-24.921	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 5825MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	47.016	48.006	-26.984	74.000	-0.990	PK
2	*	17475.000	50.817	45.517	-23.183	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:49
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5180MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10360.000	46.832	47.886	-27.168	74.000	-1.054	PK
2		15540.000	46.771	44.391	-27.229	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5180MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10360.000	44.434	45.488	-29.566	74.000	-1.054	PK
2	*	15540.000	46.111	43.731	-27.889	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5220MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	47.777	48.197	-26.223	74.000	-0.420	PK
2	*	15660.000	49.255	44.865	-24.745	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5220MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	46.724	47.144	-27.276	74.000	-0.420	PK
2	*	15660.000	49.357	44.967	-24.643	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5240MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10480.000	48.306	48.726	-25.694	74.000	-0.420	PK
2	*	15720.000	48.385	43.995	-25.615	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:50
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5240MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10480.000	47.941	48.361	-26.059	74.000	-0.420	PK
2		15720.000	47.845	43.455	-26.155	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5745MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	44.473	45.463	-29.527	74.000	-0.990	PK
2	*	17235.000	49.051	43.751	-24.949	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5745MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	44.405	45.395	-29.595	74.000	-0.990	PK
2	*	17235.000	48.481	43.181	-25.519	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5785MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.712	45.702	-29.288	74.000	-0.990	PK
2	*	17355.000	47.270	41.970	-26.730	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5785MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.680	45.670	-29.320	74.000	-0.990	PK
2	*	17355.000	49.022	43.722	-24.978	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:52
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5825MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	46.788	47.778	-27.212	74.000	-0.990	PK
2	*	17475.000	49.799	44.499	-24.201	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 5825MHz by 802.11n20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	44.162	45.152	-29.838	74.000	-0.990	PK
2	*	17475.000	48.619	43.319	-25.381	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5190MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	45.778	46.198	-28.222	74.000	-0.420	PK
2	*	15570.000	47.129	44.749	-26.871	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5190MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	46.441	46.861	-27.559	74.000	-0.420	PK
2	*	15570.000	47.306	44.926	-26.694	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5230MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	48.889	49.309	-25.111	74.000	-0.420	PK
2	*	15690.000	49.019	44.629	-24.981	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:53
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5230MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	46.622	47.042	-27.378	74.000	-0.420	PK
2	*	15690.000	47.301	42.911	-26.699	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5755MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	44.064	45.054	-29.936	74.000	-0.990	PK
2	*	17265.000	49.978	44.678	-24.022	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5755MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	45.359	46.349	-28.641	74.000	-0.990	PK
2	*	17265.000	50.401	45.101	-23.599	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5795MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	44.406	45.396	-29.594	74.000	-0.990	PK
2	*	17385.000	49.162	43.862	-24.838	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 5795MHz by 802.11n40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	45.151	46.141	-28.849	74.000	-0.990	PK
2	*	17385.000	47.948	42.648	-26.052	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5180MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10360.000	48.981	50.035	-25.019	74.000	-1.054	PK
2		15540.000	48.111	45.731	-25.889	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5180MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10360.000	45.925	46.979	-28.075	74.000	-1.054	PK
2		15540.000	44.695	42.315	-29.305	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5220MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	48.217	48.637	-25.783	74.000	-0.420	PK
2	*	15660.000	49.426	45.036	-24.574	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:56
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5220MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	47.228	47.648	-26.772	74.000	-0.420	PK
2	*	15660.000	48.381	43.991	-25.619	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5240MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10480.000	48.917	49.337	-25.083	74.000	-0.420	PK
2		15720.000	48.499	44.109	-25.501	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:57
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5240MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10480.000	47.548	47.968	-26.452	74.000	-0.420	PK
2		15720.000	47.467	43.077	-26.533	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:58
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5745MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	45.753	46.743	-28.247	74.000	-0.990	PK
2	*	17235.000	50.147	44.847	-23.853	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:58
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5745MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11490.000	44.921	45.911	-29.079	74.000	-0.990	PK
2	*	17235.000	49.669	44.369	-24.331	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5785MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.704	45.694	-29.296	74.000	-0.990	PK
2	*	17355.000	48.181	42.881	-25.819	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5785MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11570.000	44.256	45.246	-29.744	74.000	-0.990	PK
2	*	17355.000	47.941	42.641	-26.059	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5825MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	46.025	47.015	-27.975	74.000	-0.990	PK
2	*	17475.000	50.351	45.051	-23.649	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 5825MHz by 802.11ac20	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11650.000	48.073	49.063	-25.927	74.000	-0.990	PK
2	*	17475.000	51.563	46.263	-22.437	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5190MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	46.077	46.497	-27.923	74.000	-0.420	PK
2	*	15570.000	48.527	46.147	-25.473	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5190MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10380.000	46.234	46.654	-27.766	74.000	-0.420	PK
2	*	15570.000	47.810	45.430	-26.190	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5230MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	47.982	48.402	-26.018	74.000	-0.420	PK
2	*	15690.000	49.542	45.152	-24.458	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 15:59
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5230MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10460.000	45.229	45.649	-28.771	74.000	-0.420	PK
2	*	15690.000	48.132	43.742	-25.868	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5755MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	43.615	44.605	-30.385	74.000	-0.990	PK
2	*	17265.000	48.836	43.536	-25.164	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5755MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11510.000	44.882	45.872	-29.118	74.000	-0.990	PK
2	*	17265.000	51.163	45.863	-22.837	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5795MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	45.197	46.187	-28.803	74.000	-0.990	PK
2	*	17385.000	48.467	43.167	-25.533	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 5:Transmit at 5795MHz by 802.11ac40	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11590.000	44.139	45.129	-29.861	74.000	-0.990	PK
2	*	17385.000	48.737	43.437	-25.263	74.000	5.300	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:01
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5210MHz by 802.11ac80	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10420.000	45.852	46.272	-28.148	74.000	-0.420	PK
2	*	15630.000	47.216	43.654	-26.784	74.000	3.562	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:02
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5210MHz by 802.11ac80	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10420.000	45.955	46.375	-28.045	74.000	-0.420	PK
2	*	15630.000	46.327	42.765	-27.673	74.000	3.562	PK


Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 16:02
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 6:Transmit at 5775MHz by 802.11ac80	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		11550.000	44.391	45.381	-29.609	74.000	-0.990	PK
2	*	17325.000	49.603	44.303	-24.397	74.000	5.300	PK


Ant 1+2:

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 09:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 7:Transmit at 5180MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10360.000	49.665	50.719	-24.335	74.000	-1.054	PK
2		15540.000	48.646	46.266	-25.354	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 09:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 7:Transmit at 5180MHz by 802.11a	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	10360.000	47.269	48.323	-26.731	74.000	-1.054	PK
2		15540.000	46.326	43.946	-27.674	74.000	2.380	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 09:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 7:Transmit at 5220MHz by 802.11a	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	47.625	48.045	-26.375	74.000	-0.420	PK
2	*	15660.000	48.593	44.203	-25.407	74.000	4.390	PK

Engineer: Simon	
Site: AC5	Time: 2017/11/08 - 09:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Wireless Access point	Power: AC 120V/60Hz
Note: Mode 7:Transmit at 5220MHz by 802.11a	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		10440.000	47.347	47.767	-26.653	74.000	-0.420	PK
2	*	15660.000	49.832	45.442	-24.168	74.000	4.390	PK