

FCC RF Exposure Report

FCC ID : WBV-AP230

Equipment : Access Point

Model No. : AP230

Brand Name : Aerohive

Applicant : Aerohive Networks Inc.

Address : 330 Gibraltar Drive, Sunnyvale, CA 94089

Standard : 47 CFR FCC Part 2.1091

Received Date : Jan. 21, 2014

Tested Date : Jan. 21 ~ Feb. 19, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

lac MRA



Report No.: FA412201 Report Version: Rev. 01 Page : 1 of 7



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
-		
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	2
1.2	MPE EVALUATION FORMULA	2
1.3	MPE EVALUATION RESULTS	5
2	TEST LABORATORY INFORMATION	7

Report No.: FA412201

Page : 2 of 7



Release Record

Report No.	Version	Description	Issued Date	
FA412201	Rev. 01	Initial issue	Mar. 12, 2014	

Report No.: FA412201 Page: 3 of 7



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

Report No.: FA412201 Page: 4 of 7



1.3 MPE EVALUATION RESULTS

Legacy/MIMO (CDD) Non-beamforming mode

Frequency Range (MHz)	Mode	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
	11b	22.29	4.34	20	0.092	1
0440 0460	11g	22.34	4.34	20	0.093	1
2412~2462	HT20	26.65	4.34	20	0.250	1
	VHT20	26.71	4.34	20	0.253	1
	11a	15.91	6.24	20	0.033	1
	HT20	11.44	6.7	20	0.013	1
5180~5240	HT40	14.3	6.7	20	0.025	1
5160~5240	VHT20	11.53	6.7	20	0.013	1
	VHT40	14.38	6.7	20	0.026	1
	VHT80	16.05	6.7	20	0.037	1
	11a	23.81	5.79	20	0.181	1
	HT20	25.02	5.79	20	0.240	1
5745 500F	HT40	25.19	5.79	20	0.249	1
5745~5825	VHT20	25.08	5.79	20	0.243	1
	VHT40	25.24	5.79	20	0.252	1
	VHT80	23.13	5.79	20	0.155	1

Report No.: FA412201 Page: 5 of 7



Legacy/MIMO (CDD) beamforming mode

Frequency Range (MHz)	Mode	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
	11b	22.29	4.34	20	0.092	1
2412~2462	11g	22.34	4.34	20	0.093	1
2412~2462	HT20	26.68	8.87	20	0.714	1
	VHT20	26.8	8.87	20	0.734	1
	11a	15.91	6.24	20	0.033	1
	HT20	11.08	11.13	20	0.033	1
5180~5240	HT40	11.24	11.13	20	0.034	1
3100~3240	VHT20	11.18	11.13	20	0.034	1
	VHT40	11.32	11.13	20	0.035	1
	VHT80	11.28	11.13	20	0.035	1
	11a	23.81	5.79	20	0.181	1
	HT20	25.09	10.13	20	0.662	1
E74E E00E	HT40	25.17	10.13	20	0.674	1
5745~5825	VHT20	25.14	10.13	20	0.669	1
	VHT40	25.3	10.13	20	0.695	1
	VHT80	23.2	10.13	20	0.428	1

Report No.: FA412201 Page: 6 of 7



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END===

Report No.: FA412201 Page: 7 of 7