

Annex 1: Measurement diagrams to
TEST REPORT
No.: 18-1-0020401T08a

According to:

FCC Regulations

Part 15.205

Part 15.249

ISED-Regulations

RSS-Gen, Issue 5

RSS-210, Issue 9

for
SRM GmbH

EXAKT Pedal PowerMeter

FCC ID: WCS - EXAKT

ISED: 7761A - EXAKT

HVIN: EXAKT

PMN: EXAKT





Laboratory Accreditation and Listings	
<div><p>Deutsche Akkreditierungsstelle D-PL-12047-01-01 D-PL-12047-01-03 D-PL-12047-01-04</p></div> <p>Accredited EMC-Test Laboratory</p>	
 <p>Wi-Fi ALLIANCE</p> <p>AUTHORIZED RF LABORATORY</p>	 <p>ctia Authorized™ Test Lab Lab Code: 2001130-00</p>
accredited according to DIN EN ISO/IEC 17025	
<p>CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964 E-mail: info@cetecom.com • Internet: www.cetecom.com</p>	

TABLE OF CONTENTS:

1. RADIATED FIELD STRENGTH MEASUREMENTS	3
1.1. Radiated Field Strength Emissions – 9 kHz to 30 MHz	3
1.2. Radiated Field Strength Emissions – 30 MHz to 1 GHz	9
1.3. Radiated Field Strength Emissions – Field Strength	15
1.4. Radiated Field Strength Emissions – 1 GHz to 18 GHz	18
1.5. Radiated Field Strength Emissions – 18 GHz to 25 GHz	22
2. RADIATED BAND-EDGE MEASUREMENTS	24
2.1. ANT+ GFSK-Low Channel 2402 MHz (2.4 GHz ISM: left band edge)	24
2.2. ANT+ GFSK-High Channel 2480 MHz (2.4 GHz ISM: right band edge)	25
3. CONDUCTED MEASUREMENTS	26
3.1. Occupied Bandwidth	26
3.2. 20dB Emission Bandwidth	28
3.3. Frequency stability.....	31


1. Radiated Field Strength Measurements

1.1. Radiated Field Strength Emissions – 9 kHz to 30 MHz

2.01a_MODE_channel_low_laying

Test description:	Date: 16.04.2018 Page 1 of 3
Test site and distance:	Magnetic Field Strength Measurement related to 30/300 m distance
Version of Testsoftware:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Distance correction:	EMC32 V9.25.0
Technical Data:	used accord. table, pls. see test report
Rec. antenna (pre-scan):	Please see page 2 for detailed data of measurement setup
Used filter:	height 1.00 m, parallel and 90° to EUT polarisation
Test specification:	bypass
	FCC 15.205 § 15.209; RSS-Gen: Issue 5
Operator:	MBe
Operating conditions:	TX-MODE_low_laying
Power during tests:	charging
Comment 1:	Channel low
Comment 2:	DUT Laying


Full Spectrum



2.01b_MODE_low_standing

Date:	16.04.2018	Page 1 of 2
Test description:	Magnetic Field Strength Measurement related to 30/300 m distance	
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance	
Version of Testsoftware:	EMC32 V9.25.0	
Distance correction:	used accord. table, pls. see test report	
Technical Data:	Please see page 2 for detailed data of measurement setup	
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation	
Used filter:	bypass	
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 5	
Operator:	TFra	
Operating conditions:	TX-MODE_low_standing	
Power during tests:	charging	
Comment 1:	Channel low	
Comment 2:	DUT Standing	


Full Spectrum



2.02a_mid_laying

Date:	16.04.2018	Page 1 of 2
Test description:	Magnetic Field Strength Measurement related to 30/300 m distance	
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance	
Version of Testsoftware:	EMC32 V9.25.0	
Distance correction:	used accord. table, pls. see test report	
Technical Data:	Please see page 2 for detailed data of measurement setup	
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation	
Used filter:	bypass	
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 5	
Operator:	TFra	
Operating conditions:	TX-mid_laying	
Power during tests:	charging	
Comment 1:	Channel mid	
Comment 2:	DUT Laying	


Full Spectrum



2.02b_mid_standing

Date:	16.04.2018	Page 1 of 2
Test description:	Magnetic Field Strength Measurement related to 30/300 m distance	
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance	
Version of Testsoftware:	EMC32 V9.25.0	
Distance correction:	used accord. table, pls. see test report	
Technical Data:	Please see page 2 for detailed data of measurement setup	
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation	
Used filter:	bypass	
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 5	
Operator:	TFra	
Operating conditions:	TX-mid_standing	
Power during tests:	charging	
Comment 1:	Channel mid	
Comment 2:	DUT Standing	


Full Spectrum



2.03a_high_laying

Date:	16.04.2018	Page 1 of 2
Test description:	Magnetic Field Strength Measurement related to 30/300 m distance	
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance	
Version of Testsoftware:	EMC32 V9.25.0	
Distance correction:	used accord. table, pls. see test report	
Technical Data:	Please see page 2 for detailed data of measurement setup	
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation	
Used filter:	bypass	
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 5	
Operator:	TFra	
Operating conditions:	TX-high_laying	
Power during tests:	charging	
Comment 1:	Channel high	
Comment 2:	DUT Laying	


Full Spectrum



2.03b_high_standing

Date:	17.04.2018	Page 1 of 2
Test description:	Magnetic Field Strength Measurement related to 30/300 m distance	
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance	
Version of Testsoftware:	EMC32 V9.25.0	
Distance correction:	used accord. table, pls. see test report	
Technical Data:	Please see page 2 for detailed data of measurement setup	
Rec. antenna (pre-scan):	height 1.00 m, parallel and 90° to EUT polarisation	
Used filter:	bypass	
Test specification:	FCC 15.205 § 15.209; RSS-Gen: Issue 5	
Operator:	TFra	
Operating conditions:	TX-high_standing	
Power during tests:	charging	
Comment 1:	Channel high	
Comment 2:	DUT Standing	

Full Spectrum




1.2. Radiated Field Strength Emissions – 30 MHz to 1 GHz

3.01a_channel_low_laying

Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 5
Operator:	RLS
Operating conditions:	Low channel
Power during tests:	full loaded batteries
Comment 1:	

Full Spectrum




3.01b_channel_low_standing

Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 5
Operator:	RLs
Operating conditions:	Low channel
Power during tests:	full loaded batteries
Comment 1:	

Full Spectrum




3.02a_Mid_laying

Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 5
Operator:	RLS
Operating conditions:	Mid channel
Power during tests:	full loaded batteries
Comment 1:	

Full Spectrum




3.02b_Mid_Standing

Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 5
Operator:	Rls
Operating conditions:	Mid channel
Power during tests:	full loaded batteries
Comment 1:	

Full Spectrum




3.03a_high_laying

Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 5
Operator:	Rls
Operating conditions:	High channel
Power during tests:	full loaded batteries
Comment 1:	

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
419.100000	20.85	46.00	25.15	1000.0	120.000	360.0	V	24.0	18.8
850.892000	29.81	46.00	16.19	1000.0	120.000	283.0	H	99.0	25.7

3.03b_high_standing

Common Information

Test description:	Electric Field Strength Measurement
Test site and distance:	Ref.-Nr. 441 Semi Anechoic Room (SAR) with 3 m measurement distance
Version of Testsoftware:	EMC32 V9.25.0
Distance correction:	not used
Used filter:	not used
Technical Data:	please see page 2 for detailed data of measurement setup
Test specification.:	FCC 15.209; RSS-Gen: Issue 5
Operator:	Rls
Operating conditions:	High channel
Power during tests:	full loaded batteries
Comment 1:	

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Correction (dB)
87.252000	7.26	40.00	32.74	1000.0	120.000	360.0	V	86.0	8.0
865.744000	30.09	46.00	15.91	1000.0	120.000	225.0	V	27.0	26.0

1.3. Radiated Field Strength Emissions – Field Strength

4.01a_FieldStrength_channel_low

Common Information


Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 4
Antenna polarisation:	horizontal/vertical
Operation mode:	BT,CH:00
Operator Name:	MSo



4.02a_FieldStrength_mid

Common Information


Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 4
Antenna polarisation:	horizontal/vertical
Operation mode:	BT,CH:39
Operator Name:	HEI



4.03a_FieldStrength _high

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 4
Antenna polarisation:	horizontal/vertical
Operation mode:	BT,CH:80
Operator Name:	HEI




1.4. Radiated Field Strength Emissions – 1 GHz to 18 GHz

4.01b_low

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 5
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous
Operator Name:	RIs
Comment:	Channel no. low

Full Spectrum



Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)
4800.000000	---	38.95	54.00	15.05	100.0	1000.000	155.0	V	89.0	0.0
4800.000000	44.81	---	74.00	29.19	100.0	1000.000	155.0	V	62.0	0.0
7199.600000	51.46	---	150.00	98.54	100.0	1000.000	155.0	H	-4.0	0.0
7200.000000	---	38.05	150.00	111.95	100.0	1000.000	155.0	V	-41.0	0.0

(continuation of the "Final_Result" table from column 16 ...)


Frequency (MHz)	Corr.	Comment
4800.000000	4.9	01:07:02 - 19.04.2018
4800.000000	4.9	01:03:19 - 19.04.2018
7199.600000	10.5	01:01:15 - 19.04.2018
7200.000000	10.5	01:05:17 - 19.04.2018

4.02b_mid

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 5
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous
Operator Name:	RIs
Comment:	Channel no.middle

Full Spectrum



Final_Result

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Measurement Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)
4877.600000	48.69	---	74.00	25.31	100.0	1000.000	155.0	H	270.0	0.0
4878.000000	---	42.20	54.00	11.80	100.0	1000.000	155.0	H	271.0	0.0
7316.400000	49.93	---	74.00	24.07	100.0	1000.000	155.0	H	56.0	0.0
7317.200000	---	38.23	54.00	15.77	100.0	1000.000	155.0	H	216.0	0.0

(continuation of the "Final_Result" table from column 16 ...)


Frequency (MHz)	Correction	Comment
4877.600000	4.7	02:36:35 - 19.04.2018
4878.000000	4.7	02:40:00 - 19.04.2018
7316.400000	10.6	02:34:35 - 19.04.2018
7317.200000	10.6	02:38:27 - 19.04.2018

4.03b_high

Common Information

Test Description:	Radiated field strength emission in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 5
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous
Operator Name:	RLs
Comment:	Channel no.high

Full Spectrum



Final Result


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Measurement Time	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)
4955.600000	49.39	---	74.00	24.61	100.0	1000.000	155.0	H	271.0	0.0
4956.000000	---	43.20	54.00	10.80	100.0	1000.000	155.0	H	269.0	0.0
7433.600000	---	40.65	54.00	13.35	100.0	1000.000	155.0	H	61.0	0.0
7434.400000	50.16	---	74.00	23.84	100.0	1000.000	155.0	H	29.0	0.0

(continuation of the "Final_Result" table from column 16 ...)


Frequency (MHz)	Correction	Comment
4955.600000	4.3	04:09:27 - 19.04.2018
4956.000000	4.3	04:13:45 - 19.04.2018
7433.600000	11.6	04:11:42 - 19.04.2018
7434.400000	11.6	04:07:22 - 19.04.2018

1.5. Radiated Field Strength Emissions – 18 GHz to 25 GHz


4.54a Low channel:



4.55a Middle channel:



4.56a High channel:




2. Radiated Band-Edge Measurements

2.1. ANT+ GFSK-Low Channel 2402 MHz (2.4 GHz ISM: left band edge)

9.01_BE_low

Common Information

Test Description:	Band-Edge: Radiated Field Strength Emissions Emissions in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 5
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous
Operator Name:	RLs
Comment:	Channel no. low




2.2. ANT+ GFSK-High Channel 2480 MHz (2.4 GHz ISM: right band edge)

9.02_BE_high

Common Information


Test Description:	Band-Edge: Radiated Field Strength Emissions Emissions in 3m distance
Test Site:	CETECOM GmbH Essen
Test Standard:	FCC 15.249&15.209 Intentional Radiator / RSS-Gen, Issue 5
Antenna polarisation:	horizontal/vertical
Operation mode:	TX, continuous
Operator Name:	RI's
Comment:	Channel no.high

Full Spectrum




3. Conducted Measurements


3.1. Occupied Bandwidth



Occupied Channel Bandwidth Plot: 2402 MHz



Occupied Channel Bandwidth Plot: 2440 MHz



Occupied Channel Bandwidth Plot: 2480 MHz

3.2. 20dB Emission Bandwidth


Emission Bandwidth 20 dB (2402 MHz; 4,000 dBm; 2 MHz)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)
2402.000000	1.000000	---	---	2401.440000	2402.440000	-18.5

(continuation of the "20 dB Bandwidth" table from column 7 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS




Emission Bandwidth 20 dB (2442 MHz; 4,000 dBm; 2 MHz)

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)
2442.000000	1.060000	---	---	2441.420000	2442.480000	-19.3

(continuation of the "20 dB Bandwidth" table from column 7 ...)

DUT Frequency (MHz)	Result
2442.000000	PASS




Emission Bandwidth 20 dB (2480 MHz; 4,000 dBm; 2 MHz)

20 dB Bandwidth


DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)	Max Level (dBm)
2480.000000	1.020000	---	---	2479.420000	2480.440000	-19.5

(continuation of the "20 dB Bandwidth" table from column 7 ...)


DUT Frequency (MHz)	Result
2480.000000	PASS




3.3. Frequency stability




Frequency Stability Plot: Tnom | Vnom | 2402 MHz




Frequency Stability Plot: Tnom | Vmin | 2402 MHz




Frequency Stability Plot: Tmax | Vnom | 2402 MHz




Frequency Stability Plot: Tmin | Vmin | 2402 MHz




Frequency Stability Plot: Tnom | Vnom | 2480 MHz



Frequency Stability Plot: Tnom | Vmin | 2480 MHz



Frequency Stability Plot: Tmax | Vnom | 2480 MHz



Frequency Stability Plot: Tmin | Vmin | 2480 MHz