

RF TEST REPORT

Test item : IP network camera
Model No. : 2GIG-CAMHD110
Order No. : DEMC1312-03980, DEMC1401-00318
Date of receipt : 2013-12-30
Test duration : 2014-01-13 ~ 2014-01-29
Date of issue : 2014-02-27
Use of report : FCC & IC Original Grant

Applicant : 2GIG Technologies.
2961 W Maple Loop Dr. Lehi, UT 84043, USA

Test laboratory : Digital EMC Co., Ltd.
42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 449-935

Test specification : FCC Part 15 Subpart C 247
RSS-210 Issue 8: 2010
RSS-GEN Issue 3: 2010

Test environment : See appended test report

Test result : ☒ Pass ☐ Fail

The test results presented in this test report are limited only to the sample supplied by applicant and the use of this test report is inhibited other than its purpose. This test report shall not be reproduced except in full, without the written approval of DIGITAL EMC CO., LTD.

Tested by:



Engineer
HyunSu Son

Reviewed by:



Deputy General Manager
HongHee Lee

Test Report Version

Test Report No.	Date	Description
DRTFCC1402-0298	Feb. 27, 2014	Initial issue

Table of Contents

1. GENERAL INFORMATION	4
2. EUT DESCRIPTION	4
3. SUMMARY OF TESTS	5
4. TEST METHODOLOGY	6
4.1 EUT CONFIGURATION	6
4.2 EUT EXERCISE	6
4.3 GENERAL TEST PROCEDURES	6
4.4 DESCRIPTION OF TEST MODES	6
5. INSTRUMENT CALIBRATION	7
6. FACILITIES AND ACCREDITATIONS	7
6.1 FACILITIES	7
6.2 EQUIPMENT	7
7. ANTENNA REQUIREMENTS	7
8. TEST RESULT	8
8.1 6dB Bandwidth	8
8.2 Maximum Peak Conducted Output Power	17
8.3 Maximum Power Spectral Density	20
8.4 Out of Band Emissions at the Band Edge / Conducted Spurious Emissions	29
8.5 Radiated Spurious Emissions	54
8.6 Power-line Conducted Emissions	60
8.7 Occupied Bandwidth	63
9. LIST OF TEST EQUIPMENT	72
APPENDIX I	73

1. GENERAL INFORMATION

Applicant : 2GIG Technologies.
Address : 2961 W Maple Loop Dr. Lehi, UT 84042, USA
FCC ID : WDQ-CAMHD110
EUT : IP network camera
Model : 2GIG-CAMHD110
Additional Model(s) : N/A
Data of Test : 2014-01-13 ~ 2014-01-29
Contact person : Ajit Sampalli

2. EUT DESCRIPTION

Product	IP network camera
Model Name	2GIG-CAMHD110
Power Supply	DC 12 V
Frequency Range	2.4GHz Band ▪ 802.11b/g/n(20MHz): 2412 ~ 2462 MHz ▪ 802.11n(40MHz): 2422~2452 MHz
Max. RF Output Power	2.4GHz Band ▪ 802.11b: 17.96 dBm ▪ 802.11g: 24.72 dBm ▪ 802.11n (HT20): 24.30 dBm ▪ 802.11n (HT40): 19.06 dBm
Modulation Type	802.11b: DSSS/CCK 802.11g/n(HT20/HT40): OFDM
Antenna Specification	External Antenna (1TX 1RX) ▪ 2.4GHz Band Max. peak gain: 0.86 dBi

3. SUMMARY OF TESTS

FCC Part Section(s)	RSS Section(s)	Parameter	Limit	Test Condition	Status Note 1
I. Transmitter Mode (TX)					
15.247(a)	RSS-210 [A8.2]	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	RSS-210 [A8.4]	Transmitter Output Power	< 1Watt		C ^{Note2}
15.247(d)	RSS-210 [A8.5]	Out of Band Emissions / Band Edge	20dBc in any 100kHz BW		C
15.247(e)	RSS-210 [A8.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz		C
-	RSS Gen [4.6.1]	Occupied Bandwidth (99%)	RSS-Gen4.6.1		C
15.205 15.209	RSS-210 [A8.5]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	<FCC 15.209 limits	Radiated	C ^{Note3}
15.207	RSS-Gen [7.2.2]	AC Conducted Emissions	< FCC 15.207 limits	AC Line Conducted	C
15.203	-	Antenna Requirements	FCC 15.203	-	C
<p>Note 1: C=Comply NC=Not Comply NT=Not Tested NA=Not Applicable</p> <p>Note 2: This test item was determined worse case data rate for each mode and channel.</p> <p>Note 3: This test item was performed in each axis and the worst case data was reported.</p>					

4. TEST METHODOLOGY

Generally the tests were performed according to the KDB558074 v03r1. And ANSI C63.10-2009 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

4.3 GENERAL TEST PROCEDURES

Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB 558074 v03r1. So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10.

The EUT is placed on the turntable, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15MHz and 30MHz using CISPR Quasi-peak and Average detector.

Radiated Emissions

Basically the radiated tests were performed with KDB 558074 v03r1. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10 as stated on section 12.1 of the KDB 558074 v03r1.

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the highest emission, the relative positions of the EUT were rotated through three orthogonal axes..

4.4 DESCRIPTION OF TEST MODES

The EUT has been tested with all modes of operating conditions to determine the worst case emission characteristics. A test program is used to control the EUT for staying in continuous transmitting mode.

5. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipments, which is traceable to recognized national standards.

6. FACILITIES AND ACCREDITATIONS

6.1 FACILITIES

The open area test site(OATS) or semi anechoic chamber and conducted measurement facility used to collect the radiated and conducted test data are located at the 38, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 449-935. The site is constructed in conformance with the requirements.

- Semi anechoic chamber registration Number : 678747

6.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and peak, quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

7. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203& RSS-Gen [7.1.2]:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

The external antennas used a unique coupling to the intentional radiator.

Therefore this E.U.T Complies with the requirement of §15.203

8. TEST RESULT

8.1 6dB Bandwidth

Test Requirements and limit, §15.247(a) & RSS-210 [A8.2]

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer and used following test procedure of **KDB558074 v03r1**.

1. Set resolution bandwidth (RBW) = 100 KHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
(RBW:100KHz/VBW:300KHz)
3. Detector = **Peak**.
4. Trace mode = **max hold**.
5. Sweep = **auto couple**.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outer most amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


■ TEST RESULTS: **Comply**

Test Mode	Data Rate	Frequency [MHz]	Test Results[MHz]
802.11b	11Mbps	2412	7.951
		2437	7.567
		2462	8.246
802.11g	6Mbps	2412	13.646
		2437	13.766
		2462	13.954
802.11n (HT20)	MCS0	2412	16.171
		2437	15.524
		2462	15.519
802.11n (HT40)	MCS0	2422	36.267
		2437	35.955
		2452	36.253

RESULT PLOTS


6 dB Bandwidth

Test Mode: 802.11b & 11Mbps & 2412MHz




6 dB Bandwidth

Test Mode: 802.11b & 11Mbps & 2437MHz




6 dB Bandwidth

Test Mode: 802.11b & 11Mbps & 2462MHz




6 dB Bandwidth

Test Mode: 802.11g & 6Mbps & 2412MHz




6 dB Bandwidth

Test Mode: 802.11g & 6Mbps & 2437MHz




6 dB Bandwidth

Test Mode: 802.11g & 6Mbps & 2462MHz




6 dB Bandwidth

Test Mode: 802.11n(HT20) & MCS0 & 2412MHz




6 dB Bandwidth

Test Mode: 802.11n(HT20) & MCS0 & 2437MHz




6 dB Bandwidth

Test Mode: 802.11n(HT20) & MCS0 & 2462MHz




6 dB Bandwidth

Test Mode: 802.11n(HT40) & MCS0 & 2422MHz




6 dB Bandwidth

Test Mode: 802.11n(HT40) & MCS0 & 2437MHz



6 dB Bandwidth

Test Mode: 802.11n(HT40) & MCS0 & 2452MHz




8.2 Maximum Peak Conducted Output Power

Test Requirements and limit, §15.247(b) & RSS-210 [A8.4]

The maximum permissible conducted output power is **1 Watt**.

■ TEST CONFIGURATION



■ TEST PROCEDURE:

1. PKPM1 Peak power meter method of KDB558074 v03r1

The maximum conducted output powers were measured using a broadband peak RF power meter which has greater video bandwidth than DUT's DTS bandwidth and utilize a fast-responding diode detector.

2. Method AVGPM-G (Measurement using a gated RF average power meter) of KDB558074 v03r1

The average conducted output powers were measured using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

■ TEST RESULTS: **Comply**

- Measurement Data: **Comply**

Test Results

Mode	Channel	Frequency [MHz]	Detector	Test Result [dBm]							
				DATA RATE [Mbps]							
				1	2	5.5	11	N/A	N/A	N/A	N/A
802.11b	1	2412	PK	17.78	17.91	17.91	17.96	-	-	-	-
			AV	13.71	13.66	13.67	13.65	-	-	-	-
	6	2437	PK	16.89	17.02	17.01	17.05	-	-	-	-
			AV	13.07	13.02	13.05	13.04	-	-	-	-
	11	2462	PK	16.32	16.41	16.41	16.45	-	-	-	-
			AV	12.39	12.37	12.39	12.39	-	-	-	-

Mode	Channel	Frequency [MHz]	Detector	Test Result [dBm]							
				DATA RATE [Mbps]							
				1	2	5.5	11	N/A	N/A	N/A	N/A
802.11g	1	2412	PK	23.51	23.36	22.32	22.44	22.34	22.97	22.29	21.92
			AV	10.75	10.58	10.61	10.65	10.68	10.72	10.67	10.66
	6	2437	PK	24.72	24.55	23.53	23.63	23.56	24.22	23.51	24.21
			AV	15.44	15.28	15.31	15.36	15.40	15.44	15.42	15.43
	11	2462	PK	22.35	22.20	21.16	21.24	21.18	21.84	21.14	21.84
			AV	9.80	9.65	9.69	9.76	9.80	9.79	9.79	9.80

Mode	Channel	Frequency [MHz]	Detector	Test Result [dBm]							
				DATA RATE [MCS]							
				0	1	2	3	4	5	6	7
802.11n (HT20)	1	2412	PK	21.72	21.69	21.49	21.28	20.91	20.88	20.84	20.95
			AV	9.36	9.44	9.35	9.32	9.43	9.49	9.45	9.52
	6	2437	PK	24.30	24.26	24.04	23.86	23.53	23.48	23.45	23.53
			AV	13.16	13.35	13.25	13.27	13.39	13.46	13.43	13.39
	11	2462	PK	20.66	20.61	20.43	20.21	19.94	19.88	19.83	19.92
			AV	8.29	8.48	8.41	8.45	8.57	8.64	8.63	8.57

Mode	Channel	Frequency [MHz]	Detector	Test Result [dBm]							
				DATA RATE [MCS]							
				0	1	2	3	4	5	6	7
802.11n (HT40)	3	2422	PK	19.06	19.02	18.54	18.47	18.45	18.26	18.51	17.99
			AV	6.58	6.67	6.78	6.65	6.81	6.82	6.91	6.69
	6	2437	PK	18.66	18.63	18.16	18.05	18.02	17.83	18.13	17.54
			AV	6.07	6.19	6.29	6.14	6.33	6.37	6.45	6.27
	9	2452	PK	18.38	18.34	17.88	17.79	17.75	17.58	17.86	17.28
			AV	5.83	5.92	6.04	5.89	6.09	6.11	6.18	6.08

8.3 Maximum Power Spectral Density

Test requirements and limit, §15.247(e) & RSS-210 [A8.2]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard –specifies a conducted power spectral density (PSD) limit of 8 dBm in any 3 kHz band segment within the fundamental EBW during any time interval of continuous transmission.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE:

The Measurement Procedure **Method PKPSD of KDB558074 v03r1** is used.


1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to **1.5 times** the DTS bandwidth.
3. Set the RBW to: **3 kHz ≤ RBW ≤ 100 kHz**.
4. Set the VBW ≥ **3 x RBW**.
5. Detector = **peak**.
6. Sweep time = **auto couple**.
7. Trace mode = **max hold**.
8. Allow trace to fully stabilize.
9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

■ TEST RESULTS: **Comply**


Test Mode	Data Rate	Frequency [MHz]	RBW	PKPSD [dBm]
802.11b	11Mbps	2412	3 kHz	- 8.61
		2437	3 kHz	- 8.62
		2462	3 kHz	- 9.37
802.11g	6Mbps	2412	3 kHz	- 13.43
		2437	3 kHz	- 9.23
		2462	3 kHz	- 14.05
802.11n (HT20)	MCS0	2412	3 kHz	- 14.95
		2437	3 kHz	- 9.84
		2462	3 kHz	- 15.41
802.11n (HT40)	MCS0	2422	3 kHz	- 20.59
		2437	3 kHz	- 13.45
		2452	3 kHz	- 21.19

■ **RESULT PLOTS****Maximum PKPSD**

Test Mode: 802.11b & 11Mbps & 2412MHz


**Maximum PKPSD**

Test Mode: 802.11b & 11Mbps & 2437MHz




Maximum PKPSD

Test Mode: 802.11b & 11Mbps & 2462MHz




Maximum PKPSD

Test Mode: 802.11g & 6Mbps & 2412MHz




Maximum PKPSD

Test Mode: 802.11g & 6Mbps & 2437MHz




Maximum PKPSD

Test Mode: 802.11g & 6Mbps & 2462MHz




Maximum PKPSD

Test Mode: 802.11n(HT20) & MCS0 & 2412MHz




Maximum PKPSD

Test Mode: 802.11n(HT20) & MCS0 & 2437MHz




Maximum PKPSD

Test Mode: 802.11n(HT20) & MCS0 & 2462MHz




Maximum PKPSD

Test Mode: 802.11n(HT40) & MCS0 & 2422MHz




Maximum PKPSD

Test Mode: 802.11n(HT40) & MCS0 & 2437MHz



Maximum PKPSD

Test Mode: 802.11n(HT40) & MCS0 & 2452MHz



8.4 Out of Band Emissions at the Band Edge / Conducted Spurious Emissions

Test requirements and limit, §15.247(d)

§15.247(d) specifies that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

If the **peak output power procedure** is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated **by at least 20 dB** relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to **15.247(b)(3)** requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in band average PSD level.

In either case, attenuation to levels below the general emission limits specified in **§15.209(a)** is not required.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer.

- Measurement Procedure 1 – Reference Level

1. Set instrument center frequency to DTS channel center frequency.
2. Set the span to **≥ 1.5 times the DTS bandwidth**.
3. Set the **RBW = 100 kHz**.
4. Set the **VBW ≥ 3 x RBW**.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum PSD level

- Measurement Procedure 2 - Unwanted Emissions

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the **RBW = 100 kHz**.
3. Set the **VBW ≥ 3 x RBW = 300 KHz**
4. Detector = **peak**.
5. Ensure that the number of measurement points **≥ span/RBW**
6. Sweep time = **auto couple**.
7. Trace mode = **max hold**.
8. **Allow the trace to stabilize** (this may take some time, depending on the extent of the span).
9. Use the peak marker function to determine the maximum amplitude level.

Note : The conducted unwanted emission from 30 MHz to 25 GHz was tested using S/A's spurious measurement function with total 11 measurement sub ranges.

The each of the 11 measurement sub ranges of the S/A's spurious measurement function were set as below.

**RBW= 1 MHz, VBW= 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD,
SPAN = Max 3 GHz for each sub range below 15 GHz and Max 5 GHz for each sub range above 15 GHz ,
BINS = At least 9001 for each sub range below 15 GHz and At least 10001 for each sub range above 15 GHz,
Therefore BINS for each measurement sub range must be greater than 2 x SPAN/RBW.**


If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 KHz, VBW = 300KHz, SPAN = 100 MHz and BINS = 2001 to get accurate emission level within 100 KHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.


RESULT PLOTS

802.11b & 11Mbps & 2412MHz



Reference



Low Band-edge




Conducted Spurious Emissions





802.11b & 11Mbps & 2437MHz

Reference




Conducted Spurious Emissions




802.11b & 11Mbps & 2462MHz



Reference



High Band-edge




Conducted Spurious Emissions




802.11g & 6Mbps & 2412MHz



Reference



Low Band-edge




Conducted Spurious Emissions





802.11g & 6Mbps & 2437MHz

Reference




Conducted Spurious Emissions




802.11g & 6Mbps & 2462MHz



Reference



High Band-edge




Conducted Spurious Emissions




802.11n(HT20) & MCS0 & 2412MHz



Reference



Low Band-edge




Conducted Spurious Emissions





802.11n(HT20) & MCS0 & 2437MHz

Reference




Conducted Spurious Emissions




802.11n(HT20) & MCS0 & 2462MHz



Reference



High Band-edge




Conducted Spurious Emissions




802.11n(HT40) & MCS0 & 2422MHz



Reference



Low Band-edge




Conducted Spurious Emissions





802.11n(HT40) & MCS0 & 2437MHz

Reference




Conducted Spurious Emissions




802.11n(HT40) & MCS0 & 2452MHz



Reference



High Band-edge



Conducted Spurious Emissions



8.5 Radiated Spurious Emissions

Test Requirements and limit, §15.247(d), §15.205, §15.209& RSS-210 [A8.5], RSS-Gen [7.2.2]

In any 100kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) and (b), then the 15.209(a) limit in the table below has to be followed

• FCC Part 15.209(a) and (b)

Frequency (MHz)	Limit (uV/m)	Measurement Distance (meter)
0.009 – 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3


** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

• FCC Part 15.205 (a): Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.41425 ~ 8.41475	108 ~ 121.94	1300 ~ 1427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1435 ~ 1626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.1735 ~ 2.1905	12.51975 ~	149.9 ~ 150.05	1645.5 ~ 1646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.52025	156.52475 ~	1660 ~ 1710	8.025 ~ 8.5	22.01 ~ 23.12
4.17725 ~ 4.17775	12.57675 ~	156.52525	1718.8 ~ 1722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.20725 ~ 4.20775	12.57725	156.7 ~ 156.9	2200 ~ 2300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	13.36 ~ 13.41	162.0125 ~ 167.17	2310 ~ 2390	10.6 ~ 12.7	36.43 ~ 36.5
6.26775 ~ 6.26825	16.42 ~ 16.423	167.72 ~ 173.2	2483.5 ~ 2500	13.25 ~ 13.4	Above 38.6
6.31175 ~ 6.31225	16.69475 ~	240 ~ 285	2655 ~ 2900		
8.291 ~ 8.294	16.69525	322 ~ 335.4	3260 ~ 3267		
8.362 ~ 8.366	16.80425 ~	399.90 ~ 410	3332 ~ 3339		
8.37625 ~ 8.38675	16.80475	608 ~ 614	3345.8 ~ 3358		
	25.5 ~ 25.67	960 ~ 1240	3600 ~ 4400		
	37.5 ~ 38.25				
	73 ~ 74.6				
	74.8 ~ 75.2				

• **FCC Part 15.205(b):** The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

Test Configuration



■ TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

■ Measurement Instrument Setting for Radiated Emission Measurements.

Peak Measurement: 12.2.4 of KDB 558074 v03r1

RBW = As specified in below table , VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak, Trace mode = Max Hold until the trace stabilizes.

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

Average Measurement : 12.2.5 of KDB 558074 v03r1

1. RBW = 1 MHz (unless otherwise specified).
2. VBW $\geq 3 \times$ RBW.
3. Detector = RMS (Number of points $\geq 2 \times$ Span / RBW)
4. Averaging type = power (i.e., RMS).
5. Sweep time = auto.
6. Perform a trace average of at least 100 traces.
7. A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (RMS) mode was used in step 4, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.
 - 2) If linear voltage averaging mode was used in step 4, then the applicable correction factor is $20 \log(1/x)$, where x is the duty cycle.
 - 3) If a specific emission is demonstrated to be continuous (≥ 98 percent duty cycle) rather than turning on and off with the transmit cycle, then no duty cycle correction is required for that emission.

Band	Duty Cycle (%)	T _{on} (ms)	T _{on} + T _{off} (ms)	DCF = $10 \log(1/\text{Duty})$ (dB)
802.11b	92.69	1.205	1.300	0.33
802.11g	94.88	2.040	2.150	0.23
2.4GHz 802.11n(HT20)	94.03	1.890	2.010	0.27
2.4GHz 802.11n(HT40)	89.21	0.918	1.029	0.50
-	-	-	-	-
-	-	-	-	-

9KHz ~ 25GHz Data(802.11b & 11Mbps)▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2389.48	H	Y	PK	57.23	- 3.38	-	-	53.85	74.00	20.15
2389.92	H	Y	AV	46.04	- 3.38	0.33	-	42.99	54.00	11.01
4824.14	H	Y	PK	47.89	5.43	-	-	53.32	74.00	20.68
4824.26	H	Y	AV	37.81	5.43	0.33	-	43.57	54.00	10.43

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874.97	H	Y	PK	47.68	5.64	-	-	53.32	74.00	20.68
4874.99	H	Y	AV	36.60	5.64	0.33	-	42.57	54.00	11.43

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2484.13	H	Y	PK	56.98	- 2.79	-	-	54.19	74.00	19.81
2484.31	H	Y	AV	46.32	- 2.79	0.33	-	43.86	54.00	10.14
4924.14	H	Y	PK	45.65	5.99	-	-	51.64	74.00	22.36
4924.04	H	Y	AV	35.10	5.99	0.33	-	41.42	54.00	12.58

Note.

1. Measurement Distance = 3 m for below 10 GHz, Measurement Distance = 1 m for above 10 GHz.
So Distance Correction Factor :- $9.54\text{dB} = 20 \cdot \log(1\text{m}/3\text{m})$
2. No other spurious and harmonic emissions were found greater than listed emissions on above table.
3. Above listed point data is the worst case data.
4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F+ DCF + Distance Factor / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCF = Duty Cycle Correction Factor.

9KHz ~ 25GHz Data(802.11g & 6Mbps)▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2384.19	H	Y	PK	66.02	- 3.38	-	-	62.64	74.00	11.36
2384.24	H	Y	AV	53.76	- 3.38	0.23	-	50.61	54.00	3.39
4824.02	H	Y	PK	44.58	5.43	-	-	50.01	74.00	23.99
4823.97	H	Y	AV	34.39	5.43	0.23	-	40.05	54.00	13.95

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4873.60	H	Y	PK	49.11	5.64	-	-	54.75	74.00	19.25
4873.76	H	Y	AV	36.81	5.64	0.23	-	42.68	54.00	11.32

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2488.83	H	Y	PK	56.98	- 2.79	-	-	54.19	74.00	19.81
2488.95	H	Y	AV	46.32	- 2.79	0.23	-	43.76	54.00	10.24
4923.99	H	Y	PK	43.65	5.99	-	-	49.64	74.00	24.36
4924.16	H	Y	AV	34.11	5.99	0.23	-	40.33	54.00	13.67

Note.

1. Measurement Distance = 3 m for below 10 GHz, Measurement Distance = 1 m for above 10 GHz.
So Distance Correction Factor :- $9.54\text{dB} = 20 \cdot \log(1\text{m}/3\text{m})$
2. No other spurious and harmonic emissions were found greater than listed emissions on above table.
3. Above listed point data is the worst case data.
4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F+ DCF + Distance Factor / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCF = Duty Cycle Correction Factor.

9KHz ~ 25GHz Data(802.11n HT20 & MCS0)▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2384.68	H	Y	PK	65.21	- 3.38	-	-	61.83	74.00	12.17
2384.24	H	Y	AV	53.26	- 3.38	0.27	-	50.15	54.00	3.85
4824.06	H	Y	PK	43.76	5.43	-	-	49.19	74.00	24.81
4824.35	H	Y	AV	34.27	5.43	0.27	-	39.97	54.00	14.03

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874.07	H	Y	PK	46.33	5.64	-	-	51.97	74.00	22.03
4874.08	H	Y	AV	35.33	5.64	0.27	-	41.24	54.00	12.76

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2488.49	H	Y	PK	64.55	- 2.79	-	-	61.76	74.00	12.24
2488.71	H	Y	AV	52.65	- 2.79	0.27	-	50.13	54.00	3.87
4924.51	H	Y	PK	45.02	5.99	-	-	51.01	74.00	22.99
4924.32	H	Y	AV	34.04	5.99	0.27	-	40.30	54.00	13.70

Note.

1. Measurement Distance = 3 m for below 10 GHz, Measurement Distance = 1 m for above 10 GHz.
So Distance Correction Factor :- $9.54\text{dB} = 20 \cdot \log(1\text{m}/3\text{m})$
2. No other spurious and harmonic emissions were found greater than listed emissions on above table.
3. Above listed point data is the worst case data.
4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F+ DCF + Distance Factor / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCF = Duty Cycle Correction Factor.

9kHz ~ 25GHz Data(802.11n HT40 & MCS0)▪ **Lowest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2380.88	H	Y	PK	68.19	- 3.38	-	-	64.81	74.00	9.19
2380.64	H	Y	AV	53.35	- 3.38	0.50	-	50.47	54.00	3.53
4843.67	H	Y	PK	44.42	5.48	-	-	49.90	74.00	24.10
4843.84	H	Y	AV	33.77	5.48	0.50	-	39.75	54.00	14.25

▪ **Middle Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
4874.19	H	Y	PK	46.16	5.64	-	-	51.80	74.00	22.20
4874.15	H	Y	AV	35.53	5.64	0.50	-	41.67	54.00	12.33

▪ **Highest Channel**

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	T.F (dB/m)	DCF (dB)	Distance Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
2497.78	H	Y	PK	63.37	- 2.79	-	-	60.58	74.00	13.42
2497.74	H	Y	AV	52.70	- 2.79	0.50	-	50.41	54.00	3.59
4904.00	H	Y	PK	45.05	5.91	-	-	50.96	74.00	23.04
4903.63	H	Y	AV	34.28	5.91	0.50	-	40.69	54.00	13.31

Note.

1. Measurement Distance = 3 m for below 10 GHz, Measurement Distance = 1 m for above 10 GHz.
So Distance Correction Factor :- $9.54\text{dB} = 20 \cdot \log(1\text{m}/3\text{m})$
2. No other spurious and harmonic emissions were found greater than listed emissions on above table.
3. Above listed point data is the worst case data.
4. Sample Calculation.

Margin = Limit – Result / Result = Reading + T.F+ DCF + Distance Factor / T.F = AF + CL – AG
Where, T.F = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain,
DCF = Duty Cycle Correction Factor.

8.6 Power-line Conducted Emissions

Test Requirements and limit, §15.207& RSS-Gen [7.2.2]

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.5	66 to 56 *	56 to 46 *
0.5 ~ 5	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs for the actual connections between EUT and support equipment.

Test Mode

The all modes of EUT operation were investigated and the worst case mode was reported.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to the test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

■ **RESULT PLOTS****AC Line Conducted Emissions (Graph)**



Test Mode: 802.11b & 11Mbps & 2412MHz

**Results of Conducted Emission**Digital EMC
Date : 2014-01-20

Model No. : 2GIG-CAMHD110
Type :
Serial No. : Identical prototype
Test Condition : WLAN

Reference No. :
Power Supply : 120 V 60 Hz
Temp/Humi. : 24 °C 52 % R.H.
Operator : H.S.SON

Memo : 802.11b

LIMIT : FCC P15.207 QP
FCC P15.207 AV

AC Line Conducted Emissions (List)

Test Mode: 802.11b & 11Mbps & 2412MHz

Results of Conducted EmissionDigital EMC
Date : 2014-01-20Model No. : 2GIG-CAMHD110
Type :
Serial No. : Identical prototype
Test Condition : WLANReference No. :
Power Supply : 120 V 60 Hz
Temp/Humi. : 24 'C 52 % R.H.
Operator : H.S.SON

Memo : 802.11b

LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C.FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	
1	0.16617	44.5	23.3	0.1	44.6	23.4	65.1	55.1	20.5	31.7	N
2	0.20827	41.3	26.2	0.1	41.4	26.3	63.3	53.3	21.9	27.0	N
3	0.33072	32.8	22.5	0.1	32.9	22.6	59.4	49.4	26.5	26.8	N
4	0.43482	40.4	31.7	0.1	40.5	31.8	57.2	47.2	16.7	15.4	N
5	0.55685	41.1	31.8	0.1	41.2	31.9	56.0	46.0	14.8	14.1	N
6	1.17680	39.4	29.6	0.2	39.6	29.8	56.0	46.0	16.4	16.2	N
7	1.48740	40.1	29.9	0.2	40.3	30.1	56.0	46.0	15.7	15.9	N
8	3.53400	39.2	28.6	0.4	39.6	29.0	56.0	46.0	16.4	17.0	N
9	6.75680	39.6	29.9	0.5	40.1	30.4	60.0	50.0	19.9	19.6	N
10	12.08420	37.5	27.8	0.5	38.0	28.3	60.0	50.0	22.0	21.7	N
11	0.16344	44.9	25.6	0.1	45.0	25.7	65.3	55.3	20.3	29.6	L1
12	0.19173	42.6	29.6	0.1	42.7	29.7	64.0	54.0	21.3	24.3	L1
13	0.24135	38.5	26.2	0.1	38.6	26.3	62.0	52.0	23.4	25.7	L1
14	0.43315	38.7	31.2	0.1	38.8	31.3	57.2	47.2	18.4	15.9	L1
15	0.55867	41.6	32.7	0.1	41.7	32.8	56.0	46.0	14.3	13.2	L1
16	1.05300	38.5	29.5	0.2	38.7	29.7	56.0	46.0	17.3	16.3	L1
17	1.48840	39.6	30.2	0.2	39.8	30.4	56.0	46.0	16.2	15.6	L1
18	2.72440	33.6	23.1	0.4	34.0	23.5	56.0	46.0	22.0	22.5	L1
19	6.32300	34.7	25.3	0.5	35.2	25.8	60.0	50.0	24.8	24.2	L1
20	12.46740	36.9	29.6	0.5	37.4	30.1	60.0	50.0	22.6	19.9	L1

8.7 Occupied Bandwidth

Test Requirements, RSS-Gen [4.6.1]

When an occupied bandwidth value is not specified in the applicable RSS, the transmitted signal bandwidth to be reported is to be its 99% emission bandwidth, as calculated or measured.

■ TEST CONFIGURATION

Refer to the APPENDIX I.

■ TEST PROCEDURE

The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used given that a peak or peak hold may produce a wider bandwidth than actual.


■ TEST RESULTS: **Comply**

Test Mode	Data Rate	Frequency [MHz]	Test Results[MHz]
802.11b	11Mbps	2412	10.720
		2437	10.679
		2462	10.701
802.11g	6Mbps	2412	16.466
		2437	16.535
		2462	16.470
802.11n (20MHz)	MCS0	2412	17.464
		2437	17.460
		2462	17.446
802.11n (40MHz)	MCS0	2422	36.398
		2437	36.359
		2452	36.488

Note 1: See next pages for actual measured spectrum plots.


Occupied Bandwidth (99%)

802.11b & 11Mbps & 2412MHz




Occupied Bandwidth (99%)

802.11b & 11Mbps & 2437MHz




Occupied Bandwidth (99%)

802.11b & 11Mbps & 2462MHz




Occupied Bandwidth (99%)

802.11g & 6Mbps & 2412MHz




Occupied Bandwidth (99%)

802.11g & 6Mbps & 2437MHz




Occupied Bandwidth (99%)

802.11g & 6Mbps & 2462MHz




Occupied Bandwidth (99%)

802.11n(HT20) & MCS 0 & 2412MHz




Occupied Bandwidth (99%)

802.11n(HT20) & MCS 0 & 2437MHz




Occupied Bandwidth (99%)

802.11n(HT20) & MCS 0 & 2462MHz




Occupied Bandwidth (99%)

802.11n(HT40) & MCS 0 & 2422MHz




Occupied Bandwidth (99%)

802.11n(HT40) & MCS 0 & 2437MHz



Occupied Bandwidth (99%)

802.11n(HT40) & MCS 0 & 2452MHz




9. LIST OF TEST EQUIPMENT

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent	E4440A	14/01/08	15/01/08	MY44033778
Spectrum Analyzer	Agilent	N9020A	13/03/28	14/03/28	MY50510026
Spectrum Analyzer	Rohde Schwarz	FSQ26	13/02/14	14/02/14	200445
			14/02/07	15/02/07	
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A/ MA2411B	13/09/16	14/09/16	1111002 / 011290
DC Power Supply	SM techno	SDP30-5D	13/05/27	14/05/27	305DKA013
Multimeter	HP	34401A	13/02/27	14/02/27	3146A13475
Vector Signal Generator	Rohde Schwarz	SMBV100A	14/01/07	15/01/07	255571
Signal Generator	Rohde Schwarz	SMF100A	13/07/22	14/07/22	102341
Thermohygrometer	BODYCOM	BJ5478	13/06/01	14/06/01	120612-2
High-pass Filter	Wainwright Instruments	WHKX3.0	13/09/12	14/09/12	9
Loop Antenna	Schwarzbeck	FMZB1513	12/09/24	14/09/24	1513-128
BILOG ANTENNA	SCHAFFNER	CBL6112B	12/11/06	14/11/06	2737
Horn Antenna	ETS	3115	13/02/28	15/02/28	00021097
Horn Antenna	A.H.Systems Inc.	SAS-574	13/03/20	15/03/20	154
Attenuator (3dB)	WEINSCHTEL	56-3	13/09/12	14/09/12	Y2342
Amplifier (22dB)	HP	8447E	14/01/08	15/01/08	2945A02865
Amplifier (30dB)	Agilent	8449B	13/02/27	14/02/27	3008A00370
EMI TEST RECEIVER	R&S	ESU	14/01/08	15/01/08	100014
EMI TEST RECEIVER	R&S	ESCI	13/02/27	14/02/27	100364
CVCf	NF	4420	13/09/12	14/09/12	3049354420023
LISN	R&S	ESH2-Z5	13/09/12	14/09/12	828739/006

APPENDIX I

Conducted Test set up Diagram & Path loss Information

Conducted Measurement(30MHz ~ 25GHz)



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	2.96	15	4.65
1	3.04	20	5.09
2412 & 2437 & 2462	3.36	25	5.72
5	3.50	-	-
10	4.52	-	-

Note. 1: The path loss from EUT to Spectrum analyzer was measured and used for test.

Path loss (=S/A's offset value) = Cable A + ATT (Attenuator, Applied only when it was used externally)

Note. 2: For conducted spurious emissions, the path loss values were saved as the transducer factor on the spurious measurement function of the spectrum analyzer and the transducer factor of tested frequency is calculated and corrected automatically by the spectrum analyzer's measurement function.