

No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

+86 (0) 20 8215 5555 Telephone: Report No.: SZEMO081105826RFF Fax:

+86 (0) 20 8207 5059 Page: 1 of 12

Email: sgs_internet_operations@sgs.com FCC ID: WED-GY130

FCC Test Report

Application No.: SZEMO081105826RF

The NCC NY LLC Applicant:

Electronic Co.,Ltd. Manufacturer:

Electronics Factory Factory:

WED-GY130 FCC ID:

Equipment Under Test (EUT):

EUT Name: GPS

Item No.: GY130/ GY135/ GY135C/ GY120

Trade mark.: **GPS**

Standards: FCC PART15 SUBPART B:2006

Date of Receipt: 21 July 2008

Date of Test: 21 to 23 July 2008

Date of Issue: 10 October 2008

Test Result: PASS*

Authorized Signature:

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEMO081105826RFF

Page: 2 of 12

2 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 1GHz)	FCC PART 15, SUBPART B: 2006	ANSI C63.4:2003	Class B	PASS
Conducted Emission (150KHz to 30MHz)	FCC PART 15, SUBPART B: 2006	ANSI C63.4:2003	Class B	PASS

Remark:

Item No.: GY130/ GY135/ GY135C/ GY120

Only the Item GY130 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items, with only different of surface design.



Report No.: SZEMO081105826RFF

Page: 3 of 12

3 Contents

			Page
1	COV	/ER PAGE	1
2	TES	T SUMMARY	2
3	CON	ITENTS	1
J	COI	TI LIVI O	•••••••••••••••••••••••••••••••••••••••
4	GEN	IERAL INFORMATION	4
	4.1	CLIENT INFORMATION	4
	4.2	GENERAL DESCRIPTION OF E.U.T.	
	4.3	DETAILS OF E.U.T.	
	4.4	DESCRIPTION OF SUPPORT UNITS	
	4.5	STANDARDS APPLICABLE FOR TESTING	4
	4.6	TEST LOCATION	
	4.7	TEST FACILITY	
	4.8	DEVIATION FROM STANDARDS	
	4.9	ABNORMALITIES FROM STANDARD CONDITIONS	
5	EQU	JIPMENTS USED DURING TEST	6
6	TES	T RESULTS	7
	6.1	CONDUCTED EMISSIONS MAINS TERMINALS, 150KHZ TO 30MHZ	7
	6.1.	1 E.U.T. Operation	
		2 Measurement Data	
	6.2	RADIATED EMISSIONS, 30MHz TO 1GHz	
		1 E.U.T. Operation	
	6.2.2	2 Measurement Data	10-12



Report No.: SZEMO081105826RFF

Page: 4 of 12

4 General Information

4.1 Client Information

Applicant: The NCC NY LLC

Address of Applicant: 140 58th Street, Suit 6W, Brooklyn, NY 11220.

Manufacturer: Electronic Co.,Ltd.

Address of Manufacturer: New industrial Developing Zone, Xiao Bian, Chang An, Dong

Guan, Guangdong.

Factory: Electronics Factory

Address of Factory: New industrial Developing Zone, Xiao Bian, Chang An, Dong

Guan, Guangdong.

4.2 General Description of E.U.T.

EUT Name: GPS

Item No.: GY130/ GY135/ GY135C/ GY120

4.3 Details of E.U.T.

Power Supply: DC 3.7V Rechargeable Battery

4.4 Description of Support Units

The EUT has been tested with a personal computer system for 'Web-Cam' mode.

Description	Manufacturer	Model No.		
PC	IBM	2662		
Printer	Canon	BJC-1000SP		

4.5 Standards Applicable for Testing

The customer requested FCC tests for a digital camera.

The standard used was FCC PART 15, SUBPART B, CLASS B (2006)

4.6 Test Location

All tests were performed at: -

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

No tests were sub-contracted.



Report No.: SZEMO081105826RFF

Page: 5 of 12

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP – Lab Code: 200611-0

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

ACA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

VCCI

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.

Date of Registration: September 29, 2005. Valid until September 28, 2008.

SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

CNAS L0167

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, Aug. 04, 2005

• Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 6002.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.



Report No.: SZEMO081105826RFF

Page: 6 of 12

5 Equipments Used during Test

	Conducted Emission											
Item	Test Equipment Manufacturer		Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)						
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	N/A	N/A						
2	LISN	ETS-LINDGREN	3816/2	SEL0021	18-06-2008	17-06-2009						
3	ISN	Rohde & Schwarz	ENY 22 1109	EMC0114	18-06-2008	17-06-2009						
4	ISN	Rohde & Schwarz	ENY 41 1110	EMC0115	18-06-2008	17-06-2009						
5	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	18-06-2008	17-06-2009						
6	Coaxial Cable	SGS	N/A	SEL0024	18-06-2008	17-06-2009						

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2009
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	12-12-2007	11-12-2008
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	18-06-2008	17-06-2009
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0014	12-08-2007	11-08-2008
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	18-06-2008	17-06-2009
7	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0005	12-08-2007	11-08-2008
8	Pre-amplifier (1-18GHz)	Rohde & Schwarz	AFS42-00101 800-25-S-42	SEL0081	18-06-2008	17-06-2009
9	Band filter	Amindeon	82346	SEL0094	18-06-2008	17-06-2009

	General used equipment										
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)					
1	Humidity/ Temperature Indicator	Shanghai	ZJ1-2B	SEL0101 to SEL0103	18-11-2007	17-11-2008					
2	Barometer	ChangChun	DYM3	SEL0088	22-06-2006	21-06-2009					



Report No.: SZEMO081105826RFF

Page: 7 of 12

6 Test Results

6.1 Conducted Emissions Mains Terminals, 150kHz to 30MHz

Test Requirement: FCC Part15 B
Test Method: ANSI C63.4
Test Date: 28 March 2008
Frequency Range: 150KHz to 30MHz

Class / Severity: Class B

Detector: Peak for pre-scan (9kHz Resolution Bandwidth)

Quasi-Peak if maximised peak within 6dB of Quasi-Peak limit

6.1.1 E.U.T. Operation

Operating Environment:

Temper 24.0 °C Humidity: 52 % RH Atmospheric Pressure: 1012 Mbar

ature:

EUT Test in 'Web-Cam' mode with PC system.

Operation:

6.1.2 Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

The following Quasi-Peak and Average measurements were performed on the EUT on 28 March 2008:


Test the EUT on charging USB mode:



Report No.: SZEMO081105826RFF

Page: 8 of 12

Line:



Site : Shielding Room

Condition : FCC PART15B QP CE LINE

EUT : GPS NO : 3634RI


NO : 3634RF	Freq	Cable Loss	LISN Factor	Read Level <u>dBu</u> V	Level	Limit Line 	Over Limit dB	Remark
1 @	0.16155	-0.03	-0.05	59.69	59.62	65.38	-5.77	
2	0.16155	-0.03	-0.05	42.30	42.23	55.38		Average
3	0.19550	-0.09	-0.05	56.53	56.39	63.80	-7.41	
4	0.19550	-0.09	-0.05	42.31	42.17	53.80		Average
5	0.37117	0.00	-0.04	50.79	50.74	58.47	-7.73	QP
6	0.37117	0.00	-0.04	36.30	36.26	48.47	-12.22	Áverage
7	3.224	0.10	-0.08	42.98	43.00	56.00	-13.00	
2 3 4 5 6 7 8 9	3.224	0.10	-0.08	31.20	31.22	46.00	-14.78	Àverage
9	11.438	0.22	-0.36	35.91	35.77	60.00	-24.23	OP
10	11.438	0.22	-0.36	26.35	26.22	50.00	-23.78	Àverage
11	20.594	0.33	-0.66	24.37	24.04	50.00		Average
12	20.594	0.33	-0.66	34.58	34.26	60.00	-25.74	



Report No.: SZEMO081105826RFF

Page: 9 of 12

Neutral:



Site : Shielding Room

Condition : FCC PART15B QP CE NEUTRAL

EUT : GPS

МО	: 3634RF	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
		MHz	<u>dB</u>	<u>dB</u>	dBu∀	dBu∀	dBuV	dB	
1 2 3 4 5 6 7 8 9 10 11		0.20500 0.20500 0.25300 0.25300 0.35200 0.35200 0.42100 0.42100 0.82500 0.82500 1.710 1.710	-0.09 -0.09 -0.04 -0.04 0.00 0.00 0.00 0.00 0.05 0.05 0.10	-0.04 -0.04 -0.04 -0.04 -0.04 -0.04 -0.04 -0.04 -0.06	50.26 39.62 39.16 51.20 34.62 45.82 38.26 29.26 33.46 25.52 24.62 34.26		53.41 51.66 61.66	-12.58 -10.54 -14.33 -13.13 -19.21 -18.21 -22.54 -20.48	Average Average QP Average QP QP Average QP Average QP Average Average



Report No.: SZEMO081105826RFF

Page: 10 of 12

6.2 Radiated Emissions, 30MHz to 1GHz

Test FCC Part15 B

Requirement:

Test Method: ANSI C63.4
Test Date: 31 March 2008
Frequency 30MHz to 1GHz

Range:

Measurement 3m

Distance:

Class: Class B

Limit: $40.0 \text{ dB}\mu\text{V/m}$ between 30MHz & 88MHz

 $43.5 \text{ dB}\mu\text{V/m}$ between 88MHz & 216MHz $46.0 \text{ dB}\mu\text{V/m}$ between 216MHz & 960MHz

 $54.0 \text{ dB}\mu\text{V/m}$ zbove 960MHz

Detector: Peak for pre-scan (120kHz resolution bandwidth)

Quasi-Peak if maximised peak within 6dB of limit

6.2.1 E.U.T. Operation

Operating Environment:

Te 24.0 °C Humidity: 52 % RH Atmospheric Pressure: 1012 mbar

mp erat ure:

EUT Test the EUT in 'Take Photo' mode and 'Web-Cam' mode.

Operation:

6.2.2 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. The EUT was measured by Bilog antenna with 2 orthogonal polarities and peak emissions from the EUT were detected within 6dB of the class B limit line.

The following quasi-peak measurements were performed on the EUT on 31 March 2008:



Report No.: SZEMO081105826RFF

Page: 11 of 12

Test mode: charging mode.

Vertical

Frequenc y (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
56.190	0.80	7.48	28.07	42.32	22.53	40.00	-17.47
78.500	1.05	7.59	28.00	43.63	24.27	40.00	-15.73
152.220	1.32	9.14	27.44	39.04	22.06	43.50	-21.44
198.780	1.40	10.19	27.16	45.33	29.76	43.50	-13.74
299.660	1.90	13.85	26.72	43.20	32.23	46.00	-13.77
349.130	2.06	15.40	27.08	32.44	22.82	46.00	-23.18

Horizontal:

nonzoniai.	ionzoniai.										
Frequenc y (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)				
78.500	1.05	7.59	28.00	45.72	26.36	40.00	-13.64				
144.460	1.31	8.53	27.49	50.39	32.74	43.50	-10.76				
183.260	1.38	9.97	27.24	47.01	31.12	43.50	-12.38				
198.780	1.40	10.19	27.16	53.12	37.55	43.50	-5.95				
299.660	1.90	13.85	26.72	53.49	42.52	46.00	-3.48				
350.100	2.06	15.40	27.09	39.12	29.49	46.00	-16.51				



Report No.: SZEMO081105826RFF

Page: 12 of 12

Test Mode: USB mode.

Vertical:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
164.830	1.35	9.55	27.36	48.65	32.19	43.50	-11.31
198.780	1.40	10.19	27.16	48.66	33.09	43.50	-10.41
265.710	1.75	12.63	26.85	37.42	24.95	46.00	-21.05
365.620	2.11	15.78	27.20	40.67	31.36	46.00	-14.64
455.830	2.43	17.09	27.58	47.79	39.73	46.00	-6.27
832.190	3.34	22.40	26.77	39.83	38.80	46.00	-7.20

Horizontal:

Tionzoniai.			l				
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
109.540	1.23	8.62	27.78	47.93	30.00	43.50	-13.50
175.500	1.36	9.71	27.29	53.41	37.19	43.50	-6.31
199.890	1.40	10.20	27.15	53.57	38.02	43.50	-5.48
299.660	1.90	13.85	26.72	48.24	37.27	46.00	-8.73
453.890	2.43	17.03	27.58	42.71	34.59	46.00	-11.41
730.340	2.99	21.62	27.17	40.41	37.85	46.00	-8.15