

CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

RF EXPOSURE EVALUATION

Applicant : SEWOO TECH CO., LTD.

Applicant Address : 28-6, Gajangsaneopdong-ro, Osan-si, Gyeongi-

do, 447-210, Korea

Kind of Product : Mobile Printer

Equipment model name: LK-P12B

RF power : 2.037 dBm Peak Conducted

Antenna type : Chip antenna Gain 3.5 dBi

Frequency Range : 2402 - 2480 MHz

Number of channels : 79 CH



CTK Co., Ltd.

386-1, Ho-dong, Cheoin-gu, Yongin-si, Gyeonggi-do, 449-100, Korea Tel: +82-31-339-9970 Fax: +82-31-339-9855 www.e-ctk.com

** MPE Calculations **

No Evaluation Required if power is below this threshold. (60/f(GHz) mW)

Frequency (GHz)		mW	
Middle	2.441	24.58	

The MPE calculation for this exposure is shown below.

EIRP = P + G	Where, P = Conducted output power (dBm) G = Power gain of the antenna (dBi)
--------------	---

Measured Transmitter Output Power(Maximum: GFSK, CH 39)

Output Power(dBm)	Antenna gain (dBi)	EIRP (dBm)	EIRP (mW)
2.037	3.5	5.537	3.578

Conclusion: No SAR evaluation required since Transmitter EIRP is below FCC threshold.