



# Test Report

**Applicant:** EU3C Company Limited  
**Address of Applicant:** Unit 8, 17/F. Tower 1, China Hong Kong City, 33 Canton Road, Tsimshatsui, Kowloon, Hong Kong  
**Equipment Under Test (EUT):**  
EUT Name: FilmScan35 I  
Model No.: SCND502E1231  
Serial No.: Not supplied by client  
**Standards:** FCC PART15 SUBPART B: 2007  
**Date of Receipt:** Jun. 23, 2009  
**Date of Test:** Jun. 23, 2009 – Jul. 8, 2009  
**Date of Issue:** Jul. 15, 2009  
**Test Result :** **PASS\***

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Henly.xie / Manager

This report refers to the General Conditions for Inspection and Testing Services, printed overleaf

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

All test results in this report can be traceable to National or International Standards.

The test report prepare by:

Guangzhou Huesent Testing Service Co.,Ltd.

No.91, Dongguanzhuang Road,Guangzhou,China.

Tel: 86-20-28263298 Fax: 86-20-28263237 <http://www.hst.org.cn> E-mail:hst@hst.org.cn



## 2. Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 1GHz)	FCC PART 15, SUBPART B: 2007	ANSI C63.4:2003	Class B	PASS
Conducted Emission (150KHz to 30MHz)	FCC PART 15, SUBPART B: 2007	ANSI C63.4:2003	Class B	PASS



### 3. Contents

#### TITLE PAGE

<b>1. COVER PAGE .....</b>	<b>1</b>
<b>2. TEST SUMMARY .....</b>	<b>2</b>
<b>3. CONTENTS .....</b>	<b>3</b>
<b>4. GENERAL INFORMATION .....</b>	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF E.U.T .....	4
4.3 DETAILS OF E.U.T .....	4
4.4 DESCRIPTION OF SUPPORT UNITS .....	4
4.5 STANDARDS APPLICABLE FOR TESTING .....	4
4.6 TEST LOCATION .....	4
4.8 DEVIATION FROM STANDARDS .....	4
4.9 ABNORMALITIES FROM STANDARD CONDITIONS .....	4
<b>5. EQUIPMENTS USED DURING TEST .....</b>	<b>5</b>
<b>6. TEST RESULTS .....</b>	<b>6</b>
6.1 CONDUCTED EMISSIONS MAINS TERMINALS, 150 KHZ TO 30MHZ .....	6
6.1.1 <i>E.U.T. Operation</i> .....	6
6.1.2 <i>Plan View of Test Setup</i> .....	6
6.1.3 <i>Measurement Data</i> .....	6
6.2 RADIATED EMISSIONS, 30MHZ TO 1GHZ .....	9
6.2.1 <i>E.U.T. Operation</i> .....	9
6.2.2 <i>Test Setup</i> .....	9
6.2.3 <i>Measurement Data</i> .....	9
<b>7. PHOTOGRAPHS .....</b>	<b>12</b>
7.1 CONDUCTED EMISSION TEST SETUP .....	12
7.2 RADIATED EMISSION TEST SETUP .....	13
7.3 EUT CONSTRUCTIONAL DETAILS .....	14

## 4. General Information

### 4.1 Client Information

Applicant: EU3C Company Limited  
Address of Applicant: Unit 8, 17/F. Tower 1, China Hong Kong City, 33 Canton Road, Tsimshatsui, Kowloon, Hong Kong

### 4.2 General Description of E.U.T.

EUT Name: FilmScan35 I  
Trade Name: EU3C  
Item No.: See the model number shown on cover page.  
Serial No.: Not supplied by client

### 4.3 Details of E.U.T.

Power Supply: 5VDC via an USB cable by PC host  
Power Cord: 1.10 m USB cable with a core

### 4.4 Description of Support Units

Samsung's Notebook ( model: R515, Li Shin International Electronic's adapter: model: ( SADP-90FH B ) AD-9019S, input: 100-240VAC1.5A, 50-60Hz, output: 19VDC4.74A ).

### 4.5 Standards Applicable for Testing

The standard used was FCC PART 15, SUBPART B, CLASS B 2007

### 4.6 Test Location

Huesent Testing Service Ltd.  
No. 91, Dongguan Zhuang Road, Guangzhou City, Guangdong Province, P.R. China  
Tel: 86-20-28263298 Fax: 86-20-28263237

All tests were subcontract to the laboratory following:

CEPREI (headquarters) lab.  
No.110, Dongguan Zhuang Road, Tianhe District, Guangzhou city, Guangdong Province, P.R. China  
Tel: 86-20-87237178 Fax: 86-20-87236171 Email: [emc@ceprei.biz](mailto:emc@ceprei.biz)  
FCC- Registration No: 258518 on Mar 25, 2005

### 4.8 Deviation from Standards

None.

### 4.9 Abnormalities from Standard Conditions

None.



## 5. Equipments Used during Test

No.	Test item.	Name of Equipment's	Model/Type	Last Calibrated Date
1	CE	EMI Receiver	R&S ESCS 30	2009-6-8
2	CE	LISN	R&S ESH3-Z5	2009-6-8
3	CE	Shielding Room	DG ZongZhou 5x3x3 m	2009-6-8
4	RE	EMI Receiver	R&S ESU	2009-6-8
5	RE	Anechoic Chamber	ETS-Lindgren RFSD-F-100	2009-6-8
6	RE	Antenna	ETS-Lindgren 3142B	2009-6-8
Note: /				

## 6. Test Results

### 6.1 Conducted Emissions Mains Terminals, 150 kHz to 30MHz

Test Requirement: FCC Part 15 B  
Test Method: ANSI C63.4  
Class / Severity: Class B  
Detector: Peak for pre-scan (9kHz Resolution Bandwidth)  
Quasi-Peak if maximised peak within 6dB of Quasi-Peak limit  
Test Date: Jun. 23, 2009

#### 6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.0°C      Humidity: 55% RH      Atmospheric Pressure: 103.0kPa

EUT Operation:

1. Connect the EUT via an USB cable to an AC/DC adapter or Notebook in 120VAC/60Hz.
2. Pre-test the EUT work normally in three modes: previewing/ scanning/ transmit data, then select the worst case: scanning mode to measure during the whole test.


#### 6.1.2 Plan View of Test Setup

#### 6.1.3 Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized emission were detected when Peak measurement level is over Average Limit.

# Live Line, Mode: Scanning with Notebook

## Peak Scan




## Quasi-peak and Average measurement

Freq. (MHz)	Line	QP (dBμV)	Transd ucer (dB)	QP limit (dBμV)	Margin (dB)	AV (dBμV)	Transd ucer (dB)	AV limit (dBμV)	Margin (dB)
0.205	Live	52.76	4.37	63.47	-10.71	47.05	4.37	53.47	-6.42
0.415	Live	49.66	4.12	57.64	-7.98	39.00	4.12	47.64	-8.64
0.830	Live	53.34	4.06	56.00	-2.66	39.19	4.06	46.00	-6.81
3.975	Live	55.64	3.93	56.00	-0.36	42.35	3.93	46.00	-3.65
7.115	Live	51.29	3.84	60.00	-8.71	38.42	3.84	50.00	-11.58
14.31	Live	42.60	3.61	60.00	-17.40	33.76	3.61	50.00	-16.24

# Neutral Line, Mode: Scanning with Notebook

## Peak Scan



## Quasi-peak and Average measurement

Freq. (MHz)	Line	QP (dBμV)	Transducer (dB)	QP limit (dBμV)	Margin (dB)	AV (dBμV)	Transducer (dB)	AV limit (dBμV)	Margin (dB)
0.205	Neutral	52.64	4.37	63.47	-10.83	48.52	4.37	53.47	-4.95
0.415	Neutral	49.74	4.12	57.64	-7.90	40.24	4.12	47.64	-7.40
1.150	Neutral	54.17	4.04	56.00	-1.83	39.06	4.04	46.00	-6.94
3.855	Neutral	55.27	3.94	56.00	-0.73	42.05	3.94	46.00	-3.95
6.635	Neutral	50.54	3.85	60.00	-9.46	37.11	3.85	50.00	-12.89
14.23	Neutral	40.45	3.62	60.00	-19.55	31.93	3.62	50.00	-18.07



## 6.2 Radiated Emissions, 30MHz to 1GHz

Test Requirement: FCC Part15 B  
Test Method: ANSI C63.4  
Class: Class B  
Detector: Peak for pre-scan (120kHz resolution bandwidth)  
Quasi-Peak if maximised peak within 6dB of limit  
Test Date: Jul. 8, 2009

### 6.2.1 E.U.T. Operation


Operating Environment:

Temperature: 22°C      Humidity: 55% RH      Atmospheric Pressure: 103.0kPa

EUT Operation:

1. Connect the EUT via an USB cable to an AC/DC adapter or Notebook in 120VAC/60Hz.
2. Pre-test the EUT work normally in three modes: previewing/ scanning/ transmit data, then select the worst cases: scanning mode and transmit data with PC host for final measurement during the whole test.

### 6.2.2 Test Setup




### 6.2.3 Measurement Data

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bilog antenna with 2 orthogonal polarities

# Horizontal, Mode: Scanning with Notebook

## Peak Scan



## Quasi-peak measurement


Frequency MHz	Level dBuV/m	Transducer dB	Limit dBuV/m	Margin dB
64.5	35.8	8.4	40	-4.2
70.7	31.4	8.3	40	-8.6
150.5	38.6	10.6	43.5	-4.9
194.8	36.1	12.0	43.5	-7.4
240.3	40.9	13.9	46	-5.1
292.3	37.4	16.1	46	-8.6

## Note:

The transducer factor includes antenna factor and cable loss.

**Vertical, Mode: Scanning with Notebook**

**Peak Scan**



**Quasi-peak measurement**

Frequency	Level	Transducer	Limit	Margin
MHz	dBuV/m	dB	dBuV/m	dB
58.4	31.8	8.8	40	-8.2
64.5	32.7	8.4	40	-7.3
148.7	36.6	10.5	43.5	-6.9
195.4	29.0	11.9	43.5	-14.5
240.0	37.4	13.9	46	-8.6
480.0	36.5	20.1	46	-9.5

**Note:**

The transducer factor includes antenna factor and cable loss.

## 7. Photographs

### 7.1 Conducted Emission Test Setup



## 7.2 Radiated Emission Test Setup





### 7.3 EUT Constructional Details




























\*\*\*End of Report\*\*\*