

Report No.: FG070917

FCC RF Test Report

APPLICANT : EU3C Company Limited

EQUIPMENT : GPS TRACKER

BRAND NAME : EU3C

MODEL NAME : TRACKER GT100

FCC ID : WFZGT100A

STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)

CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /

869.2 ~ 893.8 MHz

GSM1900: 1850.2 ~ 1909.8 MHz / 1930.2 ~ 1989.8 MHz

MAX. ERP/EIRP POWER : GSM850 (GSM) : 0.36 W

GSM1900 (GSM): 0.86 W

EMISSION DESIGNATOR : 246KGXW

The product was received on Jul. 09, 2010 and completely tested on Sep. 11, 2010. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Anderson Chiu / Deputy Manager



Page Number

Report Version

Report Issued Date: Sep. 13, 2010

: Rev. 01



SPORTON INTERNATIONAL (KUNSHAN) INC. No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	MMA	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Feature of Equipment Under Test	5
	1.4	Testing Site	6
	1.5	Applied Standards	6
	1.6	Ancillary Equipment List	6
2	TES	T CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Test Mode	
	2.2	Connection Diagram of Test System	
3	TES	T RESULT	8
	3.1	Conducted Output Power Measurement	8
	3.2	Effective Radiated Power and Effective Isotropic Radiated Power Measurement	
	3.3	Occupied Bandwidth Measurement	
	3.4	Band Edge Measurement	
	3.5	Conducted Emission Measurement	19
	3.6	Field Strength of Spurious Radiation Measurement	25
	3.7	Frequency Stability Measurement	31
4	LIST	OF MEASURING EQUIPMENT	34
5	UNC	ERTAINTY OF EVALUATION	35
ΑP	PEND	DIX A. PHOTOGRAPHS OF EUT	
ΑP	PEND	DIX B. SETUP PHOTOGRAPHS	

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 2 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG070917	Rev. 01	Initial issue of report	Sep. 13, 2010

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 3 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Report No.: FG070917

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 22.70 dB at 2510 MHz
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 4 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



General Description 1

1.1 Applicant

EU3C Company Limited

Unit 7, 8/F., Austin Tower, 22-26 Austin Avenue, Tsim Sha Tsui, Kowloon, Hong Kong

1.2 Manufacturer

QINGBANG ELEC(SZ)CO., LTD.

No. 2, qimin Rd., North District, High-tech Industrial Park, Nan Shan, Shenzhen

1.3 Feature of Equipment Under Test

Product Feature & Specification				
Equipment	GPS TRACKER			
Brand Name	EU3C			
Model Name	TRACKER GT100			
FCC ID	WFZGT100A			
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz			
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz			
Maximum Output Power to Antenna	GSM850 : 31.96 dBm GSM1900 : 28.88 dBm			
Maximum ERP/EIRP	GSM850 (GSM): 0.36 W (25.62 dBm) GSM1900 (GSM): 0.86 W (29.34 dBm)			
Antenna Type	Fixed Internal Antenna			
HW Version	MTK6225			
SW Version	09A0932			
Type of Modulation	GMSK			
Type of Emission	246KGXW			
EUT Stage	Production Unit			

- This test report recorded only product characteristics and test results of PCS Licensed Transmitter Held to Ear (PCE).
- The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 5 of 35 Report Issued Date : Sep. 13, 2010 Report Version

: Rev. 01



1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.				
	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.				
Test Site Location	TEL: +86-0512-5790-0158				
	FAX: +86-0512-5790-0958				
Took Site No	Sporton Site No.				
Test Site No.	TH01-KS	03CH01-KS			

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- IC RSS-132 Issue 2
- IC RSS-133 Issue 5

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

SPORTON INTERNATIONAL (KUNSHAN) INC. TEL: 86-0512-5790-0158

FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 6 of 35 Report Issued Date: Sep. 13, 2010

Report No.: FG070917

Report Version : Rev. 01



Report No.: FG070917

Test Configuration of Equipment Under Test

2.1 Test Mode


During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

- 30 MHz to 9000 MHz for GSM850.
- 2. 30 MHz to 19000 MHz for GSM1900.

Test Modes						
Band	Radiated TCs	Conducted TCs				
GSM 850	■ GSM Link	■ GSM Link				
GSM 1900	■ GSM Link	■ GSM Link				

2.2 Connection Diagram of Test System



SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 7 of 35 Report Issued Date: Sep. 13, 2010 Report Version : Rev. 01



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to base station.
- 2. Set EUT at maximum power through base station.
- 3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 8 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	Conducted Power (dBm)	Conducted Power (Watts)				
	128 (Low)	824.2	31.96	1.57		
GSM850 (GSM)	189 (Mid)	836.4	31.67	1.47		
	251 (High)	848.8	31.29	1.35		

PCS Band						
Modes	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)			
	512 (Low)	1850.2	28.85	0.77		
GSM1900 (GSM)	661 (Mid)	1880.0	28.88	0.77		
	810 (High)	1909.8	28.67	0.74		

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 9 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- 1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
- 2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest radiated power.
- 4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
- 5. Taking the record of maximum ERP/EIRP.
- 6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. The conducted power at the terminal of the dipole antenna is measured.
- 8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
- 9. ERP/EIRP = Ps + Et Es + Gs = Ps + Rt Rs + Gs

Ps (dBm): Input power to substitution antenna.

Gs (dBi or dBd): Substitution antenna Gain.

Et = Rt + AF

Es = Rs + AF

AF (dB/m): Receive antenna factor

Rt: The highest received signal in spectrum analyzer for EUT.


Rs: The highest received signal in spectrum analyzer for substitution antenna.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 10 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Report No. : FG070917

3.2.4 Test Setup



TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 11 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



3.2.5 Test Result of ERP

	GSM850 (GSM) Radiated Power ERP					
		Hoi	rizontal Polariza	tion		
Frequency	Rt	Rs	Ps	Gs	ERP	ERP
(MHz)	(dBm)	(dBm)	(dBm)	(dBd)	(dBm)	(W)
824.20	-21.42	-48.12	0.00	-1.08	25.62	0.36
836.40	-22.19	-48.28	0.00	-0.93	25.16	0.33
848.80	-23.24	-48.35	0.00	-0.76	24.35	0.27
		Ve	ertical Polarizati	on		
Frequency	Rt	Rs	Ps	Gs	ERP	ERP
(MHz)	(dBm)	(dBm)	(dBm)	(dBd)	(dBm)	(W)
824.20	-28.53	-47.97	0.00	-1.08	18.36	0.07
836.40	-28.87	-48.01	0.00	-0.93	18.21	0.07
848.80	-28.71	-48.05	0.00	-0.76	18.58	0.07

3.2.6 Test Result of EIRP

	GSM1900 (GSM) Radiated Power EIRP					
		Hoi	rizontal Polariza	tion		
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.93	-51.88	0.00	1.96	27.91	0.62
1880.00	-25.65	-52.99	0.00	2.00	29.34	0.86
1909.80	-27.06	-54.28	0.00	1.98	29.20	0.83
		Ve	ertical Polarizati	on		
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.53	-52.13	0.00	1.96	26.56	0.45
1880.00	-27.07	-53.17	0.00	2.00	28.10	0.65
1909.80	-28.00	-54.13	0.00	1.98	28.11	0.65

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 12 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Report No.: FG070917

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup



SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 13 of 35 Report Issued Date: Sep. 13, 2010 Report Version : Rev. 01




Report No. : FG070917

3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 19.JUL.2010 10:50:17

26dB Bandwidth Plot on Channel 189



Date: 19.JUL.2010 10:48:59


TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 14 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Band: GSM 1900 Power Stage: High


Test Mode: GSM Link

99% Occupied Bandwidth Plot on Channel 661



Date: 19.JUL.2010 11:00:53

26dB Bandwidth Plot on Channel 661



Date: 19.JUL.2010 10:59:36

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 15 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Report No.: FG070917

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.4.4 Test Setup



SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 16 of 35 Report Issued Date: Sep. 13, 2010 Report Version : Rev. 01




Report No. : FG070917

3.4.5 Test Result (Plots) of Conducted Band Edge


Band:	GSM850	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 128



Date: 19.JUL.2010 10:52:07

Higher Band Edge Plot on Channel 251




Date: 19.JUL.2010 10:52:34

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 17 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512



Date: 19.JUL.2010 11:02:44

Higher Band Edge Plot on Channel 810



Date: 19.JUL.2010 11:03:10

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 18 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- 2. The middle channel for the highest RF power within the transmitting frequency was measured.
- 3. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup



TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 19 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01




Report No. : FG070917

3.5.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel:	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 19.JUL.2010 11:44:23

Conducted Emission Plot between 1GHz ~ 3GHz




Date: 19.JUL.2010 11:45:38

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 20 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01




Report No. : FG070917

Conducted Emission Plot between 3GHz ~ 7GHz



Date: 19.JUL.2010 11:46:57

Conducted Emission Plot between 7GHz ~ 9GHz



Date: 19.JUL.2010 11:48:16


TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 21 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Band: GSM1900 Channel: CH661


Test Mode: GSM Link

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 19.JUL.2010 11:37:15

Conducted Emission Plot between 1GHz ~ 3GHz




Date: 19.JUL.2010 11:38:20

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 22 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01




Report No. : FG070917

Conducted Emission Plot between 3GHz ~ 7GHz



Date: 19.JUL.2010 11:33:06

Conducted Emission Plot between 7GHz ~ 13.6GHz




Date: 19.JUL.2010 11:33:19

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 23 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



Report No. : FG070917

Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 19.JUL.2010 11:33:32

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 24 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

Report No.: FG070917

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

- 1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.

Page Number

Report Version

: 25 of 35

: Rev. 01


Report Issued Date: Sep. 13, 2010

- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15



Report No.: FG070917


3.6.4 Test Setup




TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 26 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



3.6.5 Test Result of Field Strength of Spurious Radiated



Spurious emissions within 30-1000MHz were found more than 20dB below limit line. Remark:




Site : 03CH01-KS Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL


	4.5	50	1.50	HEAL STREET	W1442 147 247	91633			
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-55.80	-13	-42.80	-53.35	-56.45	0.57	3.37	Н	Pass
2510	-36.89	-13	-23.89	-41.40	-39.12	0.78	5.16	Н	Pass
3346	-59.20	-13	-46.20	-61.14	-62.84	0.87	6.66	Н	Pass
4182	-58.19	-13	-45.19	-60.93	-62.78	0.97	7.71	Н	Pass
5018	-58.37	-13	-45.37	-64.57	-64.04	1.09	8.91	Н	Pass
5854	-58.96	-13	-45.96	-66.61	-65.40	1.22	9.81	Н	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 27 of 35 Report Issued Date : Sep. 13, 2010 Report Version : Rev. 01



Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.




Site : 03CH01-KS

Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

	- 10	**							
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-51.72	-13	-38.72	-53.02	-52.37	0.57	3.37	V	Pass
2510	-35.70	-13	-22.70	-42.30	-37.93	0.78	5.16	V	Pass
3344	-59.82	-13	-46.82	-61.80	-63.46	0.87	6.66	V	Pass
4182	-57.83	-13	-44.83	-61.37	-62.42	0.97	7.71	V	Pass
5018	-60.26	-13	-47.26	-65.20	-65.93	1.09	8.91	V	Pass
5854	-58.04	-13	-45.04	-66.03	-64.48	1.22	9.81	V	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 28 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

Band :	GSM1900	Temperature :	21~23°C		
Test Mode :	GSM Link	Relative Humidity :	41~43%		
Test Engineer :	Feixiang Rui	Polarization :	Horizontal		
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line				



Site : 03CH01-KS


Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-48.41	-13	-35.41	-55.19	-54.79	0.78	7.16	Н	Pass
5640	-53.70	-13	-40.70	-58.07	-62.24	1.04	9.58	Н	Pass
7520	-58.43	-13	-45.43	-63.56	-68.54	1.35	11.46	Н	Pass
9400	-55.71	-13	-42.71	-58.99	-66.77	1.75	12.81	Н	Pass
11280	-53.59	-13	-40.59	-65.40	-64.68	2	13.09	Н	Pass
13160	-44.09	-13	-31.09	-58.91	-55.80	2.04	13.75	Н	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 29 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

Band :	GSM1900	Temperature :	21~23°C
Test Mode :	GSM Link	Relative Humidity :	41~43%
Test Engineer :	Feixiang Rui	Polarization :	Vertical

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Site : 03CH01-KS

Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

Frequency	EIRP	Limit	Over Limit	SPA Reading	S.G. Power	TX Cable loss	TX Antenna Gain	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-55.71	-13	-42.71	-57.08	-62.09	0.78	7.16	V	Pass
5640	-55.45	-13	-42.45	-58.67	-63.99	1.04	9.58	V	Pass
7520	-60.56	-13	-47.56	-65.05	-70.67	1.35	11.46	V	Pass
9400	-60.15	-13	-47.15	-61.17	-71.21	1.75	12.81	V	Pass
11280	-54.56	-13	-41.56	-65.8	-65.65	2	13.09	V	Pass
13152	-45.78	-13	-32.78	-57.49	-57.49	2.04	13.75	V	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 30 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

Report No.: FG070917

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedures for Temperature Variation

- 1. The EUT was set up in the thermal chamber and connected with the base station.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three
 hours. Power was applied and the maximum change in frequency was recorded within one
 minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
- 4. If the EUT can not be turned on at -30°C, the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

- The EUT was placed in a temperature chamber at 25±5° C and connected with the base station.
- 2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.

Page Number

Report Version

: 31 of 35


: Rev. 01

Report Issued Date: Sep. 13, 2010

3. The variation in frequency was measured for the worst case.



3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel:	189
Limit (ppm) :	2.5		

_	GSM					
Temperature (°C)	Freq. Dev. (Hz)	Deviation (ppm)	Result			
-30	N/A	N/A				
-20	N/A	N/A				
-10	11	0.01				
0	14	0.02				
10	13	0.02	PASS			
20	16	0.02				
30	20	0.02				
40	-25	-0.03				
50	-22	-0.03				

Note:

- 1. The EUT stops transmitting at temperatures -20°C and -30°C.
- 2. The manufacturer declared that the EUT could work properly between temperatures -15 $^{\circ}$ C $^{\circ}$ C.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 32 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01

Band :	GSM 1900	Channel:	661
Limit (ppm) :	2.5		

	GSM			
Temperature (°C)	Freq. Dev. (Hz)	Deviation (ppm)	Result	
-30	N/A	N/A		
-20	N/A	N/A		
-10	-35	-0.02		
0	-32	-0.02		
10	-31	-0.02	PASS	
20	-33	-0.02		
30	-37	-0.02		
40	-31	-0.02		
50	-42	-0.02		

Note:

- 1. The EUT stops transmitting at temperatures -20°C and -30°C.
- 2. The manufacturer declared that the EUT could work properly between temperatures -15°C~65°C.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.7	15	0.02	2.5	PASS
		BEP	17	0.02		
		4.2	19	0.02		
GSM 1900 CH661	GSM	3.7	-31	-0.02		
		BEP	-33	-0.02		
		4.2	-47	-0.02		

Note:

- 1. Normal Voltage = 3.7V.
- 2. Battery End Point (BEP) = 3.5 V.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 33 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 18, 2010	Jan. 17, 2011	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 28, 2009	Dec. 27, 2010	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100724	9kHz – 2.75GHz	Mar. 09, 2010	Mar. 08, 2011	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Feb. 02, 2010	Feb. 01, 2011	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Actice hore antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 18, 2009	Nov. 17, 2010	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 22, 2009	Oct. 21, 2010	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 08, 2009	Jan. 07, 2011	Radiation (03CH01-KS)

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A Page Number : 34 of 35
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01



5 **Uncertainty of Evaluation**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

	Uncerta			
Contribution	dB	Probability Distribution	u(X _i)	
Receiver Reading	0.41	0.41 Normal (k=2)		
Antenna Factor Calibration	0.83	Normal (k=2)	0.42	
Cable Loss Calibration	0.25	Normal (k=2)	0.13	
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14	
RCV/SPA Specification	2.50	Rectangular	0.72	
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29	
Site Imperfection	1.43	Rectangular	0.83	
Mismatch	+0.39 / -0.41	U-Shape	0.28	
Combined Standard Uncertainty Uc(y)	1.27			
Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.54			

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

	Uncertainty of X _i				
Contribution	dB	Probability Distribution	u(X _i)	C _i	C _i * u(X _i)
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR Γ 1 = 0.197 Antenna VSWR Γ 2 = 0.194 Uncertainty = 20Log(1- Γ 1* Γ 2)	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty Uc(y)	2.36				
Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.72				

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WFZGT100A

Page Number : 35 of 35 Report Issued Date: Sep. 13, 2010

Report No.: FG070917

Report Version : Rev. 01

Appendix A. Photographs of EUT

Please refer to Sporton report number EP070917 as below.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: WFZGT100A Page Number : A1 of A1
Report Issued Date : Sep. 13, 2010
Report Version : Rev. 01