Project: Game Call Remote (WRC-Remote) Date: Aug 9, 2012

QTY. Ref. Location Description / Value	
--	--

< A >	TV	D_{A}	~ "~
\A /		-00	41 C

<a> TX E	Board	
1 U		IC(SMD) RF Transmitter Module 433MHz
1 U		IC(SMD)TQFP-32 Microcontroller
1 U	J3	IC(SMD)SOIC-8 EEPROM memory 128Kbit
1 U		IC(SMD)SOT-223 LDO 3.3V
1 Y	′1	CRYSTAL(SMD) 8.000MHz 30PPM
1 D	02	DIODE(SMD)SOT-23 dual schottky diode common cathode
1 D	08	DIODE(SMD) SOD-123 Schottky Diode 0.5A 40V
3 C	02 Q3 Q6	TRAN(SMD)SOT-23 NPN transistor
1 G	21	TRAN(SMD)SOT-23 PNP transistor
1 L	1	FERRITE(SMD)0603 Ferrite bead 0.4A <60R at 100MHz>
1 L	2	RES(SMD)0R 0805 1/8W +/-5%
6 R	R1 R2 R5 R81 R101 R113	RES(SMD)0R 0603 1/10W +/-5%
1 R	R12	RES(SMD)22R 0603 1/10W +/-5%
1 R	R71	RES(SMD)33R 0603 1/10W +/-5%
3 R	R50 R53 R77	RES(SMD)470R 0603 1/10W +/-5%
2 R	R104 R107	RES(SMD)1K 0603 1/10W +/-5%
4 R	R24 R10 R25 R33	RES(SMD)4.7K 0603 1/10W +/-5%
4 R	R54 R58 R80 R102	RES(SMD)10K 0603 1/10W +/-5%
2 R	R34 R40	RES(SMD)10K 0603 1/10W +/-1%
10 R	R7 R8 R9 R49 R55 R56 R64 R65	RES(SMD)47K 0603 1/10W +/-5%
K	(66 R69	RE3(3NID)47R 0003 1/10VV +7-3/0
2 R	R46 R68	RES(SMD)100K 0603 1/10W +/-5%
1 R	R52	RES(SMD)470K 0603 1/10W +/-5%
1 R	R16	RES(SMD)2.2M 0603 1/10W +/-5%
1 R		RES(SMD)4.7M 0603 1/10W +/-5%
1 R		RES(SMD)10M 0603 1/10W +/-5%
1 1 1	3 C4 C5 C6 C7 C11 C13 C14 C22 23 C27 C104	CAP(SMD)0603 0.1uF Y5V 50V +/-20%
3 C	C20 C24 C33	CAP(SMD)0805 10uF Y5V 10V +80-20%
1 C		CAP(SMD)0603 1uF Y5V 16V +80-20%
5 C	C105 C106 C107 C108 C109	CAP(SMD)0805 1uF Y5V 16V +80-20%
	C112 C113 C116	CAP(SMD)0805 2.2uF X5R 16V +/-10%
5 C	C1 C2 C15 C16 C115	CAP(SMD)0603 22pF NPO 50V +/-5%
	8 C17	E-Cap(SMD)22uF Electrolytic Cap 16V +/-20%
1 J:	3	JACK(LEADED) 3.5mm STEREO JACK
1 J	11	CONNECTOR(LEADED) 2.0mm PIN HEADER SINGLE ROW
113	11	STRAIGHT H=2.0mm
1 J	12	LCD MODULE TRANSFLECTIVE + Green Backlight
1 J		WIRE RED/BLACK UL1007 AWG26
1 A	NT1	ANTENNA 433Mhz screw mounting
1		PCB 2LAYER FR4 IMMERSION GOLD (Remote Gen2 V1.0)

 Key Board

2 R47 R48	RES(SMD)2.2K 0603 1/10W +/-1%
2 R39 R45	RES(SMD)5.6K 0603 1/10W +/-1%
2 R38 R44	RES(SMD)10K 0603 1/10W +/-1%
2 R37 R43	RES(SMD)27K 0603 1/10W +/-1%
2 R35 R41	RES(SMD)68K 0603 1/10W +/-1%
2 C12 C13	CAP(SMD)0603 22pF NPO 50V +/-5%
1 J1	CONNECTOR(SMD)2.0mm FEMALE HEADER SINGLE
	ROW H=4.3mm
1	Remote Keyboard membrane with dome switch
1	PCB 2LAYER FR4 IMMERSION GOLD REV3.0