

FCC RF Test Report


APPLICANT : Shanghai Longcheer Technology Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Longcheer
MODEL NAME : LCT_L6352_A01
FCC ID : WH7-LCT-L6352
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 23, 2015 and testing was completed on Jun. 17, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency Channel	7
2.2 Pre-Scanned RF Power.....	8
2.3 Test Mode.....	9
2.4 Connection Diagram of Test System.....	10
2.5 Support Unit used in test configuration and system	11
2.6 EUT Operation Test Setup	11
2.7 Measurement Results Explanation Example.....	11
3 TEST RESULT.....	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement.....	14
3.3 Power Spectral Density Measurement	15
3.4 Conducted Band Edges and Spurious Emission Measurement	17
3.5 Radiated Band Edges and Spurious Emission Measurement	30
3.6 AC Conducted Emission Measurement.....	34
3.7 Antenna Requirements.....	38
4 LIST OF MEASURING EQUIPMENT	39
5 UNCERTAINTY OF EVALUATION	40
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR542307C	Rev. 01	Initial issue of report	Jul. 09, 2015



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.03 dB at 2483.600 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.27 dB at 0.530 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Shanghai Longcheer Technology Co., Ltd.

Building 1, No.401, Caobao Rd, Xuhui District, Shanghai, P.R.China

1.2 Manufacturer

Shanghai Longcheer Technology Co., Ltd.

Building 1, No.401, Caobao Rd, Xuhui District, Shanghai, P.R.China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Longcheer
Model Name	LCT_L6352_A01
FCC ID	WH7-LCT-L6352
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(Downlink Only)/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 865843022288788 Radiation: 865843022283698 Conduction: 865843022283425
HW Version	LLDM052
SW Version	LLD0003
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 17.78 dBm (0.0600 W) 802.11g : 21.52 dBm (0.1419 W) 802.11n HT20 : 19.97 dBm (0.0993 W) 802.11n HT40 : 19.93 dBm (0.0984 W)
Antenna Type	PIFA Antenna with gain -1.0 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	CO01-KS	03CH02-KS	418269

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X/Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b mode				
Data Rate (MHz)	1M bps	2M bps	5.5M bps	11M bps
Peak Power (dBm)	17.78	17.55	17.68	17.72

2.4GHz 802.11g mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Peak Power (dBm)	21.52	21.35	21.32	21.24	21.31	21.41	21.36	21.46

2.4GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	19.97	19.76	19.88	19.74	19.56	19.57	19.92	19.32

2.4GHz 802.11n HT40 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Peak Power (dBm)	19.93	19.92	19.45	19.51	19.77	19.56	19.62	19.53

2.3 Test Mode


Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone
Remark: For radiated test cases, the tests were performed with adapter, earphone and USB cable.	

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
4.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.6 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 6 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A of this test report.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	jacky huang


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 12.JUN.2015 01:20:32

Low Channel Plot




Date: 12.JUN.2015 01:25:26

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 01:26:53

Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 01:27:11



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	jacky huang


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 12.JUN.2015 01:30:05

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 01:30:41

Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 01:30:59



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	jacky huang


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 12.JUN.2015 01:34:08

High Channel Plot




Date: 12.JUN.2015 01:34:26

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 01:34:52

Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 01:35:10



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	jacky huang


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 12.JUN.2015 01:39:10

Low Channel Plot




Date: 12.JUN.2015 01:39:31

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 01:40:55


Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 01:41:13




Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	jacky huang

WLAN 802.11g Channel 06**100kHz PSD reference Level**

Date: 12.JUN.2015 01:44:27

Spurious Emission 30MHz~3GHz

Date: 12.JUN.2015 01:44:55

Spurious Emission 2GHz~25GHz


Date: 12.JUN.2015 01:45:13



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	jacky huang


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 12.JUN.2015 01:49:28

High Channel Plot




Date: 12.JUN.2015 01:49:50

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 01:50:18

Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 01:50:36



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	jacky huang


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 12.JUN.2015 01:57:46

Low Channel Plot




Date: 12.JUN.2015 01:58:32

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 01:58:55


Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 01:59:13




Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	jacky huang

WLAN 802.11n HT20 Channel 06**100kHz PSD reference Level**

Date: 12.JUN.2015 02:02:43

Spurious Emission 30MHz~3GHz


Date: 12.JUN.2015 02:03:41

Spurious Emission 2GHz~25GHz


Date: 12.JUN.2015 02:03:59




Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	jacky huang

WLAN 802.11n HT20 Channel 11**100kHz PSD reference Level**


Date: 12.JUN.2015 02:11:46

High Channel Plot

Date: 12.JUN.2015 02:12:14

Spurious Emission 30MHz~3GHz

Date: 12.JUN.2015 02:12:48

Spurious Emission 2GHz~25GHz


Date: 12.JUN.2015 02:13:05



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	03	Test Engineer :	jacky huang


WLAN 802.11n HT40 Channel 03

100kHz PSD reference Level




Date: 12.JUN.2015 02:23:21

Low Channel Plot




Date: 12.JUN.2015 02:24:08

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 02:29:43


Spurious Emission 2GHz~25GHz




Date: 12.JUN.2015 02:27:02




Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	jacky huang

WLAN 802.11n HT40 Channel 06**100kHz PSD reference Level**

Date: 12.JUN.2015 02:34:35

Spurious Emission 30MHz~3GHz

Date: 12.JUN.2015 02:41:13

Spurious Emission 2GHz~25GHz


Date: 12.JUN.2015 02:38:34



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	09	Test Engineer :	jacky huang


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 12.JUN.2015 02:46:15

High Channel Plot




Date: 12.JUN.2015 02:46:36

Spurious Emission 30MHz~3GHz



Date: 12.JUN.2015 02:47:09

Spurious Emission 2GHz~25GHz



Date: 12.JUN.2015 02:47:27

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	97.63	8.24	0.12	300Hz
802.11g	87.31	1.36	0.73	1kHz
2.4GHz 802.11n HT20	86.41	1.27	0.79	1kHz
2.4GHz 802.11n HT40	76.08	0.64	1.57	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eko Guan	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

mode	: Mode 1							
	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.16	45.99	-19.53	65.52	33.80	1.80	10.39	QP
2	0.16	37.39	-18.13	55.52	25.20	1.80	10.39	Average
3	0.46	38.06	-18.57	56.63	27.21	0.23	10.62	QP
4	0.46	25.16	-21.47	46.63	14.31	0.23	10.62	Average
5	0.53	39.93	-16.07	56.00	29.10	0.20	10.63	QP
6 *	0.53	32.73	-13.27	46.00	21.90	0.20	10.63	Average
7	0.63	40.93	-15.07	56.00	30.10	0.20	10.63	QP
8	0.63	31.63	-14.37	46.00	20.80	0.20	10.63	Average
9	0.78	37.42	-18.58	56.00	26.60	0.18	10.64	QP
10	0.78	24.02	-21.98	46.00	13.20	0.18	10.64	Average
11	3.84	36.91	-19.09	56.00	25.90	0.18	10.83	QP
12	3.84	26.61	-19.39	46.00	15.60	0.18	10.83	Average



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eko Guan	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		



Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

mode		: Mode 1						
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.37	38.98	-19.63	58.61	27.90	0.47	10.61	QP
2	0.37	31.98	-16.63	48.61	20.90	0.47	10.61	Average
3	0.48	40.14	-16.27	56.41	29.20	0.32	10.62	QP
4 *	0.48	33.04	-13.37	46.41	22.10	0.32	10.62	Average
5	0.53	39.81	-16.19	56.00	28.89	0.29	10.63	QP
6	0.53	32.21	-13.79	46.00	21.29	0.29	10.63	Average
7	0.74	37.33	-18.67	56.00	26.50	0.19	10.64	QP
8	0.74	28.63	-17.37	46.00	17.80	0.19	10.64	Average
9	0.94	36.06	-19.94	56.00	25.30	0.11	10.65	QP
10	0.94	26.56	-19.44	46.00	15.80	0.11	10.65	Average
11	3.72	33.70	-22.30	56.00	22.70	0.18	10.82	QP
12	3.72	24.60	-21.40	46.00	13.60	0.18	10.82	Average

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 28, 2014	Jun. 12, 2015	Oct. 27, 2015	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Jan. 23, 2015	Jun. 12, 2015	Jan. 22, 2016	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 23, 2015	Jun. 12, 2015	Jan. 22, 2016	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max x 30dBm	Sep. 29, 2014	Jun. 17, 2015	Sep. 28, 2015	Radiation (03CH02-KS)
Spectrum Analyzer	R&S	FSV40	101040	10kHz~40GHz; Max 30dBm	Sep. 25, 2014	Jun. 17, 2015	Sep. 24, 2015	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Jun. 17, 2015	Nov. 12, 2015	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Sep. 13, 2014	Jun. 17, 2015	Sep. 12, 2015	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 08, 2014	Jun. 17, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Jun. 17, 2015	Nov. 07, 2015	Radiation (03CH02-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Sep. 04, 2014	Jun. 17, 2015	Sep. 03, 2015	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	May 04, 2015	Jun. 17, 2015	May 03, 2016	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A023 84	1GHz~26.5GHz Gain 30dB	Oct. 28, 2014	Jun. 17, 2015	Oct. 27, 2015	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Jun. 17, 2015	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jun. 17, 2015	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jun. 17, 2015	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2015	Jun. 09, 2015	May 03, 2016	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 25, 2014	Jun. 09, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 25, 2014	Jun. 09, 2015	Oct. 24, 2015	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 25, 2014	Jun. 09, 2015	Oct. 24, 2015	Conduction (CO01-KS)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------



Appendix A. Conducted Test Results

Test Engineer:	jacky huang	Temperature:	21~25	°C
Test Date:	2015/6/12	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	13.20	8.04	0.50	Pass
11b	1Mbps	1	6	2437	13.25	8.08	0.50	Pass
11b	1Mbps	1	11	2462	13.30	8.08	0.50	Pass
11g	6Mbps	1	1	2412	17.95	16.32	0.50	Pass
11g	6Mbps	1	6	2437	18.25	16.36	0.50	Pass
11g	6Mbps	1	11	2462	18.15	16.36	0.50	Pass
HT20	MCS0	1	1	2412	18.85	17.56	0.50	Pass
HT20	MCS0	1	6	2437	18.80	17.60	0.50	Pass
HT20	MCS0	1	11	2462	18.85	17.56	0.50	Pass
HT40	MCS0	1	3	2422	36.30	35.12	0.50	Pass
HT40	MCS0	1	6	2437	36.50	35.44	0.50	Pass
HT40	MCS0	1	9	2452	36.30	35.52	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	17.78	30.00	-1.00	16.78	36.00	Pass
11b	1Mbps	1	6	2437	16.72	30.00	-1.00	15.72	36.00	Pass
11b	1Mbps	1	11	2462	16.96	30.00	-1.00	15.96	36.00	Pass
11g	6Mbps	1	1	2412	21.52	30.00	-1.00	20.52	36.00	Pass
11g	6Mbps	1	6	2437	21.43	30.00	-1.00	20.43	36.00	Pass
11g	6Mbps	1	11	2462	20.88	30.00	-1.00	19.88	36.00	Pass
HT20	MCS0	1	1	2412	19.97	30.00	-1.00	18.97	36.00	Pass
HT20	MCS0	1	6	2437	19.73	30.00	-1.00	18.73	36.00	Pass
HT20	MCS0	1	11	2462	19.21	30.00	-1.00	18.21	36.00	Pass
HT40	MCS0	1	3	2422	19.07	30.00	-1.00	18.07	36.00	Pass
HT40	MCS0	1	6	2437	19.21	30.00	-1.00	18.21	36.00	Pass
HT40	MCS0	1	9	2452	19.93	30.00	-1.00	18.93	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.10	14.99
11b	1Mbps	1	6	2437	0.10	14.02
11b	1Mbps	1	11	2462	0.10	14.16
11g	6Mbps	1	1	2412	0.59	13.03
11g	6Mbps	1	6	2437	0.59	12.00
11g	6Mbps	1	11	2462	0.59	12.37
HT20	MCS0	1	1	2412	0.63	10.31
HT20	MCS0	1	6	2437	0.63	9.19
HT20	MCS0	1	11	2462	0.63	9.61
HT40	MCS0	1	3	2422	1.19	8.80
HT40	MCS0	1	6	2437	1.19	8.92
HT40	MCS0	1	9	2452	1.19	9.67

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-7.27	-1.00	8.00	Pass
11b	1Mbps	1	6	2437	-7.23	-1.00	8.00	Pass
11b	1Mbps	1	11	2462	-8.69	-1.00	8.00	Pass
11g	6Mbps	1	1	2412	-11.88	-1.00	8.00	Pass
11g	6Mbps	1	6	2437	-11.75	-1.00	8.00	Pass
11g	6Mbps	1	11	2462	-13.62	-1.00	8.00	Pass
HT20	MCS0	1	1	2412	-15.27	-1.00	8.00	Pass
HT20	MCS0	1	6	2437	-15.93	-1.00	8.00	Pass
HT20	MCS0	1	11	2462	-15.04	-1.00	8.00	Pass
HT40	MCS0	1	3	2422	-17.80	-1.00	8.00	Pass
HT40	MCS0	1	6	2437	-18.95	-1.00	8.00	Pass
HT40	MCS0	1	9	2452	-18.64	-1.00	8.00	Pass



Appendix B. Radiated Test Results

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2319.81	52.45	-21.55	74	47.61	31.23	6.06	32.45	156	154	P	H
		2331.96	37.78	-16.22	54	32.88	31.23	6.12	32.45	156	154	A	H
	*	2410.771	103.18	-	-	97.94	31.31	6.22	32.29	156	154	P	H
	*	2412.608	97.72	-	-	92.48	31.31	6.22	32.29	156	154	A	H
		2331.69	52.45	-21.55	74	47.55	31.23	6.12	32.45	158	92	P	V
		2327.55	37.67	-16.33	54	32.77	31.23	6.12	32.45	158	92	A	V
	*	2410.771	106.08	-	-	100.84	31.31	6.22	32.29	158	92	P	V
	*	2412.608	101.13	-	-	95.89	31.31	6.22	32.29	158	92	A	V
802.11b CH 06 2437MHz	*	2438.159	101.85	-	-	96.44	31.34	6.22	32.15	247	142	P	H
	*	2437.992	96.75	-	-	91.34	31.34	6.22	32.15	247	142	A	H
	*	2435.655	103.61	-	-	98.28	31.33	6.22	32.22	152	95	P	V
	*	2438.076	98.28	-	-	92.87	31.34	6.22	32.15	152	95	A	V
802.11b CH 11 2462MHz	*	2460.621	102.95	-	-	97.4	31.36	6.28	32.09	163	149	P	H
	*	2462.208	96.67	-	-	91.12	31.36	6.28	32.09	163	149	A	H
		2499.72	52.61	-21.39	74	46.84	31.39	6.33	31.95	163	149	P	H
		2484.6	37.97	-16.03	54	32.29	31.37	6.33	32.02	163	149	A	H
	*	2460.705	105.99	-	-	100.44	31.36	6.28	32.09	160	142	P	V
	*	2460.287	100.03	-	-	94.48	31.36	6.28	32.09	160	142	A	V
		2486.48	52.6	-21.4	74	46.92	31.37	6.33	32.02	160	142	P	V
		2483.84	38.7	-15.3	54	33.02	31.37	6.33	32.02	160	142	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	46.66	-27.34	74	37.77	34.89	8.73	34.73	153	67	P	H
		4824	47.28	-26.72	74	38.39	34.89	8.73	34.73	174	98	P	V
802.11b CH 06 2437MHz		4875	45.65	-28.35	74	36.6	34.92	8.76	34.63	169	84	P	H
		7311	46.24	-27.76	74	35.89	35.56	10.84	36.05	167	226	P	H
		4875	46.11	-27.89	74	37.06	34.92	8.76	34.63	153	24	P	V
		7311	46.09	-27.91	74	35.74	35.56	10.84	36.05	167	223	P	V
802.11b CH 11 2462MHz		4923	45.44	-28.56	74	36.22	34.95	8.79	34.52	169	201	P	H
		7386	46.76	-27.24	74	36.68	35.58	10.89	36.39	187	226	P	H
		4923	47.18	-26.82	74	37.96	34.95	8.79	34.52	163	261	P	V
		7386	47.04	-26.96	74	36.96	35.58	10.89	36.39	159	305	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.83	55.9	-18.1	74	50.79	31.3	6.17	32.36	192	95	P	H
		2390	39.24	-14.76	54	34.13	31.3	6.17	32.36	192	95	A	H
	*	2414.78	105.89	-	-	100.65	31.31	6.22	32.29	192	95	P	H
	*	2414.112	94.02	-	-	88.78	31.31	6.22	32.29	192	95	A	H
		2361.39	52.34	-21.66	74	47.32	31.26	6.17	32.41	158	142	P	V
		2346.72	38.14	-15.86	54	33.2	31.25	6.12	32.43	158	142	A	V
	*	2416.032	93.57	-	-	88.33	31.31	6.22	32.29	158	142	P	V
	*	2415.364	80.95	-	-	75.71	31.31	6.22	32.29	158	142	A	V
802.11g CH 06 2437MHz	*	2440.08	104.69	-	-	99.22	31.34	6.28	32.15	211	151	P	H
	*	2441.583	93.13	-	-	87.66	31.34	6.28	32.15	211	151	A	H
	*	2443.253	96.01	-	-	90.54	31.34	6.28	32.15	229	355	P	V
	*	2442.167	84.59	-	-	79.12	31.34	6.28	32.15	229	355	A	V
802.11g CH 11 2462MHz	*	2456.446	105.79	-	-	100.24	31.36	6.28	32.09	151	78	P	H
	*	2458.199	93.49	-	-	87.94	31.36	6.28	32.09	151	78	A	H
	!	2483.6	68.97	-5.03	74	63.29	31.37	6.33	32.02	151	78	P	H
		2483.6	44.45	-9.55	54	38.77	31.37	6.33	32.02	151	78	A	H
	*	2467.051	100.12	-	-	94.57	31.36	6.28	32.09	211	122	P	V
	*	2458.45	88.43	-	-	82.88	31.36	6.28	32.09	211	122	A	V
		2483.72	67.81	-6.19	74	62.13	31.37	6.33	32.02	211	122	P	V
		2483.52	43.67	-10.33	54	37.99	31.37	6.33	32.02	211	122	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preampl	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	47.24	-26.76	74	38.35	34.89	8.73	34.73	150	311	P	H
		4824	46.31	-27.69	74	37.42	34.89	8.73	34.73	150	215	P	V
802.11g CH 06 2437MHz		4875	47.1	-26.9	74	38.05	34.92	8.76	34.63	150	124	P	H
		7311	45.64	-28.36	74	35.29	35.56	10.84	36.05	150	236	P	H
		4875	47.52	-26.48	74	38.47	34.92	8.76	34.63	150	246	P	V
		7311	46.01	-27.99	74	35.66	35.56	10.84	36.05	150	164	P	V
802.11g CH 11 2462MHz		4923	46.71	-27.29	74	37.49	34.95	8.79	34.52	150	124	P	H
		7386	45.89	-28.11	74	35.81	35.58	10.89	36.39	150	134	P	H
		4923	47.24	-26.76	74	38.02	34.95	8.79	34.52	150	0	P	V
		7386	46.35	-27.65	74	36.27	35.58	10.89	36.39	150	345	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2363.1	52.24	-21.76	74	47.22	31.26	6.17	32.41	157	153	P	H
		2366.7	38.15	-15.85	54	33.13	31.26	6.17	32.41	157	153	A	H
	*	2407.348	100.33	-	-	95.09	31.31	6.22	32.29	157	153	P	H
	*	2408.768	88.21	-	-	82.97	31.31	6.22	32.29	157	153	A	H
		2311.98	53.35	-20.65	74	48.55	31.21	6.06	32.47	249	116	P	V
		2389.83	38.14	-15.86	54	33.03	31.3	6.17	32.36	249	116	A	V
	*	2417.201	101.55	-	-	96.31	31.31	6.22	32.29	249	116	P	V
	*	2418.37	90.05	-	-	84.81	31.31	6.22	32.29	249	116	A	V
802.11n HT20 CH 06 2437MHz	*	2430.979	97.16	-	-	91.83	31.33	6.22	32.22	150	144	P	H
	*	2432.815	85.55	-	-	80.22	31.33	6.22	32.22	150	144	A	H
	*	2432.648	101.82	-	-	96.49	31.33	6.22	32.22	150	106	P	V
	*	2442.251	89.48	-	-	84.01	31.34	6.28	32.15	150	106	A	V
802.11n HT20 CH 11 2462MHz	*	2465.213	101.4	-	-	95.85	31.36	6.28	32.09	150	164	P	H
	*	2466.216	89	-	-	83.45	31.36	6.28	32.09	150	164	A	H
		2483.64	63.69	-10.31	74	58.01	31.37	6.33	32.02	150	164	P	H
		2483.6	40.3	-13.7	54	34.62	31.37	6.33	32.02	150	164	A	H
	*	2455.528	102.95	-	-	97.4	31.36	6.28	32.09	181	138	P	V
	*	2457.949	91.51	-	-	85.96	31.36	6.28	32.09	181	138	A	V
		2484.72	62.58	-11.42	74	56.9	31.37	6.33	32.02	181	138	P	V
		2483.52	41.14	-12.86	54	35.46	31.37	6.33	32.02	181	138	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	45.18	-28.82	74	36.29	34.89	8.73	34.73	150	134	P	H
		4824	47.27	-26.73	74	38.38	34.89	8.73	34.73	150	245	P	V
802.11n HT20 CH 06 2437MHz		4875	46.44	-27.56	74	37.39	34.92	8.76	34.63	150	345	P	H
		7311	46.49	-27.51	74	36.14	35.56	10.84	36.05	150	0	P	H
		4875	46.05	-27.95	74	37	34.92	8.76	34.63	150	240	P	V
		7311	46.49	-27.51	74	36.14	35.56	10.84	36.05	150	120	P	V
802.11n HT20 CH 11 2462MHz		4923	45.82	-28.18	74	36.6	34.95	8.79	34.52	150	16	P	H
		7386	46.39	-27.61	74	36.31	35.58	10.89	36.39	150	0	P	H
		4923	47.53	-26.47	74	38.31	34.95	8.79	34.52	150	187	P	V
		7386	45.46	-28.54	74	35.38	35.58	10.89	36.39	150	125	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2310.99	52.94	-21.06	74	48.14	31.21	6.06	32.47	188	72	P	H
		2389.92	39.63	-14.37	54	34.52	31.3	6.17	32.36	188	72	A	H
	*	2407.849	99.26	-	-	94.02	31.31	6.22	32.29	188	72	P	H
	*	2409.853	88.26	-	-	83.02	31.31	6.22	32.29	188	72	A	H
		2492.76	53.28	-20.72	74	47.51	31.39	6.33	31.95	188	72	P	H
		2484.6	39.7	-14.3	54	34.02	31.37	6.33	32.02	188	72	A	H
		2331.15	53	-21	74	48.1	31.23	6.12	32.45	150	192	P	V
		2328.18	39.27	-14.73	54	34.37	31.23	6.12	32.45	150	192	A	V
	*	2412.107	93.13	-	-	87.89	31.31	6.22	32.29	150	192	P	V
	*	2411.105	81.99	-	-	76.75	31.31	6.22	32.29	150	192	A	V
		2489.36	52.72	-21.28	74	46.95	31.39	6.33	31.95	150	192	P	V
		2487.2	39.26	-14.74	54	33.58	31.37	6.33	32.02	150	192	A	V
802.11n HT40 CH 06 2437MHz		2377.32	52.52	-21.48	74	47.45	31.28	6.17	32.38	160	274	P	H
		2334.03	38.99	-15.01	54	34.09	31.23	6.12	32.45	160	274	A	H
	*	2445.925	99.82	-	-	94.35	31.34	6.28	32.15	160	274	P	H
	*	2448.513	88.06	-	-	82.59	31.34	6.28	32.15	160	274	A	H
		2484.52	52.94	-21.06	74	47.26	31.37	6.33	32.02	160	274	P	H
		2483.56	39.59	-14.41	54	33.91	31.37	6.33	32.02	160	274	A	H
		2389.11	52.39	-21.61	74	47.28	31.3	6.17	32.36	181	121	P	V
		2368.32	38.85	-15.15	54	33.83	31.26	6.17	32.41	181	121	A	V
	*	2425.301	94.18	-	-	88.85	31.33	6.22	32.22	181	121	P	V
	*	2424.466	82.19	-	-	76.86	31.33	6.22	32.22	181	121	A	V
		2485.76	53.37	-20.63	74	47.69	31.37	6.33	32.02	181	121	P	V
		2485.52	39.32	-14.68	54	33.64	31.37	6.33	32.02	181	121	A	V



802.11n HT40 CH 09 2452MHz		2362.56	52.92	-21.08	74	47.9	31.26	6.17	32.41	165	269	P	H
		2330.07	38.87	-15.13	54	33.97	31.23	6.12	32.45	165	269	A	H
	*	2444.589	98.97	-	-	93.5	31.34	6.28	32.15	165	269	P	H
	*	2449.265	87.92	-	-	82.45	31.34	6.28	32.15	165	269	A	H
		2485.08	62.08	-11.92	74	56.4	31.37	6.33	32.02	165	269	P	H
		2484.08	42.23	-11.77	54	36.55	31.37	6.33	32.02	165	269	A	H
		2385.78	52.33	-21.67	74	47.22	31.3	6.17	32.36	297	187	P	V
		2379.3	39.02	-14.98	54	33.95	31.28	6.17	32.38	297	187	A	V
	*	2454.776	93.88	-	-	88.33	31.36	6.28	32.09	297	187	P	V
	*	2450.017	82.77	-	-	77.3	31.34	6.28	32.15	297	187	A	V
		2483.72	56.57	-17.43	74	50.89	31.37	6.33	32.02	297	187	P	V
		2483.56	39.55	-14.45	54	33.87	31.37	6.33	32.02	297	187	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4845	46.57	-27.43	74	37.64	34.9	8.73	34.7	165	201	P	H
HT40		7266	46.72	-27.28	74	36.27	35.56	10.81	35.92	160	64	P	H
CH 03		4845	45.98	-28.02	74	37.05	34.9	8.73	34.7	210	198	P	V
2422MHz		7266	46.66	-27.34	74	36.21	35.56	10.81	35.92	175	100	P	V
802.11n		4875	46.45	-27.55	74	37.4	34.92	8.76	34.63	156	95	P	H
HT40		7311	47.52	-26.48	74	37.17	35.56	10.84	36.05	196	146	P	H
CH 06		4875	46.13	-27.87	74	37.08	34.92	8.76	34.63	170	30	P	V
2437MHz		7311	47.23	-26.77	74	36.88	35.56	10.84	36.05	230	165	P	V
802.11n		4905	46.43	-27.57	74	37.26	34.94	8.79	34.56	188	0	P	H
HT40		7356	46.6	-27.4	74	36.43	35.57	10.86	36.26	210	120	P	H
CH 09		4905	47.44	-26.56	74	38.27	34.94	8.79	34.56	169	260	P	V
2452MHz		7356	46.29	-27.71	74	36.12	35.57	10.86	36.26	195	246	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		31.94	24.7	-15.3	40	38.34	18.22	0.79	32.65	-	-	P	H
		81.41	29.84	-10.16	40	52.23	9.21	1.04	32.64	124	20	P	H
		149.31	27.67	-15.83	43.5	47.1	11.69	1.44	32.56	-	-	P	H
		162.89	25.05	-18.45	43.5	44.93	11.22	1.44	32.54	-	-	P	H
		207.51	27.58	-15.92	43.5	48.3	10.15	1.61	32.48	-	-	P	H
		249.22	21.18	-24.82	46	39.83	12.06	1.75	32.46	-	-	P	H
		30	33.62	-6.38	40	46.29	19.2	0.79	32.66	106	42	P	V
		67.83	31.09	-8.91	40	55.15	7.78	0.79	32.63	-	-	P	V
		80.44	33.35	-6.65	40	55.86	9.1	1.04	32.65	-	-	P	V
		163.86	25.65	-17.85	43.5	45.57	11.18	1.44	32.54	-	-	P	V
		179.38	26.39	-17.11	43.5	46.84	10.58	1.44	32.47	-	-	P	V
		205.57	34.43	-9.07	43.5	55.23	10.07	1.61	32.48	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**15C Emission below 1GHz****2.4GHz WIFI 802.11g (LF)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		31.94	23.82	-16.18	40	37.46	18.22	0.79	32.65	-	-	P	H
		42.61	16.6	-23.4	40	35.68	12.77	0.79	32.64	-	-	P	H
		78.5	24.84	-15.16	40	47.51	8.94	1.04	32.65	102	65	P	H
		148.34	21.83	-21.67	43.5	41.27	11.68	1.44	32.56	-	-	P	H
		160.95	20.72	-22.78	43.5	40.54	11.29	1.44	32.55	-	-	P	H
		203.63	26.06	-17.44	43.5	46.95	9.98	1.61	32.48	-	-	P	H
		30	32.36	-7.64	40	45.03	19.2	0.79	32.66	100	0	P	V
		41.64	24.23	-15.77	40	42.78	13.28	0.79	32.62	-	-	P	V
		67.83	29.69	-10.31	40	53.75	7.78	0.79	32.63	-	-	P	V
		81.41	32.33	-7.67	40	54.72	9.21	1.04	32.64	-	-	P	V
		152.22	25.37	-18.13	43.5	44.86	11.63	1.44	32.56	-	-	P	V
		204.6	35.08	-8.42	43.5	55.93	10.02	1.61	32.48	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		30	22.23	-17.77	40	34.89	19.2	0.79	32.65	-	-	P	H
		66.86	21.98	-18.02	40	46.16	7.57	0.79	32.54	-	-	P	H
		80.44	27.32	-12.68	40	49.67	9.1	1.04	32.49	125	200	P	H
		143.49	26.87	-16.63	43.5	46.51	11.65	1.23	32.52	-	-	P	H
		162.89	24.66	-18.84	43.5	44.53	11.22	1.44	32.53	-	-	P	H
		207.51	27.19	-16.31	43.5	47.99	10.15	1.61	32.56	-	-	P	H
	!	30	34.06	-5.94	40	46.72	19.2	0.79	32.65	100	65	P	V
		57.16	26.6	-13.4	40	51.5	6.88	0.79	32.57	-	-	P	V
		67.83	30.83	-9.17	40	54.79	7.78	0.79	32.53	-	-	P	V
		80.44	32.31	-7.69	40	54.66	9.1	1.04	32.49	-	-	P	V
		143.49	26.55	-16.95	43.5	46.19	11.65	1.23	32.52	-	-	P	V
		204.6	35.04	-8.46	43.5	55.97	10.02	1.61	32.56	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		30	24.29	-15.71	40	36.96	19.2	0.79	32.66	-	-	P	H
		41.64	16.51	-23.49	40	35.06	13.28	0.79	32.62	-	-	P	H
		74.62	24.78	-15.22	40	47.78	8.61	1.04	32.65	187	200	P	H
		149.31	27.83	-15.67	43.5	47.26	11.69	1.44	32.56	-	-	P	H
		162.89	24.31	-19.19	43.5	44.19	11.22	1.44	32.54	-	-	P	H
		203.63	26.94	-16.56	43.5	47.83	9.98	1.61	32.48	-	-	P	H
	!	30	34.44	-5.56	40	47.11	19.2	0.79	32.66	100	201	P	V
		57.16	26.65	-13.35	40	51.58	6.88	0.79	32.6	-	-	P	V
		65.89	29.88	-10.12	40	54.33	7.36	0.79	32.6	-	-	P	V
		80.44	32.61	-7.39	40	55.12	9.1	1.04	32.65	-	-	P	V
		178.41	24.88	-18.62	43.5	45.29	10.62	1.44	32.47	-	-	P	V
		204.6	35.06	-8.44	43.5	55.91	10.02	1.61	32.48	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.