

# SAR TEST REPORT

No. 2008SAR00044

For

Longcheer Technology (Shanghai) Co., Ltd..

GSM/GPRS Digital Mobile phone

X591E

With

Hardware Version: LK1M512G1-1

Software Version: LK1EF02.1.0\_M512G

FCCID: WH7X591E

Issued Date: 2008-08-05



No. DAT-P-114/01-01

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

TMC Beijing, Telecommunication Metrology Center of Ministry of Information Industry




No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100083.

Tel:+86(0)10-62303288-2105, Fax:+86(0)10-62304793 Email:welcome@emcite.com. [www.emcite.com](http://www.emcite.com)

## TABLE OF CONTENT

<b>1 TEST LABORATORY</b>	<b>4</b>
1.1 TESTING LOCATION	4
1.2 TESTING ENVIRONMENT	4
1.3 PROJECT DATA	4
<b>2 CLIENT INFORMATION</b>	<b>4</b>
2.1 APPLICANT INFORMATION	4
2.2 MANUFACTURER INFORMATION	4
<b>3 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)</b>	<b>5</b>
3.1 ABOUT EUT	5
3.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	5
<b>4 OPERATIONAL CONDITIONS DURING TEST</b>	<b>6</b>
4.1 SCHEMATIC TEST CONFIGURATION	6
4.2 SAR MEASUREMENT SET-UP	6
4.3 DASY4 E-FIELD PROBE SYSTEM	7
4.4 E-FIELD PROBE CALIBRATION	8
4.5 OTHER TEST EQUIPMENT	9
4.5.1 DEVICE HOLDER FOR TRANSMITTERS	9
4.5.2 PHANTOM	9
4.6 EQUIVALENT TISSUES	9
4.7 SYSTEM SPECIFICATIONS	10
4.7.1 ROBOTIC SYSTEM SPECIFICATIONS	10
<b>5 CHARACTERISTICS OF THE TEST</b>	<b>10</b>
5.1 APPLICABLE LIMIT REGULATIONS	10
5.2 APPLICABLE MEASUREMENT STANDARDS	11
<b>6 LABORATORY ENVIRONMENT</b>	<b>11</b>
<b>7 CONDUCTED OUTPUT POWER MEASUREMENT</b>	<b>11</b>
7.1 SUMMARY	11
7.2 CONDUCTED POWER	12
<b>8 TEST RESULTS</b>	<b>12</b>
8.1 DIELECTRIC PERFORMANCE	12
8.2 SYSTEM VALIDATION	13
8.3 SUMMARY OF MEASUREMENT RESULTS (850MHz)	13
8.4 SUMMARY OF MEASUREMENT RESULTS (1900MHz)	14
8.5 CONCLUSION	15
<b>9 MEASUREMENT UNCERTAINTY</b>	<b>15</b>
<b>10 MAIN TEST INSTRUMENTS</b>	<b>16</b>
<b>ANNEX A: MEASUREMENT PROCESS</b>	<b>17</b>
<b>ANNEX B TEST LAYOUT</b>	<b>18</b>
<b>ANNEX C: GRAPH RESULTS</b>	<b>24</b>
<b>ANNEX D SYSTEM VALIDATION RESULTS</b>	<b>100</b>
<b>ANNEX E PROBE CALIBRATION CERTIFICATE</b>	<b>102</b>
<b>ANNEX F DIPOLE CALIBRATION CERTIFICATE</b>	<b>111</b>

## SAR test report

Test report No.	2008SAR00044	Date of report	August 05 <sup>th</sup> , 2008
Test laboratory	TMC Beijing, Telecommunication Metrology Center of MII	Client	Longcheer Technology (Shanghai) Co., Ltd..
Test device	Product name: GSM/GPRS Digital Mobile phone Model type: X591E Series number: 135790246811220		
Test reference documents	<p><b>EN 50360-2006:</b> Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.</p> <p><b>EN 62209-1-2006:</b> Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures -- Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)</p> <p><b>ANSI C95.1-1999:</b> IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.</p> <p><b>IEEE 1528-2003:</b> Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.</p> <p><b>OET Bulletin 65 (Edition 97-01) and Supplement C (Edition 01-01):</b> Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.</p> <p><b>IEC 62209-1:</b> Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1:Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)</p> <p><b>IEC 62209-2 (Draft):</b> Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the Specific Absorption Rate (SAR)in the head and body for 30MHz to 6GHz Handheld and Body-Mounted Devices used in close proximity to the Body.</p>		
Test conclusion	<p>Localized Specific Absorption Rate (SAR) of this portable wireless equipment has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this test report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.</p> <p>General Judgment: <b>Pass</b></p>		
Signature	<div>             Lu Bingsong  <b>Deputy Director of the laboratory</b>            (Approved for this report)         </div> <div>             Sun Qian  <b>SAR Project Leader</b>            (Reviewed for this report)         </div> <div>             Lin Hao  <b>SAR Test Engineer</b>            (Prepared for this report )         </div>		

## 1 Test Laboratory

### 1.1 Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MII  
Address: No 52, Huayuan beilu, Haidian District, Beijing,P.R.China  
Postal Code: 100083  
Telephone: +86-10-62303288  
Fax: +86-10-62304793

### 1.2 Testing Environment

Temperature: Min. = 15 °C, Max. = 30 °C  
Relative humidity: Min. = 30%, Max. = 70%  
Ground system resistance: < 0.5  $\Omega$

Ambient noise is checked and found very low and in compliance with requirement of standards.  
Reflection of surrounding objects is minimized and in compliance with requirement of standards.

### 1.3 Project Data

Project Leader: Sun Qian  
Test Engineer: Lin Hao  
Testing Start Date: August 3, 2008  
Testing End Date: August 4, 2008

## 2 Client Information

### 2.1 Applicant Information

Company Name: Longcheer Technology (Shanghai) Co., Ltd..  
Address /Post: Building 1, No.401,Caobao Rd, Xuhui District, Shanghai, P. R. China  
City: Shanghai  
Postal Code: \  
Country: P. R. China  
Telephone: +86-21-51552388-2808  
Fax: +86-21-54970876

### 2.2 Manufacturer Information

Company Name: Longcheer Technology (Shanghai) Co., Ltd..  
Address /Post: Building 1, No.401,Caobao Rd, Xuhui District, Shanghai, P. R. China  
City: Shanghai  
Postal Code: \  
Country: P. R. China  
Telephone: +86-21-51552388-2808  
Fax: +86-21-54970876

### 3 Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1 About EUT

Description: GSM/GPRS Digital Mobile phone  
Model: X591E  
Frequency Band: GSM850/1900  
GPRS Class: 12



Picture 1: Constituents of the sample

#### 3.2 Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
<b>EUT1</b>	135790246811220	LK1M512G1-1	LK1EF02.1.0_M512G

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
<b>AE1</b>	Travel Adapter	P-032B	\	Something high electronic( Xiameng) Co,Ltd
<b>AE2</b>	Battery	BTR 1328	\	Shenzhen bak battery CO.LTD

\*AE ID: is used to identify the test sample in the lab internally

## **4 OPERATIONAL CONDITIONS DURING TEST**

### **4.1 Schematic Test Configuration**


During SAR test, EUT is in Traffic Mode (Channel Allocated) at Normal Voltage Condition. A communication link is set up with a System Simulator (SS) by air link, and a call is established. The Absolute Radio Frequency Channel Number (ARFCN) is allocated to 128, 190 and 251 respectively in the case of GSM 850 MHz, or to 512, 661 and 810 respectively in the case of PCS 1900 MHz. The EUT is commanded to operate at maximum transmitting power.

The EUT shall use its internal transmitter. The antenna(s), battery and accessories shall be those specified by the manufacturer. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output. If a wireless link is used, the antenna connected to the output of the base station simulator shall be placed at least 50 cm away from the handset. The signal transmitted by the simulator to the antenna feeding point shall be lower than the output power level of the handset by at least 30 dB.

### **4.2 SAR Measurement Set-up**

These measurements were performed with the automated near-field scanning system DASY4 Professional from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9m), which positions the probes with a positional repeatability of better than  $\pm 0.02\text{mm}$ . Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines (length = 300mm) to the data acquisition unit.

A cell controller system contains the power supply, robot controller, teaches pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the Micron Pentium III 800 MHz computer with Windows 2000 system and SAR Measurement Software DASY4 Professional, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.



**Picture 2: SAR Lab Test Measurement Set-up**

The DAE consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

### 4.3 Dasy4 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ES3DV3 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the standard procedure with an accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated and found to be better than  $\pm 0.25\text{dB}$ .

#### ES3DV3 Probe Specification

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	Basic Broad Band Calibration in air Conversion Factors (CF) for HSL 900 and HSL 1810 Additional CF for other liquids and frequencies upon request



**Picture 3: ES3DV3 E-field Probe**

Frequency	10 MHz to 4 GHz; Linearity: $\pm 0.2\text{ dB}$ (30 MHz to 4 GHz)
Directivity	$\pm 0.2\text{ dB}$ in HSL (rotation around probe axis) $\pm 0.3\text{ dB}$ in tissue material (rotation normal to probe axis)

Dynamic Range	5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm$ 0.2 dB
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Dosimetry in strong gradient fields Compliance tests of mobile phones



**Picture4:ES3DV3 E-field probe**

#### 4.4 E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm$  10%. The spherical isotropy was evaluated and found to be better than  $\pm$  0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:  $\Delta t$  = Exposure time (30 seconds),  
C = Heat capacity of tissue (brain or muscle),  
 $\Delta T$  = Temperature increase due to RF exposure.

Or

$$SAR = \frac{|E|^2 \sigma}{\rho}$$

Where:

$\sigma$  = Simulated tissue conductivity,  
 $\rho$  = Tissue density ( $\text{kg/m}^3$ ).



**Picture 5: Device Holder**



## 4.5 Other Test Equipment

### 4.5.1 Device Holder for Transmitters

In combination with the Generic Twin Phantom V3.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

### 4.5.2 Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Shell Thickness	2±0.1 mm
Filling Volume	Approx. 20 liters
Dimensions	810 x 1000 x 500 mm (H x L x W)
Available	Special



## 4.6 Equivalent Tissues

**Picture 6: Generic Twin Phantom**

The liquid used for the frequency range of 800-2000

MHz consisted of water, sugar, salt and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table 4 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528.

**Table 1. Composition of the Head Tissue Equivalent Matter**

MIXTURE %	FREQUENCY 850MHz		
Water	41.45		
Sugar	56.0		
Salt	1.45		
Preventol	0.1		
Cellulose	1.0		
Dielectric Parameters Target Value	f=850MHz	$\epsilon=41.5$	$\sigma=0.90$
MIXTURE %	FREQUENCY 1900MHz		
Water	55.242		
Glycol monobutyl	44.452		
Salt	0.306		
Dielectric Parameters Target Value	f=1900MHz	$\epsilon=40.0$	$\sigma=1.40$

**Table 2. Composition of the Body Tissue Equivalent Matter**

MIXTURE %	FREQUENCY 850MHz
Water	52.5
Sugar	45.0
Salt	1.4
Preventol	0.1
Cellulose	1.0
Dielectric Parameters Target Value	f=850MHz $\epsilon=55.2$ $\sigma=0.97$
MIXTURE %	FREQUENCY 1900MHz
Water	69.91
Glycol monobutyl	29.96
Salt	0.13
Dielectric Parameters Target Value	f=1900MHz $\epsilon=53.3$ $\sigma=1.52$

## 4.7 System Specifications

### 4.7.1 Robotic System Specifications

#### Specifications

**Positioner:** Stäubli Unimation Corp. Robot Model: RX90L

**Repeatability:**  $\pm 0.02$  mm

**No. of Axis:** 6

#### Data Acquisition Electronic (DAE) System

##### Cell Controller

**Processor:** Pentium III

**Clock Speed:** 800 MHz

**Operating System:** Windows 2000

##### Data Converter

**Features:** Signal Amplifier, multiplexer, A/D converter, and control logic

**Software:** DASY4 software

**Connecting Lines:** Optical downlink for data and status info.

Optical uplink for commands and clock

## 5 CHARACTERISTICS OF THE TEST

### 5.1 Applicable Limit Regulations

**EN 50360–2006:** Product standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones.

It specifies the maximum exposure limit of **2.0 W/kg** as averaged over any 10 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

**ANSI C95.1–1999:** IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for

portable devices being used within 20 cm of the user in the uncontrolled environment.

## 5.2 Applicable Measurement Standards

**EN 62209-1–2006:** Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz).

**IEEE 1528–2003:** Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

**OET Bulletin 65 (Edition 97-01) and Supplement C(Edition 01-01):** Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits.

**IEC 62209-1:** Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 1: Procedure to determine the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)

**IEC 62209-2 (Draft):** Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures – Part 2: Procedure to determine the Specific Absorption Rate (SAR) in the head and body for 30MHz to 6GHz Handheld and Body-Mounted Devices used in close proximity to the Body.

They specify the measurement method for demonstration of compliance with the SAR limits for such equipments.

## 6 LABORATORY ENVIRONMENT

**Table 3: The Ambient Conditions during EMF Test**

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30%, Max. = 70%
Ground system resistance	< 0.5 $\Omega$
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surround objects is minimized and in compliance with requirement of standards.	

## 7 CONDUCTED OUTPUT POWER MEASUREMENT

### 7.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure the maximum power transmission and proper modulation. This result contains conducted output power and ERP for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

## 7.2 Conducted Power

### 7.2.1 Measurement Methods

The EUT was set up for the maximum output power. The channel power was measured with Agilent Spectrum Analyzer E4440A. These measurements were done at low, middle and high channels.

### 7.2.2 Measurement result

**Table 4: Conducted Power Measurement Results**

850MHZ	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
Before SAR Test	32.28	32.27	32.51
After SAR Test	32.26	32.25	32.50
1900MHZ	Conducted Power (dBm)		
	Channel 810 (1909.8MHz)	Channel 661 (1880MHz)	Channel 512 (1850.2MHz)
Before SAR Test	28.56	28.76	29.08
After SAR Test	28.55	28.77	29.07

### 7.2.3 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 8 to Table 13 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

## 8 TEST RESULTS

### 8.1 Dielectric Performance

**Table 5: Dielectric Performance of Head Tissue Simulating Liquid**

Measurement is made at temperature 23.3 °C and relative humidity 49%.			
Liquid temperature during the test: 22.5°C			
/	Frequency	Permittivity $\epsilon$	Conductivity $\sigma$ (S/m)
Target value	850 MHz	41.5	0.90
	1900 MHz	40.0	1.40
Measurement value (Average of 10 tests)	850 MHz	40.3	0.91
	1900 MHz	40.9	1.38

**Table 6: Dielectric Performance of Body Tissue Simulating Liquid**

Measurement is made at temperature 23.3 °C and relative humidity 49%.			
Liquid temperature during the test: 22.5°C			
/	Frequency	Permittivity $\epsilon$	Conductivity $\sigma$ (S/m)
Target value	850 MHz	55.2	0.97
	1900 MHz	53.3	1.52
Measurement value (Average of 10 tests)	850 MHz	53.7	1.01
	1900 MHz	52.1	1.49

## 8.2 System Validation

**Table 7: System Validation**

Measurement is made at temperature 23.3 °C, relative humidity 49%, input power 250 mW. Liquid temperature during the test: 22.5°C							
<b>Liquid parameters</b>		<b>Frequency</b>		<b>Permittivity <math>\epsilon</math></b>		<b>Conductivity <math>\sigma</math> (S/m)</b>	
		835 MHz		43.5		0.91	
		1900 MHz		40.9		1.38	
<b>Verification results</b>	<b>Frequency</b>	<b>Target value (W/kg)</b>		<b>Measured value (W/kg)</b>		<b>Deviation</b>	
		<b>10 g Average</b>	<b>1 g Average</b>	<b>10 g Average</b>	<b>1 g Average</b>	<b>10 g Average</b>	<b>1 g Average</b>
	835 MHz	1.60	2.48	1.62	2.50	1.25%	0.81%
	1900 MHz	5.09	9.73	5.27	9.91	3.3%	1.9%

Note: Target values are the data of the dipole validation results, please check Annex F for the Dipole Calibration Certificate.

## 8.3 Summary of Measurement Results (850MHz)

**Table 8: SAR Values (850MHz-Head)**

Limit of SAR (W/kg)	10 g Average	1 g Average	Power Drift (dB)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
Left hand, Touch cheek, Top frequency(See Fig.1)	0.347	0.510	-0.110
Left hand, Touch cheek, Mid frequency(See Fig.3)	0.381	0.557	0.034
Left hand, Touch cheek, Bottom frequency(See Fig.5)	0.425	0.617	-0.106
Left hand, Tilt 15 Degree, Top frequency(See Fig.7)	0.191	0.278	-0.089
Left hand, Tilt 15 Degree, Mid frequency(See Fig.9)	0.224	0.328	-0.027
Left hand, Tilt 15 Degree, Bottom frequency(See Fig.11)	0.285	0.416	-0.017
Right hand, Touch cheek, Top frequency(See Fig.13)	0.377	0.593	-0.156
Right hand, Touch cheek, Mid frequency(See Fig.15)	0.415	0.650	-0.025
Right hand, Touch cheek, Bottom frequency(See Fig.17)	0.500	0.783	-0.005
Right hand, Tilt 15 Degree, Top frequency(See Fig.19)	0.221	0.356	-0.040
Right hand, Tilt 15 Degree, Mid frequency(See Fig.21)	0.273	0.438	-0.007
Right hand, Tilt 15 Degree, Bottom frequency(See Fig.23)	0.319	0.505	-0.124

**Table 9: SAR Values (850MHz-Body)**

Limit of SAR (W/kg)	10 g Average	1 g Average	Power Drift (dB)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
*Towards Ground, Top frequency with GPRS(See Fig.25)	0.504	0.713	-0.135
*Towards Ground, Mid frequency with GPRS(See Fig.27)	0.600	0.844	-0.116
*Towards Ground, Bottom frequency with GPRS (See Fig.29)	0.767	1.08	-0.195
*Towards Phantom, Top frequency with GPRS(See Fig.31)	0.372	0.534	-0.172
*Towards Phantom, Mid frequency with GPRS (See Fig.33)	0.411	0.589	-0.137
*Towards Phantom, Bottom frequency with GPRS (See Fig.35)	0.480	0.686	-0.033
Towards Ground, Bottom frequency with Headset (See Fig.37)	0.401	0.566	-0.113

**Note:** During the test of “GSM 850 GPRS Body”, the power reduction was applied; the maximum output power was reduced 2dB with 4 timeslots in uplink.

#### 8.4 Summary of Measurement Results (1900MHz)

**Table 10: SAR Values (1900MHz-Head)**

Limit of SAR (W/kg)	10 g Average	1 g Average	Power Drift (dB)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
Left hand, Touch cheek, Top frequency(See Fig.39)	0.284	0.530	-0.047
Left hand, Touch cheek, Mid frequency(See Fig.41)	0.313	0.579	0.040
Left hand, Touch cheek, Bottom frequency(See Fig.43)	0.379	0.691	-0.029
Left hand, Tilt 15 Degree, Top frequency(See Fig.45)	0.198	0.375	-0.038
Left hand, Tilt 15 Degree, Mid frequency(See Fig.47)	0.223	0.418	0.060
Left hand, Tilt 15 Degree, Bottom frequency(See Fig.49)	0.274	0.513	-0.037
Right hand, Touch cheek, Top frequency(See Fig.51)	0.479	0.990	-0.134
Right hand, Touch cheek, Mid frequency(See Fig.53)	0.582	1.19	0.069
Right hand, Touch cheek, Bottom frequency(See Fig.55)	0.615	1.26	-0.002
Right hand, Tilt 15 Degree, Top frequency(See Fig.57)	0.264	0.540	-0.054
Right hand, Tilt 15 Degree, Mid frequency(See Fig.59)	0.316	0.644	-0.028
Right hand, Tilt 15 Degree, Bottom frequency(See Fig.61)	0.421	0.850	-0.141

**Table 11: SAR Values (1900MHz-Body)**

Limit of SAR (W/kg)	10 g Average	1 g Average	Power Drift (dB)
	2.0	1.6	
Test Case	Measurement Result (W/kg)		
	10 g Average	1 g Average	
Towards Ground, Top frequency with GPRS(See Fig.63)	0.244	0.421	-0.156
Towards Ground, Mid frequency with GPRS(See Fig.65)	0.298	0.562	-0.178
Towards Ground, Bottom frequency with GPRS (See Fig.67)	0.413	0.779	-0.020
Towards Phantom, Top frequency with GPRS(See Fig.69)	0.196	0.369	-0.070
Towards Phantom, Mid frequency with GPRS (See Fig.71)	0.259	0.487	0.019
Towards Phantom, Bottom frequency with GPRS (See Fig.73)	0.360	0.679	-0.193
Towards Ground, Bottom frequency with Headset (See Fig.75)	0.163	0.256	0.047

## 8.5 Conclusion

Localized Specific Absorption Rate (SAR) of this portable wireless device has been measured in all cases requested by the relevant standards cited in Clause 5.2 of this report. Maximum localized SAR is below exposure limits specified in the relevant standards cited in Clause 5.1 of this test report.

## 9 Measurement Uncertainty

SN	a	Type	c	d	e = f(d,k)	f	h = c x f / e	k
	Uncertainty Component		Tol. (± %)	Prob. Dist.	Div.	c <sub>i</sub> (1 g)	1 g u <sub>i</sub> (±%)	v <sub>i</sub>
1	System repetivity	A	0.5	N	1	1	0.5	9
	Measurement System							
2	Probe Calibration	B	5	N	2	1	2.5	∞
3	Axial Isotropy	B	4.7	R	√3	$(1-c_p)^{1/2}$	4.3	∞
4	Hemispherical Isotropy	B	9.4	R	√3	√c <sub>p</sub>		∞
5	Boundary Effect	B	0.4	R	√3	1	0.23	∞
6	Linearity	B	4.7	R	√3	1	2.7	∞
7	System Detection Limits	B	1.0	R	√3	1	0.6	∞
8	Readout Electronics	B	1.0	N	1	1	1.0	∞

9	RF Ambient Conditions	B	3.0	R	$\sqrt{3}$	1	1.73	$\infty$
10	Probe Positioner Mechanical Tolerance	B	0.4	R	$\sqrt{3}$	1	0.2	$\infty$
11	Probe Positioning with respect to Phantom Shell	B	2.9	R	$\sqrt{3}$	1	1.7	$\infty$
12	Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	B	3.9	R	$\sqrt{3}$	1	2.3	$\infty$
Test sample Related								
13	Test Sample Positioning	A	4.9	N	1	1	4.9	N-1
14	Device Holder Uncertainty	A	6.1	N	1	1	6.1	N-1
15	Output Power Variation - SAR drift measurement	B	5.0	R	$\sqrt{3}$	1	2.9	$\infty$
Phantom and Tissue Parameters								
16	Phantom Uncertainty (shape and thickness tolerances)	B	1.0	R	$\sqrt{3}$	1	0.6	$\infty$
17	Liquid Conductivity - deviation from target values	B	5.0	R	$\sqrt{3}$	0.64	1.7	$\infty$
18	Liquid Conductivity - measurement uncertainty	B	5.0	N	1	0.64	1.7	M
19	Liquid Permittivity - deviation from target values	B	5.0	R	$\sqrt{3}$	0.6	1.7	$\infty$
20	Liquid Permittivity - measurement uncertainty	B	5.0	N	1	0.6	1.7	M
Combined Standard Uncertainty				RSS			11.25	
Expanded Uncertainty (95% CONFIDENCE INTERVAL)				K=2			22.5	

## 10 MAIN TEST INSTRUMENTS

**Table 12: List of Main Instruments**

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Network analyzer	HP 8753E	US38433212	August 31, 2007	One year
02	Power meter	NRVD	101253	June 20, 2008	One year
03	Power sensor	NRV-Z5	100333		
04	Power sensor	NRV-Z6	100011	September 3, 2007	One year
05	Signal Generator	E4433B	US37230472	September 5, 2007	One Year
06	Amplifier	VTL5400	0505	No Calibration Requested	
07	BTS	CMU 200	105948	August 16, 2007	One year
08	E-field Probe	SPEAG ES3DV3	3142	September 7, 2007	One year
09	DAE	SPEAG DAE4	777	September 7, 2007	One year
10	Dipole Validation Kit	SPEAG D835V2	443	February 19, 2007	Two years
11	Dipole Validation Kit	SPEAG D1900V2	541	February 20, 2007	Two years

\*\*\*END OF REPORT BODY\*\*\*



## ANNEX A: MEASUREMENT PROCESS

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the reference point was measured and was used as a reference value for assessing the power drop.

Step 2: The SAR distribution at the exposed side of the phantom was measured at a distance of 3.9 mm from the inner surface of the shell. The area covered the entire dimension of the flat phantom and the horizontal grid spacing was 10 mm x 10 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.


Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7 x 7x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

b. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x ~ y and z-directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.


c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation is repeated.




**Picture A: SAR Measurement Points in Area Scan**

## ANNEX B TEST LAYOUT



Picture B1: Specific Absorption Rate Test Layout




Picture B2: Liquid depth in the Flat Phantom (850 MHz)



**Picture B3 Liquid depth in the Flat Phantom (1900MHz)**




**Picture B4: Left Hand Touch Cheek Position**




**Picture B5: Left Hand Tilt 15° Position**




**Picture B6: Right Hand Touch Cheek Position**




**Picture B7: Right Hand Tilt 15° Position**



**Picture B8: Body-worn Position (towards ground, the distance from handset to the bottom of the Phantom is 1.5cm)**



**Picture B9: Body-worn Position (towards phantom, the distance from handset to the bottom of the Phantom is 1.5cm)**



**Picture B10: Body-worn Position with Headset (towards ground, the distance from handset to the bottom of the Phantom is 1.5cm)**

## ANNEX C: GRAPH RESULTS

### 850 Left Cheek High

Date/Time: 2008-8-3 15:14:54

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Cheek High/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.600 mW/g


**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.6 V/m; Power Drift = -0.110 dB

Peak SAR (extrapolated) = 0.682 W/kg

**SAR(1 g) = 0.510 mW/g; SAR(10 g) = 0.347 mW/g**


Maximum value of SAR (measured) = 0.544 mW/g



0 dB = 0.544mW/g

Fig. 1 850MHz CH251





**Fig. 2 Z-Scan at power reference point (850 MHz CH251)**

### 850 Left Cheek Middle

Date/Time: 2008-8-3 15:28:30

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Cheek Middle/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.630 mW/g


**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.3 V/m; Power Drift = -0.034 dB


Peak SAR (extrapolated) = 0.740 W/kg

**SAR(1 g) = 0.557 mW/g; SAR(10 g) = 0.381 mW/g**

Maximum value of SAR (measured) = 0.597 mW/g



**Fig. 3 850 MHz CH190**



**Fig. 4 Z-Scan at power reference point (850 MHz CH190)**

### 850 Left Cheek Low

Date/Time: 2008-8-3 15:41:35

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Cheek Low/Area Scan (51x81x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.21 mW/g


**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.5 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 0.815 W/kg


**SAR(1 g) = 0.617 mW/g; SAR(10 g) = 0.425 mW/g**

SAR (measured) = 0.660 mW/g



0 dB = 0.660mW/g

Fig. 5 850 MHz CH128



**Fig. 6 Z-Scan at power reference point (850 MHz CH190)**

### 850 Left Tilt High

Date/Time: 2008-8-3 16:39:07

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Tilt High/Area Scan (51x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.314 mW/g


**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.6 V/m; Power Drift = -0.089 dB

Peak SAR (extrapolated) = 0.411 W/kg


**SAR(1 g) = 0.278 mW/g; SAR(10 g) = 0.191 mW/g**

Maximum value of SAR (measured) = 0.296 mW/g



0 dB = 0.296mW/g

**Fig.7 850 MHz CH251**



**Fig. 8 Z-Scan at power reference point (850 MHz CH251)**

### 850 Left Tilt Middle

Date/Time: 2008-8-3 16:25:50

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Tilt Middle/Area Scan (51x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.364 mW/g


**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.1 V/m; Power Drift = -0.027 dB

Peak SAR (extrapolated) = 0.502 W/kg

**SAR(1 g) = 0.328 mW/g; SAR(10 g) = 0.224 mW/g**


Maximum value of SAR (measured) = 0.349 mW/g



0 dB = 0.349mW/g

**Fig.9 850 MHz CH190**





**Fig. 10 Z-Scan at power reference point (850 MHz CH190)**

### 850 Left Tilt Low

Date/Time: 2008-8-3 16:04:39

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Tilt Low/Area Scan (51x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.460 mW/g


**Tilt Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.6 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 0.642 W/kg


**SAR(1 g) = 0.416 mW/g; SAR(10 g) = 0.285 mW/g**

Maximum value of SAR (measured) = 0.450 mW/g



0 dB = 0.450mW/g

Fig. 11 850 MHz CH128



**Fig. 12 Z-Scan at power reference point (850 MHz CH128)**

### 850 Right Cheek High

Date/Time: 2008-8-4 8:04:00

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Cheek High/Area Scan (51x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.696 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.3 V/m; Power Drift = -0.156 dB

Peak SAR (extrapolated) = 1.07 W/kg

**SAR(1 g) = 0.593 mW/g; SAR(10 g) = 0.377 mW/g**

Maximum value of SAR (measured) = 0.620 mW/g





Fig. 13 850 MHz CH251



**Fig. 14 Z-Scan at power reference point (850 MHz CH251)**

### 850 Right Cheek Middle

Date/Time: 2008-8-4 8:53:11

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Cheek Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.689 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.4 V/m; Power Drift = -0.025 dB

Peak SAR (extrapolated) = 1.10 W/kg

**SAR(1 g) = 0.650 mW/g; SAR(10 g) = 0.415 mW/g**

Maximum value of SAR (measured) = 0.671 mW/g





Fig. 15    850 MHz CH190



**Fig. 16 Z-Scan at power reference point (850 MHz CH190)**

### 850 Right Cheek Low

Date/Time: 2008-8-4 9:02:49

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Cheek Low/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.830 mW/g


**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.8 V/m; Power Drift = -0.005 dB

Peak SAR (extrapolated) = 1.31 W/kg


**SAR(1 g) = 0.783 mW/g; SAR(10 g) = 0.500 mW/g**

Maximum value of SAR (measured) = 0.802 mW/g



**Fig. 17    850 MHz CH128**





**Fig. 18 Z-Scan at power reference point (850 MHz CH128)**

### 850 Right Tilt High

Date/Time: 2008-8-4 9:49:00

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 0.903$  mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Tilt High/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.358 mW/g


**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.9 V/m; Power Drift = -0.040 dB


Peak SAR (extrapolated) = 0.595 W/kg

**SAR(1 g) = 0.356 mW/g; SAR(10 g) = 0.221 mW/g**

Maximum value of SAR (measured) = 0.367 mW/g



**Fig.19    850 MHz CH251**



**Fig. 20 Z-Scan at power reference point (850 MHz CH251)**

### 850 Right Tilt Middle

Date/Time: 2008-8-4 9:17:35

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 0.891$  mho/m;  $\epsilon_r = 40.5$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Tilt Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.446 mW/g


**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 20.9 V/m; Power Drift = -0.07 dB


Peak SAR (extrapolated) = 0.724 W/kg

**SAR(1 g) = 0.438 mW/g; SAR(10 g) = 0.273 mW/g**

Maximum value of SAR (measured) = 0.459 mW/g



**Fig.21 850 MHz CH190**



**Fig. 22 Z-Scan at power reference point (850 MHz CH190)**

### 850 Right Tilt Low

Date/Time: 2008-8-4 9:38:22

Electronics: DAE4 Sn777

Medium: Head GSM850

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.88$  mho/m;  $\epsilon_r = 40.6$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.97, 5.97, 5.97)

**Tilt Low/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.527 mW/g


**Tilt Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.2 V/m; Power Drift = -0.124 dB

Peak SAR (extrapolated) = 0.819 W/kg


**SAR(1 g) = 0.505 mW/g; SAR(10 g) = 0.319 mW/g**

Maximum value of SAR (measured) = 0.513 mW/g



0 dB = 0.513mW/g

Fig. 23 850 MHz CH128



**Fig. 24 Z-Scan at power reference point (850 MHz CH128)**

### 850 Body Towards Ground High with GPRS

Date/Time: 2008-8-3 10:11:15

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.02$  mho/m;  $\epsilon_r = 53.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: DCS 1800-GPRS12 Frequency: 848.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

**Toward Ground High/Area Scan (61x91x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (interpolated) = 0.789 mW/g

**Toward Ground High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 22.0 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 0.967 W/kg

**SAR(1 g) = 0.713 mW/g; SAR(10 g) = 0.504 mW/g**

Maximum value of SAR (measured) = 0.757 mW/g





Fig. 25 850 MHz CH251





**Fig. 26 Z-Scan at power reference point (850 MHz CH251)**

### 850 Body Towards Ground Middle with GPRS

Date/Time: 2008-8-3 10:25:18

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 1.01$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: DCS 1800-GPRS12 Frequency: 836.6 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

**Toward Ground Middle/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.952 mW/g

**Toward Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.6 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 1.13 W/kg

**SAR(1 g) = 0.844 mW/g; SAR(10 g) = 0.600 mW/g**

Maximum value of SAR (measured) = 0.895 mW/g





Fig. 27 850 MHz CH190



**Fig. 28 Z-Scan at power reference point (850 MHz CH190)**

### 850 Body Towards Ground Low with GPRS

Date/Time: 2008-8-3 10:40:10

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.993$  mho/m;  $\epsilon_r = 53.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: DCS 1800-GPRS12 Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

**Toward Ground Low/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.17 mW/g

**Toward Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.0 V/m; Power Drift = -0.195 dB

Peak SAR (extrapolated) = 1.44 W/kg

**SAR(1 g) = 1.08 mW/g; SAR(10 g) = 0.767 mW/g**

Maximum value of SAR (measured) = 1.14 mW/g





Fig. 29 850 MHz CH128



**Fig. 30 Z-Scan at power reference point (850 MHz CH128)**

### 850 Body Towards Phantom High with GPRS

Date/Time: 2008-8-3 11:38:35

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used (interpolated):  $f = 848.8$  MHz;  $\sigma = 1.02$  mho/m;  $\epsilon_r = 53.7$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: DCS 1800-GPRS12 Frequency: 848.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

**Toward Pantom High/Area Scan (61x91x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (interpolated) = 0.585 mW/g

**Toward Pantom High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 22.4 V/m; Power Drift = -0.172 dB

Peak SAR (extrapolated) = 0.739 W/kg

**SAR(1 g) = 0.534 mW/g; SAR(10 g) = 0.372 mW/g**

Maximum value of SAR (measured) = 0.567 mW/g





Fig. 31 850 MHz CH251



**Fig. 32 Z-Scan at power reference point (850 MHz CH251)**

### 850 Body Towards Phantom Middle with GPRS

Date/Time: 2008-8-3 11:18:36

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used (interpolated):  $f = 836.6$  MHz;  $\sigma = 1.01$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: DCS 1800-GPRS12 Frequency: 836.6 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

**Toward Pantom Middle/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.635 mW/g

**Toward Pantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.5 V/m; Power Drift = -0.137 dB

Peak SAR (extrapolated) = 0.793 W/kg

**SAR(1 g) = 0.589 mW/g; SAR(10 g) = 0.411 mW/g**

Maximum value of SAR (measured) = 0.628 mW/g





Fig. 33 850 MHz CH190





**Fig. 34 Z-Scan at power reference point (850 MHz CH190)**

### 850 Body Towards Phantom Low with GPRS

Date/Time: 2008-8-3 10:56:36

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.993$  mho/m;  $\epsilon_r = 53.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: DCS 1800-GPRS12 Frequency: 824.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

**Toward Pantom Low/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.736 mW/g

**Toward Pantom Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.5 V/m; Power Drift = -0.033 dB

Peak SAR (extrapolated) = 0.943 W/kg

**SAR(1 g) = 0.686 mW/g; SAR(10 g) = 0.480 mW/g**

Maximum value of SAR (measured) = 0.733 mW/g





Fig. 35 850 MHz CH128



**Fig. 36 Z-Scan at power reference point (850 MHz CH128)**

### 850 Body Towards Ground Low with Headset

Date/Time: 2008-8-3 12:24:55

Electronics: DAE4 Sn777

Medium: 850 Body

Medium parameters used:  $f = 825$  MHz;  $\sigma = 0.993$  mho/m;  $\epsilon_r = 53.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 850 Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(5.66, 5.66, 5.66)

### Toward Ground Low With Earphone/Area Scan (61x91x1): Measurement grid:

dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.608 mW/g

### Toward Ground Low With Earphone/Zoom Scan (7x7x7)/Cube 0: Measurement

grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 22.6 V/m; Power Drift = -0.113 dB

Peak SAR (extrapolated) = 0.770 W/kg

**SAR(1 g) = 0.566 mW/g; SAR(10 g) = 0.401 mW/g**

Maximum value of SAR (measured) = 0.601 mW/g





Fig. 37 850 MHz CH128



**Fig. 38 Z-Scan at power reference point (850 MHz CH128)**

### 1900 Left Cheek High

Date/Time: 2008-8-4 13:12:56

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Cheek High/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.568 mW/g


**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.9 V/m; Power Drift = -0.047 dB

Peak SAR (extrapolated) = 0.943 W/kg


**SAR(1 g) = 0.530 mW/g; SAR(10 g) = 0.284 mW/g**

Maximum value of SAR (measured) = 0.531 mW/g



0 dB = 0.531mW/g

**Fig. 39 1900 MHz CH810**



**Fig. 40 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Left Cheek Middle

Date/Time: 2008-8-4 13:23:53

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Cheek Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.621 mW/g


**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.7 V/m; Power Drift = 0.040 dB

Peak SAR (extrapolated) = 1.00 W/kg

**SAR(1 g) = 0.579 mW/g; SAR(10 g) = 0.313 mW/g**


Maximum value of SAR (measured) = 0.599 mW/g



0 dB = 0.599mW/g

Fig. 41 1900 MHz CH661





**Fig. 42 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Left Cheek Low

Date/Time: 2008-8-4 13:35:56

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Cheek Low/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.749 mW/g

**Cheek Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.1 V/m; Power Drift = -0.029 dB

Peak SAR (extrapolated) = 1.19 W/kg

**SAR(1 g) = 0.691 mW/g; SAR(10 g) = 0.379 mW/g**

Maximum value of SAR (measured) = 0.714 mW/g





Fig. 43 1900 MHz CH512



**Fig. 44 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Left Tilt High

Date/Time: 2008-8-4 14:03:30

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Tilt High/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.409 mW/g


**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.0 V/m; Power Drift = -0.038 dB

Peak SAR (extrapolated) = 0.661 W/kg


**SAR(1 g) = 0.375 mW/g; SAR(10 g) = 0.198 mW/g**

Maximum value of SAR (measured) = 0.384 mW/g



0 dB = 0.384mW/g

**Fig.45 1900 MHz CH810**



**Fig. 46 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Left Tilt Middle

Date/Time: 2008-8-4 13:53:53

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Tilt Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.453 mW/g


**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.8 V/m; Power Drift = 0.060 dB

Peak SAR (extrapolated) = 0.720 W/kg


**SAR(1 g) = 0.418 mW/g; SAR(10 g) = 0.223 mW/g**

Maximum value of SAR (measured) = 0.427 mW/g



0 dB = 0.427mW/g

Fig. 47 1900 MHz CH661



**Fig. 48 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Left Tilt Low

Date/Time: 2008-8-4 13:45:04

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Tilt Low/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.556 mW/g


**Tilt Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.4 V/m; Power Drift = -0.037 dB

Peak SAR (extrapolated) = 0.882 W/kg

**SAR(1 g) = 0.513 mW/g; SAR(10 g) = 0.274 mW/g**


Maximum value of SAR (measured) = 0.523 mW/g



0 dB = 0.523mW/g

**Fig. 49 1900 MHz CH512**





**Fig. 50 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Right Cheek High

Date/Time: 2008-8-4 10:16:48

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Cheek High/Area Scan (51x91x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (interpolated) = 1.11 mW/g

**Cheek High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 11.7 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 1.91 W/kg

**SAR(1 g) = 0.990 mW/g; SAR(10 g) = 0.479 mW/g**

Maximum value of SAR (measured) = 0.998 mW/g





Fig. 51 1900 MHz CH810



**Fig. 52 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Right Cheek Middle

Date/Time: 2008-8-4 10:34:50

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Cheek Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.28 mW/g

**Cheek Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.7 V/m; Power Drift = 0.069 dB

Peak SAR (extrapolated) = 2.30 W/kg

**SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.582 mW/g**

Maximum value of SAR (measured) = 1.12 mW/g





Fig. 53 1900 MHz CH661



**Fig. 54 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Right Cheek Low

Date/Time: 2008-8-4 12:23:02

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Cheek Low 3/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 1.41 mW/g

**Cheek Low 3/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.4 V/m; Power Drift = -0.002 dB

Peak SAR (extrapolated) = 2.39 W/kg

**SAR(1 g) = 1.26 mW/g; SAR(10 g) = 0.615 mW/g**

Maximum value of SAR (measured) = 1.21 mW/g





Fig. 55 1900 MHz CH512



**Fig. 56 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Right Tilt High

Date/Time: 2008-8-4 12:51:22

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.39$  mho/m;  $\epsilon_r = 40.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1909.8 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Tilt High/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.634 mW/g

**Tilt High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.8 V/m; Power Drift = -0.054 dB

Peak SAR (extrapolated) = 1.03 W/kg

**SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.264 mW/g**

Maximum value of SAR (measured) = 0.524 mW/g





Fig. 57 1900 MHz CH810





**Fig. 58 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Right Tilt Middle

Date/Time: 2008-8-4 12:41:24

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.37$  mho/m;  $\epsilon_r = 41$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Tilt Middle/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.724 mW/g

**Tilt Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.6 V/m; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 1.21 W/kg

**SAR(1 g) = 0.644 mW/g; SAR(10 g) = 0.316 mW/g**

Maximum value of SAR (measured) = 0.662 mW/g





Fig.59 1900 MHz CH661



**Fig. 60 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Right Tilt Low

Date/Time: 2008-8-4 12:32:28

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.36$  mho/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.87, 4.87, 4.87)

**Tilt Low/Area Scan (41x71x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.978 mW/g

**Tilt Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.5 V/m; Power Drift = -0.141 dB

Peak SAR (extrapolated) = 1.57 W/kg

**SAR(1 g) = 0.850 mW/g; SAR(10 g) = 0.421 mW/g**

Maximum value of SAR (measured) = 0.874 mW/g





Fig.61 1900 MHz CH512



**Fig. 62 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Body Towards Ground High with GPRS

Date/Time: 2008-8-4 14:27:58

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Class 12 Frequency: 1909.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Ground High/Area Scan (61x91x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (interpolated) = 0.482 mW/g

**Toward Ground High/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 16.7 V/m; Power Drift = -0.156 dB

Peak SAR (extrapolated) = 0.732 W/kg

**SAR(1 g) = 0.421 mW/g; SAR(10 g) = 0.224 mW/g**

Maximum value of SAR (measured) = 0.457 mW/g





Fig. 63 1900 MHz CH810



**Fig. 64 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Body Towards Ground Middle with GPRS

Date/Time: 2008-8-4 14:40:29

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.47$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Class 12 Frequency: 1880 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Ground Middle/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.631 mW/g

**Toward Ground Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.1 V/m; Power Drift = 0.178 dB

Peak SAR (extrapolated) = 0.976 W/kg

**SAR(1 g) = 0.562 mW/g; SAR(10 g) = 0.298 mW/g**

Maximum value of SAR (measured) = 0.616 mW/g





Fig. 65 1900 MHz CH661





**Fig. 66 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Body Towards Ground Low with GPRS

Date/Time: 2008-8-4 14:53:24

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Class 12 Frequency: 1850.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Ground Low/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.952 mW/g

**Toward Ground Low/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23.6 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 1.38 W/kg

**SAR(1 g) = 0.779 mW/g; SAR(10 g) = 0.413 mW/g**

Maximum value of SAR (measured) = 0.843 mW/g





Fig. 67 1900 MHz CH512



**Fig. 68 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Body Towards Phantom High with GPRS

Date/Time: 2008-8-4 15:55:19

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used:  $f = 1910$  MHz;  $\sigma = 1.5$  mho/m;  $\epsilon_r = 52.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Class 12 Frequency: 1909.8 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Pantom High/Area Scan (61x91x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (interpolated) = 0.450 mW/g

**Toward Pantom High/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 9.96 V/m; Power Drift = -0.070 dB

Peak SAR (extrapolated) = 0.640 W/kg

**SAR(1 g) = 0.369 mW/g; SAR(10 g) = 0.196 mW/g**

Maximum value of SAR (measured) = 0.409 mW/g





Fig. 69 1900 MHz CH810



**Fig. 70 Z-Scan at power reference point (1900 MHz CH810)**

### 1900 Body Towards Phantom Middle with GPRS

Date/Time: 2008-8-4 15:14:38

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used:  $f = 1880$  MHz;  $\sigma = 1.47$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Class 12 Frequency: 1880 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Pantom Middle/Area Scan (61x91x1):** Measurement grid:  $dx=10$ mm,  $dy=10$ mm

Maximum value of SAR (interpolated) = 0.587 mW/g

**Toward Pantom Middle/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 11.8 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.846 W/kg

**SAR(1 g) = 0.487 mW/g; SAR(10 g) = 0.259 mW/g**

Maximum value of SAR (measured) = 0.540 mW/g





Fig. 71 1900 MHz CH661



**Fig. 72 Z-Scan at power reference point (1900 MHz CH661)**

### 1900 Body Towards Phantom Low with GPRS

Date/Time: 2008-8-4 15:04:42

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz GPRS Class 12 Frequency: 1850.2 MHz Duty Cycle: 1:2

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Pantom Low/Area Scan (61x91x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.820 mW/g

**Toward Pantom Low/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.6 V/m; Power Drift = -0.193 dB

Peak SAR (extrapolated) = 1.17 W/kg

**SAR(1 g) = 0.679 mW/g; SAR(10 g) = 0.360 mW/g**

Maximum value of SAR (measured) = 0.770 mW/g





Fig. 73 1900 MHz CH512





**Fig. 74 Z-Scan at power reference point (1900 MHz CH512)**

### 1900 Body Towards Ground Low with Headset

Date/Time: 2008-8-4 16:11:01

Electronics: DAE4 Sn777

Medium: Body 1900 MHz

Medium parameters used (interpolated):  $f = 1850.2$  MHz;  $\sigma = 1.45$  mho/m;  $\epsilon_r = 52.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: GSM 1900MHz Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ES3DV3 - SN3142 ConvF(4.61, 4.61, 4.61)

**Toward Ground Low With Earphone/Area Scan (41x71x1):** Measurement grid:  
dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.279 mW/g

**Toward Ground Low With Earphone/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.6 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.380 W/kg

**SAR(1 g) = 0.256 mW/g; SAR(10 g) = 0.163 mW/g**

Maximum value of SAR (measured) = 0.264 mW/g





Fig. 75 1900 MHz CH512



**Fig. 76 Z-Scan at power reference point (1900 MHz CH512)**

## ANNEX D SYSTEM VALIDATION RESULTS

### 835MHzDAE777Probe3142

Date/Time: 2008-8-3 7:27:28

Electronics: DAE4 Sn777

Medium: 835 Head

Medium parameters used:  $f = 835 \text{ MHz}$ ;  $\sigma = 0.91 \text{ mho/m}$ ;  $\epsilon_r = 43.5$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $23.3^\circ\text{C}$       Liquid Temperature:  $22.5^\circ\text{C}$

Communication System: CW Frequency: 835 MHz Duty Cycle: 1:1

Probe: ES3DV3 – SN3142 ConvF(5.97, 5.97, 5.97)

**835MHz/Area Scan (101x101x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$

Maximum value of SAR (interpolated) =  $2.68 \text{ mW/g}$

**835MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $56.8 \text{ V/m}$ ; Power Drift =  $-0.01 \text{ dB}$

Peak SAR (extrapolated) =  $3.67 \text{ W/kg}$

**SAR(1 g) =  $2.50 \text{ mW/g}$ ; SAR(10 g) =  $1.62 \text{ mW/g}$**

Maximum value of SAR (measured) =  $2.69 \text{ mW/g}$




Fig.77 validation 835MHz 250mW

## 1900MHz DAE777Probe3142

Date/Time: 2008-8-4 7:42:13

Electronics: DAE4 Sn777

Medium: Head 1900 MHz

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.38$  mho/m;  $\epsilon_r = 40.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 23.3°C      Liquid Temperature: 22.5°C

Communication System: CW Frequency: 1900 MHz Duty Cycle: 1:1

Probe: ES3DV3 – SN3142 ConvF(5.66, 5.66, 5.66)

**System Validation/Area Scan (101x101x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 11.2 mW/g

**System Validation/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 92.1 V/m; Power Drift = 0.1 dB

Peak SAR (extrapolated) = 16.9 W/kg

**SAR(1 g) = 9.91 mW/g; SAR(10 g) = 5.27 mW/g**

Maximum value of SAR (measured) = 11.3 mW/g




Fig.78 validation 1900MHz 250mW

## ANNEX E PROBE CALIBRATION CERTIFICATE

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
S Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client: TMC Beijing

Certificate No: ES3-3142\_Sep07

### CALIBRATION CERTIFICATE

Object: ES3DV3 - SN:3142

Calibration procedure(s): QA CAL-01.v6 and QA CAL-12.v6  
Calibration procedure for dosimetric E-field probes

Calibration date: September 7, 2007

Condition of the calibrated item: In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature  $(22 \pm 3)^\circ\text{C}$  and humidity  $< 70\%$ .

Calibration Equipment used (M&E critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	28-Mar-07 (METAS, No. 217-00670)	Mar-08
Power sensor E4412A	MY41495277	29-May-07 (METAS, No. 217-00670)	Mar-08
Power sensor E4412A	MY41498087	28-Mar-07 (METAS, No. 217-00670)	Mar-08
Reference 5 dB Attenuator	SN: S5054 (3c)	8-Aug-07 (METAS, No. 217-00719)	Aug-08
Reference 20 dB Attenuator	SN: S5088 (200)	28-Mar-07 (METAS, No. 217-00671)	Mar-08
Reference 30 dB Attenuator	SN: S5129 (300)	8-Aug-07 (METAS, No. 217-00720)	Aug-08
Reference Probe ES3DV2	SN: 3013	4-Jan-07 (SPEAG, No. ES3-3013_Jan07)	Jan-08
DAE4	SN: 654	20-Apr-07 (SPEAG, No. DAE4-654_Apr07)	Apr-08

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Nov-05)	In house check: Nov-07
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Oct-06)	In house check: Oct-07

	Name	Function	Signature
Calibrated by:	Klara Pokorski	Technical Manager	
Approved by:	Wolfgang Kuster	Quality Manager	

Issued: September 10, 2007

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: ES3-3142\_Sep07

Page 1 of 9

**Calibration Laboratory of**  
**Schmid & Partner**  
**Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**S** Service suisse d'étalonnage  
**C** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

#### Glossary:

TSL	tissue simulating liquid
NORM <sub>x,y,z</sub>	sensitivity in free space
ConvF	sensitivity in TSL / NORM <sub>x,y,z</sub>
DCP	diode compression point
Polarization $\phi$	$\phi$ rotation around probe axis
Polarization $\theta$	$\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis

#### Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

#### Methods Applied and Interpretation of Parameters:

- NORM<sub>x,y,z</sub>**: Assessed for E-field polarization  $\theta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not effect the E<sup>2</sup>-field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub>** = NORM<sub>x,y,z</sub> \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical Isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

ES3DV3 SN:3142

September 7, 2007

# Probe ES3DV3

## SN:3142

Manufactured:	March 13, 2007
Calibrated:	September 7, 2007

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)



ES3DV3 SN:3142

September 7, 2007

## DASY - Parameters of Probe: ES3DV3 SN:3142

### Sensitivity in Free Space<sup>A</sup>

### Diode Compression<sup>B</sup>

NormX	1.21 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP X	96 mV
NormY	1.28 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Y	95 mV
NormZ	1.15 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Z	96 mV

### Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

### Boundary Effect

TSL 900 MHz Typical SAR gradient: 5 % per mm

Sensor Center to Phantom Surface Distance	3.0 mm	4.0 mm
SAR <sub>iso</sub> [%] Without Correction Algorithm	2.6	0.8
SAR <sub>iso</sub> [%] With Correction Algorithm	0.0	0.4

TSL 1810 MHz Typical SAR gradient: 10 % per mm

Sensor Center to Phantom Surface Distance	3.0 mm	4.0 mm
SAR <sub>iso</sub> [%] Without Correction Algorithm	7.6	4.5
SAR <sub>iso</sub> [%] With Correction Algorithm	0.2	0.1

### Sensor Offset

Probe Tip to Sensor Center 2.0 mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX, Y, Z do not affect the E<sub>iso</sub>-field uncertainty inside TSL (see Page 8).


<sup>B</sup> Numerical linearization parameter: uncertainty not required.

ES3DV3 SN:3142

September 7, 2007

### Frequency Response of E-Field

(TEM-Cell: ifi110 EXX, Waveguide: R22)




Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )

ES3DV3 SN:3142

September 7, 2007

### Receiving Pattern ( $\phi$ ), $\theta = 0^\circ$




Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )

ES3DV3 SN:3142

September 7, 2007

**Dynamic Range  $f(\text{SAR}_{\text{head}})$**   
(Waveguide R22,  $f = 1800 \text{ MHz}$ )




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

ES3DV3 SN:3142

September 7, 2007

## Conversion Factor Assessment



f [MHz]	Validity [MHz] <sup>c</sup>	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
450	± 50 / ± 100	Head	43.5 ± 5%	0.87 ± 5%	0.32	1.29	6.16 ± 13.3% (k=2)
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	1.00	1.09	5.97 ± 11.0% (k=2)
1810	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.60	1.41	4.87 ± 11.0% (k=2)
450	± 50 / ± 100	Body	56.7 ± 5%	0.94 ± 5%	0.24	1.24	6.68 ± 13.3% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.94	1.16	5.66 ± 11.0% (k=2)
1810	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.73	1.33	4.81 ± 11.0% (k=2)


<sup>c</sup> The validity of ± 100 MHz only applies for DASV v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

ES3DV3 SN:3142

September 7, 2007

### Deviation from Isotropy in HSL

Error ( $\phi, \theta$ ),  $f = 900$  MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  ( $k=2$ )

## ANNEX F DIPOLE CALIBRATION CERTIFICATE

Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Federal Office of metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates  
Client: TMC China

Accreditation No.: SCS 108

Certificate No: D835V2-443\_Feb07

### CALIBRATION CERTIFICATE

Object	D835V2-SN: 443
Calibration procedure(s)	QA CAL-05.v6 Calibration procedure for dipole validation kits
Calibration date:	February 19, 2007
Condition of the calibrated item	In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements(SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted at an environment temperature  $(22\pm3)^{\circ}\text{C}$  and humidity<70%

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Data (Calibrated by, Certification NO.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	03-Oct-06 (METAS, NO. 217-00608)	Oct-07
Power sensor 8481A	US37292783	03-Oct-06 (METAS, NO. 217-00608)	Oct-07
Reference 20 dB Attenuator	SN:5086 (20g )	10-Aug-06 (METAS, NO. 217-00591)	Aug-07
Reference 10 dB Attenuator	SN:5047_2 (10r)	10-Aug-06 (METAS, NO. 217-00591)	Aug-07
DAE4	SN:601	30-Jan-07 (SPEAG, NO.DAE4-601_Jan07)	Jan-08
Reference Probe ET3DV6 (HF)	SN: 1507	19-Oct-06 (SPEAG, NO. ET3-1507_Oct06)	Oct-07
Secondary Standards	ID#	Check Data (In house)	Scheduled Calibration
Power sensor HP 8481A	MY41092317	18-Oct-02(SPEAG, in house check Oct-05)	In house check: Oct-07
RF generator Agilent E4421B	MY41000675	11-May-05(SPEAG, in house check Nov-05)	In house check: Nov -07
Network Analyzer HP 8753E	US37390585S4206	18-Oct-01(SPEAG, in house check Oct-06)	In house check: Oct -07

	Name	Function	Signature
Calibrated by:	Marcel Fehr	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Director	

Issued: February 21, 2007

This calibration certificate shall not be reported except in full without written approval of the laboratory.

Certificate No: D835V2-443\_Feb07

Page 1 of 6



Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- DASY4 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.



#### Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY4	V4.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V4.9	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

#### Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.9 $\pm$ 6 %	0.88 mho/m $\pm$ 6 %
Head TSL temperature during test	(21.2 $\pm$ 0.2) °C	----	----

#### SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.48 mW / g
SAR normalized	normalized to 1W	9.90 mW / g
SAR for nominal Head TSL parameters <sup>1</sup>	normalized to 1W	9.70 mW / g $\pm$ 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	1.60 mW / g
SAR normalized	normalized to 1W	6.40 mW / g
SAR for nominal Head TSL parameters <sup>1</sup>	normalized to 1W	6.31 mW / g $\pm$ 16.5 % (k=2)

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	$50.5\Omega - 6.8j\Omega$
Return Loss	- 25.8 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.402 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	September 3, 2001

## DASY4 Validation Report for Head TSL

Date/Time: 19.02.2007 10:04:15

Test laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; serial: D835V2-SN: 443

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL 835 MHz;

Medium parameters used:  $f=835$  MHz;  $\sigma=0.88$  mho/m;  $\epsilon_r=39.9$ ;  $\rho=1000\text{kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6-SN1507(HF); ConvF(6.01,6.01,6.01); Calibrated: 19.10.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.1\_2007
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA;
- Measurement SW: DASY, V4.7 Build 53; Post processing SW: SEMCAD, V1.8 Build 172


$P_{in} = 250$  mW;  $d = 15$  mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 56.6 V/m; Power Drift = 0.010 dB


Peak SAR (extrapolated) = 3.72 W/kg

**SAR(1 g) = 2.48 mW/g; SAR(10 g) = 1.60 mW/g**

Maximum value of SAR (measured) = 2.70 mW/g



### Impedance measurement Plot for Head TSL



Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Federal Office of metrology and accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client TMC China

Certificate No: D1900V2-541\_Feb07

# CALIBRATION CERTIFICATE

Object	D1900V2-SN: 541
Calibration procedure(s)	QA CAL-05.v6 Calibration procedure for dipole validation kits
Calibration date:	February 20, 2007
Condition of the calibrated item	In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements(SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted at an environment temperature (22±3)°C and humidity<70%

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID#	Cal Data (Calibrated by, Certification NO.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	03-Oct-06 (METAS, NO. 217-00608)	Oct-07
Power sensor 8481A	US37292783	03-Oct-06 (METAS, NO. 217-00608)	Oct-07
Reference 20 dB Attenuator	SN:5086 (20g )	10-Aug-05 (METAS, NO. 217-00591)	Aug-07
Reference 10 dB Attenuator	SN:5047_2 (10r)	10-Aug-05 (METAS, NO. 217-00591)	Aug-07
DAE4	SN:901	30-Jan-07 (SPEAG, NO DAE4-501_Jan07)	Jan-08
Reference Probe ET3DV6 (HF)	SN: 1507	19-Oct-06 (SPEAG, NO. ET3-1507_Oct06)	Oct-07
Secondary Standards	ID#	Check Data (in house)	Scheduled Calibration
Power sensor HP 8481A	MY41092317	18-Oct-02(SPEAG, in house check Oct-05)	In house check: Oct-07
RF generator Agilent E4421B	MY41000576	11-May-05(SPEAG, in house check Nov-05)	In house check: Nov -07
Network Analyzer HP 8753E	US37390585S4206	18-Oct-01(SPEAG, in house check Oct-06)	In house check: Oct -07

Calibrated by:	Name Marcel Fehr	Function Laboratory Technician	Signature 
Approved by:	Katja Pokovic	Technical Director	

Issued: February 21, 2007

This calibration certificate shall not be reported except in full without written approval of the laboratory.

Certificate No: D1900V2-541\_Feb07

Page 1 of 6



Calibration Laboratory of  
Schmid & Partner  
Engineering AG  
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst  
C Service suisse d'étalonnage  
S Servizio svizzero di taratura  
S Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

**Glossary:**

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001
- Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

**Additional Documentation:**

- DASY4 System Handbook

**Methods Applied and Interpretation of Parameters:**

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

#### Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY4	V4.7
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

#### Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	38.9 $\pm$ 6 %	1.38 mho/m $\pm$ 6 %
Head TSL temperature during test	(22.1 $\pm$ 0.2) °C	—	—

#### SAR result with Head TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL	condition	
SAR measured	250 mW input power	9.73 mW /g
SAR normalized	normalized to 1W	38.9 mW /g
SAR for nominal Head TSL parameters <sup>1</sup>	normalized to 1W	38.6 mW / g $\pm$ 17.6 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	5.09 mW /g
SAR normalized	normalized to 1W	20.4 mW /g
SAR for nominal Head TSL parameters <sup>1</sup>	normalized to 1W	20.2 mW / g $\pm$ 16.5 % (k=2)

<sup>1</sup> Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

## Appendix

### Antenna Parameters with Head TSL

Impedance, transformed to feed point	$48.4 \Omega - 8.9 j\Omega$
Return Loss	- 26.4 dB

### General Antenna Parameters and Design

Electrical Delay (one direction)	1.214 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

Manufactured by	SPEAG
Manufactured on	October 4 , 2001



## DASY4 Validation Report for Head TSL

Date/Time: 20.02.2007 09:25:37

Test laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; serial: D1900V2-SN: 541

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL 1900 MHz;

Medium parameters used:  $f=1900$  MHz;  $\sigma=1.38$  mho/m;  $\epsilon_r=38.9$ ;  $\rho=1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6-SN1507(HF); ConvF(5.03, 5.03, 5.03); Calibrated: 19.10.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 30.1\_2007
- Phantom: Flat Phantom 4.9L; Type: QD000P49AA;
- Measurement SW: DASY, V4.7 Build 53; Post processing SW: SEMCAD, V1.8 Build 172


$P_{in} = 250$  mW;  $d = 15$  mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid:  $dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 92.1 V/m; Power Drift = 0.059 dB

Peak SAR (extrapolated) = 16.9 W/kg

**SAR(1 g) = 9.73 mW/g; SAR(10 g) = 5.09 mW/g**

Maximum value of SAR (measured) = 11.3 mW/g



Impedance measurement Plot for Head TSL

