

- 1. 智能化控制系统
- 2. 全比例遥控 3.360度准确定向
- 4. 平稳悬空性能
- 5. 新研发节电功能
- 6. 呵护电池模式、延长使用寿命
- 1.Intelligentized Control System
- 2.Full Scale Remote Control
- 3.360-degree Accurate Orientation
- 4. Stable Hanging
- 5.Power Saving
- 6.Battery Protection Mode



ſ	主旋梁直径: Main Rotor Span	340mm
Γ	机身长度: Length:	370mm
Ī	机身高: Height:	175mm
	电池: Battery:	型号6590, 850毫安锂电池: 型号6590A, 380毫安镍氧电池 ModelE090, 850mAh Littsum Ballery ModelE090, 250mAh Ni-MH Battery







电池盖 Battery Case Cove

注意: : 亲电池对出版从电电池正自极与电池由正自极 切不能恢复 2 请你混合使用有证电池 Note 1. Mave sure to load the batteries according to polarity signs.

inside the bettery case. 2 Do not mix old and new betteries

动力电池充电使用说明 To Charge Rechargeable B

8090由池充由

- ・ 不能型条項は「Vield 口格入丸电套除入损死。这时实地金上的紅灯发来。紅灯方电景指示灯、绿灯方式电指示式 2. 有切力地也三部两头相入火电监输出地上。这时途色灯亮、随着电池电量逐步增加,绿灯压堆空停、曲梯灯压全熔灭。 3. 力用心相电影的以、近时介地址等。 3. 天起初川 1.5 州、高不製品区封付票。 (北京 日降力)の中心地位置的中面上,採打无受仗时,北京市场中心中心。

- Items in the CVT transfer that I set I was the CVT transfer that I was the CVT transfe

8090A由池充由: (To charge Ni-MH battery)

- 1. 将适配器直流7. 2/输出插口与电池插口连接, 适配器上的指示灯亮, 表示电池处于充电状态.

- 為完电子 146。東地東震激勃、素宗电池已充满电、青陵出电池 (注意) 清不要超出以上充电时间,不要在光电时表开。不能对电池过充!
- Insert the play of the CC 2.7 of stays or not the play of the PA 40 of the PA 40 to believe, and then the LED on the adoptor furns on, placed from the LED on the adoptor furns on, placed from the LED on the adoptor furns on, placed from the LED on the adoptor furns on, placed from the LED on the adoptor furns on, placed from the LED on the adoptor furns on the LED on the adoptor furns of the Adoptor furns on the Adoptor furns

0

注意: • 特保文电影的电压和最高符音性是对应是 • 文电明,如电池过度,要去过分变电,对电池有标言。 严重时造成电池水久部环 请立寿符止充电 • 支电明,人员切到离示

- 克根州、人林切物属并 本来是水灾是对其活的中途关电力比、大家会无电力比、 不要还是没用其它充电器分和力电化充电 以免发生物价的原则 由立场的原注等。由此追定性原是好等级 3分份是占有他的中级的海拔型力地化充电 不要把他投入火星。以免发生保好的原除。

- Note: 1.Make sure the specifications of the adaptor accords with
- 1. Make as we the spectracions of the student accords with your focal joins reply shadned.
 2. If the battley becomes too hot which caraging, it is probably on the control place of caraging immediately or the fauther year.
 3. Easy second and keep class afteriors when changing shadners, it is these changing dozene as a selectivity of the changing becomes a selectivity of the changing dozene as a selectiv

安装电池 To load the rechargeable battery

- 把电池安装到飞机下的电池架上
- 将电池插头与机身上的插座对接 注意 不要接反 把开关拨向 'ON' 处准备飞行
- 1. Skp the battery into the battery stand under the helicopter's bit. 2. Connect the battery plug with corresponding jobs on the PCB board of the helicopter. Pay attention to the polarity signs. 3. Turn the power awitch of the helicopter to "CN" position.





警告 如果不飞行此直升机的时候。请把开关披向

"OFF" 并且细由油纸斗线出来以防由油油铁 电, 如果连接器保持连接的话, 有可能会因长时 间的电量消耗而异致过放电。

Please turn the power switch of the helicopter to "OFF" position and unplug the battery when it's not in use Otherwise it might cause over-discharged of electricity and damage to the battery

飞行前环境 Notes on flying circumstance

- 1. 在温暖晴朗没风的天气飞行
- 切勿在气温极细的天气飞行 切勿在温度高于华氏113度天气飞行,或在低于华氏0度/摄氏0度的情况下飞行。在过热或过冷的天气 下飞行会影响飞行效果或提坏模型。
- 2 刊如太陽原動工句
- 3. 选择在室内宽敞处飞行, 并请确认附近有无障碍物。宠物及人。
- 1.Fly the helicopter in a fine warm weather. Do not fly the helicopter in extreme temperature. Do not fly in a temperature higher tha 46 CH181 or lower than OLYDC. Plying in estimate temperature would affect the performance of the fellologiet or even damage it. 200 and it fight windingset in sharing wind Dorseg wind would brink and infathers with the performance of the histogeter. Plying is wrong wind injust cause lost or damage on the helicopter. 37-fight be heldogiet in sporcious term adoptications of make sizer time are no batties, an intals or people around.

Changes or modifications not expressly approved by the party responsible for compliance could void the use's authority to operate the equipment.









