



NVLAP LAB CODE 200707-0



FCC PART 15.249 MEASUREMENT AND TEST REPORT

For

ANPOSI PRODUCTS LTD.

2/F, EAST OF ZONG HE LOU, No.28 YI TIAN GARDEN,
FUQIANG ROAD, SHENZHEN, CHINA

FCC ID: WHTGC767378

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: Wireless Video Doorbell
Test Engineer: <u>Alvin Huang</u> <i>Alvin Huang</i>	
Report No.: <u>RSZ08070401</u>	
Test Date: <u>2008-07-09 to 2008-08-07</u>	
Report Date: <u>2008-08-07</u>	
Reviewed By: <u>EMC Manager: Green Xu</u> <i>Green Xu</i>	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Shenzhen) This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EQUIPMENT MODIFICATIONS	5
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
§15.203 - ANTENNA REQUIREMENT.....	7
APPLICABLE STANDARD	7
ANTENNA CONNECTOR CONSTRUCTION	7
§15.205(A) §15.209(A) §15.249(A) §15.249(D) - RADIATED EMISSIONS.....	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY	8
TEST EQUIPMENT SETUP	8
EUT SETUP	9
TEST EQUIPMENT LIST AND DETAILS.....	9
TEST PROCEDURE	10
CORRECTED AMPLITUDE & MARGIN CALCULATION	10
TEST RESULTS SUMMARY	10
TEST DATA	10
§15.249(D) – OUT OF BAND EMISSIONS	14
APPLICABLE STANDARD	14
TEST PROCEDURE	14
TEST EQUIPMENT LIST AND DETAILS.....	14
TEST DATA	15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The ANPOSI PRODUCTS LTD. 's product, model number: AT-724D05 (Tx: Door bell:P205) the "EUT" as referred to in this report is a *Wireless video doorbell*, which measures approximately 9.4 cmL x 5.8 cmW x 2.0cmH, rated input voltage: DC 6V Battery.

** All measurement and test data in this report was gathered from production sample serial number: 0807010 (Assigned by BACL, Shenzhen). The EUT was received on 2008-07-04.*

Objective

This Type approval report is prepared on behalf of ANPOSI PRODUCTS LTD. in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION


Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Equipment Modifications


No modifications were made to the unit tested.

Configuration of Test Setup



EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	N/A **
§15.205(a), §15.209(a), 15.249(a), §15.249(c)	Radiated Emissions	Compliant*
§15.249(d)	Out of Band Emissions	Compliant

* Within measurement uncertainty.

** The EUT power supply with battery, no need conduction test.

§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT antenna is a permanently attached antenna, which in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

Result: Compliant.

Note: Please refer to the EUT photos.

§15.205(a) §15.209(a) §15.249(a) §15.249(d) - RADIATED EMISSIONS**Applicable Standard**

As per §15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per §15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

Test Equipment Setup

The spectrum analyzer or receiver is set as:


Below 1000MHz:

$$\text{RBW} = 100 \text{ kHz} / \text{VBW} = 300 \text{ kHz} / \text{Sweep} = \text{Auto}$$

Above 1000MHz:

- (1) Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto
- (2) Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

EUT Setup



The radiated emission and out of band emission tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209 and FCC 15.249 limits.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2007-10-16	2008-10-16
HP	Amplifier	8447E	1937A01046	2007-11-15	2008-11-15
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2007-08-14	2008-08-14
HP	Amplifier	8449B	3008A00277	2007-09-29	2008-09-29
Sunol Sciences	Horn Antenna	DRH-118	A052604	2007-09-25	2008-09-25
R&S	Spectrum Analyzer	FSEM30	849720/019	2008-05-09	2009-05-09

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test, the EUT, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.249, with the worst margin reading of:

30-1000MHz:

2.2 dB at 945.019150 MHz in the Vertical polarization.

Above 1GHz:


0.93 dB at 9656 MHz in the Vertical polarization, Low Channel
0.32 dB at 7296 MHz in the Vertical polarization, Middle Channel
0.24 dB at 7404 MHz in the Horizontal polarization, High Channel

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

The testing was performed by Alvin Huang on 2008-07-09.

30-1000 MHz:*Test Mode: Transmitting*

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Ant. Height (cm)	Ant. Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBμV/m)	Margin (dB)
945.019150	43.8	137.0	V	286.0	1.9	46.0	2.2*
918.022550	41.7	138.0	V	285.0	1.2	46.0	4.3
837.005575	40.6	152.0	V	322.0	0.3	46.0	5.4
674.996375	38.5	104.0	V	258.0	-2.2	46.0	7.5
999.009375	44.3	132.0	V	353.0	2.4	53.9	9.6
513.019600	33.4	116.0	V	259.0	-5.7	46.0	12.6

Above 1GHz:

Freq. (MHz)	Meter Reading (dBμV)	Detector PK/AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	FCC Part 15.209 & 15.249		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	Remarks
Low -Channel (2414MHz)												
9656	36.18	AV	360	1.6	V	40.1	10.79	34.0	53.07	54	0.93*	Harmonic
7242	38.18	AV	268	1.6	H	39.2	9.15	33.6	52.93	54	1.07*	Harmonic
9656	34.71	AV	149	1.8	H	41.4	10.79	34.0	52.9	54	1.10*	Harmonic
7242	39.17	AV	263	1.8	V	38.0	9.15	33.6	52.72	54	1.28*	Harmonic
4828	40.28	AV	270	1.6	H	36.3	7.56	33.7	50.44	54	3.56*	Harmonic
4828	41.26	AV	180	1.6	V	35.0	7.56	33.7	50.12	54	3.88*	Harmonic
9656	46.69	PK	230	1.8	H	41.4	10.79	34.0	64.88	74	9.12	Harmonic
7242	49.63	PK	168	1.6	H	39.2	9.15	33.6	64.38	74	9.62	Harmonic
9656	46.89	PK	358	1.3	V	40.1	10.79	34.0	63.78	74	10.22	Harmonic
2414	78.53	AV	263	1.4	H	30.9	7.90	33.9	83.43	94	10.57	Fund.
7242	49.55	PK	268	1.6	V	38.0	9.15	33.6	63.10	74	10.90	Harmonic
2414	78.13	AV	45	1.0	V	30.3	7.90	33.9	82.43	94	11.57	Fund.
4828	49.72	PK	49	1.2	H	36.3	7.56	33.7	59.88	74	14.12	Harmonic
4828	50.53	PK	250	1.0	V	35.0	7.56	33.7	59.39	74	14.61	Harmonic
2414	88.90	PK	20	1.2	H	30.9	7.90	33.9	93.80	114	20.20	Fund.
2414	87.56	PK	18	1.6	V	30.3	7.90	33.9	91.86	114	22.14	Fund.

Freq. (MHz)	Meter Reading (dBμV)	Detector PK/AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	FCC Part 15.209 & 15.249		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	Remarks
Middle Channel (2432MHz)												
7296	40.13	AV	90	1.2	V	38	9.15	33.6	53.68	54	0.32*	Harmonic
4864	40.51	AV	270	1.6	H	39.2	7.56	33.7	53.57	54	0.43*	Harmonic
7296	36.18	AV	261	1.0	H	41.4	9.15	33.6	53.13	54	0.87*	Harmonic
9728	35.50	AV	180	1.6	V	40.2	10.80	34.0	52.50	54	1.50*	Harmonic
4864	41.14	AV	180	1.6	V	35.0	7.56	33.7	50.00	54	4.00	Harmonic
2432	77.84	AV	45	1.0	V	35.0	7.90	33.9	86.84	94	7.16	Fund.
2432	75.98	AV	263	1.4	H	36.3	7.90	33.9	86.28	94	7.72	Fund.
9728	38.76	AV	270	1.6	H	30.3	10.80	34.0	45.86	54	8.14	Harmonic
9728	47.10	PK	49	1.2	H	41.4	10.80	34.0	65.30	74	8.70	Harmonic
9728	47.24	PK	250	1.0	V	40.2	10.80	34.0	64.24	74	9.76	Harmonic
7296	47.39	PK	180	1.3	H	39.2	9.15	33.6	62.14	74	11.86	Harmonic
7296	48.51	PK	180	1.0	V	38.0	9.15	33.6	62.06	74	11.94	Harmonic
4864	49.68	PK	49	1.2	H	36.3	7.56	33.7	59.84	74	14.16	Harmonic
4864	50.02	PK	250	1.0	V	35.0	7.56	33.7	58.88	74	15.12	Harmonic
2432	86.21	PK	20	1.2	H	30.9	7.90	33.9	91.11	114	22.89	Fund.
2432	86.52	PK	18	1.6	V	30.3	7.90	33.9	90.82	114	23.18	Fund.

Freq. (MHz)	Meter Reading (dBμV)	Detector PK/AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBμV/m)	FCC Part 15.209 & 15.249		
				Height (m)	Polar (H/V)	Factor (dB/m)				Limit (dBμV/m)	Margin (dB)	Remarks
High-Channel (2468MHz)												
7404	38.79	AV	268	1.6	H	39.4	9.17	33.6	53.76	54	0.24*	Harmonic
9872	34.84	AV	149	1.8	H	41.5	10.95	33.8	53.49	54	0.51*	Harmonic
9872	35.19	AV	360	1.6	V	40.3	10.95	33.8	52.64	54	1.36*	Harmonic
4936	42.13	AV	270	1.6	H	36.4	7.80	33.7	52.63	54	1.37*	Harmonic
7404	38.64	AV	263	1.8	V	38.1	9.17	33.6	52.31	54	1.69*	Harmonic
4936	41.21	AV	180	1.6	V	35.2	7.80	33.7	50.51	54	3.49*	Harmonic
7404	49.75	PK	168	1.3	H	39.4	9.17	33.6	64.72	74	9.28	Harmonic
9872	45.69	PK	250	1.4	H	41.5	10.95	33.8	64.34	74	9.66	Harmonic
9872	46.23	PK	358	1.3	V	40.3	10.95	33.8	63.68	74	10.32	Harmonic
7404	49.85	PK	268	1.5	V	38.1	9.17	33.6	63.52	74	10.48	Harmonic
2468	76.76	AV	263	1.4	H	30.9	7.90	33.9	81.66	94	12.34	Fund.
4936	51.10	PK	49	1.6	H	36.4	7.80	33.7	61.60	74	12.40	Harmonic
2468	75.10	AV	45	1.0	V	30.3	7.90	33.9	79.40	94	14.60	Fund.
4936	50.04	PK	250	1.4	V	35.2	7.80	33.7	59.34	74	14.66	Harmonic
2468	86.1	PK	20	1.2	H	30.9	7.90	33.9	91.00	114	23.00	Fund.
2468	85.67	PK	18	1.6	V	30.3	7.90	33.9	89.97	114	24.03	Fund.

* Within measurement uncertainty.

§15.249(d) – OUT OF BAND EMISSIONS

Applicable Standard

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Procedure

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2007-10-16	2008-10-16
HP	Amplifier	8447E	1937A01046	2007-11-15	2008-11-15
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2007-08-14	2008-08-14
HP	Amplifier	8449B	3008A00277	2007-09-29	2008-09-29
Sunol Sciences	Horn Antenna	DRH-118	A052604	2007-09-25	2008-09-25
R&S	Spectrum Analyzer	FSEM30	849720/019	2008-05-09	2009-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) Corp. attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	27 ° C
Relative Humidity:	45 %
ATM Pressure:	100.9 kPa

The testing was performed by Alvin Huang on 2008-08-07.

Test Result: Compliant.

Freq. (MHz)	Receiver Reading (dBµV/m)	Detector PK//AV	Direction Degree	Antenna			Cable Loss (dB)	Pre- Amp. Gain (dB)	Cord. Amp. (dBµV/m)	FCC 15.249/209	
				Height (m)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)
2345.40	34.15	AV	20	1.2	H	30.9	7.7	33.9	38.85	54	15.15
2345.40	39.30	PK	263	1.4	H	30.9	7.7	33.9	44.0	74	30.0
2396.78	34.19	AV	49	1.2	V	30.9	7.9	33.9	39.09	54	14.91
2396.78	40.62	PK	270	1.6	V	30.9	7.9	33.9	45.52	74	28.48
2489.2	32.34	AV	168	1.6	H	30.9	7.9	33.9	37.24	54	16.76
2489.2	36.69	PK	268	1.6	H	30.9	7.9	33.9	41.59	74	32.41
2486.75	32.74	AV	230	1.8	V	30.9	7.9	33.9	37.64	54	16.36
2486.75	38.15	PK	230	1.8	V	30.9	7.9	33.9	43.05	74	30.95

*******END OF REPORT*******