

TEST REPORT

REPORT NUMBER: B08GE6003-FCC-SAR

ON

Type of Equipment: GSM Mobile Phone
Type of Designation: S7
Manufacturer: SODIFF BMT

ACCORDING TO

FCC Part 2.1093: Radiofrequency radiation exposure evaluation: portable devices, e-CFR March 23, 2006


FCC OET Bulletin 65 Supplement C (Edition 01-01): Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions

IEEE Std 1528™-2003: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques

China Telecommunication Technology Labs.

Month date, year
Aug 01, 2008

Signature



He Guili
Director

FCC ID: WJG-S7
Report Date: 2008-08-01

Test Firm Name: China Telecommunication Technology Labs
Registration Number: 840587

Statement

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported tests were carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1093. The sample tested was found to comply with the requirements defined in the applied rules.

Table of Contents

1. General Information	4
1.1 NOTES	4
1.2 TESTERS	5
1.3 TESTING LABORATORY INFORMATION	6
1.4 DETAILS OF APPLICANT OR MANUFACTURER	7
2 Test Item.....	8
2.1 GENERAL INFORMATION	8
2.2 OUTLINE OF EUT	8
2.3 MODIFICATIONS INCORPORATED IN EUT	8
2.4 EQUIPMENT CONFIGURATION.....	8
2.5 OTHER INFORMATION	9
2.6 EUT PHOTOGRAPHS	9
3 Measurement Systems.....	11
3.1 SAR MEASUREMENT SYSTEMS SETUP	11
3.2 E-FIELD PROBE	12
3.3 PHANTOM	13
3.4 DEVICE HOLDER	14
4 Test Results.....	15
4.1 OPERATIONAL CONDITION.....	15
4.2 TEST EQUIPMENT USED.....	15
4.3 APPLICABLE LIMIT REGULATIONS	16
4.4 TEST RESULTS	16
4.5 TEST SETUP AND PROCEDURES	16
4.6 TEST ENVIRONMENT AND LIQUID PARAMETERS.....	17
4.7 SYSTEM VALIDATION CHECK	18
4.8 MAXIMUM OUTPUT POWER MEASUREMENT	20
4.9 TEST DATA	21
4.10 MEASUREMENT UNCERTAINTY.....	24
ANNEX A Photographs	25
ANNEX B Graphical Results.....	30
Annex C System Performance Check Graphical Results	38
ANNEX D Probes Calibration Certificates	50
ANNEX E Deviations from Prescribed Test Methods	60

1. General Information

1.1 Notes

All reported tests were carried out on a sample equipment to demonstrate limited compliance with the requirements of FCC CFR 47 Part 2.1093.

The test results of this test report relate exclusively to the item(s) tested as specified in section 2.

The following deviations from, additions to, or exclusions from the test specifications have been made. See Annex D.

China Telecommunication Technology Labs.(CTTL) authorizes the applicant or manufacturer (see section 1.4) to reproduce this report provided, and the test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTTL Mr. He Guili.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. CTTL accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

1.2 Testers

Name: Li Guoqing
Position: Engineer
Department: Department of EMC test
Signature: 李国庆

Editor of this test report:

Name: Li Guoqing
Position: Engineer
Department: Department of EMC test
Date: 2008-08-01
Signature: 李国庆

Technical responsibility for testing:

Name: Zou Dongyi
Position: Manager
Department: Department of EMC test
Date: 2008-08-01
Signature: 邹东屹

1.3 Testing Laboratory information

1.3.1 Location

Name: China Telecommunication Technology Labs.
Address: No. 52, Huanyuan Road, Haidian District
BEIJING
P. R. CHINA, 100083
Tel: +86 10 68094053
Fax: +86 10 68011404
Email: emc@chinattl.com

1.3.2 Details of accreditation status

Accredited by: China National Accreditation Service for Conformity
Assessment (CNAS)
Registration number: CNAS Registration No. CNAS L0570
Standard: ISO/IEC 17025:2005

1.3.3 Test location, where different from section 1.3.1

Name: -----
Street: -----
City: -----
Country: -----
Telephone: -----
Fax: -----
Postcode: -----

1.4 Details of applicant or manufacturer

1.4.1 Applicant

Name: SODIFF BMT
Address: 678-7, ChangMan-Ri, GwangTan-Myun, Paju-City,
Gyeonggi-Do, Korea
Country: Rep. Of Korea
Telephone: +82.70.7096.0713
Fax: +82.31.441.0171
Contact: Mr. Steve Noh
Telephone: +82.10.8568.4145
Email: Sinoh76@sodiff.net

1.4.2 Manufacturer (if different from applicant in section 1.4.1)

Name: --
Address: --

1.4.3 Manufactory (if different from applicant in section 1.4.1)

Name: --
Address: --

2 Test Item

2.1 General Information

Manufacturer: SODIFF BMT
Name: GSM Mobile phone
Model Number: S7
Serial Number: --
Production Status: Production
Receipt date of test item: 2008-07-24

2.2 Outline of EUT

E.U.T. is a GSM Mobile phone.

2.3 Modifications Incorporated in EUT

The EUT has not been modified from what is described by the brand name and unique type identification stated above.

2.4 Equipment Configuration

Equipment configuration list:

Item	Generic Description	Manufacturer	Type	Serial No.	Remarks
A	handset	SODIFF BMT	S7	--	None
B	adapter	Shenzhen Zhong Xin Tong Co.,Ltd. ZHUHAI REMINDA COMMUNICATION DEVELOPMENT CO., LTD.	ZXTSC01-5005 00	--	None
C	battery	SHENZHEN BAK BATTERY CO.,LTD	BAT-02	--	None
D	Earphone	SANG FAI ELECTRONICAL PRODUCTS CO., LTD.	SF-600KM-1	--	None

Cables:

Item	Cable Type	Manufacturer	Length	Shield	Quantity	Remarks
1	DC cable on Adapter	Unknown	1.0m	No	1	None

2.5 Other Information

Version of hardware and software:

HW Version: 2.0

SW Version: SGP500 MXC1NC_MT2706BV105_MP

Adaptor information:

Input/Output voltage: AC100-240V/DC5V

Input/output current: 200MA(max) /500mA (max)

Battery information:

Capacity: 680 mAh Voltage: 3.7 V


2.6 EUT Photographs



Front view with clip colse




Front view with clip open



Back view

3.1 SAR Measurement Systems Setup

A cell controller system containing the power supply, robot controller, teach pendant (Joystick) and remote control, is used to drive the robot motors. The PC consists of the Micron Pentium III 800 MHz computer with Windows 2000 system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc., which is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical signal to digital electric signal of the DAE and transfers data to the PC plug-in card.



Demonstration of measurement system setup

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is

accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built-in VME-bus computer.

3.2 E-field Probe

3.2.1 E-field Probe Description

The SAR measurements were conducted with the dosimetric probe ES3DV3 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the standard procedure with an accuracy of better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$.

Items	Specification
Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection System Built-in shielding against static charges PEEK enclosure material(resistant to organic solvents, e.g., glycol)
Calibration	In air from 10 MHz to 2.5 GHz In brain and muscle simulating tissue at frequencies of 450MHz, 900MHz and 1.8GHz (accuracy $\pm 8\%$) Calibration for other liquids and frequencies upon request
Frequency	10 MHz to > 6 GHz; Linearity: $\pm 0.2\text{ dB}$ (30 MHz to 3 GHz)
Directivity	$\pm 0.2\text{ dB}$ in brain tissue (rotation around probe axis) $\pm 0.4\text{ dB}$ in brain tissue (rotation normal probe axis)
Dynamic Range	5u W/g to > 100mW/g; Linearity: $\pm 0.2\text{dB}$
Surface Detection	$\pm 0.2\text{ mm}$ repeatability in air and clear liquids over diffuse reflecting surface
Dimensions	Overall length: 330mm Tip length: 16mm Body diameter: 12mm Tip diameter: 6.8mm Distance from probe tip to dipole centers: 2.7mm
Application	General dosimetry up to 3GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

3.2.2 E-field Probe Calibration

The Annex C is the copy of the calibration certificate of the used probes.

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy was evaluated and found to be better than $\pm 0.25\text{dB}$. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The free-space E-field measured in the medium correlates to temperature increase in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where: Δt = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

ΔT = Temperature increase due to RF exposure.

Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:

σ = Simulated tissue conductivity,

ρ = Tissue density (kg/m^3).

3.3 Phantom

The Generic Twin Phantom is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot.

Specifications:

Shell Thickness: $2 \pm 0.1\text{mm}$

Filling Volume: Approx. 20 liters

Dimensions: 810 x 1000 x 500 mm (H x L x W)

Liquid depth when testing: at least 150 mm

3.4 Device Holder

In combination with the Generic Twin Phantom V3.0, the Mounting Device (POM) enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeat ably positioned according to the FCC and CENELEC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom etc).

China Test Report

4 Test Results

4.1 Operational Condition

Specifications FCC OET 65C (01-01), IEEE Std 1528™-2003

Date of Tests 2008-07-24/25/26/28

Operation Mode TX at the highest output peak power level

Method of measurement: FCC OET 65C (01-01), IEEE Std 1528™-2003

4.2 Test Equipment Used

TYPE	ITEM	S/N	CALIBRATION DATE	DUE DATE
CMU200	Wireless Communication Test Set	109172	2008-04-08	2009-04-07
E5515C	Wireless Communication Test Set	GB44400824	N.A	N.A
SD000D04BC	DAE4	685	2007-11-08	2008-11-07
D835V2	dipole	4d038	2007-11-12	2008-11-11
D1900V2	dipole	5d072	2007-11-13	2008-11-12
NRVD	Power Meter	83584310014	2007-12-14	2008-12-13
SME03	Signal Generator	100029	2007-12-27	2008-12-26
NRV-Z4	Power Sensor	100381	2007-09-27	2008-09-26
NRV-Z2	Power Sensor	100211	2007-09-27	2008-09-26
8491B	Attenuator	MY39262528	NA	NA
8491B	Attenuator	MY39262663	NA	NA
8491B	Attenuator	MY39262640	NA	NA
8491B	Attenuator	MY39262638	NA	NA
778D	Dual directional coupler	20040	NA	NA
E3640A	DC Power Supply	MY40008487	2007-08-14	2008-08-13
85070E	Probe kit	MY44300214	N.A.	N.A.
E5071B	Network Analyzer	MY42404001	2008-06-20	2009-06-20

4.3 Applicable Limit Regulations

Item	Limit Level
Local Specific Absorption Rate (SAR) (1g)	1.6W/kg

4.4 Test Results

The EUT complies.

Note:

All measurements are traceable to national standards.

4.5 Test Setup and Procedures

The test setup is showed as picture 1 in the annex A.

The evaluation was performed according to the following procedure:

Step 1: The SAR value at a fixed location above the ear point was measured and was used as a reference value for assessing the power drift.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 10 mm x 10 mm. Based on these data, the area of the maximum absorption was determined by interpolation.

Step 3: Around this point, a volume of 30 mm x 30 mm x 25 mm was assessed by measuring 7 x 7 x 6 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure:

a. The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2 mm. The extrapolation was based on the least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

b. The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot"-condition (in x ~ y and z-directions). The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.

c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation should be repeated.

4.6 Test Environment and Liquid Parameters

4.6.1 Test Environment

Date	Ambient humidity (%)	Ambient temperature (°C)	Liquid temperature (°C)
standard	30 ~ ~ 70	20 ~ ~ 25	20 ~ ~ 24
Date: 2008-07-24	64	20.5	21
Date: 2008-07-25	62	22.8	21
Date: 2008-07-26	59	22.6	23
Date: 2008-07-28	58	22.8	23

4.6.2 Liquid recipe

INGREDIENTS	SIMULATING TISSUE mass percentage			
	835MHz Brain	835MHz Muscle	1900MHz Brain	1900MHz Muscle
Water	40.29	50.75	55.24	70.17
DGBE	0	0	44.45	29.44
Sugar	57.90	48.21	0	0
Salt	1.38	0.94	0.31	0.39
Cellulose	0.24	0.00	0	0
Preventol	0.18	0.10	0	0

4.6.3 Liquid Parameters

Frequency (MHz)	Tissue Type	Description	Dielectric Parameters	
			permittivity	conductivity (S/m)
835	Head	Target	41.5	0.9
		±5% window	39.425~43.575	0.855~0.945
		Date: 20080724	41.4	0.908
		Date: 20080725	41.7	0.904
1900	Head	Target	40	1.38
		±5% window	38.00~42.00	1.33~1.47
		Date: 20080725	39.9	1.44
		Date: 20080726	39	1.45
835	Body	Target	55	0.97
		±5% window	52.25~57.75	0.92~1.02
		Date: 20080726	53.9	0.992
1900	Body	Target	53.3	1.52
		±5% window	50.635~55.965	1.444~1.596
		Date: 20080728	52.8	1.52

4.7 System Validation Check

Validation Method:

The setup of system validation check or performance check is demonstrated as figure 5. The amplifier, low pass filter and attenuators are optional. The dipole shall be positioned and centered below the phantom, paralleling to the longest side of the phantom. A low loss and low dielectric constant spacer on the dipole may be used to guarantee the correct distance between the dipole top surface and the phantom bottom surface.

The separation d , which is defined as the distance from the liquid bottom surface to the dipole's central axis at location of the feed-point, should be as following: for 835 MHz dipole, $d = 15$ mm, and for 1900 MHz dipole, $d = 10$ mm, and this can be obtained using two different size spacer. The dipole arms shall be parallel to the flat phantom surface.

First the power meter PM1 is connected to the cable and it measures the forward power at the location of the dipole connector (X). The signal generator is adjusted for

the desired forward power at the dipole connector (taking into account the (Att1) value) and the power meter PM2 is read at that level. Then after connecting the cable to the dipole, the signal generator is readjusted for the same reading at the power meter PM2.

The system validation check procedures are the same as all measurement procedures used for compliance tests. A complete 1 g averaged SAR measurement is performed using the flat part of the phantom. The reference dipole input power is adjusted to produce a 1 g averaged SAR value falling in the range of 0.4 – 10 mW/g. The 1 g averaged SAR is measured at 835 MHz and 1900 MHz using corresponding dipole respectively. Then the results are normalized to 1 W forward input power and compared with the reference SAR values.




Figure 5 Illustration of system validation test setup

Validation Results

Date:	Frequency (MHz)	Tissue Type	Input Power	Targeted (SAR10g)	Measured (SAR10g)	Deviation (%)
20080725	835	Head	250	2.38	2.34	-1.68%
20080724	835	Head	250	2.38	2.43	2.10%
20080726	1900	Head	250	9.85	9.51	-3.45%
20080725	1900	Head	250	9.85	10.5	6.60%
20080726	835	Body	250	2.39	2.41	0.84%
20080728	1900	Body	250	9.41	10.2	8.40%

4.8 Maximum Output Power Measurement

According to FCC OET 65c, maximum output power shall be measured before and after each SAR test. The test setup and method are described as following.

Test setup

The output power measurement test setup is demonstrated as figure 6.




Figure 6 Demonstration of power measurement

The power control level settings and measurement value are as following table.

mode	PCL setting	Permissible max.values	Channel[low]	Channel[mid]	Channel[high]
GSM 850	5	33dBm	27.6dBm	27.9 dBm	28.2 dBm
			824.20MHz	836.60 MHz	848.80 MHz
PCS 1900	0	30dBm	26.3dBm	25.8dBm	24.9dBm
			1850.2 MHz	1880.0 MHz	1909.8 MHz

4.9 Test Data

4.9.1 Test Specifications

(a) Duty Factor and Crest Factor

For GSM mode, the duty factor is 1:8.3 and the crest factor is 8.3.

For GPRS mode, the duty factor is 1:2.075 and the crest factor is 2.075.

(b) Test configurations pictures:

Configurations	pictures no. in Annex A
Head SAR touch position, slide closed:	2
Head SAR touch position, slide open:	3
Head SAR tilt position, slide closed:	4
Head SAR tilt position, slide open:	5
Body SAR front to the phantom:	6
Body SAR back to the phantom:	7
Body SAR back to the phantom with the earphone:	8
Liquid depth for 835 band	9
Liquid depth for 1900 band	10

(d) Test description for body-worn mode

The distance between the handset and the bottom of the flat section is 15 mm.

(e) Test procedure for body-worn mode

Step 1: GSM850 band, test the middle channel of each of the front side and back side mode with the 15 mm distance between the handset and the bottom of the phantom, including slip open and close. Find out the worst case.

Step 2: For the worst case of step 1, test the low and high channel.

Step 3: Find out the worst case of step 1 and 2, and for this case, test the mode with Bluetooth on, and then with earphone using voice traffic mode.

Step 4: Repeat all the above steps for PCS 1900 band.

4.9.2 Test Data for Head mode

GSM 850 slide close

Test configuration	Test position	SAR _{1g} [W/kg] / Power Drift [dB]			
		Channel 128[low] 824.20 MHz	Channel 190[Mid] 836.60 MHz	Channel 251 [high] 848.80 MHz	
Left side of Head	Cheek	- / -	0.054 / 0.183	- / -	
	Tilted	- / -	0.049 / 0.114	- / -	
Right side of Head	Cheek	- / -	0.051 / 0.171	- / -	
	Tilted	- / -	0.036 / -0.004	- / -	

GSM 850 slide open

Test configuration	Test position	SAR _{1g} [W/kg] / Power Drift [dB]			
		Channel 128[low] 824.20 MHz	Channel 190[Mid] 836.60 MHz	Channel 251 [high] 848.80 MHz	
Left side of Head	Cheek	0.071 / 0.0377	0.067 / -0.0616	0.060 / 0.040	
	Tilted	- / -	0.052 / -0.133	- / -	
Right side of Head	Cheek	- / -	0.059 / -0.136	- / -	
	Tilted	- / -	0.041 / 0.117	- / -	

GSM 1900 slide close

Test configuration	Test position	SAR _{1g} [W/kg] / Power Drift [dB]			
		Channel 512[low] 1850.2 MHz	Channel 661[Mid] 1880.0 MHz	Channel 810 [high] 1909.8 MHz	
Left side of Head	Cheek	- / -	0.144 / 0.113	- / -	
	Tilted	- / -	0.19 / -0.030	- / -	
Right side of Head	Cheek	- / -	0.098 / 0.0211	- / -	
	Tilted	- / -	0.039 / 0.0395	- / -	

GSM 1900 slide open

Test configuration	Test position	SAR _{1g} [W/kg] / Power Drift [dB]		
		Channel 512[low] 1850.2 MHz	Channel 661[Mid] 1880.0 MHz	Channel 810 [high] 1909.8 MHz
Left side of Head	Cheek	- / -	0.142 / -0.0291	- / -
	Tilted	0.144 0.143	0.19 / 0.00644	0.102 0.0505
Right side of Head	Cheek	- / -	0.107 / -0.118	- / -
	Tilted	- / -	0.155 / 0.0849	- / -

4.9.3 Test Data for Body-Worn mode

GSM 850

Test configuration	Test position	SAR _{1g} [W/kg] / Power Drift [dB]		
		Channel 128[low] 824.20 MHz	Channel 190[Mid] 836.60 MHz	Channel 251 [high] 848.80 MHz
Front side	15mm	- / -	0.103 / -0.095	- / -
Back side	15mm	- / -	0.238 / 0.00671	- / -
Back side with earphone	15mm	0.354 / 0.0586	0.324 / 0.176	0.326 / 0.0324


GSM 1900

Test configuration	Test position	SAR _{1g} [W/kg] / Power Drift [dB]		
		Channel 512[low] 1850.2 MHz	Channel 661[Mid] 1880.0 MHz	Channel 810 [high] 1909.8 MHz
Front side	15mm	- / -	0.177 / 0.00638	- / -
Back side	15mm	- / -	0.668 / -0.0387	- / -
Back side with earphone	15mm	0.622 / 0.03	0.678 / -0.172	0.353 / -0.0852

4.10 Measurement uncertainty

ERROR SOURCE	Uncertainty value (%)	Probability distribution	Divisor	c_i (1g)	Standard Uncertainty (%)
Measurement equipment					
Probe calibration	5.9	Normal	1	1	5.9
Probe axial isotropy	4.7	Rectangular	$\sqrt{3}$	0.7	1.9
Probe hemispherical isotropy	9.6	Rectangular	$\sqrt{3}$	0.7	3.9
Probe linearity	4.7	Rectangular	$\sqrt{3}$	1	2.7
Detection limits	0.25	Rectangular	$\sqrt{3}$	1	0.6
Boundary effect	0.8	Rectangular	$\sqrt{3}$	1	0.6
Measurement device	0.3	Normal	1	1	0.3
Response time	0.0	Normal	1	1	0
Noise	0.0	Normal	1	1	0
Integration time	1.7	Normal	1	1	2.6
Mechanical constraints					
Scanning system	1.5	Rectangular	$\sqrt{3}$	1	0.2
Positioning of the probe	2.9	Normal	1	1	2.9
Phantom shell	4.0	Rectangular	$\sqrt{3}$	1	2.3
Positioning of the dipole	2.0	Normal	1	1	2.0
Positioning of the phone	2.9	Normal	1	1	2.9
Device holder disturbance	3.6	Normal	1	1	3.6
Physical parameters					
Liquid conductivity (deviation from target)	5.0	Rectangular	$\sqrt{3}$	0.5	1.4
Liquid conductivity (measurement error)	4.3	Rectangular	$\sqrt{3}$	0.5	1.2
Liquid permittivity (deviation from target)	5.0	Rectangular	$\sqrt{3}$	0.5	1.4
Liquid permittivity (measurement error)	4.3	Rectangular	$\sqrt{3}$	0.5	1.2
Drifts in output power of the phone, probe, temperature and humidity	5.0	Rectangular	$\sqrt{3}$	1	2.9
Environment disturbance	3.0	Rectangular	$\sqrt{3}$	1	1.7
Post-processing					
SAR interpolation and extrapolation	0.6	Rectangular	$\sqrt{3}$	1	0.6
Maximum SAR evaluation	1.0	Rectangular	$\sqrt{3}$		0.6
Combined standard uncertainty	$u_c = \sqrt{\sum_{i=1}^m c_i^2 \cdot u_i^2} = 11.08\%$				
Expanded uncertainty (confidence interval of 95%)	Normal $u_e = 1.96u_c = 21.7\%$				

ANNEX A Photographs



Picture 1 test setup



Picture 2: Head SAR touch position, slide closed



Picture 3: Head SAR touch position, slide open



Picture 4: Head SAR tilt position, slide closed



Picture 5: Head SAR tilt position, slide open



Picture 6: Body SAR front to the phantom



Picture 7: Body SAR back to the phantom



Picture 8:
body SAR back to the phantom with the earphone



Picture 9: Liquid depth for 835 band



Picture 10: Liquid depth for 1900 band

ANNEX B Graphical Results

B.1 Maximum head SAR of GSM 850

GSM850-LC-FO-Worst case

Date: 20080724

Communication System: GSM850; Frequency: 824.2 MHz; Duty Cycle: 1:8.3
Medium parameters used: $f = 825$ MHz; $\sigma = 0.898$ mho/m; $\epsilon_r = 41.5$; $\rho = 1000$ kg/m³ ;

Medium Notes: Ambient humidity:64; Ambient temperature: 21.0; Liquid temperature: 20.5;

Phantom section: Left Section ;Phantom: SAM with Front;Type: QD 000 P40 CA

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(6.02, 6.02, 6.02); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.71 V/m; Power Drift = 0.038 dB


Peak SAR (extrapolated) = 0.107 W/kg

SAR(1 g) = 0.071 mW/g; SAR(10 g) = 0.051 mW/g

Maximum value of SAR (measured) = 0.075 mW/g

low/Area Scan (61x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.076 mW/g



0 dB = 0.076mW/g

CTL Test Report

B.2 Maximum head SAR of GSM 1900

GSM1900-LT-FO

Date: 20080725

Communication System: PCS 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.42$ mho/m; $\epsilon_r = 39.9$;
 $\rho = 1000$ kg/m³;

Medium Notes: Ambient humidity: 62; Ambient temperature: 21.0; Liquid
temperature: 22.8;

Phantom section: Left Section ; Phantom: SAM with Right; Type: QD 000 P40 CA

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(4.63, 4.63, 4.63); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm,
dz=5mm

Reference Value = 11.4 V/m; Power Drift = 0.006 dB

Peak SAR (extrapolated) = 0.343 W/kg

SAR(1 g) = 0.190 mW/g; SAR(10 g) = 0.098 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.218 mW/g

mid/Area Scan (51x111x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.217 mW/g



0 dB = 0.217mW/g

CTL Test Report

B.3 Maximum body SAR of GPRS 850

GPRS850-BB-with earphone

Date: 20080726

DUT: SODIFF;

Communication System: GPRS850 class 12; Frequency: 824.2 MHz; Duty Cycle: 1:2.075

Medium parameters used: $f = 825 \text{ MHz}$; $\sigma = 0.983 \text{ mho/m}$; $\epsilon_r = 54$; $\rho = 1000 \text{ kg/m}^3$;
Medium Notes: Ambient humidity: 59; Ambient temperature: 23.0; Liquid temperature: 22.6;

Phantom section: Flat Section ; Phantom: Flat Phantom ELI4.0; Type: QDOVA001B

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(5.82, 5.82, 5.82); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.3 V/m; Power Drift = 0.059 dB


Peak SAR (extrapolated) = 0.491 W/kg

SAR(1 g) = 0.354 mW/g; SAR(10 g) = 0.251 mW/g

Maximum value of SAR (measured) = 0.371 mW/g

low/Area Scan (51x101x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.376 mW/g



0 dB = 0.376mW/g

B.4 Maximum body SAR of GPRS 1900

GPRS1900-BB-With earphone

Date: 20080728

Communication System: GPRS 1900 class 12; Frequency: 1880 MHz; Duty Cycle: 1:2.075

Medium parameters used (interpolated): $f = 1880$ MHz; $\sigma = 1.5$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³ ;

Medium Notes: Ambient humidity:58; Ambient temperature: 23.0; Liquid temperature: 22.8;

Phantom section: Flat Section ;Phantom: Flat Phantom ELI4.0;Type: QDOVA001B

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(4.41, 4.41, 4.41); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

mid/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 22.7 V/m; Power Drift = -0.172 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.678 mW/g; SAR(10 g) = 0.398 mW/g


[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.757 mW/g

mid/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.773 mW/g



0 dB = 0.773mW/g

Annex C System Performance Check Graphical Results

C.1 SystemPerformanceCheck-D835MHz

Date: 20080724

DUT: Dipole 835 MHz;

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835$ MHz; $\sigma = 0.908$ mho/m; $\epsilon_r = 41.4$;
 $\rho = 1000$ kg/m³ ;

Medium Notes: Ambient humidity: 64; Ambient temperature: 21.0; Liquid
temperature: 20.5;

Phantom section: Flat Section ; Phantom: SAM with Front; Type: QD 000 P40 CA

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(6.02, 6.02, 6.02); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

2008-07-09/Area Scan (51x111x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 2.65 mW/g

2008-07-09/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,
dy=5mm, dz=5mm


Reference Value = 51.4 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 3.59 W/kg

SAR(1 g) = 2.43 mW/g; SAR(10 g) = 1.59 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 2.61 mW/g



0 dB = 2.61mW/g

CTL Test Report

C.2 SystemPerformanceCheck-D835MHz

Date: 20080725

DUT: Dipole 835 MHz;

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835$ MHz; $\sigma = 0.904$ mho/m; $\epsilon_r = 41.7$;
 $\rho = 1000$ kg/m³ ;

Medium Notes: Ambient humidity: 62; Ambient temperature: 21.0; Liquid
temperature: 22.8;

Phantom section: Flat Section ; Phantom: SAM with Front; Type: QD 000 P40 CA

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(6.02, 6.02, 6.02); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

2008-07-25/Area Scan (51x111x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 2.55 mW/g

2008-07-25/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,
dy=5mm, dz=5mm


Reference Value = 50.6 V/m; Power Drift = -0.161 dB

Peak SAR (extrapolated) = 3.48 W/kg

SAR(1 g) = 2.34 mW/g; SAR(10 g) = 1.53 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 2.54 mW/g



0 dB = 2.54mW/g

C.3 SystemPerformanceCheck-body-D835MHz

Date: 20080726

DUT: Dipole 835 MHz;

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used (interpolated): $f = 835 \text{ MHz}$; $\sigma = 0.992 \text{ mho/m}$; $\epsilon_r = 53.9$;
 $\rho = 1000 \text{ kg/m}^3$;

Medium Notes: Ambient humidity: 59; Ambient temperature: 23.0; Liquid
temperature: 22.6;

Phantom section: Flat Section ; Phantom: Flat Phantom ELI4.0; Type: QDOVA001B

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(5.82, 5.82, 5.82); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

MSL/Area Scan (61x111x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 2.59 mW/g

MSL/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$,
 $dz=5\text{mm}$


Reference Value = 51.5 V/m; Power Drift = -0.101 dB

Peak SAR (extrapolated) = 3.47 W/kg

SAR(1 g) = 2.41 mW/g; SAR(10 g) = 1.6 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 2.60 mW/g



0 dB = 2.60mW/g

CTL Test Report

C.4 SystemPerformanceCheck-D1900MHz

Date: 20080725

DUT: Dipole 1900 MHz;

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 39.9$; $\rho = 1000$ kg/m³;

Medium Notes: Ambient humidity: 62; Ambient temperature: 21.0; Liquid temperature: 22.8;

Phantom section: Flat Section ; Phantom: SAM with Right; Type: QD 000 P40 CA

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(4.63, 4.63, 4.63); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

head1900/Area Scan (61x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 13.2 mW/g


head1900/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 89.0 V/m; Power Drift = -0.053 dB

Peak SAR (extrapolated) = 19.5 W/kg

SAR(1 g) = 10.5 mW/g; SAR(10 g) = 5.46 mW/g

Maximum value of SAR (measured) = 11.8 mW/g



0 dB = 11.8mW/g

CTL Test Report

C.5 SystemPerformanceCheck-D1900MHz

Date: 20080726

DUT: Dipole 1900 MHz;

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.45 \text{ mho/m}$; $\epsilon_r = 39$; $\rho = 1000 \text{ kg/m}^3$;

Medium Notes: Ambient humidity: 59; Ambient temperature: 23.0; Liquid temperature: 22.6;

Phantom section: Flat Section ; Phantom: SAM with Right; Type: QD 000 P40 CA

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(4.63, 4.63, 4.63); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

head1900/Area Scan (61x71x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 12.3 mW/g


head1900/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 85.7 V/m; Power Drift = -0.054 dB

Peak SAR (extrapolated) = 17.9 W/kg

SAR(1 g) = 9.51 mW/g; SAR(10 g) = 4.93 mW/g

Maximum value of SAR (measured) = 10.7 mW/g



0 dB = 10.7mW/g

CTL Test Report

C.6 SystemPerformanceCheck-Body-D1900MHz

Date: 20080728

DUT: Dipole 1900 MHz;

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³ ;

Medium Notes: Ambient humidity:58; Ambient temperature: 23.0; Liquid temperature: 22.8;

Phantom section: Flat Section ;Phantom: Flat Phantom ELI4.0;Type: QDOVA001B

DASY4 Configuration:

- Probe: ES3DV3 - SN3109; ConvF(4.41, 4.41, 4.41); Calibrated: 2007-11-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn685; Calibrated: 2007-11-8
- Measurement SW: DASY4, V4.7 Build 71; Postprocessing SW: SEMCAD, V1.8 Build 171

Body1900/Area Scan (61x71x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 12.5 mW/g


Body1900/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 83.9 V/m; Power Drift = -0.041 dB

Peak SAR (extrapolated) = 17.6 W/kg

SAR(1 g) = 10.2 mW/g; SAR(10 g) = 5.5 mW/g

Maximum value of SAR (measured) = 11.3 mW/g



0 dB = 11.3mW/g

ANNEX D Probes Calibration Certificates

The System Validation was conducted following the requirements of standard IEEE 1528: 2003 Clause 8.3.

The scanned copy of the calibration certificate of the probe used is as following.

Test Report

FCC Part 2.1093 (2006-3-23), FCC OET 65C (01-01), IEEE Std 1528™-2003
Equipment: S7

REPORT NO.: B08GE6003-FCC-SAR

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client **Flextronics (Auden)**

Certificate No: **ES3-3109_Nov07**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3109**

Calibration procedure(s) **QA CAL-01.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **November 12, 2007**

Condition of the calibrated item **In Tolerance**



This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&E critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-07 (METAS, No. 217-00670)	Mar-08
Power sensor E4412A	MY41495277	29-Mar-07 (METAS, No. 217-00670)	Mar-08
Power sensor E4412A	MY41498087	29-Mar-07 (METAS, No. 217-00670)	Mar-08
Reference 3 dB Attenuator	SN: S5054 (3c)	8-Aug-07 (METAS, No. 217-00719)	Aug-08
Reference 20 dB Attenuator	SN: S5086 (20b)	29-Mar-07 (METAS, No. 217-00671)	Mar-08
Reference 30 dB Attenuator	SN: S5129 (30b)	8-Aug-07 (METAS, No. 217-00720)	Aug-08
Reference Probe ES3DV2	SN: 3013	4-Jan-07 (SPEAG, No. ES3-3013_Jan07)	Jan-08
DAE4	SN: 654	20-Apr-07 (SPEAG, No. DAE4-654_Apr07)	Apr-08

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Oct-07)	In house check: Oct-09
Network Analyzer HP 8753E	US37390585	16-Oct-01 (SPEAG, in house check Oct-07)	In house check: Oct-08

	Name	Function	Signature
Calibrated by:	Katja Pokovic	Technical Manager	
Approved by:	Nils Kuster	Quality Manager	

Issued: November 12, 2007

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: ES3-3109_Nov07

Page 1 of 9

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
Polarization ϕ	ϕ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\theta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\theta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: In a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

ES3DV3 SN:3109

November 12, 2007

Probe ES3DV3

SN:3109

Manufactured:	September 20, 2005
Last calibrated:	May 24, 2006
Recalibrated:	November 12, 2007

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

ES3DV3 SN:3109

November 12, 2007

DASY - Parameters of Probe: ES3DV3 SN:3109

Sensitivity in Free Space^A

NormX	1.22 ± 10.1%	$\mu V/(V/m)^2$
NormY	1.30 ± 10.1%	$\mu V/(V/m)^2$
NormZ	1.28 ± 10.1%	$\mu V/(V/m)^2$

Diode Compression^B

DCP X	94 mV
DCP Y	96 mV
DCP Z	93 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL 900 MHz Typical SAR gradient: 5 % per mm

Sensor Center to Phantom Surface Distance	3.0 mm	4.0 mm
SAR _{ice} [%] Without Correction Algorithm	6.3	2.9
SAR _{ice} [%] With Correction Algorithm	1.7	0.5

TSL 1750 MHz Typical SAR gradient: 10 % per mm

Sensor Center to Phantom Surface Distance	3.0 mm	4.0 mm
SAR _{ice} [%] Without Correction Algorithm	7.8	4.7
SAR _{ice} [%] With Correction Algorithm	0.0	1.4

Sensor Offset

Probe Tip to Sensor Center 2.0 mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the P^2 -field uncertainty inside TSL (see Page 8).


^B Numerical linearization parameter: uncertainty not required.

ES3DV3 SN:3109

November 12, 2007

Frequency Response of E-Field

(TEM-Cell:ifl110 EXX, Waveguide: R22)






Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

ES3DV3 SN:3109

November 12, 2007

Receiving Pattern (ϕ), $\theta = 0^\circ$




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

ES3DV3 SN:3109

November 12, 2007

Dynamic Range $f(\text{SAR}_{\text{head}})$ (Waveguide R22, $f = 1800 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Certificate No: ES3-3109_Nov07



Page 7 of 9



ES3DV3 SN:3109

November 12, 2007

Conversion Factor Assessment



f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
835	± 50 / ± 100	Head	41.5 ± 5%	0.90 ± 5%	0.87	1.22	6.02 ± 11.0% (k=2)
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.85	1.23	5.98 ± 11.0% (k=2)
1750	± 50 / ± 100	Head	40.1 ± 5%	1.37 ± 5%	0.92	1.18	4.84 ± 11.0% (k=2)
1950	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.85	1.26	4.63 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.96	1.13	4.33 ± 11.8% (k=2)
835	± 50 / ± 100	Body	55.2 ± 5%	0.97 ± 5%	0.90	1.26	5.82 ± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.85	1.32	5.55 ± 11.0% (k=2)
1750	± 50 / ± 100	Body	53.4 ± 5%	1.49 ± 5%	0.76	1.40	4.68 ± 11.0% (k=2)
1950	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.75	1.40	4.41 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.80	1.08	3.97 ± 11.8% (k=2)


^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

ES3DV3 SN:3109

November 12, 2007

Deviation from Isotropy in HSL

Error (ϕ , θ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)

ANNEX E Deviations from Prescribed Test Methods

No deviation from Prescribed Test Methods.

———— The End of this Report ————

CTL Test Report