

FCC RF Exposure Report (MPE Calculation)

Test Report no.:	EMC_BO_001849	Date of Report:	11-July-2013
Number of pages:	Error! Bookmark not defined.	Project support engineer:	Robert Müller

Customer:	novero GmbH, Meesmannstrasse 103, 44807 Bochum, Germany		
Customers contact:	Hindersmann, Jürgen		
Manufacturer:	novero GmbH		
EUT ident.:	Novero, HT-6g		
FCC ID:	WJLHT-6G	IC ID:	7847A-HT6G

Referred documents:	FCC rules Part 1 and IC standards RSS-102; FCC Test Reports with FCC ID / IC ID mentioned above
----------------------------	--

Testing Laboratory:	novero Test Center, Meesmannstr.103, 44807 Bochum, Germany		
	Tel.:	+49 234/51668-0	e-mail: product-validation@novero.com
	FCC listing no.:	881111	IC recognition no.: 7847A-1
	Laboratory manager:	Jürgen Mitterer	

Test result	The EUT does comply with the requirements made in the referred test documents.
--------------------	--

Signature:



11-July-2013, Jürgen Mitterer
Manager Validation Services
Approval

This test report may not be reproduced, except in full, without written permission of testing laboratory. The test results in this test report relates only to the tested sample, which is mentioned in this test report. Novero GmbH cannot be made responsible for any generalisations or conclusions drawn from this test report. Modification of the tested sample is prohibited and leads to invalidity of this test report.

Project support engineer:	Robert Müller	Report RF Exposure
Date of issue:	11-July-2013	Template version 1.0
Report No.:	EMC_BO_001849	Copyright © 2013 novero. All rights reserved.

CONTENTS

1. MAXIMUM PERMISSIBLE EXPOSURE	3
1.1. CALCULATION METHOD AND LIMIT	3
1.1.1 §1.1310	3
1.2. RESULTS	4
1.2.1 RESULTS FOR 850 MHz OPERATIONS (PART 22)	4
1.2.2 RESULTS FOR 1900 MHz OPERATIONS (PART 24)	4
1.2.3 RESULTS FOR 1700 MHz OPERATIONS (PART 27)	5

1. Maximum Permissible Exposure

1.1. Calculation method and limit

1.1.1 §1.1310

Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure) are specified in Table 1B of 47 CFR 1.1310 and table chapter 4.2 of RSS-102 standard.

Frequency range [MHz]	Power Density[mW/cm ²]
300 – 1500	f/1500
1500 – 100,000	1.0

Calculations can be made with the following equation according to OET bulletin 65:

$$S = \frac{EIRP}{4\pi R^2} = \frac{P * G}{4\pi R^2}$$

with G = 3dBi, R = 20cm

S = power density

P = power input of the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

EIRP = equivalent (or effective) isotropic radiated power

1.2. Results

1.2.1 Results for 850 MHz Operations (Part 22)

Band	Channel	Frequency [MHz]	Conducted Peak Power [dBm]	Duty Cycle [dB]	Average Power [dBm]	MPE [mW/cm ²]	MPE Limit [mW/cm ²] §1.1310	Result
GSM	128	824.2	32.20	-9.03	23.17	0.0824	0.5495	PASSED
	192	837.0	32.40	-9.03	23.37	0.0863	0.5580	PASSED
	251	848.8	32.24	-9.03	23.21	0.0831	0.5659	PASSED
GPRS	128	824.2	32.23	-3.01	29.22	0.3318	0.5495	PASSED
	192	837.0	32.43	-3.01	29.42	0.3475	0.5580	PASSED
	251	848.8	32.29	-3.01	29.28	0.3364	0.5659	PASSED
EGPRS	128	824.2	29.59	-3.01	26.58	0.1807	0.5495	PASSED
	192	837.0	29.78	-3.01	26.77	0.1888	0.5580	PASSED
	251	848.8	29.77	-3.01	26.76	0.1883	0.5659	PASSED
FDD V	4132	826.4	25.87	0.00	25.87	0.1534	0.5509	PASSED
	4175	835.0	25.94	0.00	25.94	0.1559	0.5567	PASSED
	4233	846.6	25.86	0.00	25.86	0.1531	0.5644	PASSED

For GPRS/EGPRS mode Multislot Class12 (maximal 4 Uplink time slots) is considered for duty cycle.

1.2.2 Results for 1900 MHz Operations (Part 24)

Band	Channel	Frequency [MHz]	Conducted Peak Power [dBm]	Duty Cycle [dB]	Average Power [dBm]	MPE [mW/cm ²]	MPE Limit [mW/cm ²] §1.1310	Result
GSM	512	1850.2	29.47	-9.03	20.44	0.0439	1.0	PASSED
	661	1880.0	29.32	-9.03	20.29	0.0424	1.0	PASSED
	810	1908.8	29.13	-9.03	20.10	0.0406	1.0	PASSED
GPRS	512	1850.2	29.49	-3.01	26.48	0.1766	1.0	PASSED
	661	1880.0	29.31	-3.01	26.30	0.1694	1.0	PASSED
	810	1908.8	29.12	-3.01	26.11	0.1622	1.0	PASSED
EGPRS	512	1850.2	27.07	-3.01	24.06	0.1011	1.0	PASSED
	661	1880.0	26.95	-3.01	23.94	0.0984	1.0	PASSED
	810	1908.8	26.60	-3.01	23.59	0.0908	1.0	PASSED
FDD II	4132	1852.4	25.24	0	25.24	0.1327	1.0	PASSED
	4175	1880.0	24.85	0	24.85	0.1213	1.0	PASSED
	4233	1907.6	25.84	0	25.84	0.1210	1.0	PASSED

For GPRS/EGPRS mode Multislot Class12 (maximal 4 Uplink time slots) is considered for duty cycle.

1.2.3 Results for 1700 MHz Operations (Part 27)

Band	Mode	Channel	Frequency [MHz]	Conducted Peak Power [dBm]	Average Power [dBm]	MPE [mW/cm ²]	MPE Limit [mW/cm ²] §1.1310	Result
FDD IV	RMC	1312	1712.4	26.13	26.13	0.1629	1.0	PASSED
		1412	1732.4	26.17	26.17	0.1644	1.0	PASSED
		1513	1752.5	26.09	26.09	0.1614	1.0	PASSED