

FCC PART 15.249 TEST REPORT

For

Jiaxing Shufude Electric Bed Co., Ltd.

East No. 07 Provincial Road, Tengyun Village Wangjiangjing Development Zone, Jiaxing, Zhejiang, China

FCC ID: WKZRF358A

Report Type:		Product '	Гуре:		
Original Report		REMOTE (CONTROL	358A	
Test Engineer:	Matt Yao		Newt	t. Jas	
Report Number:	RKS15101200	1-00A			
Report Date:	2015-10-16				
Reviewed By:	Jesse Huang EMC Manager	-	Jesse. Hu	ionf	
Test Laboratory:	Bay Area Comp Chenghu Road, No.248,Kunsha Tel: +86-0512- Fax: +86-0512- www.baclcorp.	Kunshan De in, Jiangsu, C 86175000 88934268	velopment 2		CH.
				WHITE OF THE PARTY	SHIME

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	4
JUSTIFICATION	
EUT Exercise Software	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC§15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	6
Antenna Connector Construction	6
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION	7
APPLICABLE STANDARD	7
Measurement Uncertainty	7
EUT Setup	8
TEST EQUIPMENT SETUP	9
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	
TEST DATA	10
FCC §15.215(C) – 20 DB BANDWIDTH TESTING	15
APPLICABLE STANDARD	15
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	
T D	1.7

Report No.: RKS151012001-00A

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Jiaxing Shufude Electric Bed Co., Ltd.'s product, model number: RF358A (FCC ID: WKZRF358A) (the "EUT") in this report was a REMOTE CONTROL, was measured approximately: 106.5 mm (L) x51 mm (W) x 21mm (H), Weight:110g, rated input voltage: DC 4.5V DC 1.5V*3 AA battery.

Report No.: RKS151012001-00A

Note: The manufacturer information:

Name: OKIN Refined Electric Technology Co., Ltd/Address: Plant 4, No. 410, xingyonglian Road, Wangjiangjing Development Zone, Jiaxing, Zhejiang, China

All measurement and test data in this report was gathered from production sample serial number: 20151012004. (Assigned by BACL, Kunshan). The EUT was received on 2015-10-12.

Objective

This type approval report is prepared on behalf of Jiaxing Shufude Electric Bed Co., Ltd. in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

N/A.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.249 Page 3 of 17

SYSTEM TEST CONFIGURATION

Justification


The system was configured in testing mode which was provided by manufacturer.

EUT was tested with Channel 2403MHz, 2440MHz and 2480MHz.

EUT Exercise Software

No software was used during the test.

Block Diagram of Test Setup



Report No.: RKS151012001-00A

FCC Part 15.249 Page 4 of 17

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Not Applicable
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.249(d)	Out of Band Emission	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

Report No.: RKS151012001-00A

Not Applicable: The EUT is battery operated equipment.

FCC Part 15.249 Page 5 of 17

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Report No.: RKS151012001-00A

Antenna Connector Construction

The EUT has one integral antenna arrangement and antenna gain is 1dBi, which was permanently attached ,fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC Part 15.249 Page 6 of 17

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Report No.: RKS151012001-00A

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)		
902–928 MHz	50	500		
2400–2483.5 MHz	50	500		
5725–5875 MHz	50	500		
24.0–24.25 GHz	250	2500		

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Kunshan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

FCC Part 15.249 Page 7 of 17


Measurement						
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB					
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB					
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB					

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

FCC Part 15.249 Page 8 of 17

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP	
Above 1 CHz	1MHz	3 MHz	/	PK	
Above 1 GHz	1MHz	10 Hz	/	Ave.	

Report No.: RKS151012001-00A

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit –Corrected Amplitude

FCC Part 15.249 Page 9 of 17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrunent	Amplifier	330	171377	2015-09-16	2016-09-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-05-20	2016-05-19
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2014-11-07	2015-11-06
ETS	Horn Antenna	3115	6229	2014-11-07	2015-11-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-11-04	2015-11-03
Mini	Pre-amplifier	ZVA-183-S+	857001418	2015-09-16	2016-09-16
R&S	Auto test Software	EMC32	V 09.10.0	-	-

Report No.: RKS151012001-00A

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249, with the worst margin reading of:

2.17 dB at 2402 MHz in the Horizontal polarization

Test Data

Environmental Conditions


Temperature:	25.6°C
Relative Humidity:	52%
ATM Pressure:	101.2 kPa

The testing was performed by Matt Yao on 2015-10-12.

FCC Part 15.249 Page 10 of 17

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

30MHz-1GHz:



Report No.: RKS151012001-00A

Frequency	Receiver		Turntable Rx Ai		tenna	Corrected	Corrected	FCC Part 15.249/205/209	
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (cm)	Polar (H/V)	Factor (dB)	Amplitude (dBμV/m)	Limit (dB	Margin (dB)
33.900450	21.25	QP	0.0	200.0	V	-10.4	10.85	40.00	29.15
55.361200	22.75	QP	214.0	200.0	V	-16.6	6.15	40.00	33.85
70.994950	27.01	QP	194.0	100.0	V	-17.0	10.01	40.00	29.99
165.643850	19.13	QP	245.0	100.0	Н	-12.1	7.03	43.50	36.47
189.649900	19.76	QP	323.0	100.0	V	-12.0	7.76	43.50	35.74
303.998600	31.25	QP	249.0	100.0	Н	-10.1	21.15	46.00	24.85

FCC Part 15.249 Page 11 of 17

Test Mode: Transmitting (Scan with X, Y, Z axis, the worst case is X axis)

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Correcte	Corrected Amplitude	FCC Part 15.249/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)	Degree	Height (cm)	Polar (H/V)	d Factor (dB)	Ampittude (dBμV/m)	Limit (dB µ V/m)	Margin (dB)
			Low Cha	annel (2402	2 MHz)				
2403	97.75	PK	160	150	V	3.0	100.75	114	13.25
2403	88.36	Ave	160	150	V	3.0	91.36	94	2.64
2403	96.07	PK	220	200	Н	3.0	99.07	114	14.93
2403	88.83	Ave	220	200	Н	3.0	91.83	94	2.17
1201.667969	59.3	PK	200	150	Н	-2.1	57.2	74	16.8
1201.667969	48.26	Ave	200	150	Н	-2.1	46.16	54	7.84
2389.829411	35.27	PK	168	200	Н	3.8	39.07	74	34.93
2389.829411	22.03	Ave	168	200	Н	3.8	25.83	54	28.17
4804.415442	41.51	PK	78	200	Н	13.7	55.21	74	18.79
4804.415442	35.22	Ave	78	200	Н	13.7	48.92	54	5.08
6615.957828	34.23	PK	106	200	V	18.7	52.93	74	21.07
6615.957828	21.25	Ave	106	200	V	18.7	39.95	54	14.05
6645.771059	34.59	PK	33	150	Н	18.8	53.39	74	20.61
6645.771059	21.63	Ave	33	150	Н	18.8	40.43	54	13.57
7206.603697	34.97	PK	244	200	V	18.8	53.77	74	20.23
7206.603697	21.72	Ave	244	200	V	18.8	40.52	54	13.48

FCC Part 15.249 Page 12 of 17

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Correcte d Factor	Corrected	FCC Part 15.249/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (cm)	Polar (H/V)	(dB)	Amplitude (dBμV/m)	Limit (dB µ V/m)	Margin (dB)
			Middle C	hannel (24	40MHz)				
2440	97.42	PK	210	150	V	3.0	100.42	114	13.58
2440	89.66	Ave	210	150	V	3.0	91.66	94	2.34
2440	95.78	PK	130	200	Н	3.0	98.78	114	15.22
2440	89.38	Ave	130	200	Н	3.0	91.38	94	2.62
1220.031589	57.06	PK	189	150	Н	-1.9	55.16	74	18.84
1220.031589	46.08	Ave	189	150	Н	-1.9	44.18	54	9.82
4880.875443	41.19	PK	26	150	Н	13.9	55.09	74	18.91
4880.875443	33.02	Ave	26	150	Н	13.9	46.92	54	7.08
6665.311954	35.18	PK	11	200	V	18.8	53.98	74	20.02
6665.311954	21.69	Ave	11	200	V	18.8	40.49	54	13.51
6980.261312	33.8	PK	57	200	V	19.8	53.6	74	20.4
6980.261312	20.45	Ave	57	200	V	19.8	40.25	54	13.75
7320.779580	33.65	PK	78	200	V	20.8	54.45	74	19.55
7320.779580	22.43	Ave	78	200	V	20.8	43.23	54	10.77
7858.419905	29.18	PK	227	200	Н	22.5	51.68	74	22.32
7858.419905	15.31	Ave	227	200	Н	22.5	37.81	54	16.19

FCC Part 15.249 Page 13 of 17

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Correcte d Factor	Corrected	FCC Part 15.249/205/209	
	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (cm)	Polar (H/V)	(dB)	Amplitude (dBμV/m)	Limit (dB µ V/m)	Margin (dB)
			High Ch	annel (248	0MHz)				
2480	96.6	PK	62	150	V	3.0	99.6	114	14.4
2480	87.12	Ave	62	150	V	3.0	90.12	94	3.88
2480	95.84	PK	230	200	Н	3.0	98.84	114	15.16
2480	87.55	Ave	230	200	Н	3.0	90.55	94	3.45
2483.565947	41.06	AVE	176	100	V	4.3	45.36	54	8.73
2483.565947	39.74	PK	176	100	V	4.3	44.04	74	30.05
4959.884051	42.24	PK	264	150	V	14.1	56.34	74	17.66
4959.884051	35.4	Ave	264	150	V	14.1	49.5	54	4.5
6688.709825	34.93	PK	332	200	V	18.9	53.83	74	20.17
6688.709825	21.27	Ave	332	200	V	18.9	40.17	54	13.83
6980.575949	33.83	PK	93	150	Н	19.8	53.63	74	20.37
6980.575949	20.45	Ave	93	150	Н	19.8	40.25	54	13.75
7440.368290	34.33	PK	93	150	Н	21.2	55.53	74	18.47
7440.368290	27.69	Ave	93	150	Н	21.2	48.89	54	5.11
7816.889821	29.1	PK	296	200	V	22.4	51.5	74	22.5
7816.889821	15.28	Ave	296	200	V	22.4	37.68	54	16.32

FCC Part 15.249 Page 14 of 17

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Report No.: RKS151012001-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-11-4	2015-11-3

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.6°C
Relative Humidity:	51 %
ATM Pressure:	101.2kPa

^{*} The testing was performed by Matt Yao on 2015-10-14.

Test Result: Compliant.


Please refer to following tables and plots

FCC Part 15.249 Page 15 of 17

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	2.39
Middle	2440	2.43
High	2480	2.39


Low Channel



FCC Part 15.249 Page 16 of 17

Middle Channel

Report No.: RKS151012001-00A



High Channel



***** END OF REPORT *****

FCC Part 15.249 Page 17 of 17