



A D T

RF EXPOSURE REPORT

REPORT NO.: SA131126D16A

MODEL NO.: TR10Cxy

FCC ID: WL6-TRBC1CD1

RECEIVED: Dec. 18, 2013

TESTED: Dec. 19, 2013 ~ Jan. 16, 2014

ISSUED: Jan. 17, 2014

APPLICANT: Elitegroup Computer Systems Co., Ltd

ADDRESS: No. 239, Ti Ding Blvd., Sec. 2, Taipei, Taiwan 11493

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan, R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



A D T

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA	5
4. CLASSIFICATION.....	5
5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6



A D T

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA131126D16A	Original release	Jan. 17, 2014



A D T

1. CERTIFICATION

PRODUCT: Wireless Motherboard
BRAND NAME: ECS ELITEGROUP
MODEL NO.: TR10Cxy (x=0~9, A~Z or blank or "-";y=0~9, A~Z or blank or "-")
APPLICANT: Elitegroup Computer Systems Co., Ltd
TESTED: Dec. 19, 2013 ~ Jan. 16, 2014
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: FCC Part 2 (Section 2.1091)
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment has (model no.: TR10CD1) been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Annie Chang , **DATE:** Jan. 17, 2014
(Annie Chang / Supervisor)

APPROVED BY : Rex Lai , **DATE:** Jan. 17, 2014
(Rex Lai / Assistant Manager)

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412 ~ 2462	19.99	4.20	20	0.0522	1.00
5180 ~ 5320	9.67	4.20	20	0.0048	1.00
5745 ~ 5825	22.33	4.20	20	0.0895	1.00
2402 ~ 2480	4.31	3.37	20	0.0012	1.00

CONCLUSION:

Both of the modules can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

1. WLAN (2.4G) + BLUETOOTH = $0.0522/1 + 0.0012/1 = 0.0534$

2. WLAN (5.0G) + BLUETOOTH = $0.0895/1 + 0.0012/1 = 0.0907$

Therefore, the maximum calculation of this situation is 0.1441, which is less than the “1” limit.

--- END ---