





### ISO/IEC17025 Accredited Lab.

Report No: FCC0807223 File reference No: 2008-08-29

Applicant: Shenzhen ART-TECH R/C Hobby Co., Ltd.

Product: 2.4G Radio Control system

Model No: ETC61-2.4GHz

Brand Name: E-FLY

Test Standards: FCC Part 15 Subpart C, Paragraph 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: August 29,2008

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

### SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 0807223 Page 2 of 54

Date: 2008-08-29



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

### **CNAL-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

# FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

# IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 54

Report No: 0807223 Date: 2008-08-29



# Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	5
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards.	7
4.0	EUT Modification	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
6.5	Test Result.	14
7.0	Band Edge	29
8.0	Antenna Requirement.	32
9.0	20dB Bandwidth.	33
10.0	FCC ID Label	35
11.0	Photo of Test Setup and EUT View.	37

Date: 2008-08-29



### 1.0 General Details

### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

### 1.2 Applicant Details

Applicant: Shenzhen ART-TECH R/C Hobby Electronic Limited

Address: 3/F,NO.1 Wanyelong Industrial Park,Liyuan Industrial Area,Tangtou Village,Shiyan

Town, Baoan District, Shenzhen City, China

Telephone: 0755-29810925-822 Fax: 0755-29810957

### 1.3 Description of EUT

Product: 2.4G Radio Control system

Manufacturer: Shenzhen ART-TECH R/C Hobby Co., Ltd.

Brand Name: E-FLY

Model Number: ETC61-2.4GHz Additional Model Name ETC62-2.4GHz

Additional Trade Name N/A

Rating: Input: DC12 (8pcs AAA batteries)

Modulation Type: GFSK

Operation Frequency 2402-2480MHz

Number of Channel 195

### 1.4 Submitted Sample

2 Sample

### 1.5 Test Duration

2008-08-02 to 2008-08-26

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 5 of 54

Report No: 0807223 Date: 2008-08-29



1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

2.0		Test Equi	ipments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2007-12-05	2008-12-04
Absorbing Clamp	ROHDE&SCHWARZ	MDS-21	100126	2007-12-05	2008-12-04
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2007-12-05	2008-12-04
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2007-12-05	2008-12-04
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2007-12-05	2008-12-04
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2008-04-26	2009-04-25
4-WIRE ISN	ROHDE&SCHWARZ	ENY 41	830663/044	2008-02-18	2009-02-17
GG ENY22 Double 2-Wire ISN	ROHDE&SCHWARZ	ENY22	83066/016	2008-02-18	2009-02-17
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2008-02-18	2009-02-17
System Controller	CT	SC100	-	2008-02-18	2009-02-17
Printer	EPSON	РНОТО ЕХЗ	CFNH234850	2008-02-18	2009-02-17
FM-AM Signal Generator	JUNG.JIN	SG-150M	389911177	2008-02-18	2009-02-17
Color TV Pattern Generator	PHILIPS	PM5418	LO621747	2008-02-18	2009-02-17
Computer	IBM	8434	1S8434KCE99BLX LO*	-	-
Oscillator	KENWOOD	AG-203D	3070002	2008-02-18	2009-02-17

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 6 of 54

			<>)/		
Spectrum Analyzer	HAMEG	HM5012	<del>-</del>	2008-04-26	2009-04-25
Power Supply	LW	APS1502	-	-	-
5K VA AC Power Source	California Instruments	5001iX	56060	2008-02-18	2009-02-17
CDN	EM TEST	CDN M2/M3	-	2008-02-18	2009-02-17
Attenuation	EM TEST	ATT6/75	-	2008-02-18	2009-02-17
Resistance	EM TEST	R100	-	2008-02-18	2009-02-17
Electromagnetic Injection Clamp	LITTHI	EM101	35708	2008-02-18	2009-02-17
Signal Generator	ROHDE&SCHWARZ	SMT03	100029	2008-02-18	2009-02-17
Power Amplifier	AR	150W1000	300999	2008-02-18	2009-02-17
Field probe	Holaday	HI-6005	105152	2008-02-18	2009-02-17
Bilog Antenna	Chase	CBL6111C	2576	2008-02-18	2009-02-17
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2008-02-18	2009-02-17
3m OATS			N/A	2008-02-18	2009-02-17
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2008-08-18	2009-08-17
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2008-04-26	2009-04-25

Page 7 of 54

Report No: 0807223 Date: 2008-08-29



### 3.0 **Technical Details**

### 3.1 **Summary of test results**

The EUT has been tested according to the	ie following speci	ncations:	
Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	PASS	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	PASS	Complies

### 3.2 **Test Standards**

FCC Part 15 Subpart C, Paragraph 15.249

### 4.0 **EUT Modification**


No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Report No: 0807223 Date: 2008-08-29



### 5. Power Line Conducted Emission Test

### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 500hm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

### Block diagram of Test setup



### 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

One channels are provided to the EUT

### A. EUT

Device	Manufacturer	Model	FCC ID
2.4GHz Radio	ART-TECH	ETC61-2.4G	WL9ETC
Control system			

### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 9 of 54

Report No: 0807223 Date: 2008-08-29



### C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Eraguanay (MHz)	Class A Lir	nits (dB µ V)	Class B Limits (dB $\mu$ V)		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0	

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Report No: 0807223 Date: 2008-08-29




# A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Charging

**Results:** Pass

Please refer to following diagram for individual

### **Conducted Emission Measurement**



Eraguanav		Reading	Limi	t		
Frequency (MHz)	Line	<b>;</b>	Neutral		(dB µ	V)
	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.1901	40.60	21.50			64.03	54.03
4.1266	27.40	16.50			56.00	46.00

Report No: 0807223 Date: 2008-08-29




### B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Charging

**Results:** Pass

Please refer to following diagram for individual

### **Conducted Emission Measurement**



Eraguanay		Reading	Limi	t		
Frequency (MHz)	Live		Neutral		(dB µ V)	
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.1941			42.40	25.60	63.86	53.86
4.1931	-	-	30.20	18.80	56.00	46.00

Page 12 of 54

Report No: 0807223 Date: 2008-08-29



### 6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2001.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

# Block diagram of Test setup Distance = 3m Computer Pre -Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT
  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

Page 13 of 54

Report No: 0807223 Date: 2008-08-29



### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

### A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Strength of Fundamental (3m)			Field S	trength of Harmo	onics (3m)
(MHz)	mV/m	dBuV/m		uV/m	dBu	V/m
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

### B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

Report No: 0807223 Page 14 of 54

Date: 2008-08-29



### 6.5 Test result

### $\mathbf{A}$ **Fundamental & Harmonics Radiated Emission Data**

Product:	2.4G Radio Control system	Test Mode:	Low Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	12VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2402	81.6/73.2	Н	114/94	-32.4/-20.8
2402	89.6/80.8	V	114/94	-24.4/-13.2
4804	49.6/39.4	V	74/54	-24.4/-14.6
4804	44.5/30.3	Н	74/54	-29.5/-23.7
7206		H/V	74/54	
9608		H/V	74/54	
12010		H/V	74/54	
14412		H/V	74/54	
16814		H/V	74/54	
19216		H/V	74/54	
21618		H/V	74/54	
24020		H/V	74/54	

Page 15 of 54

Product:	2.4G Radio Control system	Test Mode:	Middle Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	12VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2442	62.7/51.9	Н	114/94	-51.3/-42.1
2442	74.5/64.8	V	114/94	-39.5/-29.2
4884	41.3/30.8	V	74/54	-32.7/-23.2
4884	38.4/28.9	Н	74/54	-35.6/-25.1
7326		H/V	74/54	
9768		H/V	74/54	
12210		H/V	74/54	
14652		H/V	74/54	
17094		H/V	74/54	
19536		H/V	74/54	
21978		H/V	74/54	
24420		H/V	74/54	

Page 16 of 54

Report No: 0807223 Date: 2008-08-29

Product:	2.4G Radio Control system	Test Mode:	High Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	12VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2480	75.7/68.3	Н	114/94	-38.3/-25.7
2480	84.7/72.8	V	114/94	-29.3/-21.2
4960	49.5/37.2	Н	74/54	-24.5/-16.8
4960	53.9/42.1	V	74/54	-20.14/-11.9
7440		H/V	74/54	
9920		H/V	74/54	
12400		H/V	74/54	
14880		H/V	74/54	
17360		H/V	74/54	
19840		H/V	74/54	
22320		H/V	74/54	
24800		H/V	74/54	

Note: (1) PK= Peak, AV= Average

- (2) Emission Level = Reading Level + Probe Factor + Cable Loss-AMP.
- (3)Margin=Emission-Limits
- (4)According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) Due to measured PK value less than the AV limit, the measured AV value must be less than AV limit
- (6) Because the two models employ the same RF module, the model of ETC61-2.4G, producing the worse case after pre-scanning, is selected to conduct test.


Page 17 of 54

Report No: 0807223 Date: 2008-08-29



Please refer to the following test plots for details

Low Channel: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 18 of 54

Report No: 0807223 Date: 2008-08-29



**Low Channel: Vertical** 




Page 19 of 54

Report No: 0807223 Date: 2008-08-29



**Middle Channel: Horizontal** 




The report refers only to the sample tested and does not apply to the bulk.

Page 20 of 54

Report No: 0807223 Date: 2008-08-29



Middle Channel :: Vertical




The report refers only to the sample tested and does not apply to the bulk.

Page 21 of 54

Report No: 0807223 Date: 2008-08-29



**High Channel: Horizontal** 




The report refers only to the sample tested and does not apply to the bulk.

Page 22 of 54

Report No: 0807223 Date: 2008-08-29



**High Channel: Vertical** 




Page 23 of 54

Report No: 0807223 Date: 2008-08-29



18-25G High Channel




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 24 of 54



18-25G High Channel



Report No: 0807223 Page 25 of 54

Date: 2008-08-29



### Test result

### General Radiated Emission Data and Harmonics Radiated Emission Data

### Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Low channel Model: **ETC61-2.4GHz** 

**Results: Pass** 

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
	-	Н	1
		V	


Page 26 of 54

Report No: 0807223 Date: 2008-08-29




Test Figure: Low Channel Model: ETC61-2.4GHz

Η



Date: 5.AUG.2008 11:59:00





Date: 5.AUG.2008 11:57:58

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0807223 Page 27 of 54

Date: 2008-08-29



### Test result

### General Radiated Emission Data and Harmonics Radiated Emission Data

### Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Low channel Model: ETC62-2.4GHz

**Results: Pass** 


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \( \mu \)V/m)
	1	Н	-
111.56	47.52	V	43.50


Page 28 of 54

Report No: 0807223 Date: 2008-08-29



Test Figure: Low Channel Model: ETC62-2.4GHz





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0807223 Page 29 of 54

Date: 2008-08-29



# 7. Band Edge

### **Band Edge Limit**

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB below that in the 100kHz, bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Page 30 of 54

Report No: 0807223 Date: 2008-08-29



### **Test Result**

Product:	2.4G Padio	Control system	Test Mode:	Low Ch	annal
Mode Mode		Transmitting	Input Voltage	DC1	
Temperature		deg. C,	Humidity	+	
Test Result:		Pass	Detector	56% RH PK	
Test Result.	PK (dBμV/m)	38.6(V)/36.1(H)	Detector	74(dBµ	
2390MHz	$AV(dB\mu V/m)$	Limit		54(dBp	
Test Figure only fo		27.4( V )/20.0(11)		J4(uDμ	t v / III )
rest rigure only ic					
Ref Lvl	Marker	1 [ 1] 89.70 dBμV	RBW 100 kH VBW 100 kH		0 dB
$97 \text{ dB}\mu\text{V}$	2	.40214429 GHz	SWT 28 ms		dB $\mu$ V
97					
			<b>v</b> 1	[T1] <sub>1</sub> 89.	70 dB $\mu$ V
90			∀2	[T1] 2.70214 [T1] 36.	<del>425 bnz</del> 30 dB <i>µ</i> V
			2		000 GHz
80					
70					
1MAX					1MA
60					
50					
30					
40					
Market Ma	hours and		11-mm	A Zurwin	and make
30	- Valor		Manapulan		
20		+			
10					
0					
-3 Start 2.3		11 MH	<u> </u>	C+c= 2	.42 GHz
			1∠/	3 LUP 2	.42 UNZ
Date: 05	.AUG.2008 17:	06:38			

### Note:1. Field Strength in restrict band measured in conventional manner

2. Because the two models employ the same RF module, the model of ETC61-2.4G, producing the worse case after pre-scanning, is selected to conduct test.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No: 0807223 Date: 2008-08-29

Product:	2.4G Radio	Control system	Tes	t Mode:		High C	hannel	
Mode	Keeping	Transmitting	Input	Voltage		DC1	2V	
Temperature	24	deg. C,	Humie	dity		56% RH		
Test Result:	]	Pass	D	etector		PK		
2483.5MHz	PK (dBμV/m)	40.2(H)/43.7(V)		[ imit		74(dB <sub>l</sub>	ιV/m)	
2403.3WIIIZ	$AV(dB\mu V/m)$	31.8(H)/32.9(V)	Limit			54(dB <sub>l</sub>	ιV/m)	
Test Figure only for	r reference							
Ŕ	Marker	1 [T1]	RBW	100 kH	Hz RF	- Att	0 dB	
Ref Lvl		$87.35~\mathrm{dB}\mu\mathrm{V}$	VBW	100 kH				
97 dB $\mu$ V	2	.48016032 GHz	SWT	12.5 ms	s Ur	nit	dBμV	
97				<b>v</b> <sub>1</sub>	[T1]	87.	$35~\mathrm{dB}\mu\mathrm{V}$	Α
90				7 ∇2	[T1]	<del>2.48818</del> 43.	<del>832 GHz</del> 33 dB <i>µ</i> V	
							000 GHz	
80								
70								
1MAX								1MA
50			porter Notes	My2				
40			<u> </u>	~~~	μ <u>,                                     </u>			
30	Mary Many Mary Mary	mula marketing			May	~~wholey	moral de	
Mylmm mm	Janous -							
20								
20								
10								
10								
-3								
Start 2.4	5 GHz	5 MI	Hz/			Stop	2.5 GHz	
Date: 05.	AUG.2008 17:	28:40						

### Note:1. Field Strength in restrict band measured in conventional manner

2. Because the two models employ the same RF module, the model of ETC61-2.4G, producing the worse case after pre-scanning, is selected to conduct test.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0807223 Page 32 of 54

Date: 2008-08-29



## 8.0 Antenna Requirement


### **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.


This product has a permanent antenna, fulfill the requirement of this section.

Test Result: Pass

Page 33 of 54



Page 34 of 54



Page 35 of 54

Product:	2.4G Radio Control system			Tes	t Mode:		High C	hannel	
Mode	Keepi	ng Transmit	ting	Test V	oltage		DC12V		
Temperature		24 deg. C,		Humio	Humidity		56% RH PK		
Test Result:	Pass			De	etector				
OdB Bandwidth		1.148MHz					_	-	
Ref Lvl	Delta		51 dB	RBW VBW	100 k 100 k	Hz	FAtt	0 dB	
97 dBμV		1.148296	659 MHz	SWT	5 m	s U	nit	dBμV	_
90					<b>▼</b> 1	[T1]	65.	20 dBμV	Α
80					<b>1</b>	[T1]	1.14829	.51 dB 659 MHz	
					>				
IMAX	ΙΒμν-	1 January			~	1			1 M
60	Mary Mary	, p				Mun	W. Marrie		
50								Mark Mark	
40									
30									
20									
10									
0									

Page 36 of 54

Report No: 0807223 Date: 2008-08-29




### 10.0 FCC ID Label

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

### Mark Location:



Page 37 of 54

Report No: 0807223 Date: 2008-08-29



## 11.0 Photo of testing

### 11.1 Conducted test View—



Page 38 of 54

Report No: 0807223 Date: 2008-08-29



## 11.2 Radiated emission test view





Page 39 of 54

Report No: 0807223 Date: 2008-08-29



#### 11.3 Photo for the EUT

# Outside View



Page 40 of 54

Report No: 0807223 Date: 2008-08-29





Page 41 of 54

Report No: 0807223 Date: 2008-08-29





Page 42 of 54

Report No: 0807223 Date: 2008-08-29





Page 43 of 54

Report No: 0807223 Date: 2008-08-29





Page 44 of 54

Report No: 0807223 Date: 2008-08-29






Page 45 of 54

Report No: 0807223 Date: 2008-08-29





Page 46 of 54

Report No: 0807223 Date: 2008-08-29






Page 47 of 54

Report No: 0807223 Date: 2008-08-29






Page 48 of 54

Report No: 0807223 Date: 2008-08-29






Page 49 of 54

Report No: 0807223 Date: 2008-08-29





Page 50 of 54

Report No: 0807223 Date: 2008-08-29






DSC-H10 F3.5 1/10s ISO 400

Page 51 of 54

Report No: 0807223 Date: 2008-08-29





DSC-H10 F4.0 1/50s ISO 200

Page 52 of 54

Report No: 0807223 Date: 2008-08-29





DSC-H10 F3.5 1/50s ISO125

Page 53 of 54

Report No: 0807223 Date: 2008-08-29





Page 54 of 54

Report No: 0807223 Date: 2008-08-29





## -- End of the report--