

FCC RF Test Report

APPLICANT : Shanghai Longcheer 3g Technology Co., Ltd
EQUIPMENT : LTE USB Modem
BRAND NAME : FSMobile
MODEL NAME : WM320
FCC ID : WLPWM320
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
MAX. ERP/EIRP POWER : GSM850 (GPRS 8) : 0.12 W
GSM850 (EDGE 8) : 0.06 W
GSM1900 (GPRS 8) : 0.83 W
GSM1900 (EDGE 8) : 0.48 W

The product was received on Mar. 07, 2012 and completely tested on Mar. 21, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	5
1.4 Emission Designator and Maximum ERP/EIRP Power	6
1.5 Testing Site	6
1.6 Applied Standards	6
1.7 Ancillary Equipment List.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
3 TEST RESULT.....	9
3.1 Conducted Output Power Measurement.....	9
3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	11
3.3 Occupied Bandwidth Measurement	15
3.4 Band Edge Measurement.....	20
3.5 Conducted Emission Measurement	29
3.6 Field Strength of Spurious Radiation Measurement	40
3.7 Frequency Stability Measurement.....	50
4 LIST OF MEASURING EQUIPMENT	55
5 UNCERTAINTY OF EVALUATION	56
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG230705	Rev. 01	Initial issue of report	Apr. 10, 2012

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	Under limit 37.12 dB at 2510 MHz
3.7	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

Shanghai Longcheer 3g Technology Co., Ltd

No.1,Building 5, 299 Bisheng Rd, Zhangjiang Hi-Tech Park, Pudong, Shanghai, P.R. China

1.2 Manufacturer

Shanghai Longcheer 3g Technology Co., Ltd

No.1,Building 5, 299 Bisheng Rd, Zhangjiang Hi-Tech Park, Pudong, Shanghai, P.R. China

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	LTE USB Modem
Brand Name	FSMobile
Model Name	WM320
FCC ID	WLPWM320
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 29.36 dBm GSM1900 : 29.81 dBm
Antenna Type	Fixed Internal Antenna
HW Version	LQBMI34B1-2
SW Version	LQBJC02.1.2_MI34
Type of Modulation	GSM / GPRS: GMSK EDGE: GMSK / 8PSK
EUT Stage	Identical Prototype

Remark:

1. EUT is only support GPRS/EDGE 850/1900 in US band.
2. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Emission Designator and Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Emission Designator	Maximum ERP/EIRP
Part 22	GSM850 GPRS 8	GMSK	244KGXW	0.12 W
Part 22	GSM850 EDGE 8	8PSK	244KG7W	0.06 W
Part 24	GSM1900 GPRS 8	GMSK	244KGXW	0.83 W
Part 24	GSM1900 EDGE 8	8PSK	252KG7W	0.48 W

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH01-KS	03CH01-KS	149928/4086E-1

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Vostro 1450	N/A	N/A	AC I/P: Unshielded, 0.8 m DC O/P: Shielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19000 MHz for GSM1900.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GPRS 8 Link ■ EDGE 8 Link


Note:

1. The maximum power levels are GPRS multi-slot class 8 mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS 8 (1 Uplink) – CS1	29.35	29.35	29.36	29.81	29.78	29.27
GPRS 10 (2 Uplink) – CS1	27.63	27.53	27.80	26.85	26.86	26.43
GPRS 11 (3 Uplink) – CS1	26.35	26.60	26.63	23.32	23.18	22.79
GPRS 12 (4 Uplink) – CS1	25.34	25.18	25.44	23.23	23.13	22.77
EDGE 8 (GMSK, 1 Uplink) – MCS1	28.99	29.03	29.19	29.79	29.46	29.17
EDGE 10 (GMSK, 2 Uplink) – MCS1	27.30	27.18	27.53	26.83	26.46	26.36
EDGE 11 (GMSK, 3 Uplink) – MCS1	25.97	26.25	26.35	23.29	22.94	22.60
EDGE 12 (GMSK, 4 Uplink) – MCS1	25.43	25.31	25.00	23.43	23.39	23.06
EDGE 8 (8PSK, 1 Uplink) – MCS9	25.54	25.59	25.69	26.80	26.14	25.90
EDGE 10 (8PSK, 2 Uplink) – MCS9	22.95	22.96	23.13	24.32	24.09	23.96
EDGE 11 (8PSK, 3 Uplink) – MCS9	21.58	21.59	21.73	23.05	22.70	22.42
EDGE 12 (8PSK, 4 Uplink) – MCS9	21.68	21.64	21.78	21.70	21.63	21.24

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band						
Modes	GSM850 (GPRS 8)			GSM850 (EDGE 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
Conducted Power (dBm)	29.35	29.35	29.36	25.54	25.59	25.69
Conducted Power (Watts)	0.86	0.86	0.86	0.36	0.36	0.37

PCS Band						
Modes	GSM1900 (GPRS 8)			GSM1900 (EDGE 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
Conducted Power (dBm)	29.81	29.78	29.27	26.80	26.14	25.90
Conducted Power (Watts)	0.96	0.95	0.85	0.48	0.41	0.39

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$

P_s (dBm) : Input power to substitution antenna.

G_s (dBi or dBd) : Substitution antenna Gain.

$E_t = R_t + AF$


$E_s = R_s + AF$

AF (dB/m) : Receive antenna factor

R_t : The highest received signal in spectrum analyzer for EUT.

R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup



3.2.5 Test Result of ERP

GSM850 (GPRS 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-26.21	-48.12	0.00	-1.08	20.83	0.12
836.40	-27.77	-48.28	0.00	-0.93	19.58	0.09
848.80	-27.90	-48.35	0.00	-0.76	19.69	0.09
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-33.71	-47.97	0.00	-1.08	13.18	0.02
836.40	-33.13	-48.01	0.00	-0.93	13.95	0.02
848.80	-32.44	-48.05	0.00	-0.76	14.85	0.03

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-29.80	-48.12	0.00	-1.08	17.24	0.05
836.40	-30.24	-48.28	0.00	-0.93	17.11	0.05
848.80	-29.80	-48.35	0.00	-0.76	17.79	0.06
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-36.48	-47.97	0.00	-1.08	10.41	0.01
836.40	-34.77	-48.01	0.00	-0.93	12.31	0.02
848.80	-33.84	-48.05	0.00	-0.76	13.45	0.02

3.2.6 Test Result of EIRP

GSM1900 (GPRS 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-24.63	-51.88	0.00	1.96	29.21	0.83
1880.00	-26.65	-52.99	0.00	2.00	28.34	0.68
1909.80	-28.34	-54.28	0.00	1.98	27.92	0.62
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.36	-52.13	0.00	1.96	23.73	0.24
1880.00	-31.40	-53.17	0.00	2.00	23.77	0.24
1909.80	-31.58	-54.13	0.00	1.98	24.53	0.28

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-27.06	-51.88	0.00	1.96	26.78	0.48
1880.00	-28.90	-52.99	0.00	2.00	26.09	0.41
1909.80	-29.78	-54.28	0.00	1.98	26.48	0.44
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-33.15	-52.13	0.00	1.96	20.94	0.12
1880.00	-32.82	-53.17	0.00	2.00	22.35	0.17
1909.80	-32.71	-54.13	0.00	1.98	23.40	0.22

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup




3.3.5 Test Result (Plots) of Occupied Bandwidth

Band :	GSM 850	Power Stage :	High
Test Mode :	GPRS 8 Link		


99% Occupied Bandwidth Plot on Channel 189


Date: 20.MAR.2012 00:00:14


26dB Bandwidth Plot on Channel 189


Date: 19.MAR.2012 23:58:53

Band :	GSM 850	Power Stage :	High
Test Mode :	EDGE 8 Link		


99% Occupied Bandwidth Plot on Channel 189


Date: 20.MAR.2012 22:48:08


26dB Bandwidth Plot on Channel 189


Date: 20.MAR.2012 22:46:49

Band :	GSM 1900	Power Stage :	High
Test Mode :	GPRS 8 Link		


99% Occupied Bandwidth Plot on Channel 661


Date: 20.MAR.2012 00:11:10


26dB Bandwidth Plot on Channel 661


Date: 20.MAR.2012 00:09:52

Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 661


Date: 20.MAR.2012 23:59:38

26dB Bandwidth Plot on Channel 661


Date: 20.MAR.2012 23:45:26

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.4.4 Test Setup

<Conducted Band Edge >






3.4.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Power Stage :	High
Test Mode :	GPRS 8 Link	26dB Bandwidth:	0.312MHz
Correction Factor:	0.23dB	Measurement Value:	-18.98dBm
Band Edge:	-18.75dBm		


Lower Band Edge Plot on Channel 128



Date: 20.MAR.2012 00:02:07

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Power Stage :	High
Test Mode :	GPRS 8 Link	26dB Bandwidth:	0.316MHz
Correction Factor:	0.23dB	Measurement Value:	-17.44dBm
Band Edge:	-17.21dBm		

Higher Band Edge Plot on Channel 251


Date: 20.MAR.2012 00:02:33

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link	26dB Bandwidth:	0.308MHz
Correction Factor:	0.11dB	Measurement Value:	-25.69dBm
Band Edge:	-25.58dBm		

Lower Band Edge Plot on Channel 128


Date: 20.MAR.2012 22:49:58

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link	26dB Bandwidth:	0.294MHz
Correction Factor:	0.11dB	Measurement Value:	-24.83dBm
Band Edge:	-24.72dBm		

Higher Band Edge Plot on Channel 251


Date: 20.MAR.2012 22:50:24

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Power Stage :	High
Test Mode :	GPRS 8 Link	26dB Bandwidth:	0.310MHz
Correction Factor:	0.20dB	Measurement Value:	-18.50dBm
Band Edge:	-18.30dBm		

Lower Band Edge Plot on Channel 512


Date: 20.MAR.2012 00:13:00

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Power Stage :	High
Test Mode :	GPRS 8 Link	26dB Bandwidth:	0.314MHz
Correction Factor:	0.20dB	Measurement Value:	-20.03dBm
Band Edge:	-19.83dBm		

Higher Band Edge Plot on Channel 810


Date: 20.MAR.2012 00:13:26

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link	26dB Bandwidth:	0.306MHz
Correction Factor:	0.20dB	Measurement Value:	-28.09dBm
Band Edge:	-27.89dBm		


Lower Band Edge Plot on Channel 512


Date: 20.MAR.2012 23:48:34

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link	26dB Bandwidth:	0.296MHz
Correction Factor:	0.20dB	Measurement Value:	-21.58dBm
Band Edge:	-21.38dBm		

Higher Band Edge Plot on Channel 810



Date: 20.MAR.2012 23:49:00

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup




3.5.5 Test Result (Plots) of Conducted Emission

Band :	GSM850	Channel :	CH189
Test Mode :	GPRS 8 Link		


Conducted Emission Plot between 30MHz ~ 1GHz


Date: 20.MAR.2012 00:46:50

Conducted Emission Plot between 1GHz ~ 3GHz



Date: 20.MAR.2012 00:48:07

Conducted Emission Plot between 3GHz ~ 7GHz




Date: 20.MAR.2012 00:48:48

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 20.MAR.2012 00:49:28

Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		


Conducted Emission Plot between 30MHz ~ 1GHz


Date: 20.MAR.2012 23:05:47

Conducted Emission Plot between 1GHz ~ 3GHz



Date: 20.MAR.2012 23:21:37

Conducted Emission Plot between 3GHz ~ 7GHz




Date: 20.MAR.2012 23:22:24

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 20.MAR.2012 23:14:43

Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS 8 Link		


Conducted Emission Plot between 30MHz ~ 1GHz


Date: 20.MAR.2012 00:25:59

Conducted Emission Plot between 1GHz ~ 3GHz



Date: 20.MAR.2012 00:26:45

Conducted Emission Plot between 3GHz ~ 7GHz




Date: 20.MAR.2012 00:28:04

Conducted Emission Plot between 7GHz ~ 13.6GHz




Date: 20.MAR.2012 00:28:44

Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 20.MAR.2012 00:29:43


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 21.MAR.2012 00:11:41

Conducted Emission Plot between 1GHz ~ 3GHz


Date: 21.MAR.2012 00:14:50


Conducted Emission Plot between 3GHz ~ 7GHz


Date: 21.MAR.2012 00:19:30

Conducted Emission Plot between 7GHz ~ 13.6GHz


Date: 21.MAR.2012 00:21:43

Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 21.MAR.2012 00:23:26

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$

3.6.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz




3.6.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.6.6 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	20~21°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 230705

Plan : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-65.14	-13	-52.14	-60.92	-65.79	0.57	3.37	H	Pass
2510	-54.57	-13	-41.57	-56.82	-56.80	0.78	5.16	H	Pass
3344	-59.30	-13	-46.30	-61.24	-62.94	0.87	6.66	H	Pass
4182	-62.66	-13	-49.66	-65.40	-67.25	0.97	7.71	H	Pass
5018	-59.35	-13	-46.35	-65.55	-65.02	1.09	8.91	H	Pass
5854	-58.09	-13	-45.09	-66.80	-64.53	1.22	9.81	H	Pass


Band :	GSM850	Temperature :	20~21°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 230705
 Plan : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-63.63	-13	-50.63	-59.28	-64.28	0.57	3.37	V	Pass
2510	-55.21	-13	-42.21	-58.32	-57.44	0.78	5.16	V	Pass
3344	-57.60	-13	-44.60	-59.58	-61.24	0.87	6.66	V	Pass
4182	-61.31	-13	-48.31	-65.15	-65.90	0.97	7.71	V	Pass
5018	-61.06	-13	-48.06	-66.00	-66.73	1.09	8.91	V	Pass
5854	-58.89	-13	-45.89	-66.88	-65.33	1.22	9.81	V	Pass


Band :	GSM850	Temperature :	20~21°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 230705
Plan : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-65.52	-13	-52.52	-61.30	-66.17	0.57	3.37	H	Pass
2510	-50.12	-13	-37.12	-52.37	-52.35	0.78	5.16	H	Pass
3345	-60.95	-13	-47.95	-62.89	-64.59	0.87	6.66	H	Pass
4182	-62.47	-13	-49.47	-65.21	-67.06	0.97	7.71	H	Pass
5018	-59.07	-13	-46.07	-65.27	-64.74	1.09	8.91	H	Pass
5854	-57.65	-13	-44.65	-66.36	-64.09	1.22	9.81	H	Pass

Band :	GSM850	Temperature :	20~21°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
Project : (FG) 230705
Plan : H

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-66.56	-13	-53.56	-62.21	-67.21	0.57	3.37	V	Pass
2510	-52.04	-13	-39.04	-55.15	-54.27	0.78	5.16	V	Pass
3344	-58.39	-13	-45.39	-60.37	-62.03	0.87	6.66	V	Pass
4182	-61.30	-13	-48.30	-65.14	-65.89	0.97	7.71	V	Pass
5018	-60.62	-13	-47.62	-65.56	-66.29	1.09	8.91	V	Pass
5854	-57.37	-13	-44.37	-65.36	-63.81	1.22	9.81	V	Pass




Band :	GSM1900	Temperature :	20~21°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 230705
Plan : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-62.78	-13	-49.78	-63.75	-69.16	0.78	7.16	H	Pass
5640	-60.13	-13	-47.13	-64.31	-68.67	1.04	9.58	H	Pass
7520	-60.97	-13	-47.97	-66.10	-71.08	1.35	11.46	H	Pass
9400	-66.14	-13	-53.14	-69.40	-77.20	1.75	12.81	H	Pass
11280	-60.29	-13	-47.29	-71.78	-71.38	2	13.09	H	Pass
13160	-60.59	-13	-47.59	-71.89	-72.30	2.04	13.75	H	Pass

Band :	GSM1900	Temperature :	20~21°C
Test Mode :	GPRS 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 230705
 Plan : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-54.31	-13	-41.31	-55.68	-60.69	0.78	7.16	V	Pass
5640	-57.73	-13	-44.73	-60.95	-66.27	1.04	9.58	V	Pass
7520	-61.63	-13	-48.63	-66.12	-71.74	1.35	11.46	V	Pass
9400	-67.58	-13	-54.58	-68.8	-78.64	1.75	12.81	V	Pass
11280	-59.80	-13	-46.80	-71.04	-70.89	2	13.09	V	Pass
13160	-61.15	-13	-48.15	-72.34	-72.86	2.04	13.75	V	Pass




Band :	GSM1900	Temperature :	20~21°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
Project : (FG) 230705
Plan : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-61.87	-13	-48.87	-62.84	-68.25	0.78	7.16	H	Pass
5640	-59.07	-13	-46.07	-63.25	-67.61	1.04	9.58	H	Pass
7520	-60.63	-13	-47.63	-65.76	-70.74	1.35	11.46	H	Pass
9400	-65.39	-13	-52.39	-68.65	-76.45	1.75	12.81	H	Pass
11280	-59.84	-13	-46.84	-71.33	-70.93	2	13.09	H	Pass
13160	-60.73	-13	-47.73	-72.03	-72.44	2.04	13.75	H	Pass

Band :	GSM1900	Temperature :	20~21°C
Test Mode :	EDGE 8 Link	Relative Humidity :	45~46%
Test Engineer :	Chenmy Cheng	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 230705
 Plan : H

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-57.85	-13	-44.85	-59.22	-64.23	0.78	7.16	V	Pass
5640	-58.22	-13	-45.22	-61.44	-66.76	1.04	9.58	V	Pass
7520	-62.51	-13	-49.51	-67	-72.62	1.35	11.46	V	Pass
9400	-67.15	-13	-54.15	-68.37	-78.21	1.75	12.81	V	Pass
11280	-60.23	-13	-47.23	-71.47	-71.32	2	13.09	V	Pass
13160	-61.02	-13	-48.02	-72.21	-72.73	2.04	13.75	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	NA	NA	NA	NA	PASS
-20	NA	NA	NA	NA	
-10	43	0.05	25	0.03	
0	-44	-0.05	15	0.02	
10	-41	-0.05	19	0.02	
20	34	0.04	24	0.03	
30	17	0.02	16	0.02	
40	12	0.01	28	0.03	
50	27	0.03	11	0.01	
55	-17	-0.02	-22	-0.03	

Note:

1. The EUT stops transmitting at temperatures -20°C and -30°C.
2. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GPRS 8		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	NA	NA	NA	NA	PASS
-20	NA	NA	NA	NA	
-10	97	0.05	78	0.04	
0	89	0.05	62	0.03	
10	57	0.03	58	0.03	
20	52	0.03	38	0.02	
30	19	0.01	-43	-0.02	
40	-24	-0.01	35	0.02	
50	-19	-0.01	43	0.02	
55	-12	-0.01	38	0.02	

Note:

1. The EUT stops transmitting at temperatures -20°C and -30°C.
2. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS 8	5.0	21	0.02	2.5	PASS
		BEP	25	0.03		
		5.5	16	0.02		
	EDGE 8	5.0	12	0.01		
		BEP	11	0.01		
		5.5	13	0.02		
GSM 1900 CH661	GPRS 8	5.0	-28	-0.01		
		BEP	-36	-0.02		
		5.5	-34	-0.02		
	EDGE 8	5.0	36	0.02		
		BEP	38	0.02		
		5.5	47	0.02		

1. Normal Voltage = 5.0V.
2. Battery End Point (BEP) = 4.5 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Mar. 21, 2012	Dec. 29, 2012	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 30, 2011	Mar. 21, 2012	Dec. 29, 2012	Conducted (TH01-KS)
DC Power Supply	TOPWARD	GPS-3030D	E1884515	N/A	Aug. 23, 2011	Mar. 21, 2012	Aug. 22, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 30, 2011	Mar. 21, 2012	Dec. 29, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Mar. 14, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Mar. 14, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Mar. 14, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Mar. 14, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060007	30MHz~2GHz	Dec. 30, 2011	Mar. 14, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Mar. 14, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
SHE-EHF Horn	Schwarzbeck	BBHA9170	BBHA170249	15GHz~40GHz	Oct. 11, 2011	Mar. 14, 2012	Oct. 10, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00	9kHz~30 MHz	Jul. 28, 2011	Mar. 14, 2012	Jul. 27, 2012	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 20, 2011	Mar. 14, 2012	Sep. 19, 2012	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\log(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP230705 as below.