

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

Polk Audio

FR1 WIRELESS DONGLE

Model Number: FR1 WIRELESS DONGLE

FCC ID: WLQAM1520DNGL

Prepared for : Polk Audio

5601 Metro Drive, Baltimore, Maryland, United States, 21215

Prepared By : EST Technology Co., Ltd.

Santun(guantai Road), Houjie Town, DongGuan City,  
GuangDong, China.

Tel: 86-769-83081888-808

Report Number: ESTE-R1408020

Date of Test : July 15 ~ August 03, 2014




Date of Report : August 11, 2014

## TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT) .....	5
2. SUMMARY OF TEST .....	6
2.1. Summary of test result.....	6
2.2. Test Facilities .....	7
2.3. Assistant equipment used for test .....	8
2.4. Block Diagram .....	8
2.5. Test mode .....	9
2.6. Channel List for FHSS .....	9
2.7. Test Equipment.....	10
3. MAXIMUM PEAK OUTPUT POWER .....	11
3.1. Limit .....	11
3.2. Test Procedure .....	11
3.3. Test Result.....	11
3.4. Test Data .....	12
4. 20 DB BANDWIDTH.....	14
4.1. Limit .....	14
4.2. Test Procedure .....	14
4.3. Test Result.....	14
4.4. Test Data .....	15
5. CARRIER FREQUENCY SEPARATION .....	17
5.1. Limit .....	17
5.2. Test Procedure .....	17
5.3. Test Result.....	17
5.4. Test Data .....	18
6. NUMBER OF HOPPING CHANNEL .....	20
6.1. Limit .....	20
6.2. Test Procedure .....	20
6.3. Test Result.....	20
6.4. Test Data .....	21
7. DWELL TIME .....	22
7.1. Limit .....	22
7.2. Test procedure .....	22
7.3. Test Result.....	22
7.4. Test Data .....	23
8. RADIATED EMISSIONS.....	24
8.1. Limit .....	24
8.2. Block Diagram of Test setup.....	25
8.3. Test Procedure .....	25
8.4. Test Result.....	25

8.5. Test Data .....	26
9. BAND EDGE COMPLIANCE .....	44
9.1. Limit .....	44
9.2. Block Diagram of Test setup .....	44
9.3. Test Procedure .....	44
9.4. Test Result .....	44
9.5. Test Data .....	45
10. POWER LINE CONDUCTED EMISSIONS .....	54
10.1. Limit .....	54
10.2. Test Procedure .....	54
11. ANTENNA REQUIREMENTS .....	57
11.1. Limit .....	57
11.2. Result .....	57
12. TEST SETUP PHOTO .....	58
13. PHOTOS OF EUT .....	60

## Test Report Verification

<b>Applicant:</b>	Polk Audio		
<b>Address:</b>	5601 Metro Drive, Baltimore, Maryland, United States, 21215		
<b>Manufacturer Address:</b>	Zhao Yang Electronic (Shenzhen) Co.,Ltd Section A, 4th Floor, Building 1& Building 2, De Yong Jia Industrial Park, Guang Qiao Road, Yu Lv Community, Gong Ming Street, Guang Ming New District, Shenzhen		
<b>E.U.T:</b>	FR1 WIRELESS DONGLE		
<b>Model Number:</b>	FR1 WIRELESS DONGLE		
<b>Power Supply:</b>	DC 5V From Soundbar Input AC 100~240V 50/60Hz		
<b>Test Voltage:</b>	DC 5V From Soundbar Input AC 120V/60Hz		
<b>Trade Name:</b>	Polk	Serial No.:	-----
<b>Date of Receipt:</b>	July 14, 2014	<b>Date of Test:</b>	July 15 ~ August 03, 2014
<b>Test Specification:</b>	FCC Rules and Regulations Part 15 Subpart C:2013 ANSI C63.4:2009		
<b>Test Result:</b>	<p>The device described above is tested by EST Technology Co., Ltd.. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the ETSI EN FCC Rules and Regulations Part 15 Subpart C requirements.</p> <p>This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.</p> <p style="text-align: right;">Date: August 11, 2014</p>		
Prepared by:	Tested by:	Approved by:	
			
Ada / Assistant	Tony.Tang/ Engineer	IcemanHu / Manager	
<b>Other Aspects:</b>	None.		
Abbreviations: OK/P=passed    fail/F=failed    n.a/N=not applicable    E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

<b>Product Name</b>	:	FR1 WIRELESS DONGLE
<b>Model Number</b>	:	FR1 WIRELESS DONGLE
<b>FCC ID</b>	:	WLQAM1520DNGL
<b>Operation frequency</b>	:	2403.5MHz~2477.3MHz
<b>Number of channel</b>	:	49
<b>Antenna</b>	:	Internal antenna, 3.3 dBi gain
<b>Modulation</b>	:	FHSS (GFSK)
<b>Sample Type</b>	:	Prototype production

## 2. SUMMARY OF TEST

### 2.1. Summary of test result

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) DA 00-705	PASS
20dB Bandwidth	FCC Part 15: 15.215 DA 00-705	PASS
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1) DA 00-705	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) DA 00-705	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.4: 2009 DA 00-705	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) DA 00-705	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.4: 2009 DA 00-705	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

## 2.2. Test Facilities


EMC Lab	:	<p>Certificated by CNAL, CHINA  Registration No.: L5288  Date of registration: October 28, 2011</p> <p>Certificated by FCC, USA  Registration No.: 989591  Date of registration: November 20, 2013</p> <p>Certificated by Industry Canada  Registration No.: 46405-9405  Test Side Number: 9405A-1  Date of registration: January 03, 2013</p> <p>Certificated by VCCI, Japan  Registration No.: R-3663 &amp; C-4103  Date of registration: July 25, 2011</p> <p>Certificated by TUV Rheinland, Germany  Registration No.: UA 50195514 0001  Date of registration: January 07, 2011</p> <p>Certificated by TUV/PS, Shenzhen  Registration No.: SCN1017  Date of registration: January 27, 2011</p> <p>Certificated by Intertek ETL SEMKO  Registration No.: 2011-RTL-L1-18  Date of registration: April 28, 2011</p> <p>Certificated by Siemic, Inc.  Registration No.: SLCN021  Date of registration: November 8, 2011</p> <p>Certificated by Nemko, Hong Kong  Registration No.: 175193  Date of registration: May 4, 2011</p>
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	San Tun Management Zone, Houjie Town, Dongguan, Guangdong, China

## 2.3. Assistant equipment used for test

### 2.3.1. N/A

## 2.4. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 meter high above ground. EUT was be set into BT test mode by software before test.



(EUT: FR1 WIRELESS DONGLE)



## 2.5. Test mode

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Mode	Channel	Frequency
GFSK	Low	2403.5MHz
	Middle	2440.4MHz
	High	2477.3MHz

## 2.6. Channel List for FHSS

1	2.4035	26	2.4420
2	2.4051	27	2.4435
3	2.4066	28	2.4450
4	2.4081	29	2.4466
5	2.4097	30	2.4481
6	2.4112	31	2.4496
7	2.4128	32	2.4512
8	2.4143	33	2.4527
9	2.4158	34	2.4543
10	2.4174	35	2.4558
11	2.4189	36	2.4573
12	2.4204	37	2.4589
13	2.4220	38	2.4604
14	2.4235	39	2.4619
15	2.4251	40	2.4635
16	2.4266	41	2.4650
17	2.4281	42	2.4666
18	2.4297	43	2.4681
19	2.4312	44	2.4696
20	2.4327	45	2.4712
21	2.4343	46	2.4727
22	2.4358	47	2.4742
23	2.4374	48	2.4758
24	2.4389	49	2.4773
25	2.4404		

## 2.7. Test Equipment

### 2.7.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	June,28,14	1 Year
Artificial Mains Networ	Rohde & Schwarz	ENV216	101260	June,28,14	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	June,28,14	1 Year

### 2.7.2. For radiated emission test(30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June,28,14	1 Year
Spectrum Analyzer	Agilent	E4411B	MY50140697	June,28,14	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June,28,14	1 Year
Signal Amplifier	Agilent	310N	187037	June,28,14	1 Year

### 2.7.3. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA9120D1002	June,28,14	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	June,28,14	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June,28,14	1 Year
RF Cable	Hubersuhner	RG 214/U	513423	June,28,14	1 Year

### 3. MAXIMUM PEAK OUTPUT POWER

#### 3.1. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

#### 3.2. Test Procedure


The transmitter output (antenna port) was connected to the spectrum analyzer

#### 3.3. Test Result


EUT: FR1 WIRELESS DONGLE					
M/N: FR1 WIRELESS DONGLE					
Test date: 2014-08-01		Test site: RF site		Tested by: Tony Tang	
Mode	Freq (MHz)	Result (dBm)	Limit		Margin (dB)
			dBm	W	
GFSK	2403.5	8.317	21.00	0.125	12.683
	2440.4	8.219	21.00	0.125	12.781
	2477.3	8.079	21.00	0.125	12.921
Conclusion: PASS					

3.4. Test Data


GFSK 2403.5 MHz



GFSK 2440.4 MHz



GFSK 2477.3 MHz



## 4. 20 DB BANDWIDTH

### 4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 4.2. Test Procedure


The transmitter output was coupled to a spectrum analyzer via a antenna. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 4.3. Test Result


EUT: FR1 WIRELESS DONGLE				
M/N: FR1 WIRELESS DONGLE				
Test date: 2014-08-01		Test site: RF site		Tested by: Tony Tang
Mode	Freq (MHz)	20dB Bandwidth (MHz)	Limit (kHz)	Conclusion
GFSK	2403.5	2.210	/	PASS
	2440.4	2.225	/	PASS
	2477.3	2.247	/	PASS

4.4. Test Data


GFSK 2403.5MHz



GFSK 2440.4MHz



GFSK 2477.3MHz





## 5. CARRIER FREQUENCY SEPARATION

### 5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW


### 5.2. Test Procedure

The transmitter output was coupled to a spectrum analyzer via a antenna. The carrier frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW.


### 5.3. Test Result

EUT: FR1 WIRELESS DONGLE				
M/N: FR1 WIRELESS DONGLE				
Test date: 2014-08-01		Test site: RF site		Tested by: Tony Tang
Mode	Channel	Channel separation (MHz)	Limit	Conclusion
GFSK	Low CH	1.54	> 2/3 of the 20dB Bandwidth or 25[kHz]( whichever is greater)	PASS
	Mid CH	1.54		PASS
	High CH	1.53		PASS


## 5.4. Test Data

GFSK  
Low Channel

## Mid Channel



# High Channel



## 6. NUMBER OF HOPPING CHANNEL

### 6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

### 6.2. Test Procedure




The transmitter output was coupled to a spectrum analyzer via a antenna. The number of hopping channel was measured by spectrum analyzer with 300kHz RBW and 300kHz VBW.

### 6.3. Test Result

EUT: FR1 WIRELESS DONGLE			
M/N: FR1 WIRELESS DONGLE			
Test date: 2014-08-01		Test site: RF site	Tested by: Tony.Tang
Mode	Number of hopping channel	Limit	Conclusion
GFSK	20	>15	PASS

## 6.4. Test Data

## GFSK



## 7. DWELL TIME

### 7.1. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



### 7.2. Test procedure

1. Connect the antenna port of the EUT to the spectrum analyzer by a low loss cable.
2. Set the EUT to proper test mode with relative test software and hardware.
3. Spectrum analyzer setting: Centered Frequency = measured channel, RBW = 1MHz, VBW= 1MHz, Frequency Span = 0 Hz.
4. Set sweep time properly to capture the entire dwell time per hopping channel.
5. Set detector type to Peak and trace mode to Max Hold and make the measurement.
6. Repeat step 3-5 until all channels measured were complete.

### 7.3. Test Result

EUT: FR1 WIRELESS DONGLE			
M/N: FR1 WIRELESS DONGLE			
Test date: 2014-08-01		Test site: RF site	Tested by: Tony Tang
Mode	Dwell time (ms)	Limit	Conclusion
GFSK	281.60	<400ms	PASS

## 7.4. Test Data

**GFSK DH1 :  $64\text{hop}/1\text{s} * 0.4 * 20 * 0.55\text{ms} = 281.60$** 

## 8. RADIATED EMISSIONS

### 8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

#### 15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

#### 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	



## 8.2. Block Diagram of Test setup



## 8.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

## 8.4. Test Result


30MHz—25GHz Radiated emissison Test result
EUT: FR1 WIRELESS DONGLE
M/N: FR1 WIRELESS DONGLE
Power: DC 5V From Soundbar Input AC 120V/60Hz
Test date: 2014-07-20~23    Test site: 3m Chamber    Tested by: Tony Tang
Test mode: Tx Mode
Pass

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2403.5MHz 、 2440.4MHz and 2477.3MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


## 8.5. Test Data

30 MHz – 1000 MHz




Site no.	: 3m Chamber	Data no.	: 143
Dis. / Ant.	: 3m 27137	Ant. pol.	: VERTICAL
Limit	: FCC PART 15 B		
Env. / Ins.	: Temp:25.6';Humi:56%;Press:101.52kPa		
Engineer	: Tony		
EUT	: FR1 WIRELESS DONGLE		
Power	: DC 15V From SOUNDBAR Input AC 120V/60Hz		
M/N	: FR1 WIRELESS DONGLE		
Test Mode	: TX 2403.5MHz		

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	48.43	8.37	0.98	24.98	34.33	40.00	5.67	QP
2	96.93	8.92	1.33	22.61	32.86	43.50	10.64	QP
3	148.34	11.00	1.69	25.84	38.53	43.50	4.97	QP
4	196.84	7.72	1.81	27.38	36.91	43.50	6.59	QP
5	221.09	9.26	2.01	18.55	29.82	46.00	16.18	QP
6	293.84	12.92	2.33	14.28	29.53	46.00	16.47	QP




Site no. : 3m Chamber Data no. : 144  
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 15V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	48.43	8.37	0.98	21.29	30.64	40.00	9.36	QP
2	106.63	10.15	1.38	21.75	33.28	43.50	10.22	QP
3	148.34	11.00	1.69	24.93	37.62	43.50	5.88	QP
4	232.73	9.59	2.08	26.41	38.08	46.00	7.92	QP
5	293.84	12.92	2.33	21.67	36.92	46.00	9.08	QP
6	392.78	15.73	2.58	19.41	37.72	46.00	8.28	QP




Site no. : 3m Chamber Data no. : 145  
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B  
 Env. / Ins. : Temp:25.6°;Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 15V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2440.4MHz

	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	67.83	5.39	1.13	21.15	27.67	40.00	12.33	QP
2	104.69	9.95	1.44	20.09	31.48	43.50	12.02	QP
3	179.38	8.96	1.72	27.19	37.87	43.50	5.63	QP
4	293.84	12.92	2.33	18.67	33.92	46.00	12.08	QP
5	405.39	16.18	2.61	16.09	34.88	46.00	11.12	QP
6	809.88	22.38	3.83	7.02	33.23	46.00	12.77	QP




Site no. : 3m Chamber Data no. : 146  
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 15V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2440.4MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	67.83	5.39	1.13	29.29	35.81	40.00	4.19	QP
2	135.73	11.38	1.59	21.27	34.24	43.50	9.26	QP
3	179.38	8.96	1.72	29.20	39.88	43.50	3.62	QP
4	358.83	14.45	2.56	16.71	33.72	46.00	12.28	QP
5	405.39	16.18	2.61	20.95	39.74	46.00	6.26	QP
6	809.88	22.38	3.83	11.01	37.22	46.00	8.78	QP



Site no. : 3m Chamber Data no. : 147  
 Dis. / Ant. : 3m 27137 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 B  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 15V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz


	Freq.	Ant.	Cable		Emission			
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	53.28	6.11	0.91	21.03	28.05	40.00	11.95	QP
2	133.79	11.36	1.56	22.67	35.59	43.50	7.91	QP
3	148.34	11.00	1.69	17.83	30.52	43.50	12.98	QP
4	172.59	9.07	1.68	17.13	27.88	43.50	15.62	QP
5	256.98	12.63	2.17	18.02	32.82	46.00	13.18	QP
6	269.59	12.56	2.25	21.05	35.86	46.00	10.14	QP



Site no. : 3m Chamber Data no. : 148  
 Dis. / Ant. : 3m 27137 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 B  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 15V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	96.93	8.92	1.33	23.36	33.61	43.50	9.89	QP
2	133.79	11.36	1.56	24.95	37.87	43.50	5.63	QP
3	196.84	7.72	1.81	25.29	34.82	43.50	8.68	QP
4	232.73	9.59	2.08	25.89	37.56	46.00	8.44	QP
5	305.48	13.11	2.31	13.47	28.89	46.00	17.11	QP
6	392.78	15.73	2.58	17.44	35.75	46.00	10.25	QP

## 1000 MHz – 18000MHz




Site no. : 3m Chamber Data no. : 21  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6°;Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Level				
1	2403.50	27.61	6.64	34.18	106.93	107.00	74.00	-33.00	Peak
2	4791.00	31.22	11.69	31.80	35.78	46.89	74.00	27.11	Peak
3	7443.00	36.54	11.61	31.93	34.38	50.60	74.00	23.40	Peak
4	9619.00	37.93	11.68	31.92	33.18	50.87	74.00	23.13	Peak
5	10979.00	39.50	11.29	33.62	29.96	47.13	74.00	26.87	Peak
6	14447.00	41.83	10.93	32.90	29.69	49.55	74.00	24.45	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 22  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2403.50	27.61	6.64	34.18	98.78	98.85	74.00	-24.85	Peak
2	5233.00	31.68	12.31	32.18	35.53	47.34	74.00	26.66	Peak
3	8004.00	37.01	11.40	31.22	34.40	51.59	74.00	22.41	Peak
4	10078.00	38.24	11.54	31.92	34.11	51.97	74.00	22.03	Peak
5	14294.00	41.71	10.92	33.08	32.86	52.41	74.00	21.59	Peak
6	17048.00	39.93	10.97	33.09	29.64	47.45	74.00	26.55	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 25  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2477.30	27.58	6.71	34.03	109.02	109.28	74.00	-35.28	Peak
2	5029.00	31.56	12.55	32.06	34.37	46.42	74.00	27.58	Peak
3	7426.00	36.56	11.60	31.95	34.73	50.94	74.00	23.06	Peak
4	9908.00	38.14	11.61	31.76	33.39	51.38	74.00	22.62	Peak
5	11098.00	39.45	11.22	33.84	32.36	49.19	74.00	24.81	Peak
6	14464.00	41.85	10.93	32.96	29.62	49.44	74.00	24.56	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Level				
1	2477.30	27.58	6.71	34.03	99.44	99.70	74.00	-25.70	Peak
2	4978.00	31.52	12.52	31.99	34.16	46.21	74.00	27.79	Peak
3	7987.00	36.98	11.41	31.23	32.25	49.41	74.00	24.59	Peak
4	10044.00	38.18	11.56	31.85	32.71	50.60	74.00	23.40	Peak
5	11149.00	39.42	11.18	33.94	33.59	50.25	74.00	23.75	Peak
6	14294.00	41.71	10.92	33.08	30.56	50.11	74.00	23.89	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 33  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2440.4MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2440.40	27.60	6.67	34.12	108.15	108.30	74.00	-34.30	Peak
2	5029.00	31.56	12.55	32.06	33.75	45.80	74.00	28.20	Peak
3	8004.00	37.01	11.40	31.22	31.97	49.16	74.00	24.84	Peak
4	10673.00	39.17	11.30	33.04	32.22	49.65	74.00	24.35	Peak
5	14328.00	41.74	10.92	32.98	31.42	51.10	74.00	22.90	Peak
6	16980.00	39.69	10.97	33.32	26.56	43.90	74.00	30.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 34  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2440.4MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.40	27.60	6.67	34.12	98.91	99.06	74.00	-25.06	Peak
2	4825.00	31.28	11.84	31.83	35.08	46.37	74.00	27.63	Peak
3	7443.00	36.54	11.61	31.93	34.09	50.31	74.00	23.69	Peak
4	10163.00	38.39	11.50	32.08	31.56	49.37	74.00	24.63	Peak
5	14158.00	41.60	10.91	33.49	30.06	49.08	74.00	24.92	Peak
6	17201.00	40.52	10.91	33.45	28.00	45.98	74.00	28.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.


## 18000MHz – 25000MHz



Site no. : 3m Chamber Data no. : 35  
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
					Level				
1 20562.00	46.03	19.94	36.21	11.86	41.62		74.00	32.38	Peak
2 22347.00	45.77	20.77	34.53	11.47	43.48		74.00	30.52	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 36  
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Emission		Limits (dBuV/m)	Margin (dB)	Remark
				Reading	Level			
1 21003.00	46.30	20.13	35.80	13.09	43.72	74.00	30.28	Peak
2 23089.00	45.62	21.22	33.74	13.35	46.45	74.00	27.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 37  
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2440.4MHz

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	21031.00	46.27	20.15	35.78	12.87	43.51	74.00	30.49	Peak
2	23250.00	45.65	21.37	33.59	12.28	45.71	74.00	28.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 38  
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2440.4MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)		
1 20772.00	46.16	20.03	36.00	13.08	43.27	74.00	30.73	Peak
2 23166.00	45.63	21.30	33.67	12.85	46.11	74.00	27.89	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 39  
 Dis. / Ant. : 3m ANT ABVOE 18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 20471.00	46.01	19.89	36.27	11.72	41.35	74.00	32.65	Peak	
2 22445.00	45.79	20.82	34.43	11.25	43.43	74.00	30.57	Peak	

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 40  
 Dis. / Ant. : 3m ANT ABOVE 18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz

Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission		Margin (dB)	Remark
					Level (dBuV/m)	Limits (dBuV/m)		
1 19904.00	46.07	19.58	36.62	12.83	41.86	74.00	32.14	Peak
2 21696.00	45.88	20.43	35.17	13.12	44.26	74.00	29.74	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 9. BAND EDGE COMPLIANCE

### 9.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 9.2. Block Diagram of Test setup



### 9.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of emissions

- (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
- (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO


### 9.4. Test Result

EUT: FR1 WIRELESS DONGLE
M/N: FR1 WIRELESS DONGLE
Power: DC 5V From Soundbar Input AC 120V/60Hz
Test date: 2014-07-20 Test site: 3m Chamber Tested by: Tony Tang
Test mode: Tx Mode (Hopping On & No Hopping)
Pass

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2403.5MHz 、 2440.4MHz and 2477.3MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.


## 9.5. Test Data



Site no. : 3m Chamber Data no. : 23  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz(No Hopping)

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2334.54	27.73	6.56	34.23	37.40	37.46	74.00	36.54	Peak
2	2390.00	27.64	6.62	34.19	36.11	36.18	74.00	37.82	Peak
3	2403.62	27.61	6.64	34.18	102.61	102.68	74.00	-28.68	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 24  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz(No Hopping)

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2342.02	27.70	6.56	34.22	43.64	43.68	74.00	30.32	Peak
2	2390.00	27.64	6.62	34.19	40.75	40.82	74.00	33.18	Peak
3	2392.84	27.61	6.62	34.18	52.84	52.89	74.00	21.11	Peak
4	2403.62	27.61	6.64	34.18	114.09	114.16	74.00	-40.16	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 27  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz (No Hopping)

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	2477.23	27.58	6.71	34.03	102.28	102.54	74.00	-28.54	Peak
2	2483.50	27.58	6.71	34.03	37.15	37.41	74.00	36.59	Peak
3	2489.55	27.58	6.73	34.03	40.70	40.98	74.00	33.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 28  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz(No Hopping)

	Freq.	Ant.	Cable	Amp	Emission		Limits	Margin	Remark
	(MHz)	Factor	Loss	Factor	Reading	Level	(dBuV/m)	(dB)	
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)			
1	2477.23	27.58	6.71	34.03	115.00	115.26	74.00	-41.26	Peak
2	2483.50	27.58	6.71	34.03	44.63	44.89	74.00	29.11	Peak
3	2489.55	27.58	6.73	34.03	46.30	46.58	74.00	27.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 29  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz (Hopping On)

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1	2475.68	27.58	6.71	34.06	113.22	113.45	74.00	-39.45	Peak
2	2483.50	27.58	6.71	34.03	52.38	52.64	74.00	21.36	Peak
3	2484.43	27.58	6.71	34.03	50.42	50.68	74.00	23.32	Peak
4	2490.23	27.58	6.73	34.03	46.47	46.75	74.00	27.25	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 30  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2477.3MHz (Hopping On)

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2477.23	27.58	6.71	34.03	101.24	101.50	74.00	-27.50	Peak
2	2483.50	27.58	6.71	34.03	49.01	49.27	74.00	24.73	Peak
3	2486.05	27.58	6.71	34.03	47.07	47.33	74.00	26.67	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 31  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz (Hopping On)

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	2344.77	27.70	6.56	34.22	39.81	39.85	74.00	34.15	Peak
2	2390.00	27.64	6.62	34.19	46.17	46.24	74.00	27.76	Peak
3	2403.07	27.61	6.64	34.18	101.31	101.38	74.00	-27.38	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 63  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS SUBWOOFER  
 Power : AC 120V/60Hz  
 M/N : FR1 WIRELESS SUBWOOFER  
 Test Mode : TX 2477.5MHz(Hopping On)

	Freq.	Ant.	Cable	Amp	Emission				
	(MHz)	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dB)	(dBUV)	(dBUV/m)	(dBUV/m)	(dB)	
1	2477.30	27.58	6.71	34.03	102.18	102.44	74.00	-28.44	Peak
2	2483.50	27.58	6.71	34.03	49.13	49.39	74.00	24.61	Peak
3	2485.18	27.58	6.71	34.03	51.38	51.64	74.00	22.36	Peak
4	2486.73	27.58	6.71	34.03	49.71	49.97	74.00	24.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32  
 Dis. / Ant. : 3m ANT 1-18G Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : Temp:25.6';Humi:56%;Press:101.52kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX 2403.5MHz (Hopping On)

	Ant.	Cable	Amp	Emission					
Freq.	Factor	Loss	Factor	Reading	Level	Limits	Margin	Remark	
(MHz)	(dB/m)	(dB)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)		
1 2324.64	27.73	6.54	34.23	41.74	41.78	74.00	32.22	Peak	
2 2390.00	27.64	6.62	34.19	50.07	50.14	74.00	23.86	Peak	
3 2404.72	27.61	6.64	34.18	106.53	106.60	74.00	-32.60	Peak	

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 10. POWER LINE CONDUCTED EMISSIONS

### 10.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 10.2. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT was charged from PC's USB port which connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#).. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.4: 2009 on Conducted Emission Test.


The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.

### 10.3. Test Result


0.15MHz—30MHz Conducted emissison Test result	
EUT: FR1 WIRELESS DONGLE	M/N:FR1 WIRELESS DONGLE
Power: DC 5V From Soundbar Input AC 120V/60Hz	
Test date: 2014-07-25 Test site: 3m Chamber Tested by: Tony.Tang	
Test mode: Tx Mode	
Pass	

## 10.4. Test data



Site no. : EST Conduction Shielded RoomData no. : 353  
 Limit : FCC PART 15B QP LINE Phase : NEUTRAL  
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX Mode

	Freq.	LISN	Cable	Emission				
	(MHz)	Factor	Loss	Reading	Level	Limits	Margin	Remark
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.16	9.48	9.81	26.98	46.27	65.65	19.38	QP
2	0.16	9.48	9.81	8.98	28.27	55.65	27.38	Average
3	0.18	9.55	9.80	23.70	43.05	64.42	21.37	QP
4	0.18	9.55	9.80	5.70	25.05	54.42	29.37	Average
5	0.22	9.60	9.80	22.36	41.76	63.01	21.25	QP
6	0.22	9.60	9.80	4.36	23.76	53.01	29.25	Average
7	0.24	9.60	9.82	18.16	37.58	62.22	24.64	QP
8	0.24	9.60	9.82	3.16	22.58	52.22	29.64	Average
9	0.31	9.60	9.83	19.04	38.47	59.97	21.50	QP
10	0.31	9.60	9.83	4.04	23.47	49.97	26.50	Average
11	0.39	9.59	9.82	10.53	29.94	58.12	28.18	QP
12	0.39	9.59	9.82	2.53	21.94	48.12	26.18	Average



Site no. : EST Conduction Shielded Room Data no. : 355  
 Limit : FCC PART 15B QP LINE Phase : LINE  
 Env. / Ins. : Temp:25.3'C Humi:58% Press:101.50kPa  
 Engineer : Tony  
 EUT : FR1 WIRELESS DONGLE  
 Power : DC 5V From SOUNDBAR Input AC 120V/60Hz  
 M/N : FR1 WIRELESS DONGLE  
 Test Mode : TX Mode

		LISN	Cable		Emission			
	Freq.	Factor	Loss	Reading	Level	Limits	Margin	Remark
	(MHz)	(dB/m)	(dB)	(dBuV)	(dBuV/m)	(dBuV/m)	(dB)	
1	0.15	9.61	9.81	26.26	45.68	65.78	20.10	QP
2	0.15	9.61	9.81	10.26	29.68	55.78	26.10	Average
3	0.17	9.61	9.81	26.79	46.21	64.99	18.78	QP
4	0.17	9.61	9.81	9.79	29.21	54.99	25.78	Average
5	0.18	9.61	9.80	23.72	43.13	64.42	21.29	QP
6	0.18	9.61	9.80	3.72	23.13	54.42	31.29	Average
7	0.21	9.61	9.80	22.13	41.54	63.10	21.56	QP
8	0.21	9.61	9.80	4.13	23.54	53.10	29.56	Average
9	0.31	9.61	9.83	18.26	37.70	59.97	22.27	QP
10	0.31	9.61	9.83	6.26	25.70	49.97	24.27	Average
11	0.38	9.61	9.82	9.50	28.93	58.30	29.37	QP
12	0.38	9.61	9.82	3.50	22.93	48.30	25.37	Average



## **11.ANTENNA REQUIREMENTS**

### **11.1.Limit**


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **11.2.Result**


The antennas used for this product are integral Patch Antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 3.3dBi.

## 12. TEST SETUP PHOTO


Conducted Test



Radiated Test (30-1000 MHz)



Radiated Test (1000-25000 MHz)





## 13. PHOTOS OF EUT

**External Photos**  
M/N: FR1 WIRELESS DONGLE



**External Photos**  
M/N: FR1 WIRELESS DONGLE







**External Photos**  
M/N: FR1 WIRELESS DONGLE




**Internal Photos**  
M/N: FR1 WIRELESS DONGLE





Internal Photos  
M/N: FR1 WIRELESS DONGLE



FHSS  
Antenna

