

FCC TEST REPORT

REPORT NO.: SE08FCI169R

MODEL NO.: T-20

LISTED MODELS: N/A

RECEIVED: Aug 15, 2008

TESTED: Aug 15, 2008 to Aug 21, 2008

APPLICANT: Shenzhen pc-pen Co., Ltd

ADDRESS: 12A01 Leizhen Building Fuming Rd, Shenzhen China

ISSUED BY: SHENZHEN SETEK TECHNOLOGY CO., LTD.

LAB LOCATION: 2/F,A3 Bldg, East Industry Zone, Overseas Chinese Town,
Shenzhen,China

This test report consists of 34 pages in total, it may be duplicated completely for legal use with the approval of the applicant, It should not be reproduced except in full, without the written approval of our laboratory, The test results in the report only apply to the tested sample.

SHENZHEN SETEK TECHNOLOGY CO., LTD.

Our website: www.setek.com.cn
TEL:86-755-26966362

E-mail:Service@setek.com.cn
FAX: 86-755-26966270

Prepared for : Shenzhen pc-pen Co., Ltd
Address : 12A01 Leizhen Building Fuming Rd. Shenzhen China

Product : Wireless pc-pen
Model No(s). : T-20
Trademark : PC-PEN
Test Standard : FCC Part 15 Paragraph 15.249

Prepared by : SHENZHEN SETEK TECHNOLOGY CO., LTD.
Address : 2/F, A3 Bldg, East Industry Zone, Overseas Chinese Town,
Shenzhen, China

FCC Registration Number: 966959


Tel: (86-755) 26966362 Fax:(86-755) 26966270

Prepared by :



(Engineer)

Reviewer by :



(Project Engineer)

Approved by :



(Manager)

Report Number : SE08FCI169R
Date of Test : Aug 15, 2008 to Aug 21, 2008
Date of Report : Aug 22, 2008

The device described above is tested by SHENZHEN SETEK TECHNOLOGY CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. This report applies to above tested sample only and shall not be reproduced in part without written approval of SHENZHEN SETEK TECHNOLOGY CO., LTD.

TABLE OF CONTENTS

Description	Page
1 General Information.....	5
1.1 Description of Device (EUT).....	5
1.2 Test Summary.....	6
1.3 Description of Support Device.....	7
1.4 Standards Applicable for Testing.....	7
1.5 List of Measuring Equipments Used.....	8
1.6 Test Facility.....	8
1.7 Measurement Uncertainty.....	8
2 Conducted Emission Test.....	9
2.1 Test Equipment.....	9
2.2 Test Procedure.....	9
2.3 Conducted Test Setup.....	10
2.4 EUT Operating Condition.....	10
2.5 Conducted Emission Limits.....	11
2.6 Test result.....	11
3 Radiation Emission Test.....	14
3.1 Test Equipment.....	14
3.2 Measurement Uncertainty.....	14
3.3 Test Procedure.....	14
3.4 Radiated Test Setup.....	15
3.5 Spectrum Analyzer Setup.....	15
3.6 Corrected Amplitude & Margin Calculation.....	16
3.7 Summary of Test Results.....	16
3.8 EUT Operating Condition.....	16
3.9 Radiated Emissions Limit.....	16
3.10 Radiated Emissions Test Result.....	16
4 Band Edge.....	22
4.1 Test Equipment.....	22
4.2 Test Procedure.....	22
4.3 Applied Procedures/Limit.....	25

4.4	Test Equipment.....	25
4.5	Test Procedure.....	25
4.6	Applied Procedures/Limit.....	25
4.7	Band Edge Test Result.....	25
5	Photographs of Test setup.....	27
6	Photographs of EUT.....	28
7	FCC ID Label.....	34

1. GENERAL INFORMATION

1.1 Description of Device (EUT)

Applicant : Shenzhen pc-pen Co.,Ltd

Address : 12A01 Leizhen Building Fuming Rd. Shenzhen China

Manufacturer : Shenzhen pc-pen Co.,Ltd

Address : 12A01 Leizhen Building Fuming Rd. Shenzhen China

EUT : Wireless pc-pen

Model Number(s) : T-20

Description of EUT : 2.4G Wireless pc-pen

Description of Antenna : built-in antenna 1.0dBi

Power Supply : Wireless pc-pen: DC 3.7V/300mA by the internal rechargeable battery
Pen pedestal: DC 5V by PC USB port

Operation Frequency : 2408 MHz ~ 2472 MHz

Number of Channels : 9

Type of Modulation : GFSK

Output Power Class : Class 2

Received : Aug 15, 2008

Date of Test : Aug 15, 2008 to Aug 21, 2008

1.2. Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 25GHz)	FCC PART 15: 2003	ANSI C63.4: 2003	Class B	PASS
Conducted Emission (150KHz to 30MHz)	FCC PART 15: 2003	ANSI C63.4: 2003	Class B	PASS

1.3. Description of Support Device

PC	: Manufacturer: DELL M/N: E157FPc S/N: 53SM12X CCC,FCC,VCCI,GS,S,CE
Monitor	: Manufacturer: SAMSUNG M/N: 710MP [R]S S/N: MH17HVVY500468F CCC,SA,UL
Mouse	: Manufacturer: DELL M/N: M056UOA S/N: F1101WOS CE, VCCI,FCC,GS,UL
Keyboard	: Manufacturer: DELL M/N: SK-8135 S/N: CN-0DJ340-71616683-01U6 VCCI,CE, FCC

1.4. Standards Applicable for Testing

The customer requested FCC tests for a Zigbee module. The standards used were FCC 15 Paragraph 15.249, Paragraph 15.207, Paragraph 15.209, Paragraph 15.31, Paragraph 15.33, Paragraph 15.35.

1.5. List of Measuring Equipments Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4408B	MY44210575	May 29,2008	1 Year
2.	Test Receiver	Rohde & Schwarz	ESIB26	100234	May 29,2008	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	142	May 29,2008	1 Year
4.	Loop Antenna	EMCO	6502	00042960	May 29,2008	1 Year
5.	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	May 29,2008	1 Year
6.	Cable	Schwarzbeck	AK9513(1m)	CR RX2	May 29,2008	1 Year
7.	Cable	Schwarzbeck	AK9513(10m)	AC RX1	May 29,2008	1 Year
8.	Cable	Rosenberger	N/A(6m)	CR RX1	May 29,2008	1 Year
9.	Cable	Rosenberger	N/A(10m)	FP2RX2	May 29,2008	1 Year
9.	DC Power Filter	MPE	23872C	N/A	May 29,2008	1 Year
10.	Single Phase Power Line Filter	MPE	23332C	N/A	May 29,2008	1 Year
11.	3 Phase Power Line Filter	MPE	23333C	N/A	May 29,2008	1 Year
12.	Signal Generator	HP	8648A	3625U00573	May 29,2008	1 Year
13.	Test Receiver	Rohde & Schwarz	ESCS30	100350	May 29,2008	1 Year
14.	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	May 29,2008	1 Year
15.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	May 29,2008	1 Year
16.	RF Cable	FUJIKURA	RG-55/U	LISN Cable	May 29,2008	1 Year
17.	Spectrum Analyzer	Agilent	E4446A	MY43360126	May 29,2008	1 Year
18.	Spectrum Analyzer	Agilent	E7405A	US41160416	May 29,2008	1 Year

1.6. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 966959

SHENZHEN SETEK TECHNOLOGY CO., LTD, the EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission.

1.7. Measurement Uncertainty

Radiation Uncertainty : $U_r = \pm 3.84\text{dB}$

Conduction Uncertainty : $U_c = \pm 2.72\text{dB}$

2 Conducted Emission Test

Product Name:	Wireless pc-pen
Test Requirement:	FCC Part15 Paragraph 15.207
Test Method:	Based on FCC Part15 Paragraph 15.207
Test Date:	Aug 19, 2008
Frequency Range:	150 kHz to 30MHz
Class:	Class B
Detector:	Peak for pre-scan (9 kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

2.1. Test Equipment


Please refer to Section 1.5. this report.

2.2. Test Procedure

1. The EUT was tested according to ANSI C63.4: 2003. The frequency spectrum from 150kHz to 30MHz was investigated.
2. The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

2.3. Conducted Test Setup


The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003, The specification used in this report was the FCC Part15 Paragraph 15.207 limits.



2.4. EUT Operating Condition

Operating condition is according to ANSI C63.4: 2003.

- A. Setup the EUT and simulators as shown on follow.
- B. Enable RF signal and confirm EUT active.
- C. Modulate output capacity of EUT up to specification.



2.5. Conducted Emission Limits

66-56 dBuV/m between 0.15MHz & 0.5MHz

56 dBuV/m between 0.5MHz & 5MHz

60 dBuV/m between 5MHz & 30MHz


Note: In the above limits, the tighter limit applies at the band edges.

2.6 Test result

See the following pages.

SCAN TABLE: "Voltage (150K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT:**


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
2.072000	37.90	10.2	56	18.1	QP	N	GND
2.144000	36.60	10.2	56	19.4	QP	N	GND
2.576000	35.10	10.2	56	20.9	QP	N	GND
2.702000	36.70	10.2	56	19.3	QP	N	GND
4.406000	37.30	10.3	56	18.7	QP	N	GND

MEASUREMENT RESULT:

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.314000	36.20	10.1	50	13.7	AV	N	GND
0.818000	30.10	10.1	46	15.9	AV	N	GND
0.944000	30.60	10.1	46	15.4	AV	N	GND
1.448000	30.00	10.2	46	16.0	AV	N	GND
2.078000	29.50	10.2	46	16.5	AV	N	GND

SCAN TABLE: "Voltage (150K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT:**

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.314000	41.60	10.1	60	18.3	QP	L1	GND
0.692000	35.30	10.1	56	20.7	QP	L1	GND
1.448000	41.60	10.2	56	14.4	QP	L1	GND
1.760000	35.60	10.2	56	20.4	QP	L1	GND
2.072000	40.10	10.2	56	15.9	QP	L1	GND
4.316000	37.80	10.3	56	18.2	QP	L1	GND

MEASUREMENT RESULT:

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.314000	37.90	10.1	50	12.0	AV	L1	GND
1.448000	39.00	10.2	46	7.0	AV	L1	GND
2.012000	33.80	10.2	46	12.2	AV	L1	GND
2.078000	34.20	10.2	46	11.8	AV	L1	GND

3. Radiation Emission Test

Product Name:	Wireless pc-pen
Test Requirement:	FCC Part15 Paragraph 15.249
Test Method:	Based on FCC Part15 Paragraph 15.31 and Paragraph 15.33
Test Date:	Aug 20, 2008
Frequency Range:	30MHz to 25GHz
Measurement Distance:	3m
Detector:	Peak for pre-scan (120KHz resolution bandwidth) Quasi-Peak if maximised peak within 6dB of limit

3.1. Test Equipment

Please refer to Section 1.5. this report.

3.2. Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase centre variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on ANSI C63.4: 2003, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at the EMC Lab is $\pm 3.84\text{dB}$.

3.3. Test Procedure

1. Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.
2. All data was recorded in the peak detection mode.
3. The EUT was under normal mode during the final qualification test and the configuration was used to represent the worst case results.
4. According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna to the intentional radiator shall be considered sufficient to comply with the provisions of this section. This product has a permanent antenna, fulfill the requirement of this section.

3.4. Radiated Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003, The specification used in this report was the FCC Part15 Paragraph 15.249 and Paragraph 15.209 limits.



3.5. Spectrum Analyzer Setup

According to FCC Part15 Paragraph 15.249 Rules, the system was tested to 25000 MHz.

Start Frequency.....	30 MHz
Stop Frequency.....	25000 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	100 kHz
Video Bandwidth.....	1 MHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode	Normal
Resolution Bandwidth	1MHz

3.6. Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dBuV means the emission is 7dBuV below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$

3.7. Summary of Test Results

According to the data in section 7.10, the EUT complied with the FCC Part15 Paragraph 15.249 standards.

3.8. EUT Operating Condition

Same as section 2.4. of this report.

3.9. Radiated Emissions Limit

A. FCC Part 15 subpart C Paragraph 15.249 Limit

Fundamental Frequency	Field Strength of Fundamental		Field Strength of Harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25GHz	250	108	2500	68

- Note:**
- (1) RF Voltage(dBuV)=20 log RF Voltage(uV)
 - (2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 - (3) The emission limit in this paragraph is based on measurement instrumentation employing an average detector. Measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
 - (4) Limit fundamental is 94dBuV/m@3m(AV)and114dBuV/m@3m(PK)
Limit field strength of harmonics: 54 dBuV/m@3m(AV)and74dBuV/m@3m(PK)

B. Frequencies in restricted band are complied to limit on Paragraph 15.209

Frequency(MHZ)	Distance(m)	Field strength(dBuV/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note: (1) RF Voltage(dBuV)=20 log RF Voltage(uV)
 (2) In the Above Table, the tighter limit applies at the band edges.
 (3) Distance refers to the distance in meters between the measuring instrument antenna.

3.10. Radiated Emissions Test Result

Formula of conversion factors: the field strength at 3m was established by adding The meter reading of the spectrum analyzer (which is set to read in units of dBuV) To the antenna correction factor supplied by the antenna manufacturer. The antenna Correction factors are stated in terms of dB. The gain of the pressletor was accounted For in the spectrum analyser meter reading.

Example:

Freq(MHz) Meter Reading +ACF=FS

33 20dBuV+10.36dB=30.36dBuV/m @3m

Radiated Emission Test Data

Test Voltage: DC 3.7V by battery

Test Mode: TX On

Temperature: 24 °C

Humidity: 52%RH

Test Result: PASS

Remarks: No further spurious emission found between lowest internal generated/used frequency to 30 MHz

30-1000MHz radiation test no significant emissions above the equipment noise floor were detected.

Frequency (MHz)	Detector	Antenna Polarization	Emission Level (dBuV/m)	FCC 15 Subpart C Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Turntable Angle (°)
Low frequency							
2408.0	AV	Vertical	84.65	94.00	9.35	1.5	120

4816.0	AV	Vertical	44.17	54.00	9.83	1.5	60
7224.0	AV	Vertical	44.26	54.00	9.74	1.8	45
9632.0	AV	Vertical	45.59	54.00	8.41	1.0	90
12040.0	AV	Vertical	45.68	54.00	8.32	1.5	60
14448.0	AV	Vertical	45.77	54.00	8.23	1.2	100
16856.0	AV	Vertical	46.12	54.00	7.88	1.8	120
19264.0	AV	Vertical	46.38	54.00	7.62	1.2	60
21672.0	AV	Vertical	46.82	54.00	7.18	1.5	90
24080.0	AV	Vertical	47.20	54.00	6.80	1.0	120
2408.0	AV	Horizontal	81.11	94.00	12.89	1.5	270
4816.0	AV	Horizontal	43.59	54.00	10.41	1.6	180
7224.0	AV	Horizontal	44.22	54.00	9.78	1.5	120
9632.0	AV	Horizontal	45.62	54.00	8.38	1.6	200
12040.0	AV	Horizontal	45.66	54.00	8.34	1.5	100
14448.0	AV	Horizontal	45.57	54.00	8.43	1.2	270
16856.0	AV	Horizontal	45.10	54.00	8.90	1.8	180
19264.0	AV	Horizontal	46.22	54.00	7.78	1.0	90
21672.0	AV	Horizontal	46.77	54.00	7.23	1.5	60
24080.0	AV	Horizontal	46.10	54.00	7.90	1.2	100
2408.0	PK	Vertical	87.44	114.00	26.56	1.5	45
4816.0	PK	Vertical	48.88	74.00	25.12	1.5	120
7224.0	PK	Vertical	48.90	74.00	25.10	1.8	60
9632.0	PK	Vertical	49.11	74.00	24.89	1.0	270
12040.0	PK	Vertical	49.54	74.00	24.46	1.2	180
14448.0	PK	Vertical	49.62	74.00	24.38	1.5	60
16856.0	PK	Vertical	50.57	74.00	23.43	1.8	100
19264.0	PK	Vertical	50.83	74.00	23.17	1.2	120
21672.0	PK	Vertical	51.30	74.00	22.70	1.8	100
24080.0	PK	Vertical	51.65	74.00	22.35	1.0	90
2408.0	PK	Horizontal	88.15	114.00	25.85	1.5	120
4816.0	PK	Horizontal	48.72	74.00	25.28	1.6	180
7224.0	PK	Horizontal	48.85	74.00	25.15	1.5	120
9632.0	PK	Horizontal	49.03	74.00	24.97	1.6	90
12040.0	PK	Horizontal	49.44	74.00	24.56	1.8	180
14448.0	PK	Horizontal	49.59	74.00	24.41	1.2	120
16856.0	PK	Horizontal	49.17	74.00	24.83	1.5	100
19264.0	PK	Horizontal	50.33	74.00	23.67	1.0	45
21672.0	PK	Horizontal	51.26	74.00	22.74	1.5	60
24080.0	PK	Horizontal	51.57	74.00	22.43	1.0	90

Middle frequency							
2440.00	AV	Vertical	81.89	94.00	12.11	1.5	60
4880.00	AV	Vertical	44.41	54.00	9.59	1.5	45
7320.00	AV	Vertical	44.73	54.00	9.27	1.6	90
9760.00	AV	Vertical	45.15	54.00	8.85	1.5	180
12200.00	AV	Vertical	45.65	54.00	8.35	1.2	120
14640.00	AV	Vertical	46.12	54.00	7.88	1.0	100
17080.00	AV	Vertical	46.75	54.00	7.25	1.5	90
19520.00	AV	Vertical	46.81	54.00	7.19	1.8	45
21960.00	AV	Vertical	47.77	54.00	6.23	1.2	60
24400.00	AV	Vertical	47.82	54.00	6.18	1.6	120
2440.00	AV	Horizontal	71.76	94.00	22.24	1.5	60
4880.00	AV	Horizontal	44.11	54.00	6.89	1.5	180
7320.00	AV	Horizontal	44.23	54.00	9.89	1.8	120
9760.00	AV	Horizontal	45.06	54.00	8.94	1.2	90
12200.00	AV	Horizontal	45.57	54.00	8.43	1.5	60
14640.00	AV	Horizontal	45.59	54.00	8.41	1.0	100
17080.00	AV	Horizontal	46.44	54.00	7.56	1.5	90
19520.00	AV	Horizontal	46.70	54.00	7.30	1.8	120
21960.00	AV	Horizontal	47.66	54.00	6.34	1.5	180
24400.00	AV	Horizontal	47.71	54.00	6.29	1.8	270
2440.00	PK	Vertical	87.67	114.00	26.33	1.5	90
4880.00	PK	Vertical	50.51	74.00	22.49	1.5	60
7320.00	PK	Vertical	50.77	74.00	23.23	1.5	120
9760.00	PK	Vertical	51.32	74.00	22.68	1.2	270
12200.00	PK	Vertical	51.46	74.00	22.54	1.8	100
14640.00	PK	Vertical	52.25	74.00	21.75	1.5	180
17080.00	PK	Vertical	52.77	74.00	21.23	1.2	90
19520.00	PK	Vertical	52.98	74.00	21.02	1.8	45
21960.00	PK	Vertical	53.26	74.00	20.74	1.2	100
24400.00	PK	Vertical	53.44	74.00	20.56	1.0	90
2440.00	PK	Horizontal	88.55	114.00	25.45	1.5	180
4880.00	PK	Horizontal	49.99	74.00	24.01	1.8	90
7320.00	PK	Horizontal	50.52	74.00	23.48	1.5	120
9760.00	PK	Horizontal	51.17	74.00	22.83	1.5	100
12200.00	PK	Horizontal	51.22	74.00	22.78	1.8	45
14640.00	PK	Horizontal	52.28	74.00	21.72	1.5	90

17080.00	PK	Horizontal	51.59	74.00	22.41	1.5	180
19520.00	PK	Horizontal	52.15	74.00	21.85	1.6	120
21960.00	PK	Horizontal	53.13	74.00	20.87	1.2	270
24400.00	PK	Horizontal	53.41	74.00	20.59	1.0	180
High frequency							
2472.00	AV	Vertical	80.47	94.00	13.53	1.5	120
4944.00	AV	Vertical	44.23	54.00	9.77	1.5	90
7416.00	AV	Vertical	44.49	54.00	9.51	1.5	45
9888.00	AV	Vertical	45.23	54.00	8.77	1.5	100
12360.00	AV	Vertical	45.65	54.00	8.35	1.2	180
14832.00	AV	Vertical	46.18	54.00	7.82	1.6	120
17304.00	AV	Vertical	46.65	54.00	7.35	1.8	45
19776.00	AV	Vertical	46.88	54.00	7.12	1.2	60
22248.00	AV	Vertical	47.20	54.00	6.80	1.5	90
24720.00	AV	Vertical	47.63	54.00	6.37	1.8	100
2472.00	AV	Horizontal	80.66	94.00	13.34	1.5	180
4944.00	AV	Horizontal	44.11	54.00	9.89	1.5	60
7416.00	AV	Horizontal	44.26	54.00	9.74	1.5	120
9888.00	AV	Horizontal	45.19	54.00	8.81	1.8	270
12360.00	AV	Horizontal	45.42	54.00	8.58	1.2	180
14832.00	AV	Horizontal	45.88	54.00	8.12	1.6	90
17304.00	AV	Horizontal	46.41	54.00	7.59	1.8	120
19776.00	AV	Horizontal	46.57	54.00	7.43	1.5	100
22248.00	AV	Horizontal	46.18	54.00	7.82	1.2	45
24720.00	AV	Horizontal	47.52	54.00	6.48	1.6	90
2472.00	PK	Vertical	85.21	114.00	28.79	1.5	180
4944.00	PK	Vertical	49.59	74.00	24.41	1.5	270
7416.00	PK	Vertical	50.11	74.00	23.89	1.5	45
9888.00	PK	Vertical	50.27	74.00	23.73	1.2	90
12360.00	PK	Vertical	50.85	74.00	23.15	1.6	180
14832.00	PK	Vertical	51.12	74.00	22.88	1.8	60
17304.00	PK	Vertical	52.26	74.00	21.74	1.5	90
19776.00	PK	Vertical	52.58	74.00	21.42	1.2	180
22248.00	PK	Vertical	52.77	74.00	21.23	1.0	270
24720.00	PK	Vertical	53.39	74.00	20.61	1.2	90
2472.00	PK	Horizontal	86.72	114.00	27.28	1.5	60
4944.00	PK	Horizontal	49.42	74.00	24.58	1.5	120

7416.00	PK	Horizontal	50.03	74.00	23.97	1.5	180
9888.00	PK	Horizontal	50.21	74.00	23.79	1.2	90
12360.00	PK	Horizontal	50.42	74.00	23.58	1.0	270
14832.00	PK	Horizontal	51.08	74.00	22.92	1.2	120
17304.00	PK	Horizontal	52.15	74.00	21.85	1.5	90
19776.00	PK	Horizontal	52.46	74.00	21.54	1.8	60
22248.00	PK	Horizontal	52.68	74.00	21.32	1.3	180
24720.00	PK	Horizontal	53.25	74.00	20.75	1.6	100

Note: Above 1GHz,do a Peak and Average measurements for all emissions:
Limit fundamental is 94dBuV/m@3m(AV)and114dBuV/m@3m(PK)
Limit field strength of harmonics: 54 dBuV/m@3m(AV)and74dBuV/m@3m(PK)

4 Band Edge

4.1. Test Equipment

Please refer to Section 1.5. this report.

4.2. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below:




2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 100KHz RBW and 300KHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power 20dB.


4.3. 20db Bandwidth Test Result

Product Name: Wireless pc-pen
 Test Item: 20db Band Edge Test
 Test Voltage: DC 3.7V by the by battery
 Mode: TX On
 Temperature: 24 °C
 Humidity: 52%RH


2408 MHz



2440 MHz



2472 MHz




4.4. Test Equipment

Please refer to Section 1.5. this report.

4.5. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below:



2. Emissions radiated outside of the specified frequency bands was measure by spectrum analyser with 100KHz RBW and 100KHz VBW..


4.6. Applied Procedures/Limit

Requirements: FCC 15.249(d), the emission power at the START and STOP frequencies shall be at least 50dB below the level of the fundamental or to the general radiated emission limits in FCC 15.209.


4.7. Band Edge Test Result

Product Name:	Wireless pc-pen
Test Item:	Emissions radiated outside of the specified frequency bands
Test Voltage:	DC 3.7V by battery
Test Mode:	TX On
Temperature:	24 °C
Humidity:	52%RH


2408MHz



2472 MHz






5 Photographs of Test setup




6 Photographs of EUT














7 FCC ID Label

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.



FCC ID Label Location

End of Report