

TEST REPORT
For

Americhip, Inc

Digital Media Player

Model No.: AMC-43-00, AMC-70-00, AMC-100-00

FCC ID: WN7AMC-43-00

Prepared for : Americhip, Inc
Address : Room 212, Block 2, NANHAI E COOL No.6 Xing Hua Road,
Shekou, Shenzhen, 518067 China.

Prepared by : SHENZHEN EMTEK CO., LTD.
Address : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ES111108026F-1
Date of Test : November 08, 2011 to March 19, 2012
Date of Report : March 21, 2012

TABLE OF CONTENT

| Test Report Description | Page |
|---|-----------|
| 1. SUMMARY OF TEST RESULT | 4 |
| 2. GENERAL INFORMATION..... | 5 |
| 2.1. Description of Device (EUT)..... | 5 |
| 2.2. Description of Support Device..... | 6 |
| 2.3. Description of Test Facility | 7 |
| 2.4. Measurement Uncertainty | 7 |
| 3. MEASURING DEVICE AND TEST EQUIPMENT | 8 |
| 3.1. For Power Line Conducted Emission Measurement..... | 8 |
| 3.2. For Radiated Emission Measurement(3m Chamber)..... | 8 |
| 4. POWER LINE CONDUCTED EMISSION MEASUREMENT | 9 |
| 4.1. Block Diagram of Test Setup | 9 |
| 4.2. Measuring Standard | 9 |
| 4.3. Power Line Conducted Emission Limits (Class B) | 9 |
| 4.4. EUT Configuration on Measurement..... | 9 |
| 4.5. Operating Condition of EUT..... | 10 |
| 4.6. Test Procedure..... | 10 |
| 4.7. Measuring Results..... | 10 |
| 5. RADIATED EMISSION MEASUREMENT..... | 11 |
| 5.1. Block Diagram of Test Setup | 11 |
| 5.2. Measuring Standard | 11 |
| 5.3. Radiated Emission Limits (Class B) | 12 |
| 5.4. EUT Configuration on Measurement..... | 12 |
| 5.5. Operating Condition of EUT..... | 12 |
| 5.6. Test Procedure..... | 12 |
| 5.7. Measuring Results..... | 13 |
| 6. PHOTOGRAPHS..... | 14 |
| 6.1. Photos of Conducted Emission Measurement | 14 |
| 6.2. Photos of Radiation Emission Measurement | 15 |
| APPENDIX I (8 Pages) | |
| APPENDIX II (12 Pages) | |
| APPENDIX III (Photos of EUT) (9 Pages) | |

TEST REPORT DESCRIPTION

Applicant : Americhip, Inc
Manufacturer : Americhip, Inc
Trademark : Americhip
EUT : Digital Media Player
Model No. : AMC-43-00, AMC-70-00, AMC-100-00
FCC ID : WN7AMC-43-00
Power Supply : Adapter: Input: 100-240V~50/60Hz max.0.6A, Output: DC12V, 1.5A


Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart B Class B & FCC / ANSI C63.4-2009


The device described above is tested by SHENZHEN EMTEK CO., LTD. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and SHENZHEN EMTEK CO., LTD. is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of SHENZHEN EMTEK CO., LTD.

Date of Test : November 08, 2011 to March 19, 2012

Prepared by : 
(Engineer)

Reviewer : 
(Quality Manager)

Approved & Authorized Signer : 
(Manager)



1. SUMMARY OF TEST RESULT

| EMISSION | | |
|--|---|---------|
| Description of Test Item | Standard & Limits | Results |
| Conducted Disturbance at Mains Terminals | FCC Part 15, Subpart B, Class B ANSI C63.4: 2009 | Pass |
| Radiated Disturbance | FCC Part 15, Subpart B, Class B ANSI C63.4: 2009 | Pass |
| Note: N/A is an abbreviation for Not Applicable. | | |

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

| | | |
|------------------|---|--|
| EUT | : | Digital Media Player |
| Model Number | : | AMC-43-00, AMC-70-00, AMC-100-00 (Note: all the models are the same, except their different sizes of screen. We take AMC-43-00 and AMC-100-00 to test.) |
| Test Voltage | : | AC 120V |
| Applicant | : | Americhip, Inc |
| Address | : | Room 212, Block 2, NANHAI E COOL No.6 Xing Hua Road, Shekou, Shenzhen, 518067 China. |
| Manufacturer | : | Americhip, Inc |
| Address | : | Room 212, Block 2, NANHAI E COOL No.6 Xing Hua Road, Shekou, Shenzhen, 518067 China. |
| Date of Received | : | November 08, 2011 |
| Date of Test | : | November 08, 2011 to March 19, 2012 |

2.2. Description of Support Device

| | | |
|-------------|---|--|
| PC | : | Manufacturer: LENOVO M/N: 9702 S/N: L3C4410 CE, FCC: DOC Power cord : Unshielded, Detachable, 1.5m |
| LCD Monitor | : | Manufacturer: LENOVO M/N: 9227-AE6 S/N: 4M0293084302824 CE, FCC: DOC Power cord : Unshielded, Detachable, 1.5m Data Cable: Unshielded, Detachable, 2.0m |
| LED Monitor | : | Manufacturer: PHILIPS M/N: 224EL2 S/N: DLAA1111431625 CE, FCC: DOC Power cord : Unshielded, Detachable, 1.5m Data Cable: Unshielded, Detachable, 2.0m |
| Keyboard | : | Manufacturer: LENOVO M/N: KU-0225 S/N: 0585494 CE, FCC: DOC Data Cable: Unshielded, Undetachable, 2.0m |
| Mouse | : | Manufacturer: LENOVO M/N: MO28UOL S/N: 44G7862 068 CE, FCC: DOC Data Cable: Unshielded, Undetachable, 2.0m |
| Printer | : | Manufacturer: HP M/N: C89520 S/N: CN25S182N6 CE, FCC: DOC USB Cable : Unshielded, Detachable, 1.8m Power cord : Unshielded, Detachable, 1.8m |

2.3. Description of Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2010.10.29
The certificate is valid until 2013.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Accredited by FCC, October 28, 2010
The Certificate Registration Number is 406365.

Accredited by Industry Canada, March 5, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm : SHENZHEN EMTEK CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

2.4. Measurement Uncertainty

Conducted Emission Uncertainty : 2.8dB

Radiated Emission Uncertainty : 3.3dB (3m Chamber)

3. MEASURING DEVICE AND TEST EQUIPMENT

3.1. For Power Line Conducted Emission Measurement

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|--------------------|-----------------|-----------|--------------|--------------|---------------|
| 1. | Test Receiver | Rohde & Schwarz | ESCS30 | 100162 | May 29, 2011 | 1 Year |
| 2. | L.I.S.N. | Rohde & Schwarz | ENV216 | 3560.6550.12 | May 29, 2011 | 1 Year |
| 3. | 50Ω Coaxial Switch | Anritsu | MP59B | 6100214550 | N/A | N/A |
| 4. | Voltage Probe | Rohde & Schwarz | TK9416 | N/A | May 29, 2011 | 1 Year |
| 5. | I.S.N | Rohde & Schwarz | ENY22 | 1109.9508.02 | May 29, 2011 | 1 Year |


3.2. For Radiated Emission Measurement(3m Chamber)

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|-------------------|-----------------|------------|--------------|--------------|---------------|
| 1. | EMI Test Receiver | Rohde & Schwarz | ESU | 1302.6005.26 | May 29, 2011 | 1 Year |
| 2. | Pre-Amplifier | HP | 8447D | 2944A07999 | May 29, 2011 | 1 Year |
| 3. | Bilog Antenna | Schwarzbeck | VULB9163 | 142 | May 29, 2011 | 1 Year |
| 4. | Loop Antenna | ARA | PLA-1030/B | 1029 | May 29, 2011 | 1 Year |
| 5. | Horn Antenna | Schwarzbeck | BBHA 9170 | BBHA9170399 | May 29, 2011 | 1 Year |
| 6. | Horn Antenna | Schwarzbeck | BBHA 9120 | D143 | May 29, 2011 | 1 Year |
| 7. | Cable | Schwarzbeck | AK9513 | ACRX1 | May 29, 2011 | 1 Year |
| 8. | Cable | Rosenberger | N/A | FP2RX2 | May 29, 2011 | 1 Year |
| 9. | Cable | Schwarzbeck | AK9513 | CRPX1 | May 29, 2011 | 1 Year |
| 10. | Cable | Schwarzbeck | AK9513 | CRRX2 | May 29, 2011 | 1 Year |

4. POWER LINE CONDUCTED EMISSION MEASUREMENT

4.1. Block Diagram of Test Setup

During test, continuous communication was taking place between the EUT and the host computer by a batch file loop that constantly uploads- and deletes a video file of 50MByte from the PC into the EUT without interruption.



4.2. Measuring Standard

FCC Part 15, Subpart B, Class B ANSI C63.4: 2009

4.3. Power Line Conducted Emission Limits (Class B)

| Frequency (MHz) | Limit (dB μ V) | |
|---|--------------------|---------------|
| | Quasi-peak Level | Average Level |
| 0.15 ~ 0.50 | 66.0 ~ 56.0 * | 56.0 ~ 46.0 * |
| 0.50 ~ 5.00 | 56.0 | 46.0 |
| 5.00 ~ 30.00 | 60.0 | 50.0 |
| NOTE1-The lower limit shall apply at the transition frequencies. NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz. | | |

4.4. EUT Configuration on Measurement

The following equipments are installed on Conducted Emission Measurement to meet FCC requirements and operating in a manner which tends to maximize its emission characteristics in a normal application.

EUT : Digital Media Player
Model Number : AMC-43-00, AMC-100-00

4.5. Operating Condition of EUT

4.5.1. Setup the EUT as shown on Section 4.1.

4.5.2. Turn on the power of all equipments.

4.5.3. Let the EUT work in measuring mode (Connect to PC, SD Card Play) and measure it.

4.6. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and connected to PC, and then PC connect to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are investigated to find out the maximum conducted emission according to the FCC regulations during conducted emission measurement.

The bandwidth of the field strength meter (R&S Test Receiver ESCS30) is set at 9kHz in 150kHz~30MHz and 200Hz in 9kHz~150kHz.

The frequency range from 150kHz to 30MHz is investigated.

All the scanning waveform is put in Appendix I.

4.7. Measuring Results

PASS.

Please refer to Appendix I.


5. RADIATED EMISSION MEASUREMENT

5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators


For Connect to PC:

During test, continuous communication was taking place between the EUT and the host computer by a batch file loop that constantly uploads- and deletes a video file of 50MByte from the PC into the EUT without interruption.



(EUT: Digital Media Player)

5.1.2. Block diagram of test setup (In chamber)



(EUT: Digital Media Player)

5.2. Measuring Standard

FCC Part 15, Subpart B, Class B ANSI C63.4: 2009

5.3. Radiated Emission Limits (Class B)

| Frequency MHz | Distance Meters | Field Strengths Limit | |
|------------------|--------------------|-----------------------|-----------------------------------|
| | | $\mu\text{V/m}$ | $\text{dB}(\mu\text{V})/\text{m}$ |
| 30 ~ 88 | 3 | 100 | 40.0 |
| 88 ~ 216 | 3 | 150 | 43.5 |
| 216 ~ 960 | 3 | 200 | 46.0 |
| 960 ~ 1000 | 3 | 500 | 54.0 |

| Frequency (GHz) | Distance (Meters) | Field Strengths Limit | |
|--------------------|----------------------|--------------------------------------|-----------------------------------|
| | | Average ($\text{dB}\mu\text{V/m}$) | Peak ($\text{dB}\mu\text{V/m}$) |
| 1~6 | 3 | 54 | 74 |

- Remark:
- (1) Emission level ($\text{dB}\mu\text{V}$) = $20 \log$ Emission level $\mu\text{V/m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

5.4. EUT Configuration on Measurement

The FCC Class B regulations test method must be used to find the maximum emission during radiated emission measurement.

EUT : Digital Media Player
Model Number : AMC-43-00, AMC-100-00

5.5. Operating Condition of EUT

5.5.1. Setup the EUT as shown on Section 5.1.

5.5.2. Turn on the power of all equipments.

5.5.3. Let the EUT work in measuring mode (Connect to PC, SD Card Play) and measure it.

5.6. Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Bilog antenna (calibrated by Dipole Antenna) and horn antenna are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the Receiver (ESU26) is set at 120kHz.
The worst scanning curves are attached in Appendix II.


5.7.Measuring Results

PASS.



The frequency range from 30MHz to 6GHz is investigated.
Please refer to Appendix II.


6. PHOTOGRAPHS

6.1.Photos of Conducted Emission Measurement




6.2.Photos of Radiation Emission Measurement





APPENDIX I

AMC-43-00 test data



Site Conduction #1

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz


Humidity: 60 %

Mode: SD Card play

Note:

| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | | |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
| | | MHz | Level | Factor | ment | | | Detector | Comment |
| | | | dBuV | dB | dBuV | dBuV | dB | | |
| 1 | | 0.1500 | 28.89 | 0.00 | 28.89 | 66.00 | -37.11 | QP | |
| 2 | | 0.1500 | 10.09 | 0.00 | 10.09 | 56.00 | -45.91 | AVG | |
| 3 | | 0.2300 | 27.54 | 0.00 | 27.54 | 62.45 | -34.91 | QP | |
| 4 | | 0.2300 | 9.76 | 0.00 | 9.76 | 52.45 | -42.69 | AVG | |
| 5 | * | 0.5700 | 39.52 | 0.00 | 39.52 | 56.00 | -16.48 | QP | |
| 6 | | 0.5700 | 17.26 | 0.00 | 17.26 | 46.00 | -28.74 | AVG | |
| 7 | | 1.5250 | 30.35 | 0.00 | 30.35 | 56.00 | -25.65 | QP | |
| 8 | | 1.5250 | 19.05 | 0.00 | 19.05 | 46.00 | -26.95 | AVG | |
| 9 | | 7.3500 | 26.09 | 0.00 | 26.09 | 60.00 | -33.91 | QP | |
| 10 | | 7.3500 | 15.75 | 0.00 | 15.75 | 50.00 | -34.25 | AVG | |
| 11 | | 21.1750 | 28.43 | 0.00 | 28.43 | 60.00 | -31.57 | QP | |
| 12 | | 21.1750 | 16.94 | 0.00 | 16.94 | 50.00 | -33.06 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site Conduction #1
Limit: (CE)FCC PART 15 class B_QP
Mode: SD Card play
Note:

Phase: **N**
Power: AC 120V/60Hz

Temperature: 26
Humidity: 60 %


| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | | Detector | Comment |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
| | | MHz | Level | Factor | ment | dBuV | dB | | |
| 1 | | 0.1500 | 26.99 | 0.00 | 26.99 | 66.00 | -39.01 | QP | |
| 2 | | 0.1500 | 9.87 | 0.00 | 9.87 | 56.00 | -46.13 | AVG | |
| 3 | | 0.2300 | 28.73 | 0.00 | 28.73 | 62.45 | -33.72 | QP | |
| 4 | | 0.2300 | 10.03 | 0.00 | 10.03 | 52.45 | -42.42 | AVG | |
| 5 | * | 0.5950 | 40.74 | 0.00 | 40.74 | 56.00 | -15.26 | QP | |
| 6 | | 0.5950 | 17.16 | 0.00 | 17.16 | 46.00 | -28.84 | AVG | |
| 7 | | 1.4600 | 29.50 | 0.00 | 29.50 | 56.00 | -26.50 | QP | |
| 8 | | 1.4600 | 17.17 | 0.00 | 17.17 | 46.00 | -28.83 | AVG | |
| 9 | | 21.1750 | 30.50 | 0.00 | 30.50 | 60.00 | -29.50 | QP | |
| 10 | | 21.1750 | 18.56 | 0.00 | 18.56 | 50.00 | -31.44 | AVG | |
| 11 | | 26.0000 | 30.13 | 0.00 | 30.13 | 60.00 | -29.87 | QP | |
| 12 | | 26.0000 | 15.25 | 0.00 | 15.25 | 50.00 | -34.75 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | | |
|-----|-----|--------|---------|---------|----------|-------|--------|----------|---------|
| | | MHz | Level | Factor | ment | | | Detector | Comment |
| 1 | | 0.1500 | 27.35 | 0.00 | 27.35 | 66.00 | -38.65 | QP | |
| 2 | | 0.1500 | 9.63 | 0.00 | 9.63 | 56.00 | -46.37 | AVG | |
| 3 | | 0.2050 | 29.12 | 0.00 | 29.12 | 63.41 | -34.29 | QP | |
| 4 | | 0.2300 | 29.40 | 0.00 | 29.40 | 62.45 | -33.05 | QP | |
| 5 | | 0.2300 | 10.04 | 0.00 | 10.04 | 52.45 | -42.41 | AVG | |
| 6 | * | 0.5700 | 41.65 | 0.00 | 41.65 | 56.00 | -14.35 | QP | |
| 7 | | 0.5700 | 17.21 | 0.00 | 17.21 | 46.00 | -28.79 | AVG | |
| 8 | | 1.4550 | 29.86 | 0.00 | 29.86 | 56.00 | -26.14 | QP | |
| 9 | | 1.4550 | 16.77 | 0.00 | 16.77 | 46.00 | -29.23 | AVG | |
| 10 | | 3.0400 | 25.97 | 0.00 | 25.97 | 56.00 | -30.03 | QP | |
| 11 | | 3.0400 | 17.02 | 0.00 | 17.02 | 46.00 | -28.98 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site Conduction #1

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 60 %


Mode: connect to pc

Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.1550 | 29.73 | 0.00 | 29.73 | 65.73 | -36.00 | QP | |
| 2 | | 0.1550 | 9.46 | 0.00 | 9.46 | 55.73 | -46.27 | AVG | |
| 3 | | 0.2300 | 28.46 | 0.00 | 28.46 | 62.45 | -33.99 | QP | |
| 4 | | 0.2300 | 9.35 | 0.00 | 9.35 | 52.45 | -43.10 | AVG | |
| 5 | * | 0.5700 | 39.21 | 0.00 | 39.21 | 56.00 | -16.79 | QP | |
| 6 | | 0.5700 | 15.24 | 0.00 | 15.24 | 46.00 | -30.76 | AVG | |
| 7 | | 1.5250 | 29.07 | 0.00 | 29.07 | 56.00 | -26.93 | QP | |
| 8 | | 1.5250 | 19.65 | 0.00 | 19.65 | 46.00 | -26.35 | AVG | |
| 9 | | 2.9463 | 24.67 | 0.00 | 24.67 | 56.00 | -31.33 | QP | |
| 10 | | 2.9463 | 17.65 | 0.00 | 17.65 | 46.00 | -28.35 | AVG | |
| 11 | | 22.5000 | 32.29 | 0.00 | 32.29 | 60.00 | -27.71 | QP | |
| 12 | | 22.5000 | 17.40 | 0.00 | 17.40 | 50.00 | -32.60 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:

AMC-100-00 test data




Site Conduction #2
Limit: (CE)FCC PART 15 class B_QP
Mode: sd card play
Note:

Phase: **N**
Power: AC 120V/60Hz

Temperature: 26
Humidity: 60 %

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1 | | 0.4950 | 38.24 | 0.00 | 38.24 | 56.08 | -17.84 | QP | |
| 2 | | 0.4950 | 34.49 | 0.00 | 34.49 | 46.08 | -11.59 | AVG | |
| 3 | | 0.6400 | 46.10 | 0.00 | 46.10 | 56.00 | -9.90 | QP | |
| 4 | * | 0.6400 | 41.03 | 0.00 | 41.03 | 46.00 | -4.97 | AVG | |
| 5 | | 1.0250 | 35.93 | 0.00 | 35.93 | 56.00 | -20.07 | QP | |
| 6 | | 1.0250 | 27.40 | 0.00 | 27.40 | 46.00 | -18.60 | AVG | |
| 7 | | 1.3950 | 40.33 | 0.00 | 40.33 | 56.00 | -15.67 | QP | |
| 8 | | 1.3950 | 34.02 | 0.00 | 34.02 | 46.00 | -11.98 | AVG | |
| 9 | | 2.4100 | 33.67 | 0.00 | 33.67 | 56.00 | -22.33 | QP | |
| 10 | | 2.4100 | 26.86 | 0.00 | 26.86 | 46.00 | -19.14 | AVG | |
| 11 | | 4.1800 | 38.13 | 0.00 | 38.13 | 56.00 | -17.87 | QP | |
| 12 | | 4.1800 | 31.64 | 0.00 | 31.64 | 46.00 | -14.36 | AVG | |

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver. Operator:



Site Conduction #2

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz


Humidity: 60 %

Mode: sd card play

Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | | |
|-----|-----|--------|---------------|----------------|--------------|-------|--------|----------|---------|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.1500 | 40.57 | 0.00 | 40.57 | 66.00 | -25.43 | QP | |
| 2 | | 0.1500 | 22.20 | 0.00 | 22.20 | 56.00 | -33.80 | AVG | |
| 3 | | 0.6400 | 44.00 | 0.00 | 44.00 | 56.00 | -12.00 | QP | |
| 4 | * | 0.6400 | 36.59 | 0.00 | 36.59 | 46.00 | -9.41 | AVG | |
| 5 | | 1.3900 | 45.85 | 0.00 | 45.85 | 56.00 | -10.15 | QP | |
| 6 | | 1.3900 | 36.27 | 0.00 | 36.27 | 46.00 | -9.73 | AVG | |
| 7 | | 2.6400 | 34.41 | 0.00 | 34.41 | 56.00 | -21.59 | QP | |
| 8 | | 2.6400 | 26.08 | 0.00 | 26.08 | 46.00 | -19.92 | AVG | |
| 9 | | 4.1700 | 38.21 | 0.00 | 38.21 | 56.00 | -17.79 | QP | |
| 10 | | 4.1700 | 29.17 | 0.00 | 29.17 | 46.00 | -16.83 | AVG | |
| 11 | | 5.5700 | 36.84 | 0.00 | 36.84 | 60.00 | -23.16 | QP | |
| 12 | | 5.5700 | 25.28 | 0.00 | 25.28 | 50.00 | -24.72 | AVG | |

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site Conduction #2

Limit: (CE)EN55022 class B_QP

Mode: connect to pc

Note:

Phase: L1

Power: AC 230V/50Hz

Temperature: 26

Humidity: 60 %

| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | | |
|-----|-----|--------|---------|---------|----------|-------|--------|----------|---------|
| | | MHz | Level | Factor | ment | | | Detector | Comment |
| | | | dBuV | dB | dBuV | dBuV | dB | | |
| 1 | | 0.1650 | 54.60 | 0.00 | 54.60 | 65.21 | -10.61 | QP | |
| 2 | | 0.1700 | 27.26 | 0.00 | 27.26 | 54.96 | -27.70 | AVG | |
| 3 | | 0.2150 | 53.60 | 0.00 | 53.60 | 63.01 | -9.41 | QP | |
| 4 | | 0.2200 | 28.12 | 0.00 | 28.12 | 52.82 | -24.70 | AVG | |
| 5 | | 0.3150 | 52.40 | 0.00 | 52.40 | 59.84 | -7.44 | QP | |
| 6 | | 0.3200 | 21.22 | 0.00 | 21.22 | 49.71 | -28.49 | AVG | |
| 7 | | 0.6150 | 50.13 | 0.00 | 50.13 | 56.00 | -5.87 | QP | |
| 8 | * | 0.6400 | 41.68 | 0.00 | 41.68 | 46.00 | -4.32 | AVG | |
| 9 | | 2.3800 | 27.11 | 0.00 | 27.11 | 46.00 | -18.89 | AVG | |
| 10 | | 2.4200 | 35.02 | 0.00 | 35.02 | 56.00 | -20.98 | QP | |
| 11 | | 2.9700 | 35.96 | 0.00 | 35.96 | 56.00 | -20.04 | QP | |
| 12 | | 2.9700 | 26.75 | 0.00 | 26.75 | 46.00 | -19.25 | AVG | |


*:Maximum data

x:Over limit

!:over margin

Comment: Factor build in receiver.

Operator:



Site Conduction #2

Phase: L1

Temperature: 26

Limit: (CE)EN55022 class B_QP

Power: AC 120V/60Hz

Humidity: 60 %

Mode: connect to pc

Note:

| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | | |
|-----|-----|--------|---------|---------|----------|-------|--------|----------|---------|
| | | MHz | Level | Factor | ment | | | Detector | Comment |
| | | | dBuV | dB | dBuV | dBuV | dB | | |
| 1 | | 0.1650 | 54.60 | 0.00 | 54.60 | 65.21 | -10.61 | QP | |
| 2 | | 0.1650 | 27.26 | 0.00 | 27.26 | 55.21 | -27.95 | AVG | |
| 3 | | 0.2150 | 53.60 | 0.00 | 53.60 | 63.01 | -9.41 | QP | |
| 4 | | 0.2150 | 28.12 | 0.00 | 28.12 | 53.01 | -24.89 | AVG | |
| 5 | | 0.3150 | 52.40 | 0.00 | 52.40 | 59.84 | -7.44 | QP | |
| 6 | | 0.3150 | 21.22 | 0.00 | 21.22 | 49.84 | -28.62 | AVG | |
| 7 | | 0.6150 | 50.13 | 0.00 | 50.13 | 56.00 | -5.87 | QP | |
| 8 | * | 0.6150 | 41.68 | 0.00 | 41.68 | 46.00 | -4.32 | AVG | |
| 9 | | 2.3800 | 35.02 | 0.00 | 35.02 | 56.00 | -20.98 | QP | |
| 10 | | 2.3800 | 27.11 | 0.00 | 27.11 | 46.00 | -18.89 | AVG | |
| 11 | | 2.9700 | 35.96 | 0.00 | 35.96 | 56.00 | -20.04 | QP | |
| 12 | | 2.9700 | 26.75 | 0.00 | 26.75 | 46.00 | -19.25 | AVG | |

*:Maximum data

x:Over limit


!:over margin

Comment: Factor build in receiver.

Operator:


APPENDIX II

AMC-43-00 test data




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure-ment | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|--------------|--------|-------|----------------|--------------|--------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | Detector | cm | degree |
| 1 | | 235.1923 | 24.74 | 13.45 | 38.19 | 46.00 | -7.81 | QP | | |
| 2 | | 298.9262 | 25.16 | 13.84 | 39.00 | 46.00 | -7.00 | QP | | |
| 3 | I | 393.7500 | 23.29 | 16.90 | 40.19 | 46.00 | -5.81 | QP | | |
| 4 | I | 407.7403 | 22.85 | 17.20 | 40.05 | 46.00 | -5.95 | QP | | |
| 5 | I | 449.7115 | 21.34 | 18.88 | 40.22 | 46.00 | -5.78 | QP | | |
| 6 | * | 480.8012 | 22.01 | 18.45 | 40.46 | 46.00 | -5.54 | QP | | |

*:Maximum data x:Over limit I:over margin Operator: RJB



*:Maximum data x:Over limit !:over margin Operator: RJB



Site site #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 60 %


Mode:Connect to PC

Note:

| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 1496.795 | 63.10 | -12.27 | 50.83 | 74.00 | -23.17 | peak | | |
| 2 | | 1496.795 | 52.30 | -12.27 | 40.03 | 54.00 | -13.97 | AVG | | |
| 3 | | 1993.590 | 58.09 | -10.81 | 47.28 | 74.00 | -26.72 | peak | | |
| 4 | | 1993.590 | 47.60 | -10.81 | 36.79 | 54.00 | -17.21 | AVG | | |
| 5 | | 2394.231 | 66.17 | -8.66 | 57.51 | 74.00 | -16.49 | peak | | |
| 6 | * | 2394.231 | 57.30 | -8.66 | 48.64 | 54.00 | -5.36 | AVG | | |
| 7 | | 3748.397 | 55.98 | -6.72 | 49.26 | 74.00 | -24.74 | peak | | |
| 8 | | 3748.397 | 42.30 | -6.72 | 35.58 | 54.00 | -18.42 | AVG | | |
| 9 | | 4501.602 | 55.28 | -5.05 | 50.23 | 74.00 | -23.77 | peak | | |
| 10 | | 4501.602 | 42.80 | -5.05 | 37.75 | 54.00 | -16.25 | AVG | | |
| 11 | | 5254.808 | 53.36 | -4.06 | 49.30 | 74.00 | -24.70 | peak | | |
| 12 | | 5254.808 | 41.90 | -4.06 | 37.84 | 54.00 | -16.16 | AVG | | |

*:Maximum data x:Over limit !:over margin

Operator: RJB




Site site #1 Polarization: **Vertical** Temperature: 26
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 60 %
 Mode: Connect to PC
 Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1 | | 1496.795 | 70.23 | -12.27 | 57.96 | 74.00 | -16.04 | peak | | |
| 2 | * | 1496.795 | 60.50 | -12.27 | 48.23 | 54.00 | -5.77 | AVG | | |
| 3 | | 1993.590 | 59.51 | -10.81 | 48.70 | 74.00 | -25.30 | peak | | |
| 4 | | 1993.590 | 47.60 | -10.81 | 36.79 | 54.00 | -17.21 | AVG | | |
| 5 | | 2394.231 | 56.74 | -8.66 | 48.08 | 74.00 | -25.92 | peak | | |
| 6 | | 2394.231 | 42.80 | -8.66 | 34.14 | 54.00 | -19.86 | AVG | | |
| 7 | | 3003.205 | 55.10 | -7.58 | 47.52 | 74.00 | -26.48 | peak | | |
| 8 | | 3003.205 | 41.65 | -7.58 | 34.07 | 54.00 | -19.93 | AVG | | |
| 9 | | 3748.397 | 59.36 | -6.72 | 52.64 | 74.00 | -21.36 | peak | | |
| 10 | | 3748.397 | 47.60 | -6.72 | 40.88 | 54.00 | -13.12 | AVG | | |
| 11 | | 5254.808 | 52.58 | -4.06 | 48.52 | 74.00 | -25.48 | peak | | |
| 12 | | 5254.808 | 40.50 | -4.06 | 36.44 | 54.00 | -17.56 | AVG | | |


*:Maximum data x:Over limit !:over margin

Operator: RJB



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|-------|----------|--------|--------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | Detector | cm | degree |
| 1 | | 382.8684 | 22.81 | 16.63 | 39.44 | 46.00 | -6.56 | QP | | |
| 2 | ! | 404.6313 | 24.48 | 17.14 | 41.62 | 46.00 | -4.38 | QP | | |
| 3 | | 410.8493 | 20.10 | 17.25 | 37.35 | 46.00 | -8.65 | QP | | |
| 4 | * | 415.5128 | 24.90 | 17.33 | 42.23 | 46.00 | -3.77 | QP | | |
| 5 | ! | 427.9485 | 23.83 | 17.55 | 41.38 | 46.00 | -4.62 | QP | | |
| 6 | ! | 449.7115 | 22.08 | 18.88 | 40.96 | 46.00 | -5.04 | QP | | |

*:Maximum data x:Over limit !:over margin Operator: RJB



Site site #1

Polarization: *Horizontal*

Temperature: 26

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 60 %

Mode:SD Card Play


Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|-------|----------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | Detector | cm | degree | Comment |
| 1 | ! | 149.6954 | 29.22 | 9.02 | 38.24 | 43.50 | -5.26 | QP | | | |
| 2 | | 168.3490 | 25.43 | 9.70 | 35.13 | 43.50 | -8.37 | QP | | | |
| 3 | | 224.3108 | 24.34 | 12.13 | 36.47 | 46.00 | -9.53 | QP | | | |
| 4 | ! | 298.9261 | 26.49 | 13.89 | 40.38 | 46.00 | -5.62 | QP | | | |
| 5 | | 393.7500 | 21.29 | 17.81 | 39.10 | 46.00 | -6.90 | QP | | | |
| 6 | * | 404.6313 | 23.09 | 18.27 | 41.36 | 46.00 | -4.64 | QP | | | |

*:Maximum data x:Over limit !:over margin


Operator: RJB

AMC-100-00 test data




| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table |
|-----|-----|----------|---------|---------|----------|--------|-------|---------|--------|
| | | MHz | Level | Factor | ment | | | Height | Degree |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree |
| 1 | ! | 337.7884 | 25.45 | 14.96 | 40.41 | 46.00 | -5.59 | QP | |
| 2 | * | 473.0288 | 23.48 | 18.33 | 41.81 | 46.00 | -4.19 | QP | |
| 3 | ! | 605.1602 | 20.30 | 20.67 | 40.97 | 46.00 | -5.03 | QP | |
| 4 | | 807.2435 | 17.28 | 22.53 | 39.81 | 46.00 | -6.19 | QP | |
| 5 | | 880.3044 | 15.95 | 23.28 | 39.23 | 46.00 | -6.77 | QP | |
| 6 | | 944.0384 | 14.51 | 24.66 | 39.17 | 46.00 | -6.83 | QP | |

*:Maximum data x:Over limit !:over margin Operator: RJB



*:Maximum data x:Over limit !:over margin Operator: RJB



Site site #1

Polarization: **Vertical**

Temperature: 26

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 60 %


Mode:CONNECT TO PC

Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector | Antenna Height cm | Table Degree degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|-------------------------|---------------------------|---------|
| 1 | | 1024.038 | 69.22 | -13.57 | 55.65 | 74.00 | -18.35 | peak | | | |
| 2 | * | 1024.038 | 53.88 | -13.57 | 40.31 | 54.00 | -13.69 | AVG | | | |
| 3 | | 1200.321 | 66.89 | -13.02 | 53.87 | 74.00 | -20.13 | peak | | | |
| 4 | | 1200.321 | 49.59 | -13.02 | 36.57 | 54.00 | -17.43 | AVG | | | |
| 5 | | 1272.436 | 70.32 | -12.49 | 57.83 | 74.00 | -16.17 | peak | | | |
| 6 | | 1272.436 | 47.50 | -12.49 | 35.01 | 54.00 | -18.99 | AVG | | | |
| 7 | | 1488.782 | 63.86 | -12.26 | 51.60 | 74.00 | -22.40 | peak | | | |
| 8 | | 1488.782 | 50.14 | -12.26 | 37.88 | 54.00 | -16.12 | AVG | | | |
| 9 | | 2113.782 | 57.19 | -9.30 | 47.89 | 74.00 | -26.11 | peak | | | |
| 10 | | 2113.782 | 40.44 | -9.30 | 31.14 | 54.00 | -22.86 | AVG | | | |
| 11 | | 2498.397 | 58.09 | -8.62 | 49.47 | 74.00 | -24.53 | peak | | | |
| 12 | | 2498.397 | 39.19 | -8.62 | 30.57 | 54.00 | -23.43 | AVG | | | |

*:Maximum data x:Over limit !:over margin

Operator: RJB



Site site #1

Polarization: **Horizontal**

Temperature: 26

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 60 %


Mode:CONNECT TO PC

Note:

| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|--------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 1144.231 | 64.29 | -13.27 | 51.02 | 74.00 | -22.98 | peak | | |
| 2 | | 1144.231 | 53.76 | -13.27 | 40.49 | 54.00 | -13.51 | AVG | | |
| 3 | | 1208.333 | 64.17 | -12.96 | 51.21 | 74.00 | -22.79 | peak | | |
| 4 | | 1208.333 | 50.92 | -12.96 | 37.96 | 54.00 | -16.04 | AVG | | |
| 5 | | 1280.449 | 62.57 | -12.42 | 50.15 | 74.00 | -23.85 | peak | | |
| 6 | * | 1280.449 | 53.86 | -12.42 | 41.44 | 54.00 | -12.56 | AVG | | |
| 7 | | 1352.564 | 58.00 | -12.20 | 45.80 | 74.00 | -28.20 | peak | | |
| 8 | | 1352.564 | 48.45 | -12.20 | 36.25 | 54.00 | -17.75 | AVG | | |
| 9 | | 1480.769 | 57.85 | -12.24 | 45.61 | 74.00 | -28.39 | peak | | |
| 10 | | 1480.769 | 48.26 | -12.24 | 36.02 | 54.00 | -17.98 | AVG | | |
| 11 | | 1689.103 | 59.56 | -12.30 | 47.26 | 74.00 | -26.74 | peak | | |
| 12 | | 1689.103 | 46.74 | -12.30 | 34.44 | 54.00 | -19.56 | AVG | | |


*:Maximum data x:Over limit l:over margin

Operator: RJB



| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table |
|-----|-----|----------|---------|---------|----------|--------|----------|---------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree |
| | | | | | | | Detector | | Comment |
| 1 | | 269.3910 | 24.28 | 14.11 | 38.39 | 46.00 | -7.61 | QP | |
| 2 | | 485.4646 | 20.30 | 18.53 | 38.83 | 46.00 | -7.17 | QP | |
| 3 | ! | 648.6856 | 19.49 | 21.19 | 40.68 | 46.00 | -5.32 | QP | |
| 4 | * | 757.5000 | 18.54 | 23.01 | 41.55 | 46.00 | -4.45 | QP | |
| 5 | | 920.7210 | 14.39 | 24.20 | 38.59 | 46.00 | -7.41 | QP | |
| 6 | | 972.0191 | 18.88 | 24.67 | 43.55 | 54.00 | -10.45 | QP | |

*:Maximum data x:Over limit !:over margin Operator: RJB





| No. | Mk. | Freq. | Reading | Correct | Measure- | Limit | Over | Antenna | Table | |
|-----|-----|----------|---------|---------|----------|--------|-------|---------|--------|---------|
| | | MHz | Level | Factor | ment | | | Height | Degree | |
| | | | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | | 269.3910 | 26.77 | 13.08 | 39.85 | 46.00 | -6.15 | QP | | |
| 2 | ! | 432.6120 | 22.66 | 17.54 | 40.20 | 46.00 | -5.80 | QP | | |
| 3 | | 539.8716 | 19.10 | 19.86 | 38.96 | 46.00 | -7.04 | QP | | |
| 4 | * | 594.2788 | 20.58 | 20.34 | 40.92 | 46.00 | -5.08 | QP | | |
| 5 | | 703.0930 | 14.11 | 23.93 | 38.04 | 46.00 | -7.96 | QP | | |
| 6 | | 757.5000 | 16.46 | 22.54 | 39.00 | 46.00 | -7.00 | QP | | |

*:Maximum data x:Over limit !:over margin Operator: RJB

APPENDIX III (Photos of EUT)

Photos of AMC-43-00











Photos of AMC-100-00



