# System Performance Check Data (850MHz Head)

Report No: KS101011B03

Date of measurement: 13/10/2010

Area Scan: 7 x 7 x 1 dx=15mm dy=15mm

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm


#### A. Experimental conditions.

Phantom File	surf_sam_plan.txt, Adaptative 2 max	
Phantom	Validation plane	
Device Position	Body	
Band	GSM850	
Channels	Middle	
Signal	CW	


PC	HP (Pentium(R) V3.06GHz,	Calibration Due: N/A
	SN:375052-AA1)	
Wireless Communication Test Set	R&S (CMU200,	Calibration Due: 05/25/2011
	SN:B23-03291)	
Network Analyzer	Agilent(E5071B,	Calibration Due: 03/24/2011
	MY42301382)	
Voltmeter	Keithley (2000,	Calibration Due: 05/25/2011
	SN:1015843)	
Signal Generator	Agilent (E8257C,	Calibration Due: 03/24/2011
	SN:MY43321570)	
Amplifier	Mini-Circuits (ZHL-42,	Calibration Due: 07/29/2011
	SN:110405)	
Power Meter	Agilent (E4416A,	Calibration Due: 03/24/2011
	SN:QB41292714)	
Probe	Antennessa	Calibration Due: 05/10/2011
	(SN:SN_1109_EP_100)	
DIPOLE 835	Antennessa (DIPI32,SN	Calibration Due: 02/09/2011
	48/05)	
Phantom	Antennessa	Calibration Due: N/A
	(SN:SN41_05_SAM29)	
Liquid	Antennessa	Calibration Due: N/A
Measurement SW	OPEN SAR V2.1	Calibration Due: N/A



Frequency (MHz)	835.000024
Relative permitivity (real part)	41.417999
Relative permitivity (imaginary part)	20.020350
Conductivity (S/m)	0.930279
Variation (%)	-0.470000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C
ConvF:	20.66, 20.51, 28.36
Crest factor:	1:1




# System Performance Check Data (850MHz Body)



Maximum location: X=0.00, Y=-5.00

SAR 10g (W/Kg)	6.384533
SAR 1g (W/Kg)	9.537344

SAR, Z Axis Scan (X = 0, Y = -2)



Date of measurement: 13/10/2010

Zoom Scan:  $5 \times 5 \times 7$  dx=5mm dy=5mm dz=5mm Z Axis Scan:  $1 \times 1 \times 21$  dx=20mm dy=20mm dz=5mm


Report No: KS101011B03

### A. Experimental conditions.

Phantom File	surf_sam_plan.txt, Adaptative 2 max	
Phantom	Validation plane	
Device Position	Body	
Band	GSM850	
Channels	Middle	
Signal	CW	


P (Pentium(R) V3.06GHz, SN:375052-AA1) R&S (CMU200,	Calibration Due: N/A
•	
R&S (CMU200,	
	Calibration Due: 05/25/2011
SN:B23-03291)	
Agilent(E5071B,	Calibration Due: 03/24/2011
MY42301382)	
Keithley (2000,	Calibration Due: 05/25/2011
SN:1015843)	
Agilent (E8257C,	Calibration Due: 03/24/2011
SN:MY43321570)	
Mini-Circuits (ZHL-42,	Calibration Due: 07/29/2011
SN:110405)	
Agilent (E4416A,	Calibration Due: 03/24/2011
SN:QB41292714)	
Antennessa	Calibration Due: 05/10/2011
(SN:SN_1109_EP_100)	
Antennessa (DIPI32,SN	Calibration Due: 02/09/2011
48/05)	
Antennessa	Calibration Due: N/A
(SN:SN41_05_SAM29)	
Antennessa	Calibration Due: N/A
OPEN SAR V2.1	Calibration Due: N/A
	SN:B23-03291)  Agilent(E5071B,

Frequency (MHz)	835.000024
Relative permitivity (real part)	57.501999
Relative permitivity (imaginary part)	21.866249
Conductivity (S/m)	1.016052
Variation (%)	-0.740000
Ambient Temperature:	21 °C
Liquid Temperature:	20 °C
ConvF:	20.00, 19.88, 27.77
Crest factor:	1:1



# System Performance Check Data (1900MHz Head)

Report No: KS101011B03



Maximum location: X=0.00, Y=-5.00

SAR 10g (W/Kg)	6.854345
SAR 1g (W/Kg)	10.171448

#### **Z Axis Scan**

SAR, Z Axis Scan (X = 0, Y = 0)

10.68

8.00

4.00

1.50

0.02.55.07.510.0 15.0 20.0 25.0 30.0 35.0 Z (mm)

Page 6 FCC ID: WNKUMEOX-QPAD2

Date of measurement: 13/10/2010

Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm


Report No: KS101011B03

### A. Experimental conditions.


Phantom File	surf_sam_plan.txt, Adaptative 2 max
Phantom	Validation plane
Device Position	Body
Band	GSM1900
Channels	Middle
Signal	CW

		I
PC	HP (Pentium(R) V3.06GHz,	Calibration Due: N/A
	SN:375052-AA1)	
Wireless Communication Test Set	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2011
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C,	Calibration Due: 03/24/2011
	SN:MY43321570)	
Amplifier	Mini-Circuits (ZHL-42,	Calibration Due: 07/29/2011
	SN:110405)	
Power Meter	Agilent (E4416A,	Calibration Due: 03/24/2011
	SN:QB41292714)	
Probe	Antennessa	Calibration Due: 05/10/2011
	(SN:SN_1109_EP_100)	
DIPOLE 1900	Antennessa (DIPI36, SN 48/05	Calibration Due: 02/09/2011
Phantom	Antennessa	Calibration Due: N/A
	(SN:SN41_05_SAM29)	
Liquid	Antennessa	Calibration Due: N/A
Measurement SW	OPEN SAR V2.1	Calibration Due: N/A

Frequency (MHz)	1950.000000
Relative permitivity (real part)	40.306999
Relative permitivity (imaginary part)	13.506150
Conductivity (S/m)	1.410642
Variation (%)	-0.460000
Ambient Temperature	21 °C
Liquid Temperature	20 °C
ConvF	41.91, 43.15, 56.44
Crest factor	1:1








Maximum location: X=0.00, Y=-5.00

SAR 10g (W/Kg)	21.122345
SAR 1g (W/Kg)	39.374234

SAR, Z Axis Scan (X = 0, Y = 0)



Page 9 FCC ID: WNKUMEOX-QPAD2

## System Performance Check Data (1900MHz Body)

Report No: KS101011B03

Date of measurement: 13/10/2010

Area Scan: 7 x 7 x 1 dx=15mm dy=15mm


Zoom Scan: 5 x 5 x 7 dx=5mm dy=5mm dz=5mm Z Axis Scan: 1 x 1 x 21 dx=20mm dy=20mm dz=5mm


### A. Experimental conditions.

Phantom File	surf_sam_plan.txt, Adaptative 2 max
Phantom	Validation plane
Device Position	Body
Band	GSM1900
Channels	Middle
Signal	CW

PC	HP (Pentium(R) V3.06GHz,	Calibration Due: N/A
	SN:375052-AA1)	
Wireless Communication Test Set	R&S (CMU200, SN:B23-03291)	Calibration Due: 05/25/2011
Network Analyzer	Agilent(E5071B, MY42301382)	Calibration Due: 03/24/2011
Voltmeter	Keithley (2000, SN:1015843)	Calibration Due: 05/25/2011
Signal Generator	Agilent (E8257C,	Calibration Due: 03/24/2011
	SN:MY43321570)	
Amplifier	Mini-Circuits (ZHL-42,	Calibration Due: 07/29/2011
	SN:110405)	
Power Meter	Agilent (E4416A,	Calibration Due: 03/24/2011
	SN:QB41292714)	
Probe	Antennessa	Calibration Due: 05/10/2011
	(SN:SN_1109_EP_100)	
DIPOLE 1900	Antennessa (DIPI36, SN 48/05	Calibration Due: 02/09/2011
Phantom	Antennessa	Calibration Due: N/A
	(SN:SN41_05_SAM29)	
Liquid	Antennessa	Calibration Due: N/A
Measurement SW	OPEN SAR V2.1	Calibration Due: N/A

Frequency (MHz)	1950.000000
Relative permitivity (real part)	52.143660
Relative permitivity (imaginary part)	13.691050
Conductivity (S/m)	1.4431460
Variation (%)	-0.450000
Ambient Temperature	21 °C
Liquid Temperature	20 °C
ConvF	41.01, 42.41, 55.65
Crest factor	1:1






Report No: KS101011B03

Maximum location: X=0.00, Y=-1.00

SAR 10g (W/Kg)	20.234145
SAR 1g (W/Kg)	38.414545

#### **Z Axis Scan**

SAR, Z Axis Scan (X = 0, Y = -1)



FCC ID: WNKUMEOX-QPAD2