

Test Report of FCC CFR 47 Part 15 Subpart B

On Behalf of

SHENZHEN XI LONG ELECTRONICS CO., LTD

FCC ID: WO9- PIR-SD

Product Description: PIR motion sensor with hidden camera,SD recorder

Model No.: PIR-SD

Supplementary Model: N/A

Brand Name: N/A

Prepared for: SHENZHEN XI LONG ELECTRONICS CO., LTD

No.2201, bldg.2, duoli industrial park, no.105, mei hua road, shang
meilin, fu tian, shen zhen city, guang dong, china,

Prepared by: Shenzhen Bontek Compliance Testing Laboratory Co., Ltd.

1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East
Road, Nanshan, Shenzhen, China

Tel: 86-755-86337020


Fax: 86-755-86337028

Report No.: BCT13AR-0085E-2


Issue Date: May 2, 2013

Test Date: March 25~May 2, 2013

Tested by:


Lion Cai

Reviewed by:


Kendy Wang

Approved by:



Tony Wu

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS	4
1.3 TEST FACILITY	4
2. SYSTEM TEST CONFIGURATION	5
2.1 EUT CONFIGURATION	5
2.2 SUPPORT EQUIPMENTS	5
2.3 GENERAL TEST PROCEDURES	5
2.4 MEASUREMENT UNCERTAINTY	5
2.5 LIST OF MEASURING EQUIPMENTS USED	6
3. SUMMARY OF TEST RESULTS.....	7
4. TEST OF AC POWER LINE CONDUCTED EMISSION	8
4.1 LIMIT OF AC POWER LINE CONDUCTED EMISSION	8
4.2 EUT SETUP	8
4.3 INSTRUMENT SETUP	9
4.4 TEST PROCEDURE	9
4.5 TEST RESULT	9
5 - RADIATED DISTURBANCES	14
5.1 LIMIT OF RADIATED DISTURBANCES	14
5.2 EUT SETUP	14
5.3 TEST RECEIVER SETUP	15
5.4 TEST PROCEDURE	15
5.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	15
5.6 RADIATED EMISSIONS TEST RESULT	15

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	SHENZHEN XI LONG ELECTRONICS CO., LTD
Address of Applicant:	No.2201, bldg.2, duoli industrial park, no.105, mei hua road, shang meilin, fu tian, shen zhen city, guang dong, china,
Manufacturer:	SHENZHEN XI LONG ELECTRONICS CO., LTD
Address of Manufacturer:	No.2201, bldg.2, duoli industrial park, no.105, mei hua road, shang meilin, fu tian, shen zhen city, guang dong, china,

General Description of E.U.T

Items	Description
EUT Description:	PIR motion sensor with hidden camera,SD recorder
Trade Name:	N/A
Model No.:	PIR-SD
Rated Voltage	DC 5V 1000mA
Frequency range	433.92MHz
Number of channels	1
Channel Separation	None
Product Class:	Part 15 Security/Remote Control Transmitter

** The test data gathered are from the production sample provided by the manufacturer.*

1.2 Test Standards

The report of EUT is prepared in accordance with FCC Rules and Regulations Part 15 Subpart B. The objective of the manufacturer is to demonstrate compliance with the described above standards.

1.3 Test Facility

All measurement required was performed at laboratory of Shenzhen Bontek Compliance Testing Laboratory Co., Ltd. at 1/F, Block East H-3, OCT Eastern Ind. Zone, Qiaocheng East Road, Nanshan, Shenzhen, China.

The test facility is recognized, certified, or accredited by the following organizations:

FCC – Registration No.: 338263

Shenzhen Bontek Compliance Testing Laboratory Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 338263, March 03, 2011.

IC Registration No.: 7631A

The 3m alternate test site of Shenzhen Bontek Compliance Testing Laboratory Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 7631A on January 25, 2011.

CNAS - Registration No.: L3923

Shenzhen Bontek Compliance Testing Laboratory Co., Ltd. to ISO/IEC 17025:25 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. The acceptance letter from the CNAS is maintained in our files: Registration: L3923, March 22, 2012.

TUV - Registration No.: UA 50242657-0001

Shenzhen Bontek Compliance Testing Laboratory Co., Ltd. An assessment of the laboratory was conducted according to the "Procedures and Conditions for EMC Test Laboratories" with reference to EN ISO/IEC 17025 by a TUV Rheinland auditor. Audit Report NO. 17010783-003.

2. SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2 Support Equipments

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 3 or 10 meters from the leading edge of the turntable.

Support equipments or special accessories in test configuration:

AUX Description:	Manufacturer	Model No.	Certificate	CABLE
Host Computer	Dell	78MD82X	CE, FCC	1.5m Unshielded Power Cord
Monitor	Dell	E178Pc	CE, FCC	1.5m Unshielded Power Cord 1.8m shielded data Cable with core
Keyboard	Dell	L100	CE, FCC	1.8m shielded data Cable with core
Mouse	Dell	OCJ339	CE, FCC	1.8m shielded data Cable with core
Printer	EPSON	P330A	CE, FCC	1.2m Unshielded Power Cord 1.5m shielded data Cable

2.3 General Test Procedures

Conducted Emissions: The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 7.1 of ANSI C63.4-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak detector mode.

Radiated Emissions: The EUT is placed on a turntable, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4-2009.

2.4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Power Line Conducted Emission	+/- 2.3 dB
Radiated Emission	+/- 3.4 dB

Uncertainty figures are valid to a confidence level of 95%.

2.5 List of Measuring Equipments Used

Test equipments list of Shenzhen Bontek Compliance Testing Laboratory Co., Ltd.

No.	Instrument no.	Equipment	Manufacturer	Model No.	S/N	Last Calculator	Due Calculator
1	BCT-EMC001	EMI Test Receiver	R&S	ESCI	100687	2013-4-16	2014-4-17
2	BCT-EMC002	EMI Test Receiver	R&S	ESPI	100097	2012-11-1	2013-10-31
3	BCT-EMC003	Amplifier	HP	8447D	1937A02492	2013-4-19	2014-4-18
4	BCT-EMC004	Single Power Conductor Module	R&S	NNBM 8124	242	2013-4-19	2014-4-18
5	BCT-EMC005	Single Power Conductor Module	R&S	NNBM 8124	243	2013-4-19	2014-4-18
6	BCT-EMC006	Power Clamp	SCHWARZBECK	MDS-21	3812	2012-11-5	2013-11-4
7	BCT-EMC007	Positioning Controller	C&C	CC-C-1F	MF7802113	N/A	N/A
8	BCT-EMC008	Electrostatic Discharge Simulator	TESEQ	NSG437	125	2012-11-2	2013-11-1
9	BCT-EMC009	Fast Transient Burst Generator	SCHAFFNER	MODULA6150	34572	2013-4-16	2014-4-17
10	BCT-EMC010	Fast Transient Noise Simulator	Noiseken	FNS-105AX	10501	2012-6-26	2013-6-25
11	BCT-EMC011	Color TV Pattern Generator	PHILIPS	PM5418	TM209947	N/A	N/A
12	BCT-EMC012	Power Frequency Magnetic Field Generator	EVERFINE	EMS61000-8K	608002	2013-4-16	2014-4-17
14	BCT-EMC014	Capacitive Coupling Clamp	TESEQ	CDN8014	25096	2013-4-16	2014-4-17
15	BCT-EMC015	High Field Biconical Antenna	ELECTRO-METRICS	EM-6913	166	2012-11-28	2013-11-27
16	BCT-EMC016	Log Periodic Antenna	ELECTRO-METRICS	EM-6950	811	2012-11-28	2013-11-27
17	BCT-EMC017	Remote Active Vertical Antenna	ELECTRO-METRICS	EM-6892	304	2012-11-28	2013-11-27
18	BCT-EMC018	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9163	9163-324	2012-5-19	2014-5-18
19	BCT-EMC019	Horn Antenna	SCHWARZBECK	BBHA9120A	0499	2012-11-28	2013-11-27
20	BCT-EMC020	Teo Line Single Phase Module	SCHWARZBECK	NSLK8128	8128247	2012-11-1	2013-10-31
21	BCT-EMC021	Triple-Loop Antenna	EVERFINE	LLA-2	711002	2012-11-15	2013-11-14
22	BCT-EMC022	Electric bridge	Jhai	JK2812C	803024	N/A	N/A
23	BCT-EMC026	RF POWER AMPLIFIER	FRANKONIA	FLL-75	1020A1109	2012-4-17	2013-4-16
24	BCT-EMC027	CDN	FRANKONIA	CDN M2+M3	A3027019	2012-4-17	2013-4-16
25	BCT-EMC029	6DB Attenuator	FRANKONIA	N/A	1001698	2012-4-17	2013-4-16

26	BCT-EMC030	EM Injection clamp	FCC	F-203I-23mm	091536	2013-4-16	2014-4-17
27	BCT-EMC031	9kHz-2.4GHz signal generator 2024	MARCONI	10S/6625-99-457-8730	112260/042	2013-4-16	2014-4-17
28	BCT-EMC032	10dB attenuator	ELECTRO-METRICS	EM-7600	836	2013-4-16	2014-4-17
29	BCT-EMC033	ISN	TESEQ	ISN-T800	30301	2012-11-15	2013-11-14
30	BCT-EMC034	10KV surge generator	SANKI	SKS-0510M	048110003E321	2012-11-01	2013-10-31
31	BCT-EMC035	HRMONICS&FLICKRE ANALYSER	VOLTECH	PM6000	200006700433	2012-11-20	2013-11-19
32	BCT-EMC036	Spectrum Analyzer	R&S	FSP	100397	2012-11-1	2013-10-31
33	BCT-EMC037	Broadband preamplifier	SCHWARZBECK	BBV9718	9718-182	2013-4-19	2014-4-18

3. SUMMARY OF TEST RESULTS

Standard	Test Items	Result
FCC Part 15 Subpart B	Conduction Emission, 0.15MHz to 30MHz	Pass
FCC Part 15 Subpart B	Radiation Emission, 30MHz to 1000MHz	Pass

4. TEST OF AC POWER LINE CONDUCTED EMISSION

4.1 Limit of AC Power Line Conducted Emission

Frequency Range (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

4.2 EUT Setup


The setup of EUT is according with ANSI C63.4-2009 measurement procedure. The specification used was the FCC Rules and Regulations Part 15 Subpart B limits.

The EUT was placed center and the back edge of the test table.

The AV cables were draped along the test table and bundled to 30-40cm in the middle.

The spacing between the peripherals was 10 cm.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.



Remark: The EUT was connected to a 120VAC/ 60Hz power source.

4.3 Instrument Setup

The test receiver was set with the following configurations:

Test Receiver Setting:

Frequency Range.....150 KHz to 30 MHz
Detector.....Peak & Quasi-Peak & Average
Sweep Speed.....Auto
IF Band Width.....9 KHz

4.4 Test Procedure

During the conducted emission test, the EUT power cord was connected to the auxiliary outlet of the first Artificial Mains.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination.

All data was recorded in the peak detection mode. Quasi-peak and Average readings were only performed when an emission was found to be marginal (within -10 dB μ V of specification limits). Quasi-peak readings are distinguished with a "QP". Average readings are distinguished with a "AV".


4.5 Test Result

Temperature (°C) : 22~23	EUT: PIR motion sensor with hidden camera, SD recorder
Humidity (%RH) : 50~54	M/N: PIR-SD
Barometric Pressure (mbar) : 950~1000	Operation Condition: Charging & Camera / PC & Download

Conducted Emission:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: Charging & Camera
Test Site: Shielded Room
Operator: Yang
Test Specification: AC 120V/60Hz for adapter
Comment: L Line

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "AR-0085E N_fin"

4/18/2013 2:16PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.451500	41.20	10.3	57	15.6	QP	N	GND
1.126500	36.90	10.3	56	19.1	QP	N	GND
23.347500	33.30	10.8	60	26.7	QP	N	GND
23.370000	35.50	10.8	60	24.5	QP	N	GND
23.379000	33.60	10.8	60	26.4	QP	N	GND
23.752500	34.10	10.8	60	25.9	QP	N	GND

MEASUREMENT RESULT: "AR-0085E N_fin2"


4/18/2013 2:16PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.226500	37.10	10.7	53	15.5	AV	N	GND
0.451500	35.50	10.3	47	11.3	AV	N	GND
0.676500	25.90	10.2	46	20.1	AV	N	GND
0.901500	30.00	10.2	46	16.0	AV	N	GND
1.126500	30.70	10.3	46	15.3	AV	N	GND
1.576500	22.10	10.2	46	23.9	AV	N	GND

Conducted Emission:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: Charging & Camera
Test Site: Shielded Room
Operator: Yang
Test Specification: AC 120V/60Hz for adapter
Comment: N Line

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "AR-0085E L_fin"

4/18/2013 2:13PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.226500	45.20	10.7	63	17.4	QP	L1	GND
0.451500	44.40	10.3	57	12.4	QP	L1	GND
0.901500	37.30	10.2	56	18.7	QP	L1	GND
1.131000	39.00	10.3	56	17.0	QP	L1	GND
2.481000	36.10	10.2	56	19.9	QP	L1	GND
23.419500	31.60	10.8	60	28.4	QP	L1	GND

MEASUREMENT RESULT: "AR-0085E L_fin2"

4/18/2013 2:13PM


Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.226500	44.20	10.7	53	8.4	AV	L1	GND
0.451500	43.10	10.3	47	3.7	AV	L1	GND
0.906000	34.80	10.2	46	11.2	AV	L1	GND
1.131000	37.40	10.3	46	8.6	AV	L1	GND
1.356000	30.70	10.2	46	15.3	AV	L1	GND
2.265000	26.00	10.2	46	20.0	AV	L1	GND



Conducted Emission:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: PC & Download
Test Site: Shielded Room
Operator: Yang
Test Specification: AC 120V/60Hz for PC
Comment: L Line

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "AR-0085E L1_fin"

2/18/2013 2:41PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.694500	37.70	10.2	56	18.3	QP	L1	GND
1.149000	38.90	10.3	56	17.1	QP	L1	GND
1.243500	39.10	10.3	56	16.9	QP	L1	GND
1.666500	37.70	10.2	56	18.3	QP	L1	GND
17.781000	49.80	10.6	60	10.2	QP	L1	GND

MEASUREMENT RESULT: "AR-0085E L1_fin2"


2/18/2013 2:41PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.699000	37.80	10.2	46	8.2	AV	L1	GND
0.735000	37.90	10.2	46	8.1	AV	L1	GND
0.811500	37.60	10.2	46	8.4	AV	L1	GND
17.781000	47.40	10.6	50	2.6	AV	L1	GND

Conducted Emission:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: PC & Download
Test Site: Shielded Room
Operator: Yang
Test Specification: AC 120V/60Hz for PC
Comment: N Line

SCAN TABLE: "Voltage (9K-30M)FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "AR-0085E N1_fin"

4/18/2013 2:38PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.694500	38.20	10.2	56	17.8	QP	N	GND
0.807000	38.70	10.2	56	17.3	QP	N	GND
1.239000	38.90	10.3	56	17.1	QP	N	GND
1.266000	39.10	10.3	56	16.9	QP	N	GND
17.794500	50.80	10.6	60	9.2	QP	N	GND

MEASUREMENT RESULT: "AR-0085E N1_fin2"

4/18/2013 2:38PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.672000	36.50	10.2	46	9.5	AV	N	GND
0.699000	36.60	10.2	46	9.4	AV	N	GND
0.735000	37.80	10.2	46	8.2	AV	N	GND
0.807000	36.80	10.2	46	9.2	AV	N	GND
1.266000	36.00	10.3	46	10.0	AV	N	GND
17.803500	33.40	10.6	50	16.6	AV	N	GND

5 - RADIATED DISTURBANCES

5.1 Limit of Radiated Disturbances

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dB μ V/m)
30 ~ 88	3	40
88~216	3	43.5
216 ~ 960	3	46
960 ~ 1000	3	54

Note:

- (1) The tighter limit shall apply at the edge between two frequency bands.
- (2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.


5.2 EUT Setup

The radiated emission tests were performed in the in the 3-meter anechoic chamber, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC Part 15 Subpart B limits.

The EUT was placed on the center of the test table.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.

Below 1 GHz



5.3 Test Receiver Setup

According to FCC Part 15 rule, the frequency was investigated from 30 to 1000 MHz. During the radiated emission test, the test receiver was set with the following configurations:

Test Receiver Setting:

Detector.....Peak & Quasi-Peak
IF Band Width.....120KHz
Frequency Range.....30MHz to 1000MHz
Turntable Rotated.....0 to 360 degrees

Antenna Position:

Height.....1m to 4m
Polarity.....Horizontal and Vertical

5.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings performed only when an emission was found to be marginal (within -10 dB μ V of specification limits), and are distinguished with a "QP" in the data table.

5.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for Subpart B. The equation for margin calculation is as follows:

Margin = Limit – Corr. Ampl.

5.6 Radiated Emissions Test Result


Temperature (°C) : 22~23	EUT: PIR motion sensor with hidden camera, SD recorder
Humidity (%RH) : 50~54	M/N: PIR-SD
Barometric Pressure (mbar) : 950~1000	Operation Condition: Charging & Camera / PC & Download

Radiated Emission Test Data:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: Charging & Camera
Test Site: 3m CHAMBER
Operator: Chen
Test Specification: AC 120V/60Hz for adapter
Comment: Polarization: Horizontal

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency				
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	VULB9163 NEW



MEASUREMENT RESULT: "13AR-0085EH11_red"

4/21/2013


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
88.200000	36.70	15.5	43.5	6.8	QP	300.0	0.00	HORIZONTAL
148.340000	36.10	12.3	43.5	7.4	QP	300.0	0.00	HORIZONTAL
222.060000	38.50	15.5	46.0	7.5	QP	100.0	0.00	HORIZONTAL
429.640000	40.50	22.0	46.0	5.5	QP	100.0	0.00	HORIZONTAL
579.020000	38.20	25.5	46.0	7.8	QP	100.0	0.00	HORIZONTAL
743.920000	39.90	27.2	46.0	6.1	QP	100.0	0.00	HORIZONTAL

Radiated Emission Test Data:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: Charging & Camera
Test Site: 3m CHAMBER
Operator: Chen
Test Specification: AC 120V/60Hz for adapter
Comment: Polarization: Vertical

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency				
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	VULB9163 NEW



MEASUREMENT RESULT: "13AR-0085EH11_red "

4/21/2013


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	35.80	14.3	40.0	4.2	QP	100.0	0.00	VERTICAL
82.380000	34.50	13.4	40.0	5.5	QP	100.0	0.00	VERTICAL
117.300000	37.90	15.1	43.5	5.6	QP	100.0	0.00	VERTICAL
433.520000	38.90	22.0	46.0	7.1	QP	100.0	0.00	VERTICAL
536.340000	38.50	24.7	46.0	7.5	QP	100.0	0.00	VERTICAL
743.920000	37.30	27.2	46.0	8.7	QP	100.0	0.00	VERTICAL

Radiated Emission Test Data:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: PC & Download
Test Site: 3m CHAMBER
Operator: Chen
Test Specification: AC 120V/60Hz for PC
Comment: Polarization: Horizontal

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
Frequency	Frequency				
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	VULB9163 NEW



MEASUREMENT RESULT: "13AR-0085E_red "

4/21/2013


Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
31.940000	33.60	14.4	40.0	6.4	QP	300.0	0.00	HORIZONTAL
47.460000	32.40	15.8	40.0	7.6	QP	300.0	0.00	HORIZONTAL
142.520000	34.60	12.3	43.5	8.9	QP	300.0	0.00	HORIZONTAL
371.440000	36.70	20.8	46.0	9.3	QP	100.0	0.00	HORIZONTAL
429.640000	36.90	22.0	46.0	9.1	QP	100.0	0.00	HORIZONTAL
743.920000	39.70	27.2	46.0	6.3	QP	100.0	0.00	HORIZONTAL

Radiated Emission Test Data:

EUT: PIR motion sensor with hidden camera,SD recorder
M/N: PIR-SD
Operating Condition: PC & Download
Test Site: 3m CHAMBER
Operator: Chen
Test Specification: AC 120V/60Hz for PC
Comment: Polarization: Vertical

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start	Stop	Detector	Meas.	IF	Transducer
Frequency	Frequency		Time	Bandw.	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	VULB9163 NEW



MEASUREMENT RESULT: "13AR-0085E_red"

4/21/2013

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
31.940000	36.60	14.4	40.0	3.4	QP	100.0	0.00	VERTICAL
84.320000	36.30	14.1	40.0	3.7	QP	100.0	0.00	VERTICAL
128.940000	33.90	13.2	43.5	9.6	QP	100.0	0.00	VERTICAL
204.600000	31.80	15.0	43.5	11.7	QP	100.0	0.00	VERTICAL
515.000000	38.00	24.2	46.0	8.0	QP	100.0	0.00	VERTICAL
928.220000	36.40	29.4	46.0	9.6	QP	100.0	0.00	VERTICAL