PDI-CV2600 solution:

TV MSD119+XC5000 +LGDT1129

Panel 26' AUO T260XW04 V7 Inverter: build in with panel

Power supply: NA

## 1. Features

- $\ \, \bigcirc \ \,$  26' 16:10 panel ,1366 X 768
- © Y/Pb/Pr interface ,support 480P ,720P,1080I.
- © Support AV VGA S-Video HDMI, SPDIF out ,CCI&MTI ,PILLOW SPEAKER ,NTSC/ATSC TUNER,FM
- O V-chip and CCD

## 2. General Specifications

Voltage	100-240V
Temperature	-10~+40°C
Frequency Range	57~ 803MHz
Receive Sensitivity	0DB~80DB
Power Consumption	60W

3. The channel center frequency and CHNL\_ID numbers shall be shown in the following table.

Tuner Channel Center Frequency		
CHNL_ID	Frequency (MHz)	
2	57	
3	63	
4	69	
5	79	
6	85	
7	177	
8	183	
9	189	
10	195	
11	201	
12	207	
13	213	
14	473	
15	479	
16	485	
17	491	
18	497	
19	503	
20	509	
21	515	
22	521	

23 24	527
24	
	533
25	539
26	545
27	551
28	557
29	563
30	569
31	575
32	581
33	587
34	593
35	599
36	605
37	611
38	617
39	623
40	629
41	635
42	641
43	647
44	653
45	659
46	665
47	671
48	677
49	683
50	689
51	695
52	701
53	707
54	713
55	719
56	725
57	731
58	737
59	743
60	749
61	755
62	761
63	767
64	773
65	779

66	785
67	791
68	797
69	803