

## FCC PART 15.247

## TEST REPORT

For

**Autel Intelligent Tech. Co., Ltd**

6th--10th Floor,Building B1,Zhiyuan, Xueyuan Road,Xili,Nanshan, Shenzhen, 518055,China

**FCC ID: WQ8301AC58A1**

<b>Report Type:</b> Original Report	<b>Product Type:</b> X-Star 3
<b>Test Engineer:</b> David Lee <i>David Lee</i>	
<b>Report Number:</b> RSZ150104016-00B	
<b>Report Date:</b> 2015-03-04	
Jimmy Xiao <i>Jimmy Xiao</i>	
<b>Reviewed By:</b> RF Engineer	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EQUIPMENT MODIFICATIONS .....	6
EUT EXERCISE SOFTWARE .....	6
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>FCC §15.247 (i) &amp; §1.1307 (b) (1) &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
RESULT .....	9
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP .....	11
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	12
TEST PROCEDURE .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	13
TEST RESULTS SUMMARY .....	13
TEST DATA .....	13
<b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>	<b>22</b>
APPLICABLE STANDARD .....	22
TEST PROCEDURE .....	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA .....	22
<b>FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER .....</b>	<b>37</b>
APPLICABLE STANDARD .....	37
TEST PROCEDURE .....	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA .....	37
<b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b>	<b>39</b>
APPLICABLE STANDARD .....	39
TEST PROCEDURE .....	39
TEST EQUIPMENT LIST AND DETAILS.....	39
TEST DATA .....	39

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....49**  
    APPLICABLE STANDARD .....49  
    TEST PROCEDURE .....49  
    TEST EQUIPMENT LIST AND DETAILS.....49  
    TEST DATA .....49

---

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Autel Intelligent Tech. Co., Ltd's* product, model number: *XS3 (FCC ID: WQ8301AC58A1)* or the "EUT" in this report was a *X-Star 3*, which was measured approximately: 240 mm (L) × 170 mm (W) × 21 mm (H), rated voltage: DC 11.1V from battery.

*\*All measurement and test data in this report was gathered from production sample serial number: 1501027 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2015-01-04*

### Objective

This report is prepared on behalf of *Autel Intelligent Tech. Co., Ltd* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

No related submissions.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with RF radiated emission is 5.91 dB for 30MHz-1GHz. and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

## Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3<sup>rd</sup> Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g, and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	/	/
4	2437	/	/
5	2442	/	/

EUT was tested with Channel 1, 4 and 7.

### Equipment Modifications

No modification was made to the EUT tested.

### EUT Exercise Software

Atheros Radio Test 2.

The test was performed under:


802.11b: Data rate: 1 Mbps, Power level: 08

802.11g: Data rate: 6 Mbps, Power level: 14

802.11n-HT20: Data rate: MCS0, Power level: 14

802.11n-HT40: Data rate: MCS0, Power level: 14

Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1307 (b) (1) & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Not Applicable: The EUT powered by battery in normal operation mode.



## FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### Result

#### Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2422	2	1.58	22.37	172.58	20	0.0543	1

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has two internal antennas arrangement, which was permanently attached and the peak gain is 2 dBi, fulfill the requirement of this section. Please refer to the internal photos.

**Result:** Compliance.

## **FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**

### **Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

### **Measurement Uncertainty**

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expanded combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement at antenna port. And the uncertainty will not be taken into consideration for the test data recorded in the report

### **EUT Setup**



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2014-05-06	2015-05-06
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2014-11-03	2015-11-03
Sunol Sciences	Broadband Antenna	JB3	A111513	2014-06-18	2017-06-17
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2015-02-10
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2014-08-22	2015-08-22
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2014-04-03	2015-04-03
TDK	Chamber	Chamber A	2#	2012-10-15	2015-10-15
TDK	Chamber	Chamber B	1#	2012-07-23	2015-07-22
R&S	Auto test Software	EMC32	V9.10	-	-

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

### 5.39 at 7236.00 MHz in the Vertical polarization for 802.11g mode Low channel

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL,  $U_{(Lm)}$  is less than  $U_{cispr}$ , if  $L_m$  is less than  $L_{lim}$ , it implies that the EUT complies with the limit.

## Test Data

### Environmental Conditions

<b>Temperature:</b>	23 °C
<b>Relative Humidity:</b>	50 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by David Lee on 2014-12-16*

*EUT operation mode: Transmitting*

**30 MHz-25 GHz:****802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
159.1	35.95	QP	205	2.3	V	-15.30	20.65	43.50	22.85
2412.00	89.04	PK	17	1.2	H	4.27	93.31	/	/
2412.00	85.55	Ave.	17	1.2	H	4.27	89.82	/	/
2412.00	88.68	PK	231	2.1	V	4.17	92.85	/	/
2412.00	84.60	Ave.	231	2.1	V	4.17	88.77	/	/
2380.21	38.52	PK	98	2.2	H	4.27	42.79	74	31.21
2380.21	23.67	Ave.	98	2.2	H	4.27	27.94	54	26.06
2492.46	42.53	PK	338	2.5	H	7.99	50.52	74	23.48
2492.46	20.52	Ave.	338	2.5	H	7.99	28.51	54	25.49
2852.19	36.96	PK	87	2.4	V	8.56	45.52	74	28.48
2852.19	21.30	Ave.	87	2.4	V	8.56	29.86	54	24.14
4824.00	35.12	PK	156	2.4	H	18.31	53.43	74	20.57
4824.00	22.50	Ave.	156	2.4	H	18.31	40.81	54	13.19
7236.00	35.78	PK	133	1.4	H	22.28	58.06	74	15.94
7236.00	21.98	Ave.	133	1.4	H	22.28	44.26	54	9.74
9648.00	34.11	PK	138	2.3	H	25.02	59.13	74	14.87
9648.00	20.37	Ave.	138	2.3	H	25.02	45.39	54	8.61

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (2437 MHz)									
159.1	35.74	QP	339	1.1	V	-15.30	20.44	43.50	23.06
2437.00	90.78	PK	93	1.7	H	4.27	95.05	/	/
2437.00	85.31	Ave.	93	1.7	H	4.27	89.58	/	/
2437.00	89.96	PK	151	1.1	V	4.17	94.13	/	/
2437.00	83.41	Ave.	151	1.1	V	4.17	87.58	/	/
2385.32	38.91	PK	128	2.5	H	4.27	43.18	74	30.82
2385.32	24.85	Ave.	128	2.5	H	4.27	29.12	54	24.88
2484.99	42.89	PK	268	2.1	H	7.99	50.88	74	23.12
2484.99	20.52	Ave.	268	2.1	H	7.99	28.51	54	25.49
2827.84	36.76	PK	30	1.7	H	8.41	45.17	74	28.83
2827.84	22.22	Ave.	30	1.7	H	8.41	30.63	54	23.37
4874.00	36.67	PK	317	1.4	H	19.21	55.88	74	18.12
4874.00	22.05	Ave.	317	1.4	H	19.21	41.26	54	12.74
7311.00	35.52	PK	90	2.5	V	22.60	58.12	74	15.88
7311.00	21.15	Ave.	90	2.5	V	22.60	43.75	54	10.25
9748.00	34.07	PK	287	1.4	H	25.02	59.09	74	14.91
9748.00	19.60	Ave.	287	1.4	H	25.02	44.62	54	9.38
High Channel (2462 MHz)									
159.1	35.94	QP	110	2.4	V	-15.30	20.64	43.50	22.86
2462.00	89.32	PK	6	2.1	H	7.99	97.31	/	/
2462.00	84.12	Ave.	6	2.1	H	7.99	92.11	/	/
2462.00	89.42	PK	238	1.7	V	7.59	97.01	/	/
2462.00	83.82	Ave.	238	1.7	V	7.59	91.41	/	/
2326.44	38.15	PK	118	2.2	H	3.93	42.08	74	31.92
2326.44	24.42	Ave.	118	2.2	H	3.93	28.35	54	25.65
2484.79	41.73	PK	99	1.6	H	7.99	49.72	74	24.28
2484.79	20.52	Ave.	99	1.6	H	7.99	28.51	54	25.49
2777.28	37.16	PK	293	1.7	H	8.41	45.57	74	28.43
2777.28	21.03	Ave.	293	1.7	H	8.41	29.44	54	24.56
4924.00	35.47	PK	239	1.7	V	19.41	54.88	74	19.12
4924.00	22.92	Ave.	239	1.7	V	19.41	42.33	54	11.67
7386.00	35.39	PK	312	1.3	H	21.54	56.93	74	17.07
7386.00	20.24	Ave.	312	1.3	H	21.54	41.78	54	12.22
9848.00	34.01	PK	217	1.3	V	26.29	60.30	74	13.70
9848.00	20.88	Ave.	217	1.3	V	26.29	47.17	54	6.83

**802.11g Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
159.1	36.52	QP	297	1.7	V	-15.30	21.22	43.50	22.28
2412.00	92.21	PK	67	2.0	H	4.27	96.48	/	/
2412.00	87.82	Ave.	67	2.0	H	4.27	92.09	/	/
2412.00	90.35	PK	76	1.8	V	4.17	94.52	/	/
2412.00	86.33	Ave.	76	1.8	V	4.17	90.50	/	/
2389.03	44.22	PK	133	1.5	H	4.27	48.49	74	25.51
2389.03	31.34	Ave.	133	1.5	H	4.27	35.61	54	18.39
2495.27	41.07	PK	267	2.5	H	7.99	49.06	74	24.94
2495.27	20.52	Ave.	267	2.5	H	7.99	28.51	54	25.49
2779.26	38.36	PK	50	1.1	H	8.41	46.77	74	27.23
2779.26	22.76	Ave.	50	1.1	H	8.41	31.17	54	22.83
4824.00	41.06	PK	348	1.0	V	18.51	59.57	74	14.43
4824.00	26.21	Ave.	348	1.0	V	18.51	44.72	54	9.28
7236.00	39.24	PK	64	2.5	H	22.28	61.52	74	12.48
7236.00	26.33	Ave.	64	2.5	H	22.28	48.61	54	5.39
9648.00	34.45	PK	10	1.8	V	25.22	59.67	74	14.33
9648.00	22.69	Ave.	10	1.8	V	25.22	47.91	54	6.09
Middle Channel (2437 MHz)									
159.1	36.69	QP	99	1.9	V	-15.30	21.39	43.50	22.11
2437.00	89.66	PK	130	1.7	H	4.27	93.93	/	/
2437.00	85.98	Ave.	130	1.7	H	4.27	90.25	/	/
2437.00	88.90	PK	55	1.7	V	4.17	93.07	/	/
2437.00	83.85	Ave.	55	1.7	V	4.17	88.02	/	/
2384.08	38.62	PK	352	2.0	H	4.27	42.89	74	31.11
2384.08	23.66	Ave.	352	2.0	H	4.27	27.93	54	26.07
2489.57	42.01	PK	225	2.1	H	7.99	50.00	74	24.00
2489.57	20.52	Ave.	225	2.1	H	7.99	28.51	54	25.49
2922.45	36.23	PK	118	1.6	H	8.96	45.19	74	28.81
2922.45	21.29	Ave.	118	1.6	H	8.96	30.25	54	23.75
4874.00	36.18	PK	22	1.2	H	19.21	55.39	74	18.61
4874.00	21.95	Ave.	22	1.2	H	19.21	41.16	54	12.84
7311.00	35.21	PK	94	1.4	V	22.60	57.81	74	16.19
7311.00	21.23	Ave.	94	1.4	V	22.60	43.83	54	10.17
9748.00	34.52	PK	102	2.2	H	25.02	59.54	74	14.46
9748.00	19.24	Ave.	102	2.2	H	25.02	44.26	54	9.74



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
159.1	36.63	QP	102	1.1	V	-15.30	21.33	43.50	22.17
2462.00	90.99	PK	336	1.6	H	7.99	98.98	/	/
2462.00	84.10	Ave.	336	1.6	H	7.99	92.09	/	/
2462.00	89.91	PK	277	2.3	V	7.59	97.50	/	/
2462.00	83.80	Ave.	277	2.3	V	7.59	91.39	/	/
2340.59	37.19	PK	143	2.5	H	3.93	41.12	74	32.88
2340.59	23.06	Ave.	143	2.5	H	3.93	26.99	54	27.01
2483.62	41.83	PK	48	1.3	H	7.99	49.82	74	24.18
2483.62	20.52	Ave.	48	1.3	H	7.99	28.51	54	25.49
2890.65	36.83	PK	228	1.4	H	8.96	45.79	74	28.21
2890.65	21.43	Ave.	228	1.4	H	8.96	30.39	54	23.61
4924.00	36.26	PK	230	2.3	H	19.21	55.47	74	18.53
4924.00	21.83	Ave.	230	2.3	H	19.21	41.04	54	12.96
7386.00	34.90	PK	269	1.9	H	21.54	56.44	74	17.56
7386.00	21.46	Ave.	269	1.9	H	21.54	43.00	54	11.00
9848.00	34.10	PK	55	2.3	V	26.29	60.39	74	13.61
9848.00	19.33	Ave.	55	2.3	V	26.29	45.62	54	8.38

**802.11n-HT20 Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2412 MHz)									
159.1	36.03	QP	297	1.8	V	-15.30	20.73	43.50	22.77
2412.00	93.36	PK	307	2.5	H	4.27	97.63	/	/
2412.00	88.52	Ave.	307	2.5	H	4.27	92.79	/	/
2412.00	92.17	PK	331	1.9	V	4.17	96.34	/	/
2412.00	86.78	Ave.	331	1.9	V	4.17	90.95	/	/
2389.22	54.21	PK	342	1.1	H	4.27	58.48	74	15.52
2389.22	40.16	Ave.	342	1.1	H	4.27	44.43	54	9.57
2485.83	51.13	PK	126	1.1	H	7.99	59.12	74	14.88
2485.83	39.72	Ave.	126	1.1	H	7.99	47.71	54	6.29
2832.16	36.52	PK	179	1.4	V	8.01	44.53	74	29.47
2832.16	28.77	Ave.	179	1.4	V	8.01	36.78	54	17.22
4824.00	39.62	PK	182	2.2	H	18.31	57.93	74	16.07
4824.00	24.22	Ave.	182	2.2	H	18.31	42.53	54	11.47
7236.00	37.56	PK	315	1.2	H	22.28	59.84	74	14.16
7236.00	23.19	Ave.	315	1.2	H	22.28	45.47	54	8.53
9648.00	34.71	PK	128	1.3	H	25.02	59.73	74	14.27
9648.00	21.01	Ave.	128	1.3	H	25.02	46.03	54	7.97
Middle Channel (2437 MHz)									
159.1	36.34	QP	25	1.1	V	-15.30	21.04	43.50	22.46
2437.00	90.21	PK	352	1.8	H	4.27	94.48	/	/
2437.00	84.72	Ave.	352	1.8	H	4.27	88.99	/	/
2437.00	89.85	PK	92	1.0	V	4.17	94.02	/	/
2437.00	84.94	Ave.	92	1.0	V	4.17	89.11	/	/
2383.45	37.66	PK	248	2.5	H	4.27	41.93	74	32.07
2383.45	23.17	Ave.	248	2.5	H	4.27	27.44	54	26.56
2489.20	42.16	PK	238	2.2	H	7.99	50.15	74	23.85
2489.20	20.52	Ave.	238	2.2	H	7.99	28.51	54	25.49
2724.72	36.46	PK	191	2.0	V	7.91	44.37	74	29.63
2724.72	22.73	Ave.	191	2.0	V	7.91	30.64	54	23.36
4874.00	35.56	PK	190	1.2	H	19.21	54.77	74	19.23
4874.00	22.20	Ave.	190	1.2	H	19.21	41.41	54	12.59
7311.00	35.46	PK	333	1.0	V	22.60	58.06	74	15.94
7311.00	20.58	Ave.	333	1.0	V	22.60	43.18	54	10.82
9748.00	35.59	PK	200	1.2	H	25.02	60.61	74	13.39
9748.00	19.45	Ave.	200	1.2	H	25.02	44.47	54	9.53

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2462 MHz)									
159.1	36.12	QP	247	2.2	V	-15.30	20.82	43.50	22.68
2462.00	89.83	PK	53	2.1	H	7.99	97.82	/	/
2462.00	85.16	Ave.	53	2.1	H	7.99	93.15	/	/
2462.00	89.31	PK	248	2.2	V	7.59	96.90	/	/
2462.00	83.29	Ave.	248	2.2	V	7.59	90.88	/	/
2338.99	37.30	PK	267	1.1	H	3.93	41.23	74	32.77
2338.99	23.97	Ave.	267	1.1	H	3.93	27.90	54	26.10
2484.25	42.50	PK	199	1.1	H	7.99	50.49	74	23.51
2484.25	20.52	Ave.	199	1.1	H	7.99	28.51	54	25.49
2993.94	37.04	PK	128	1.8	H	11.28	48.32	74	25.68
2993.94	22.06	Ave.	128	1.8	H	11.28	33.34	54	20.66
4924.00	36.26	PK	286	2.1	V	19.41	55.67	74	18.33
4924.00	21.63	Ave.	286	2.1	V	19.41	41.04	54	12.96
7386.00	36.07	PK	352	2.3	V	21.54	57.61	74	16.39
7386.00	21.75	Ave.	352	2.3	V	21.54	43.29	54	10.71
9848.00	34.81	PK	164	1.1	H	26.09	60.90	74	13.10
9848.00	20.88	Ave.	164	1.1	H	26.09	46.97	54	7.03

**802.11n-HT40 Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2422 MHz)									
159.1	35.08	QP	193	2.0	V	-15.30	19.78	43.50	23.72
2422.00	89.20	PK	247	1.1	H	4.27	93.47	/	/
2422.00	84.64	Ave.	247	1.1	H	4.27	88.91	/	/
2422.00	88.08	PK	106	1.1	V	4.17	92.25	/	/
2422.00	83.22	Ave.	106	1.1	V	4.17	87.39	/	/
2382.07	38.22	PK	148	1.0	H	4.27	42.49	74	31.51
2382.07	24.34	Ave.	148	1.0	H	4.27	28.61	54	25.39
2488.27	41.08	PK	360	1.1	H	7.99	49.07	74	24.93
2488.27	20.52	Ave.	360	1.1	H	7.99	28.51	54	25.49
2782.59	37.23	PK	256	1.7	H	8.41	45.64	74	28.36
2782.59	21.54	Ave.	256	1.7	H	8.41	29.95	54	24.05
4844.00	35.06	PK	44	1.7	H	18.31	53.37	74	20.63
4844.00	21.54	Ave.	44	1.7	H	18.31	39.85	54	14.15
7266.00	35.54	PK	151	2.1	V	22.60	58.14	74	15.86
7266.00	21.30	Ave.	151	2.1	V	22.60	43.90	54	10.10
9688.00	35.19	PK	279	2.1	H	25.02	60.21	74	13.79
9688.00	20.67	Ave.	279	2.1	H	25.02	45.69	54	8.31
Middle Channel (2437 MHz)									
159.1	36.22	QP	319	1.8	V	-15.30	20.92	43.50	22.58
2437.00	89.78	PK	289	2.1	H	4.27	94.05	/	/
2437.00	85.58	Ave.	289	2.1	H	4.27	89.85	/	/
2437.00	89.49	PK	120	1.1	V	4.17	93.66	/	/
2437.00	84.29	Ave.	120	1.1	V	4.17	88.46	/	/
2389.66	37.26	PK	86	1.4	H	4.27	41.53	74	32.47
2389.66	23.48	Ave.	86	1.4	H	4.27	27.75	54	26.25
2498.60	42.67	PK	17	2.1	H	7.99	50.66	74	23.34
2498.60	20.52	Ave.	17	2.1	H	7.99	28.51	54	25.49
2825.98	36.90	PK	104	1.2	H	8.41	45.31	74	28.69
2825.98	21.57	Ave.	104	1.2	H	8.41	29.98	54	24.02
4874.00	35.46	PK	186	2.0	H	19.21	54.67	74	19.33
4874.00	21.59	Ave.	186	2.0	H	19.21	40.80	54	13.20
7311.00	35.62	PK	80	2.3	H	22.60	58.22	74	15.78
7311.00	21.61	Ave.	80	2.3	H	22.60	44.21	54	9.79
9748.00	35.31	PK	191	1.2	H	25.02	60.33	74	13.67
9748.00	19.82	Ave.	191	1.2	H	25.02	44.84	54	9.16

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2452 MHz)									
159.1	36.38	QP	192	1.6	V	-15.30	21.08	43.50	22.42
2452.00	89.48	PK	335	1.8	H	7.99	97.47	/	/
2452.00	85.05	Ave.	335	1.8	H	7.99	93.04	/	/
2452.00	89.16	PK	269	2.3	V	7.59	96.75	/	/
2452.00	84.46	Ave.	269	2.3	V	7.59	92.05	/	/
2313.61	37.69	PK	54	1.4	H	3.93	41.62	74	32.38
2313.61	23.97	Ave.	54	1.4	H	3.93	27.90	54	26.10
2483.86	42.01	PK	267	2.4	H	7.99	50.00	74	24.00
2483.86	20.52	Ave.	267	2.4	H	7.99	28.51	54	25.49
2874.76	36.13	PK	54	1.6	V	8.56	44.69	74	29.31
2874.76	21.18	Ave.	54	1.6	V	8.56	29.74	54	24.26
4904.00	35.95	PK	161	1.3	V	19.41	55.36	74	18.64
4904.00	21.88	Ave.	161	1.3	V	19.41	41.29	54	12.71
7356.00	34.55	PK	299	1.9	V	21.54	56.09	74	17.91
7356.00	21.63	Ave.	299	1.9	V	21.54	43.17	54	10.83
9808.00	34.28	PK	275	1.4	V	26.29	60.57	74	13.43
9808.00	20.99	Ave.	275	1.4	V	26.29	47.28	54	6.72

**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

**FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH****Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2014-06-13	2015-06-13

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

Temperature:	21 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

*The testing was performed by David Lee from 2015-02-11*

**Test Result:** Pass.

Please refer to the following tables and plots.


*EUT operation mode: Transmitting*

Antenna 0


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	10.08	$\geq 500$
Middle	2437	10.08	$\geq 500$
High	2462	10.08	$\geq 500$
802.11g mode			
Low	2412	16.41	$\geq 500$
Middle	2437	16.41	$\geq 500$
High	2462	16.41	$\geq 500$
802.11n-HT20 mode			
Low	2412	17.61	$\geq 500$
Middle	2437	17.61	$\geq 500$
High	2462	17.61	$\geq 500$
802.11n-HT40 mode			
Low	2422	36.36	$\geq 500$
Middle	2437	36.36	$\geq 500$
High	2452	36.36	$\geq 500$

## Antenna 0

## 6 dB Emission Bandwidth, 802.11b Low Channel




## 6 dB Emission Bandwidth, 802.11b Middle Channel







### 6 dB Emission Bandwidth, 802.11b High Channel




### 6 dB Emission Bandwidth, 802.11g Low Channel




### 6 dB Emission Bandwidth, 802.11g Middle Channel




### 6 dB Emission Bandwidth, 802.11g High Channel




### 6 dB Emission Bandwidth, 802.11n-HT20 Low Channel




### 6 dB Emission Bandwidth, 802.11n-HT20 Middle Channel




### 6 dB Emission Bandwidth, 802.11n-HT20 High Channel




### 6 dB Emission Bandwidth, 802.11n-HT40 Low Channel



### 6 dB Emission Bandwidth, 802.11n-HT40 Middle Channel



### 6 dB Emission Bandwidth, 802.11n-HT40 High Channel




## Antenna 1


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	10.08	$\geq 500$
Middle	2437	10.08	$\geq 500$
High	2462	10.08	$\geq 500$
802.11g mode			
Low	2412	16.35	$\geq 500$
Middle	2437	16.35	$\geq 500$
High	2462	16.35	$\geq 500$
802.11n-HT20 mode			
Low	2412	17.58	$\geq 500$
Middle	2437	17.58	$\geq 500$
High	2462	17.58	$\geq 500$
802.11n-HT40 mode			
Low	2422	36.36	$\geq 500$
Middle	2437	36.36	$\geq 500$
High	2452	36.36	$\geq 500$

Antenna 1


6 dB Emission Bandwidth, 802.11b Low Channel



6 dB Emission Bandwidth, 802.11b Middle Channel




## 6 dB Emission Bandwidth, 802.11b High Channel



Date: 11.FEB.2015 20:49:48


## 6 dB Emission Bandwidth, 802.11g Low Channel



Date: 11.FEB.2015 20:42:53




### 6 dB Emission Bandwidth, 802.11g Middle Channel




Date: 11.FEB.2015 20:44:42

### 6 dB Emission Bandwidth, 802.11g High Channel




Date: 11.FEB.2015 20:45:56

### 6 dB Emission Bandwidth, 802.11n-HT20 Low Channel



Date: 11.FEB.2015 20:36:22

### 6 dB Emission Bandwidth, 802.11n-HT20 Middle Channel



Date: 11.FEB.2015 20:38:23

**Spectrum**

Ref Level 20.00 dBm Offset 3.50 dB RBW 100 kHz

Att 30 dB SWT 95  $\mu$ s VBW 300 kHz Mode Auto FFT Input 1 AC

1Pk Max

D2[1] 1.53 dBm  
17.5800 MHz  
-8.00 dBm  
2.4532250 GHz

M1[1]

D1 -1.050 dBm  
D2 -7.000 dBm

CF 2.462 GHz 1000 pts Span 30.0 MHz

Date: 11.FEB.2015 20:40:49

**Spectrum**

Ref Level 20.00 dBm Offset 3.50 dB RBW 100 kHz  
 Att 30 dB SWT 95  $\mu$ s VBW 300 kHz Mode Auto FFT Input 1 AC

1Ppk Max

0.81 dB  
 36.3600 MHz  
 -8.31 dBm  
 2.4038500 GHz


D2[1]  
 M1[1]

D1 -3.400 dBm  
 D2 -9.400 dBm


CF 2.422 GHz 1000 pts Span 60.0 GHz

Date: 11.FEB.2015 20:34:58

### 6 dB Emission Bandwidth, 802.11n-HT40 Middle Channel



### 6 dB Emission Bandwidth, 802.11n-HT40 High Channel




## FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Power Meter	EPM-441A	GB37481494	2014-11-03	2015-11-03
HP	Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	21 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

*The testing was performed by David Lee on 2015-02-11*

*EUT operation mode: Transmitting*

Channel	Frequency (MHz)	Antenna Port	Peak Output Power (dBm)	Limit (dBm)	
802.11b mode					
Low	2412	0	7.56	30	
		1	6.72		
Middle	2437	0	7.62	30	
		1	6.62		
High	2462	0	7.24	30	
		1	6.70		
802.11g mode					
Low	2412	0	17.82	30	
		1	17.39		
Middle	2437	0	18.17	30	
		1	17.00		
High	2462	0	17.36	30	
		1	16.92		
802.11n-HT20 mode					
Low	2412	0	17.61	21.08	30
		1	18.48		
Middle	2437	0	17.72	20.44	30
		1	17.11		
High	2462	0	17.40	20.12	30
		1	16.79		
802.11n-HT40 mode					
Low	2422	0	19.07	22.37	30
		1	19.63		
Middle	2437	0	19.06	21.79	30
		1	18.48		
High	2452	0	18.80	21.75	30
		1	18.68		


## FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2014-06-13	2015-06-13

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	20~21 °C
Relative Humidity:	50~51 %
ATM Pressure:	101.0 kPa

*The testing was performed by David Lee from 2015-02-10 to 2015-02-11*

**Test Result:** *Compliance, please refer to the following plots.*


**For Antenna 0**

**802.11b: Band Edge, Left Side**







### 802.11b: Band Edge, Right Side




### 802.11g: Band Edge, Left Side







### 802.11g: Band Edge, Right Side




### 802.11n-HT20: Band Edge, Left Side




**802.11n-HT20: Band Edge, Right Side****802.11n-HT40: Band Edge, Left Side**

**802.11n-HT40: Band Edge, Right Side****For Antenna 1****802.11b: Band Edge, Left Side**


### 802.11b: Band Edge, Right Side




### 802.11g: Band Edge, Left Side




### 802.11g: Band Edge, Right Side




### 802.11n-HT20: Band Edge, Left Side




### 802.11n-HT20: Band Edge, Right Side



### 802.11n-HT40: Band Edge, Left Side



# 802.11n-HT40: Band Edge, Right Side



Date: 11.FEB.2015 21:05:08



## FCC §15.247(e) - POWER SPECTRAL DENSITY


### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

According to KDB558074 D01 DTS Meas Guidance v03r02

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2014-06-13	2015-06-13

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

Temperature:	21 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa


*The testing was performed by David Lee on 2015-02-11*

*EUT operation mode: Transmitting***Test Result: Pass**


Channel	Frequency (MHz)	Antenna Port	Data Rate (Mbps)	Correct Power spectral density (dBm/3kHz)		Limit (dBm/3kHz)	Result
802.11b mode							
Low	2412	0	1	-20.01		8	Pass
		1		-20.67		8	Pass
Middle	2437	0	1	-20.04		8	Pass
		1		-20.83		8	Pass
High	2462	0	1	-20.36		8	Pass
		1		-20.98		8	Pass
802.11g mode							
Low	2412	0	6	-13.76		8	Pass
		1		-14.69		8	Pass
Middle	2437	0	6	-13.78		8	Pass
		1		-14.31		8	Pass
High	2462	0	6	-13.79		8	Pass
		1		-15.28		8	Pass
802.11n-HT20 mode							
Low	2412	0	MCS0	-15.10	-11.74	8	Pass
		1		-14.42		8	Pass
Middle	2437	0	MCS0	-14.33	-11.56	8	Pass
		1		-14.83		8	Pass
High	2462	0	MCS0	-14.90	-12.22	8	Pass
		1		-15.58		8	Pass
802.11n-HT40 mode							
Low	2422	0	MCS0	-15.42	-12.39	8	Pass
		1		-15.39		8	Pass
Middle	2437	0	MCS0	-16.29	-13.84	8	Pass
		1		-17.49		8	Pass
High	2452	0	MCS0	-16.24	-13.40	8	Pass
		1		-16.58		8	Pass

**For Antenna 0**


**Power Spectral Density, 802.11b Low Channel**




**Power Spectral Density, 802.11b Middle Channel**




### Power Spectral Density, 802.11b High Channel



### Power Spectral Density, 802.11g Low Channel




### Power Spectral Density, 802.11g Middle Channel




Date: 11.FEB.2015 19:31:52

### Power Spectral Density, 802.11g High Channel




Date: 11.FEB.2015 19:33:10


## Power Spectral Density, 802.11n-HT20 Low Channel




## Power Spectral Density, 802.11n-HT20 Middle Channel




### Power Spectral Density, 802.11n-HT20 High Channel




### Power Spectral Density, 802.11n-HT40 Low Channel



**Power Spectral Density, 802.11n-HT40 Middle Channel**

Date: 11.FEB.2015 19:24:45


**Power Spectral Density, 802.11n-HT40 High Channel**

Date: 11.FEB.2015 19:22:53




**For Antenna 1**


**Power Spectral Density, 802.11b Low Channel**




**Power Spectral Density, 802.11b Middle Channel**




## Power Spectral Density, 802.11b High Channel



## Power Spectral Density, 802.11g Low Channel




### Power Spectral Density, 802.11g Middle Channel




Date: 11.FEB.2015 21:12:28

### Power Spectral Density, 802.11g High Channel




Date: 11.FEB.2015 21:11:52

### Power Spectral Density, 802.11n-HT20 Low Channel




Date: 11.FEB.2015 21:09:43

### Power Spectral Density, 802.11n-HT20 Middle Channel




Date: 11.FEB.2015 21:10:24


## Power Spectral Density, 802.11n-HT20 High Channel



## Power Spectral Density, 802.11n-HT40 Low Channel




### Power Spectral Density, 802.11n-HT40 Middle Channel



Date: 11.FEB.2015 21:07:52

### Power Spectral Density, 802.11n-HT40 High Channel



Date: 11.FEB.2015 21:08:31

\*\*\*\*\* END OF REPORT \*\*\*\*\*