DUT: MaxiSys MS906BT; Type: MS906BT;

Communication System: Wi-Fi band; Frequency: 2472 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2472 MHz; σ = 2 mho/m; εr = 51.57; ρ = 1000 kg/m^3
Phantom section: Flat Section

DASY4 Configuration:
- Probe: EX3DV4 – SN7382; ConvF(7.88, 7.88, 7.88); Calibrated: 26/10/2016
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

Body Back/WLAN-802.11b-2472MHz/Area Scan (91x101x1): Measurement grid:
dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 0.307 mW/g

Body Back/WLAN-802.11b-2472MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=5mm
Reference Value = 7.13 V/m; Power Drift = 0.171 dB
Peak SAR (extrapolated) = 0.538 W/kg
SAR(1 g) = 0.208 mW/g; SAR(10 g) = 0.125 mW/g
Maximum value of SAR (measured) = 0.275 mW/g

DUT: MaxiSys MS906BT; Type: MS906BT;

Communication System: Wi-Fi band; Frequency: 2472 MHz;Duty Cycle: 1:1
Medium parameters used: f = 2472 MHz; σ = 2 mho/m; εr = 51.57; ρ = 1000 kg/m^3
Phantom section: Flat Section

DASY4 Configuration:
- Probe: EX3DV4 – SN7382; ConvF(7.88, 7.88, 7.88); Calibrated: 26/10/2016
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

Body Right/WLAN-802.11b-2472MHz/Area Scan (91x101x1): Measurement grid:
dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 0.489 mW/g

Body Right/WLAN-802.11b-2472MHz/Zoom Scan (7x7x7)/Cube 0: Measurement
grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 8.39 V/m; Power Drift = 0.081 dB
Peak SAR (extrapolated) = 0.873 W/kg
SAR(1 g) = 0.392 mW/g; SAR(10 g) = 0.188 mW/g
Maximum value of SAR (measured) = 0.466 mW/g

DUT: MaxiSys MS906BT; Type: MS906BT;

Communication System: Bluetooth; Frequency: 2480 MHz;Duty Cycle: 1:3
Medium parameters used: f = 2480 MHz; σ = 2.01 mho/m; εr = 51.66; ρ = 1000 kg/m^3
Phantom section: Flat Section

DASY4 Configuration:
- Probe: EX3DV4 – SN7382; ConvF(7.88, 7.88, 7.88); Calibrated: 26/10/2016
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE – SN772; Calibrated: 25/10/2016
- Phantom: TWIN SAM; Type: Twin SAM V5.0; Serial: 1909
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

Body Back/Bluetooth BDR-2480MHz/Area Scan (81x141x1): Measurement grid:
dx=10mm, dy=10mm
Maximum value of SAR (interpolated) = 0.127 mW/g

Body Back/Bluetooth BDR-2480MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid:
dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.73 V/m; Power Drift = 0.116 dB
Peak SAR (extrapolated) = 0.203 W/kg
SAR(1 g) = 0.081 mW/g; SAR(10 g) = 0.037 mW/g
Maximum value of SAR (measured) = 0.115 mW/g