



AUDIX Technology Corp.
No. 53-11, Dingfu, Linkou, Dist.,
New Taipei City 244, Taiwan

APPENDIX A-Page 1 of 13

Tel: +886 2 26099301

Fax: +886 2 26099303

APPDNDIX A

TEST PLOTS

(Model: SUG-100-04)

File Number: C1S1510156

Report Number: EM-F150710

This test report may be reproduced in full only. The document may only be updated by AUDIX Technology Corp. personnel. Any changes will be noted in the Document History section of the report.

TABLE OF CONTENTS

A.1	20dB BANDWIDTH MEASUREMENT.....	2
A.1.1	20dB Bandwidth Result.....	2
A.1.2	Measurement Plots	3
A.2	CARRIER FREQUENCY SEPARATION MEASUREMENT.....	4
A.2.1	Measurement Plots	4
A.3	TIME OF OCCUPANCY MEASUREMENT	5
A.3.1	Time of Occupancy.....	5
A.3.2	Measurement Plots	5
A.4	NUMBER OF HOPPING CHANNELS MEASUREMENT	7
A.4.1	Measurement Plots	7
A.5	MAXIMUM PEAK OUTPUT POWER MEASUREMENT	8
A.5.1	Output Power.....	8
A.5.2	Measurement Plots	9
A.6	EMISSION LIMITATIONS MEASUREMENT	10
A.6.1	Band Edge	10
A.6.2	Spurious Emission	11

A.1 20dB BANDWIDTH MEASUREMENT


Test Date	2015/11/17	Temp./Hum.	22°C /45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz

A.1.1 20dB Bandwidth Result

Modulation	Centre Frequency (MHz)	20 dB Bandwidth (kHz)	2/3 (20dB Bandwidth)
FHSS	902.75	43.45	28.967
	914.75	43.49	28.993
	927.75	43.51	29.007

Remark: The maximum two-thirds of the 20dB bandwidth is the limit for carrier frequency separation presented.


A.1.2 Measurement Plots



A.2 CARRIER FREQUENCY SEPARATION MEASUREMENT

Test Date	2015/11/17	Temp./Hum.	22°C/45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz

A.2.1 Measurement Plots



A.3 TIME OF OCCUPANCY MEASUREMENT

Test Date	2015/11/17	Temp./Hum.	22°C/45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz

A.3.1 Time of Occupancy

Modulation	Centre Frequency (MHz)	Time of Occupancy (ms)	Maximum accumulated Time of Occupancy (ms)	Limit (ms)
FHSS	902.75	98.8	395.2	<400
	914.75	98.8	395.2	<400
	927.75	98.8	395.2	<400

Observation Period: 50 channels*0.4 seconds = 20 seconds

Centre Frequency: 902.75MHz

For each second of 2 channel appearance, the longest time of occupancy for each of 20 seconds is:

$$2\text{channels} \times 20\text{ seconds} \times 98.8\text{ms} = 395.2\text{ms}$$

Centre Frequency: 914.75MHz

For each second of 2 channel appearance, the longest time of occupancy for each of 20 seconds is:


$$2\text{channels} \times 20\text{ seconds} \times 98.8\text{ms} = 395.2\text{ms}$$

Centre Frequency: 927.75MHz

For each second of 2 channel appearance, the longest time of occupancy for each of 20 seconds is:

$$2\text{channels} \times 20\text{ seconds} \times 98.8\text{ms} = 395.2\text{ms}$$


A.3.2 Measurement Plots



A.4 NUMBER OF HOPPING CHANNELS MEASUREMENT

Test Date	2015/11/23	Temp./Hum.	23°C/51%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz

A.4.1 Measurement Plots




A.5 MAXIMUM PEAK OUTPUT POWER MEASUREMENT

Test Date	2015/11/17	Temp./Hum.	22°C/45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz

A.5.1 Output Power

Modulation	Centre Frequency (MHz)	Peak Output Power		Limit
		dBm	W	
FHSS	902.75	28.001	0.631103	30dBm (1W)
	914.75	27.944	0.622874	
	927.75	27.967	0.626181	


A.5.2 Measurement Plots



A.6 EMISSION LIMITATIONS MEASUREMENT


A.6.1 Band Edge

Test Date	2015/11/23	Temp./Hum.	23°C/51%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz




A.6.2 Spurious Emission

Test Date	2015/11/17	Temp./Hum.	22°C/45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz
Modulation	FHSS	Frequency	902.75MHz




Note: All results have been included cable loss.

Test Date	2015/11/17	Temp./Hum.	22°C/45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz
Modulation	FHSS	Frequency	914.75MHz



Note: All results have been included cable loss.

Test Date	2015/11/17	Temp./Hum.	22°C/45%
Cable Loss	2dB	Test Voltage	AC 120V, 60Hz
Modulation	FHSS	Frequency	927.75MHz



Note: All results have been included cable loss.