

Report No.: FR972333A



FCC RADIO TEST REPORT

FCC ID : WR974100118120

Equipment : SmartCamera with voice control

Brand Name : ecobee **Model Name** : EBSCV01

Applicant : ecobee Incorporated

207 Queens Quay West, Suite 600, Toronto,

Ontario, M5J 1A7, Canada

Manufacturer : Wistron Corporation

21F, No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih Dist,

New Taipei City 221, Taiwan R.O.C

Standard : FCC Part 15 Subpart C §15.247

The product was received on Jul. 23, 2019 and testing was started from Jul. 29, 2019 and completed on Aug. 16, 2019. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Reviewed by: Louis Wu

Louis Wa

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 59 FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019 : 01

Table of Contents

Report No.: FR972333A

His	tory o	f this test reportf	3
Su	mmary	y of Test Result	4
1	Gene	ral Description	5
	1.1	Product Feature of Equipment Under Test	5
	1.2	Modification of EUT	5
	1.3	Testing Location	5
	1.4	Applicable Standards	6
2	Test	Configuration of Equipment Under Test	7
	2.1	Carrier Frequency Channel	7
	2.2	Test Mode	8
	2.3	Connection Diagram of Test System	9
	2.4	Support Unit used in test configuration and system	9
	2.5	EUT Operation Test Setup	10
	2.6	Measurement Results Explanation Example	10
3	Test	Result	11
	3.1	Number of Channel Measurement	11
	3.2	Hopping Channel Separation Measurement	13
	3.3	Dwell Time Measurement	19
	3.4	20dB and 99% Bandwidth Measurement	21
	3.5	Output Power Measurement	32
	3.6	Conducted Band Edges Measurement	33
	3.7	Conducted Spurious Emission Measurement	40
	3.8	Radiated Band Edges and Spurious Emission Measurement	
	3.9	AC Conducted Emission Measurement	54
	3.10	Antenna Requirements	56
4	List o	of Measuring Equipment	57
5	Unce	rtainty of Evaluation	59
Ap	pendix	x A. Conducted Test Results	
Ap	pendix	k B. AC Conducted Emission Test Result	
Ap	pendix	c C. Radiated Spurious Emission	
Ap	pendix	c D. Radiated Spurious Emission Plots	
Ap	pendix	k E. Duty Cycle Plots	

TEL: 886-3-327-3456 Page Number : 2 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

History of this test report

Report No. : FR972333A

Report No. Version		Description	Issued Date
FR972333A	01	Initial issue of report	Oct. 24, 2019

TEL: 886-3-327-3456 Page Number : 3 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

Summary of Test Result

Report No.: FR972333A

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 6.19 dB at 384.050 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 18.81 dB at 0.506 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang Report Producer: Ann Lee

TEL: 886-3-327-3456 Page Number : 4 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

1 General Description

1.1 Product Feature of Equipment Under Test

Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, and Sub-gig

Product Specification subjective to this standard					
	WLAN: PIFA Antenna				
Antenna Type	Bluetooth: PIFA Antenna				
	Sub-gig: PIFA Antenna				

Report No.: FR972333A

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory			
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978			
Test Site No.	Sporton	Site No.		
rest site NO.	TH05-HY	CO05-HY		

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH11HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

TEL: 886-3-327-3456 Page Number : 5 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Report No.: FR972333A

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 886-3-327-3456 Page Number : 6 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

2 Test Configuration of Equipment Under Test

Report No.: FR972333A

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
2400-2483.5 MHz	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

TEL: 886-3-327-3456 Page Number : 7 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.

Report No.: FR972333A

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

	Summary table of Test Cases							
	Data Rate / Modulation							
Test Item	Bluetooth BR 1Mbps	Bluetooth EDR 2Mbps	Bluetooth EDR 3Mbps					
	GFSK	π/4-DQPSK	8-DPSK					
Conducted	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz					
Conducted	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz					
Test Cases	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz					
	Bluetooth BR 1Mbps GFSK							
Radiated								
Test Cases	Mode 2: CH39_2441 MHz							
	Mode 3: CH78_2480 MHz							
AC								
Conducted								
Emission								

Remark: For radiated test cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.

TEL: 886-3-327-3456 Page Number : 8 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

2.3 Connection Diagram of Test System



Report No.: FR972333A

2.4 Support Unit used in test configuration and system

Item	Equipment	ITrade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Spectrum Analyzer	Agilent	N9030A	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
3.	Power Supply	Ecobee	SAW12D	SAW12D-120-1000U	N/A	N/A

TEL: 886-3-327-3456 Page Number : 9 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

2.5 EUT Operation Test Setup

The RF test items, utility "adb cmd" was installed in EUT which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

Report No.: FR972333A

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB). = 4.2 + 10 = 14.2 (dB)

TEL: 886-3-327-3456 Page Number: 10 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Report No.: FR972333A

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 7.8.3.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Enable the EUT hopping function.
- Use the following spectrum analyzer settings: Span = the frequency band of operation;
 RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
- 6. The number of hopping frequency used is defined as the number of total channel.
- 7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




TEL: 886-3-327-3456 Page Number : 11 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.1.5 Test Result of Number of Hopping Frequency


Please refer to Appendix A.

Number of Hopping Channel Plot on Channel 00 - 78

Report No.: FR972333A



Date: 16.AUG.2019 10:51:59



Date: 16.AUG.2019 10:52:57

TEL: 886-3-327-3456 Page Number : 12 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Report No.: FR972333A


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.2.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Enable the EUT hopping function.
- Use the following spectrum analyzer settings:
 Span = wide enough to capture the peaks of two adjacent channels;
 RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
- 6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 13 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<1Mbps>


Channel Separation Plot on Channel 00 - 01



Report No.: FR972333A

Date: 16.AUG.2019 10:10:35


Channel Separation Plot on Channel 39 - 40



Date: 16.AUG.2019 10:12:08

TEL: 886-3-327-3456 Page Number : 14 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

Channel Separation Plot on Channel 77 - 78




Report No.: FR972333A

Date: 16.AUG.2019 10:13:51

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 16.AUG.2019 10:20:32

TEL: 886-3-327-3456 Page Number : 15 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


Channel Separation Plot on Channel 39 - 40



Report No.: FR972333A

Date: 16.AUG.2019 10:43:45

Channel Separation Plot on Channel 77 - 78




Date: 16.AUG.2019 10:45:12

TEL: 886-3-327-3456 Page Number : 16 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<3Mbps>


Channel Separation Plot on Channel 00 - 01



Report No.: FR972333A

Date: 16.AUG.2019 10:47:41


Channel Separation Plot on Channel 39 - 40



Date: 16.AUG.2019 10:48:50

TEL: 886-3-327-3456 Page Number : 17 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

Channel Separation Plot on Channel 77 - 78



Report No.: FR972333A

Date: 16.AUG.2019 10:50:22

TEL: 886-3-327-3456 Page Number : 18 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Report No.: FR972333A

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.4.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Enable the EUT hopping function.
- 5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
- 6. Measure and record the results in the test report.

3.3.4 Test Setup




3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 19 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019



Report No.: FR972333A



Date: 7.AUG.2019 04:03:17

Remark:

- 1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4×79) (s), Hops Over Occupancy Time comes to $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$ hops.
- **2.** In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4×20) (s), Hops Over Occupancy Time comes to $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$ hops.
- 3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

TEL: 886-3-327-3456 Page Number : 20 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Report No.: FR972333A

- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
 - Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
 - RBW ≥ 1% of the 20 dB bandwidth; VBW ≥ RBW; Sweep = auto; Detector function = peak;


Trace = max hold.

- 5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
 - Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
 - RBW ≥ 1-5% of the 99% bandwidth; VBW ≥ 3 * RBW; Sweep = auto; Detector function = peak;

Trace = max hold.

6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number : 21 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<1Mbps>


20 dB Bandwidth Plot on Channel 00



Report No.: FR972333A

Date: 16.AUG.2019 10:55:51


20 dB Bandwidth Plot on Channel 39



Date: 16.AUG.2019 10:57:10

TEL: 886-3-327-3456 Page Number : 22 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

20 dB Bandwidth Plot on Channel 78




Report No.: FR972333A

Date: 16.AUG.2019 11:00:55

<2Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 16.AUG.2019 11:03:38

TEL: 886-3-327-3456 Page Number : 23 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


20 dB Bandwidth Plot on Channel 39



Report No.: FR972333A

Date: 16.AUG.2019 11:10:32

20 dB Bandwidth Plot on Channel 78




Date: 16.AUG.2019 11:12:56

TEL: 886-3-327-3456 Page Number : 24 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<3Mbps>


20 dB Bandwidth Plot on Channel 00



Report No.: FR972333A

Date: 16.AUG.2019 11:15:52


20 dB Bandwidth Plot on Channel 39



Date: 16.AUG.2019 11:18:38

TEL: 886-3-327-3456 Page Number : 25 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

20 dB Bandwidth Plot on Channel 78



Report No.: FR972333A

Date: 16.AUG.2019 11:20:52


TEL: 886-3-327-3456 Page Number : 26 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00




Report No.: FR972333A

Date: 16.AUG.2019 11:57:50

TEL: 886-3-327-3456 Page Number : 27 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

99% Occupied Bandwidth Plot on Channel 39



Report No.: FR972333A

Date: 16.AUG.2019 12:00:42

99% Occupied Bandwidth Plot on Channel 78




Date: 16.AUG.2019 12:03:40

TEL: 886-3-327-3456 Page Number : 28 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



Report No.: FR972333A

Date: 16.AUG.2019 12:09:00


99% Occupied Bandwidth Plot on Channel 39



Date: 16.AUG.2019 12:12:55

TEL: 886-3-327-3456 Page Number : 29 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

99% Occupied Bandwidth Plot on Channel 78




Report No.: FR972333A

Date: 16.AUG.2019 13:52:47

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 16.AUG.2019 13:56:54

TEL: 886-3-327-3456 Page Number: 30 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

99% Occupied Bandwidth Plot on Channel 39



Report No.: FR972333A

Date: 16.AUG.2019 13:59:27

99% Occupied Bandwidth Plot on Channel 78



Date: 16.AUG.2019 14:07:17

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

TEL: 886-3-327-3456 Page Number : 31 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.

Report No.: FR972333A


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.5.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power with cable loss and record the results in the test report.
- 5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

TEL: 886-3-327-3456 Page Number: 32 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

Report No.: FR972333A

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

- 1. The testing follows ANSI C63.10-2013 clause 7.8.6.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
- 4. Enable hopping function of the EUT and then repeat step 2. and 3.
- 5. Measure and record the results in the test report.

3.6.4 Test Setup




TEL: 886-3-327-3456 Page Number: 33 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

3.6.5 Test Result of Conducted Band Edges

<1Mbps>


Low Band Edge Plot on Channel 00



Report No.: FR972333A

Date: 16.AUG.2019 11:23:27

High Band Edge Plot on Channel 78




Date: 16.AUG.2019 11:22:47

TEL: 886-3-327-3456 Page Number : 34 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<2Mbps>


Low Band Edge Plot on Channel 00



Report No.: FR972333A

Date: 16.AUG.2019 11:24:41

High Band Edge Plot on Channel 78




Date: 16.AUG.2019 11:25:11

TEL: 886-3-327-3456 Page Number : 35 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<3Mbps>


Low Band Edge Plot on Channel 00



Report No.: FR972333A

Date: 16.AUG.2019 11:26:11

High Band Edge Plot on Channel 78




Date: 16.AUG.2019 11:27:21

TEL: 886-3-327-3456 Page Number : 36 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.6.6 Test Result of Conducted Hopping Mode Band Edges

<1Mbps>


Hopping Mode Low Band Edge Plot



Report No.: FR972333A

Date: 16.AUG.2019 11:45:46

Hopping Mode High Band Edge Plot




Date: 16.AUG.2019 11:47:04

TEL: 886-3-327-3456 Page Number: 37 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

<2Mbps>


Hopping Mode Low Band Edge Plot



Report No.: FR972333A

Date: 16.AUG.2019 11:49:38

Hopping Mode High Band Edge Plot




Date: 16.AUG.2019 11:51:22

TEL: 886-3-327-3456 Page Number: 38 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

<3Mbps>


Hopping Mode Low Band Edge Plot



Report No.: FR972333A

Date: 16.AUG.2019 11:54:34

Hopping Mode High Band Edge Plot



Date: 16.AUG.2019 11:56:27

TEL: 886-3-327-3456 Page Number: 39 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

Report No.: FR972333A

3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

3.7.3 Test Procedure

- 1. The testing follows ANSI C63.10-2013 clause 7.8.8.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
- 5. Measure and record the results in the test report.
- The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup




TEL: 886-3-327-3456 Page Number: 40 of 59
FAX: 886-3-328-4978 Issued Date: Oct. 24, 2019

3.7.5 Test Result of Conducted Spurious Emission

<1Mbps>


CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 11:58:42


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 11:59:09

TEL: 886-3-327-3456 Page Number : 41 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 12:02:04


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 12:02:49

TEL: 886-3-327-3456 Page Number : 42 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 12:05:34

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 16.AUG.2019 12:06:25

TEL: 886-3-327-3456 Page Number : 43 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<2Mbps>


CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 12:11:32


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 12:10:42

TEL: 886-3-327-3456 Page Number : 44 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 12:13:29


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 12:13:59

TEL: 886-3-327-3456 Page Number : 45 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 13:53:29

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 16.AUG.2019 13:53:58

TEL: 886-3-327-3456 Page Number : 46 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

<3Mbps>


CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 13:57:34


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 13:58:14

TEL: 886-3-327-3456 Page Number : 47 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 14:04:38


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 14:05:05

TEL: 886-3-327-3456 Page Number : 48 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Report No.: FR972333A

Date: 16.AUG.2019 14:07:56

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 16.AUG.2019 14:09:08

TEL: 886-3-327-3456 Page Number : 49 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Report No.: FR972333A

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring equipment of this test report.

TEL: 886-3-327-3456 Page Number : 50 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.

Report No.: FR972333A

- 2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 4. Set to the maximum power setting and enable the EUT transmit continuously.
- 5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz, RBW=1MHz for f>1GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).

Duty cycle = On time/100 milliseconds

On time = $N_1*L_1+N_2*L_2+...+N_{n-1}*LN_{n-1}+N_n*L_n$

Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.

Average Emission Level = Peak Emission Level + 20*log(Duty cycle)


- 6. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from 20log (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

TEL: 886-3-327-3456 Page Number : 51 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019


3.8.4 Test Setup

For radiated emissions below 30MHz




Report No.: FR972333A

For radiated emissions from 30MHz to 1GHz



TEL: 886-3-327-3456 Page Number : 52 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

For radiated emissions above 1GHz



Report No.: FR972333A

3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.8.7 Duty Cycle

Please refer to Appendix E.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

TEL: 886-3-327-3456 Page Number : 53 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR972333A

Eroquency of emission (MUz)	Conducted	limit (dΒμV)
Frequency of emission (MHz)	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

^{*}Decreases with the logarithm of the frequency.

3.9.2 Measuring Instruments


See list of measuring equipment of this test report.

3.9.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

TEL: 886-3-327-3456 Page Number: 54 of 59
FAX: 886-3-328-4978 Issued Date: 0ct. 24, 2019

3.9.4 Test Setup



Report No.: FR972333A

AMN = Artificial mains network (LISN)

AE = Associated equipment

EUT = Equipment under test

ISN = Impedance stabilization network

3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

TEL: 886-3-327-3456 Page Number : 55 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

Report No.: FR972333A

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

TEL: 886-3-327-3456 Page Number : 56 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 27, 2018	Jul. 29, 2019~ Aug.16, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 27, 2018	Jul. 29, 2019~ Aug.16, 2019	Dec. 26, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2018	Jul. 29, 2019~ Aug.16, 2019	Nov. 20, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Jul. 29, 2019~ Aug.16, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	EM	EMSW18	SW107090 3	N/A	Dec. 19, 2018	Jul. 29, 2019~ Aug.16, 2019	Dec. 18, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 30, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 12, 2018	Jul. 30, 2019	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Jul. 30, 2019	Nov. 13, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 30, 2019	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Dec. 31, 2018	Jul. 30, 2019	Dec. 30, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Dec. 31, 2018	Jul. 30, 2019	Dec. 30, 2019	Conduction (CO05-HY)

Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : 57 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	Aug. 10, 2019~ Aug. 16, 2019	Dec. 05, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 04, 2018	Aug. 10, 2019~ Aug. 16, 2019	Dec. 03, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-0 6	35414&AT- N0602	30MHz~1GHz	Oct. 13, 2018	Aug. 10, 2019~ Aug. 16, 2019	Oct. 12, 2019	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 6	1GHz ~ 18GHz	Oct. 30, 2018	Aug. 10, 2019~ Aug. 16, 2019	Oct. 29, 2019	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 22, 2018	Aug. 10, 2019~ Aug. 16, 2019	Nov. 21, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY532700 80	1GHz~26.5GHz	Nov. 14, 2018	Aug. 10, 2019~ Aug. 16, 2019	Nov. 13, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz ~ 44GHz	Oct. 19, 2018	Aug. 10, 2019~ Aug. 16, 2019	Oct. 18, 2019	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1~4m	N/A	Aug. 10, 2019~ Aug. 16, 2019	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Aug. 10, 2019~ Aug. 16, 2019	N/A	Radiation (03CH11-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May. 20, 2019	Aug. 10, 2019~ Aug. 16, 2019	May. 19, 2020	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec. 05, 2018	Aug. 10, 2019~ Aug. 16, 2019	Dec. 04, 2019	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY541300 85	N/A	Nov. 01, 2018	Aug. 10, 2019~ Aug. 16, 2019	Oct. 31, 2019	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-00104 2	N/A	N/A	Aug. 10, 2019~ Aug. 16, 2019	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz-30MHz	Mar. 13, 2019	Aug. 10, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 13, 2019	Aug. 10, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	30M-18G	Mar. 13, 2019	Aug. 10, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 13, 2019	Aug. 10, 2019~ Aug. 16, 2019	Mar. 12, 2020	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN11	1G Low Pass	Sep. 16, 2018	Aug. 10, 2019~ Aug. 16, 2019	Sep. 17, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60SS	SN3	2.7G High Pass	Sep. 17, 2018	Aug. 10, 2019~ Aug. 16, 2019	Sep. 16, 2019	Radiation (03CH11-HY)

Report No. : FR972333A

TEL: 886-3-327-3456 Page Number : 58 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.2
of 95% (U = 2Uc(y))	2.2

Report No.: FR972333A

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.2
of 95% (U = 2Uc(y))	3.2

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	5
of 95% (U = 2Uc(y))	5.5

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	
of 95% (U = 2Uc(y))	5.2

TEL: 886-3-327-3456 Page Number : 59 of 59
FAX: 886-3-328-4978 Issued Date : Oct. 24, 2019

Report Number : FR972333A

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Derek Hsu	Temperature:	21~25	°C
Test Date:	2019/7/29~08/16	Relative Humidity:	51~54	%

			20dB	and 99	% Occup		SULTS DATA Ith and Hopping	Channel Separ	ation
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.932	0.856	0.990	0.6213	Pass
DH	1Mbps	1	39	2441	0.932	0.852	1.008	0.6213	Pass
DH	1Mbps	1	78	2480	0.936	0.856	0.996	0.6240	Pass
2DH	2Mbps	1	0	2402	1.242	1.140	1.008	0.8280	Pass
2DH	2Mbps	1	39	2441	1.242	1.140	1.002	0.8280	Pass
2DH	2Mbps	1	78	2480	1.242	1.140	1.002	0.8280	Pass
3DH	3Mbps	1	0	2402	1.218	1.124	1.002	0.8120	Pass
3DH	3Mbps	1	39	2441	1.218	1.124	1.002	0.8120	Pass
3DH	3Mbps	1	78	2480	1.218	1.120	1.020	0.8120	Pass

			<u>TES</u>	T RESULTS Dwell Time		
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.88	0.31	0.4	Pass
AFH	20	53.33	2.88	0.15	0.4	Pass

					T RESUL eak Powe
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
	0	1	12.62	20.97	Pass
DH1	39	1	12.46	20.97	Pass
	78	1	12.44	20.97	Pass
	0	1	12.59	20.97	Pass
2DH1	39	1	12.44	20.97	Pass
	78	1	12.42	20.97	Pass
	0	1	12.46	20.97	Pass
3DH1	39	1	12.30	20.97	Pass
	78	1	12.27	20.97	Pass

				Ave	ST RESULTS DATA erage Power Table Reporting Only)
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)	
	0	1	12.25	5.25	
DH1	39	1	12.11	5.25	
	78	1	12.10	5.25	
	0	1	10.49	5.18	
2DH1	39	1	10.34	5.18	
	78	1	10.33	5.18	
	0	1	10.32	5.18	
3DH1	39	1	10.21	5.18	
	78	1	10.20	5.18	

		TEST RE Number of He	SULTS DA oppina Fre	
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail	
79	20	> 15	Pass	

Appendix B. AC Conducted Emission Test Results

Toot Engineer	limmy Chang	Temperature	e:	25.5~26.3℃
Test Engineer :	Jiminy Chang	Relative Hui	midity:	58~61%

Report No.: FR972333A

TEL: 886-3-327-3456 Page Number: B1 of B1

EUT Information


 Report NO :
 972333

 Test Mode :
 Mode 1

 Test Voltage :
 120Vac/60Hz

Phase: Line

FullSpectrum




Final Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dB)			(dB)
0.161250		26.73	55.40	28.67	L1	OFF	19.4
0.161250	34.18		65.40	31.22	L1	OFF	19.4
0.505500		27.19	46.00	18.81	L1	OFF	19.4
0.505500	30.04	-	56.00	25.96	L1	OFF	19.4
0.829500		23.79	46.00	22.21	L1	OFF	19.5
0.829500	25.38		56.00	30.62	L1	OFF	19.5
1.862250		22.87	46.00	23.13	L1	OFF	19.5
1.862250	23.78		56.00	32.22	L1	OFF	19.5
4.096500		24.41	46.00	21.59	L1	OFF	19.6
4.096500	25.44		56.00	30.56	L1	OFF	19.6
17.331000		24.40	50.00	25.60	L1	OFF	20.1
17.331000	25.55		60.00	34.45	L1	OFF	20.1

EUT Information

Report NO: 972333
Test Mode: Mode 1
Test Voltage: 120Vac/60Hz
Phase: Neutral

FullSpectrum



Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBuV)	(dBuV)	(dBuV)	(dB)			(dB)
0.161250		26.63	55.40	28.77	N	OFF	19.5
0.161250	33.70		65.40	31.70	N	OFF	19.5
0.298500		23.57	50.28	26.71	N	OFF	19.5
0.298500	25.50		60.28	34.78	N	OFF	19.5
0.809250		22.57	46.00	23.43	N	OFF	19.5
0.809250	23.75		56.00	32.25	N	OFF	19.5
2.125500		22.95	46.00	23.05	N	OFF	19.6
2.125500	23.99		56.00	32.01	N	OFF	19.6
5.028000		24.71	50.00	25.29	N	OFF	19.7
5.028000	25.84		60.00	34.16	N	OFF	19.7
20.107500		24.30	50.00	25.70	N	OFF	20.3
20.107500	25.17		60.00	34.83	N	OFF	20.3

Appendix C. Radiated Spurious Emission

Test Engineer :	Bill Kuo, Fu Chen and Troye Hsieh	Temperature :	21.3~27.3°C
rest Engineer.		Relative Humidity :	48.7~65.9%

Report No.: FR972333A

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

ВТ	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2329.425	43.3	-30.7	74	42.63	27.68	6.64	33.65	328	113	Р	Н
		2329.425	18.51	-35.49	54	-	-	ı	-	-	-	Α	Н
	*	2402	104.55	-	-	104.06	27.4	6.72	33.63	328	113	Р	Н
	*	2402	79.76	-	-	-	-	-	-	-	-	Α	Н
DT													Н
BT													Н
CH00 2402MHz		2376.15	42.7	-31.3	74	42.14	27.5	6.69	33.63	108	160	Р	V
2402141712		2376.15	17.91	-36.09	54	-	-	1	-	-	-	Α	V
	*	2402	107.1	-	-	106.61	27.4	6.72	33.63	108	160	Р	V
	*	2402	82.31	-	-	-	-	-	-	-	-	Α	V
													V
													V

TEL: 886-3-327-3456 Page Number : C1 of C7



вт Over Limit Read Antenna Path Preamp Table Peak Pol. Note **Frequency** Level Ant Limit Line **Factor** Level Loss Factor Pos Pos Avg. (dBµV/m) (deg) (P/A) (H/V) (MHz) (dB) (dBµV/m) (dB_µV) (dB/m) (dB) (dB) (cm) 2350.74 42.36 -31.64 74 41.74 27.6 6.66 33.64 324 126 Η 2350.74 17.57 -36.43 54 ----Α Н 2441 104.27 103.8 27.32 6.76 33.61 324 126 Ρ Н 2441 79.48 Α Н 2488.38 42.81 -31.19 42.29 27.3 33.59 324 Ρ Н 74 6.81 126 BT 2488.38 18.02 -35.98 54 Α Н **CH 39** 2318.54 43.14 -30.86 74 42.44 27.73 6.63 33.66 100 279 Ρ V 2441MHz 2318.54 18.35 -35.65 54 ٧ Α 2441 107.56 107.09 27.32 6.76 33.61 100 279 ٧ 2441 Α ٧ 82.77 -_ -_ ---Р ٧ 2492.79 42.49 -31.51 74 41.96 27.3 6.82 33.59 100 279 ٧ 2492.79 17.7 -36.3 --Α 54 * 2480 104.51 Ρ Н 104.01 27.3 6.8 33.6 346 130 2480 79.72 Н Р 2483.64 45.04 -28.96 74 44.53 27.3 6.81 33.6 346 130 Н 2483.64 20.25 -33.75 54 Α Н Н BT Н **CH 78** 2480 107.29 106.79 27.3 6.8 33.6 100 278 V 2480MHz ٧ 2480 82.5 _ _ _ -Α 2483.96 Ρ ٧ 46.99 -27.01 74 46.48 27.3 6.81 33.6 100 278 -31.8 2483.96 22.2 Α ٧ 54 V ٧ 1. No other spurious found. Remark All results are PASS against Peak and Average limit line.

Report No.: FR972333A

TEL: 886-3-327-3456 Page Number: C2 of C7



2.4GHz 2400~2483.5MHz

Report No. : FR972333A

BT (Harmonic @ 3m)

ВТ	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		3600	51.56	-22.44	74	70.93	29.1	9.75	58.22	100	0	Р	Н
		3600	26.77	-27.23	54	ı	-	-	-	-	-	Α	Н
BT CH 00		4804	41.7	-32.3	74	57.18	31.1	11	57.58	100	0	Р	Н
		4804	16.91	-37.09	54	1	-	-	-	-	-	Α	Н
2402MHz		3600	44.93	-29.07	74	64.3	29.1	10.54	58.22	100	0	Р	V
2402WII 12		3600	20.14	-33.86	54	-	-	-	-	-	-	Α	V
		4804	41.87	-32.13	74	57.35	31.1	11.44	57.58	100	0	Р	V
		4804	17.08	-36.92	54	-	-	-	-	-	-	Α	V
		3660	50.59	-23.41	74	69.9	29.2	9.78	58.29	100	0	Р	Н
		3660	25.8	-28.2	54	-	-	-	-	-	-	Α	Н
		4882	44.94	-29.06	74	60.28	31.04	11.06	57.44	100	0	Р	Н
		4882	20.15	-33.85	54	-	-	-	-	-	-	Α	Н
D.T.		7323	44.87	-29.13	74	51.96	36.55	13.65	57.29	100	0	Р	Τ
BT CH 39		7323	20.08	-33.92	54	-	-	-	-	-	-	Α	Н
2441MHz		3660	43.17	-30.83	74	62.48	29.2	9.78	58.29	100	0	Р	V
244 I WIFI2		3660	18.38	-35.62	54	-	-	-	-	-	-	Α	٧
		4882	44.44	-29.56	74	59.78	31.04	11.06	57.44	100	0	Р	٧
		4882	19.65	-34.35	54	-	-	-	-	-	-	Α	V
		7323	42.99	-31.01	74	50.08	36.55	13.65	57.29	100	0	Р	V
		7323	18.2	-35.8	54	-	-	-	-	-	-	Α	V

TEL: 886-3-327-3456 Page Number : C3 of C7



BT Level Preamp Note Frequency Over Limit Read Antenna Path Ant Table Peak Pol. Limit Line Level Factor Factor Pos Pos Loss Avg. (deg) (P/A) (H/V) (MHz) (dBµV/m) (dB) (dBµV/m) (dB_µV) (dB/m) (dB) (dB) (cm) 49.38 -24.62 68.7 29.24 3720 74 9.81 58.37 100 0 Η 3720 24.59 -29.41 54 Α Н ---Ρ 4960 47.14 -26.86 74 61.98 31.32 11.11 57.27 100 0 Н 4960 22.35 -31.65 Α Η 54 Р 7440 44.65 -29.35 74 51.99 36.48 13.62 57.44 100 0 Н BT 7440 19.86 -34.14 54 Α Н **CH 78** 3720 43.43 -30.57 74 62.75 29.24 9.81 58.37 100 0 Р ٧ 2480MHz 3720 18.64 -35.36 54 Α ٧ ٧ 4960 47.37 -26.63 74 62.21 31.32 11.11 57.27 100 0 ٧ 4960 22.58 -31.42 54 Α _ -_ --7440 43.89 -30.11 74 100 0 Р ٧ 51.23 36.48 13.62 57.44 7440 19.1 -34.9 Α ٧ 54 No other spurious found. Remark

Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : C4 of C7

All results are PASS against Peak and Average limit line.

Emission below 1GHz

Report No. : FR972333A

2.4GHz BT (LF)

вт	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V
		30	21.52	-18.48	40	29.12	24.01	0.77	32.38	-	-	Р	Н
		136.7	32.15	-11.35	43.5	45.69	17.2	1.55	32.29	-	-	Р	Н
		384.05	39.81	-6.19	46	48.26	21.05	2.66	32.16	100	0	Р	Н
		946.65	32.71	-13.29	46	28.96	30.37	4.3	30.92	-	-	Р	Н
		949.56	32.84	-13.16	46	28.87	30.55	4.31	30.89	-	-	Р	Н
		958.29	32.9	-13.1	46	28.44	30.93	4.34	30.81	-	-	Р	Н
													Н
													Н
													Н
													Н
2.4GHz													Н
BT													Н
LF		55.22	23.96	-16.04	40	43.36	11.98	0.98	32.36	-	-	Р	V
		137.67	31.02	-12.48	43.5	44.57	17.18	1.56	32.29	-	-	Р	V
		384.05	27.45	-18.55	46	35.9	21.05	2.66	32.16	-	-	Р	V
		931.13	32.59	-13.41	46	29.87	29.52	4.26	31.06	-	-	Р	V
		947.62	33.37	-12.63	46	29.54	30.43	4.31	30.91	-	-	Р	V
		956.35	33.72	-12.28	46	29.37	30.85	4.33	30.83	100	0	Р	V
													V
													V
													V
													V
													V
													V

TEL: 886-3-327-3456 Page Number : C5 of C7

Note symbol

Report No.: FR972333A

*	Fundamental Frequency which can be ignored. However, the level of any
	unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

TEL: 886-3-327-3456 Page Number : C6 of C7

A calculation example for radiated spurious emission is shown as below:

Report No.: FR972333A

ВТ	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
вт		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 00													
2402MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

- 1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
- 2. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dB μ V) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

TEL: 886-3-327-3456 Page Number : C7 of C7

Appendix D. Radiated Spurious Emission Plots

Toot Engineer		Temperature :	21.3~27.3°C
Test Engineer :	Bill Kuo, Fu Chen and Troye Hsieh	Relative Humidity :	48.7~65.9%

Report No.: FR972333A


Note symbol

-L	Low channel location
-R	High channel location


TEL: 886-3-327-3456 Page Number : D1 of D11

2.4GHz 2400~2483.5MHz BT (Band Edge @ 3m)

Report No.: FR972333A




TEL: 886-3-327-3456 Page Number : D2 of D11



Report No.: FR972333A


TEL: 886-3-327-3456 Page Number : D3 of D11

Report No.: FR972333A




: D4 of D11 TEL: 886-3-327-3456 Page Number

FCC RADIO TEST REPORT




Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : D5 of D11



Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : D6 of D11




Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : D7 of D11


2.4GHz 2400~2483.5MHz

Report No.: FR972333A

BT (Harmonic @ 3m)




TEL: 886-3-327-3456 Page Number : D8 of D11



Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : D9 of D11




Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : D10 of D11

Emission below 1GHz 2.4GHz BT (LF)

Report No.: FR972333A




TEL: 886-3-327-3456 Page Number : D11 of D11




Report No.: FR972333A

Appendix E. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



Note:

- 1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.88 / 100 = 5.76 %
- 2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.79 dB
- **DH5** has the highest duty cycle worst case and is reported.

TEL: 886-3-327-3456 Page Number : E-1 of 2



FCC RADIO TEST REPORT

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

2.88 ms x 20 channels = 57.6 ms

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. [100ms / 57.6ms] = 2 hops

Thus, the maximum possible ON time:

2.88 ms x 2 = 5.76 ms

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

 $20 \times log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$

_____THE END_____

Report No.: FR972333A

TEL: 886-3-327-3456 Page Number : E-2 of 2