

#### **FCC - TEST REPORT**

Report Number	: <b>68.760.12.03</b>	3.01	Date of Issue:	18 August 2012
Model	: KT400			
Product Type	: Vehicle ECU	Diagnosis		
Applicant	: Bosch Autom	notive Diagno	stics Equipment	(Shenzhen) Limited
Address	: 5/F,A, Gardo	n City Cyber	Port, Nanhai Roa	ad No.1079,
	Nanshan Dis	trict, Shenzhe	en518067 P.R. C	hina
Production Facility	: Bosch Autom	notive Diagno	stics Equipment	(Shenzhen) Limited
Address	: 5/F,A, Gardo	n City Cyber	Port, Nanhai Roa	ad No.1079,
	Nanshan Dis	trict, Shenzhe	en518067 P.R. C	hina
Test Result	: Positive	□ Negativ	ve	
Total pages including Appendices	: 34			

Jiangsu TÜV Product Service Ltd. - Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

Jiangsu TÜV Product Service Ltd. - Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. Jiangsu TÜV Product Service Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Jiangsu TÜV Product Service Ltd. – Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval



## 1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Technical Requirements 7.1 Radiated Emissions 7.2 Conducted Emission Test	8 8 25
8	System Measurement Uncertainty.	34



#### 2 Details about the Test Laboratory

## **Details about the Test Laboratory**

Test site1:

Jiangsu TÜV Product Service Ltd. - Shenzhen Branch Company name:

6th Floor, H Hall,

Century Craftwork Culture Square,

No. 4001, Fuqiang Road, Futian District 518048,

Shenzhen, P.R.C.

Telephone: 86 755 8828 6998 Fax: 86 755 8828 5299

Test site2:

Shenzhen Academy of Metrology & Quality Inspection Company name:

> Longzhu road, Nan Shan,

Shenzhen 518055, Guangdong, China

Telephone: 86 755 2694 1723 Fax: 86 755 2694 1545



## 3 Description of the Equipment Under Test

## **Description of the Equipment Under Test**

Product: Vehicle ECU Diagnosis

Model no.: KT400

Brand Name: BOSCH

Options and accessories: NIL

Rating: 7-32VDC

Charged by external adapter FJ-SW1402800T: Adaptor Input: 100-240VAC, 50/60Hz, 1.5A Max

Adaptor Output: 14VDC, 2800mA

or charged by Lead-acid battery power sources used on vehicles

Description of the EUT: NIL

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	T61	-
Engine	IMSEOER	ME797	-



# 4 Summary of Test Standards

	Test Standards
FCC Part 15 Subpart B, 10-1-2011 Edition	Unintentional Radiators



# **5 Summary of Test Results**

	<b>Emission Te</b>	sts			
FCC Part 15 Subpart B					
Test Condition	Pages	Tes	st Result		Test Site
	_	Pass	Fail	N/A	
Radiated Emission	8	$\boxtimes$			Site 2
30MHz to 6000MHz					
Conducted Emission on AC	25	$\boxtimes$			Site 2
150kHz to 30MHz					



#### **6 General Remarks**

#### Remarks

This submittal(s) (test report) is intended for FCC ID: WSO-KT400 complies with Section 15.107, 15.109 of the FCC Part 15, Subpart B Rules.

All the configurations of the product were tested and only the worst test results are listed in the report.

#### **SUMMARY:**

All tests according to the regulations cited on page 5 were

- Performed
- ☐ Not Performed

The Equipment Under Test

- - Fulfills the general approval requirements.
- ☐ **Does not** fulfill the general approval requirements.

Sample Received Date: 19 June 2012

Testing Start Date: 20 June 2012

Testing End Date: 3 July 2012

- Jiangsu TÜV Product Service Ltd. - Shenzhen Branch -

Reviewed by:

Prepared by:

Tested by:

Ken Li **EMC Project Manager** 

Cookies Bu **EMC Project Engineer** 

Eric Gao **EMC Test Engineer** 

Eno Gas



#### 7 Emission Test Results


#### 7.1 Radiated Emission Test 30MHz - 6000MHz

EUT: KT400

Op Cond: Data transmitting via USB port

Test Spec: Vertical and horizontal, 30MHz-1GHz

Comment: AC 120V/60Hz





## Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Data transmitting via USB port Operating mode

**Test Specification** Horizontal and Vertical, 30MHz-1GHz

Model No KT400

Frequency MHz	Horizontal dBμV/m	Limit dBµV/m	Margin dB
447.426	44.0	46.0	2.0
665.651	41.5	46.0	4.5


Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
41.664	31.9	40.0	8.1
148.577	36.9	43.5	6.6



EUT: KT400

Op Cond: Data transmitting via USB port Test Spec: Vertical and horizontal, above 1GHz

Comment: AC 120V/60Hz





#### Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via USB port

**Test Specification** Horizontal and Vertical, above 1GHz

Model No KT400

Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
	1	1	

Frequency Vertical Limit Margin dBµV/m dBµV/m MHz dB




EUT: KT400

Op Cond: Data transmitting via USB port

Test Spec: Vertical and horizontal, 30MHz-1GHz

Comment: **DC 12V** 





#### Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Data transmitting via USB port Operating mode

**Test Specification** Horizontal and Vertical, 30MHz-1GHz

Model No KT400

Frequency MHz	Horizontal dBµV/m	Limit dBµV/m	Margin dB
113.587	31.2	43.5	12.3
665.05	43.1	46.0	2.9
447.935	41.2	46.0	4.8


Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
111.643	33.9	43.5	9.6
447 93	44 2	46 O	1.8



EUT: KT400

Op Cond: Data transmitting via USB port Test Spec: Vertical and horizontal, above 1GHz

Comment: DC12V





#### Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via USB port

**Test Specification** Horizontal and Vertical, above 1GHz

Model No KT400

Frequency	Horizontal	Limit	Margin
MHz	dBμV/m	dBµV/m	dB
 1	/	1	


Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz



EUT: KT400

Op Cond: Diagnostic mode Test Spec: Vertical and horizontal

Comment: AC 120V/60Hz





## Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Diagnostic mode Operating mode

**Test Specification** Horizontal and Vertical, 30MHz-1GHz

Model No KT400

Frequency MHz	Horizontal dBµV/m	Limit dBµV/m	Margin dB
146.661	32.7	43.5	10.8
447.41	43.6	46.0	2.4

Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
43.607	32.4	40.0	7.6
152.464	36.8	43.5	6.7




EUT: KT400

Op Cond: Diagnostic mode

Test Spec: Vertical and horizontal, above 1GHz

Comment: AC 120V/60Hz





#### Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Operating mode Diagnostic mode

**Test Specification** Horizontal and Vertical, above 1GHz

Model No KT400

 Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
1	/	/	


Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz



EUT: KT400

Op Cond: Diagnostic mode Test Spec: Vertical and horizontal

Comment: DC12V





3July 2012 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Diagnostic mode Operating mode

**Test Specification** Horizontal and Vertical

Model No KT400

Passed	
Not Passed	

Test Result

Frequency MHz	Horizontal dBµV/m	Limit dBµV/m	Margin dB
111.643	35.4	43.5	8.1
447.41	44.5	46.0	1.5

	Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB	_
_	37.775	34.6	40.0	5.4	




EUT: KT400

Op Cond: Diagnostic mode

Test Spec: Vertical and horizontal, above 1GHz

Comment: **DC 12V** 





#### Radiated Emission Test 30MHz - 6000MHz

3 July 2012 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Operating mode Diagnostic mode

**Test Specification** Horizontal and Vertical, above 1GHz

Model No KT400

 Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
1	/	/	

Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz



# **Test Equipment List**

#### **Radiated Emission Test**

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESI26	838786/013	2013-01-20
Bilog Antenna	Chase	CBL6112B	2591	2013-01-20
Horn Antenna	Rohde & Schwarz	HF906	100014	2013-01-20
3m Semi-anechoic chamber	Albatross Project	9X6X6		2012-10-09




## 7.2 Conducted Emission Test 150kHz - 30MHz

EUT: KT400

Op Cond: Data transmitting via USB port

Test Spec: Power line, Live AC 120V/60Hz Comment:





#### Conducted Emission Test 150kHz - 30MHz

Date of test 20 June 2012

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via USB port

Tested on Power Line, Live

Model No KT400

> **QP Limit Frequency QP Test result** Margin MHz  $dB\mu V$ dΒμV dB

**Frequency AV Test result AV Limit** Margin MHz dBµV dB<sub>µ</sub>V dB




## Conducted Emission Test 150kHz - 30MHz

EUT: KT400

Op Cond: Data transmitting via USB port

Test Spec: Power line, Neutral AC 120V/60Hz Comment:





Test Result Passed

Not Passed

#### Conducted Emission Test 150kHz - 30MHz

Date of test 20 June 2012

Test requirement : FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Data transmitting via USB port Operating mode

Tested on Power Line, Neutral

Model No KT400

Frequency	QP Test result	QP Limit	Margin
MHz	dBμV	dBμV	dB
	/	1	1


Frequency **AV Test result AV Limit** Margin MHz dBµV dB<sub>µ</sub>V dB



## Conducted Emission Test 150kHz - 30MHz

EUT: KT400

Op Cond: Test Spec: Diagnostic mode Power line, Live Comment: AC 120V/60Hz





Test Result

Passed Not Passed

#### Conducted Emission Test 150kHz - 30MHz

Date of test 20 June 2012

Test requirement: FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Diagnostic mode Operating mode

Tested on Power Line, Live

Model No KT400

Frequency	QP Test result	QP Limit	Margin
MHz	dBμV	dBμV	dB
	/	1	1


Frequency **AV Test result AV Limit** Margin MHz dBµV dΒμV dB



## Conducted Emission Test 150kHz - 30MHz

EUT: KT400

Op Cond: Diagnostic mode Test Spec: Power line, Neutral AC 120V/60Hz Comment:





#### Conducted Emission Test 150kHz - 30MHz

Date of test 20 June 2012

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Diagnostic mode

Tested on Power Line, Neutral

Model No KT400

> **QP Limit** Frequency **QP Test result** Margin MHz  $dB\mu V$ dΒμV dB

**Frequency AV Test result AV Limit** Margin MHz dBµV dΒμV dB



# **Test Equipment List**

#### **Conducted Emission Test**

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	2013-01-20
AMN	Rohde & Schwarz	ESH3-Z5	100229	2013-01-20
AMN	Rohde & Schwarz	ENV216	100042	2013-01-20



## **8 System Measurement Uncertainty**

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

**System Measurement Uncertainty** 

Items		Extended Uncertainty
RE	Field strength (dBμV/m)	U=4.60dB (30MHz-25GHz)
CE	Disturbance Voltage (dBμV)	U=3.50dB(150KHz-30MHz)